

Title...

D. Schrijver

Affiliation...

(Dated: June 30, 2026)

Abstract will come here...

I. INTRODUCTION

Wet-node boundary conditions, where the boundary is defined to be infinitesimally close to the fluid nodes, have been shown in various test cases to be able to achieve higher accuracy at straight boundaries than link-wise boundary conditions, where the boundary is defined to be half a grid-point away from the fluid nodes. This has been shown for velocity boundaries [1] and pressure boundaries [2]. Especially methods that conserve the known particle populations, which stream in from the bulk of the domain, are very accurate at moderate Reynolds number [1]. For instance, the Non-Equilibrium Bounce-Back (NEBB) method [2] has been shown to be third-order accurate for prescribing the no-slip condition on straight boundaries for single-component fluids in the absence of external forcing [3].

In this paper, we aim to expand upon the NEBB method to enable its use in more complex flow problems with straight boundaries and moderate Reynolds numbers. For this, we define a stencil-independent formulation of the force-corrected and mass-corrected multi-component NEBB method.

Stencil-independent formulations for single-component fluids have been posed in previous research [3][4], but not in the presence of external forces. Force-corrections have been introduced in previous research too, in the context of single-component pseudopotential wetting simulations at a no-slip boundary [5], and two-component pseudopotential simulations at an outlet [6]. However, both of these are formulated specifically for the D2Q9.

Furthermore, mass corrections have also been defined in previous research for single-component fluids in the absence of external forces [4]. Finally, a multi-component formulation of the NEBB has been derived two-component pseudopotential simulations [6], but again specifically for the D2Q9. This method also does not take mass corrections into account and simplifications made in the derivation can lead to deviations of the density and velocity from the imposed values.

After the derivation of the expanded NEBB method, we will use an asymptotic analysis in Knudsen number [7] to assess its accuracy and the validity of the mass correction. Next, we will perform various numerical test cases for the expanded NEBB against the widely-used Halfway Bounce-Back (HWBB) method, both for single-component fluids and immiscible multi-component fluids. The multi-component simulations will be performed with both the Shan-Chen method [8] and the Color-Gradient method [9]. These simulations include static contact-

angle wetting simulations [10] and capillary rise simulations [11][12] and results will be compared to state-of-the-art research on wetting, which use common Halfway Bounce-Back scheme for the no-slip boundaries.

II. MULTI-COMPONENT LATTICE BOLTZMANN METHOD

The Lattice Boltzmann Equation using the BGK collision operator [13] for a two-component system is given as follows,

$$f_i^\sigma(\mathbf{x} + \mathbf{c}_i, t + 1) - f_i^\sigma = -\frac{1}{\tau^\sigma} (f_i^\sigma - f_i^{\text{eq},\sigma}), \quad (1)$$

where σ indicates the fluid component and τ^σ gives the corresponding relaxation time. As is common for the Lattice Boltzmann method, the time step and grid spacing are set to unity. Lastly, the discrete velocity directions are indicated by $\mathbf{c}_i$. The macroscopic quantities can be derived from the distribution functions,

$$\rho^\sigma = \sum_i f_i^\sigma, \quad \rho \mathbf{u} = \sum_\sigma \sum_i f_i^\sigma \mathbf{c}_i, \quad (2)$$

where $\rho = \sum_\sigma \rho^\sigma$. Two different methods will be used to separate the two fluids and create surface tension. The Shan-Chen method uses a repulsion force between the two fluids [8] and the Color-Gradient method adds surface tension and repulsion using two extra collision operators [9].

A. The Shan-Chen Method

The Shan-Chen force is given as follows [8],

$$\mathbf{F}_{\text{SC}}^\sigma(\mathbf{x}) = -G\rho^\sigma(\mathbf{x}) \sum_i w_i \rho^{\tilde{\sigma}}(\mathbf{x} + \mathbf{c}_i) \mathbf{c}_i, \quad (3)$$

where $\tilde{\sigma}$ indicates the other fluid component and G is the interaction strength. Furthermore, w_i indicates the weight attributed to the velocity component $\mathbf{c}_i$. A source term S_i^σ is introduced on the right-hand-side of Eq. (1) to incorporate this force [14],

$$S_i^\sigma = \left(1 - \frac{1}{2\tau^\sigma}\right) w_i \left(\frac{\mathbf{c}_i \cdot \mathbf{u}}{c_s^2} + \frac{\mathbf{c}_i \cdot \mathbf{u}}{c_s^4} \mathbf{c}_i \right) \cdot \mathbf{F}^\sigma, \quad (4)$$

where $c_s = \sqrt{1/3}$. Furthermore, the velocity given in Eq. (2) is shifted by the external forcing,

$$\rho \mathbf{u} = \sum_\sigma \sum_i f_i^\sigma \mathbf{c}_i + \frac{1}{2} \sum_\sigma \mathbf{F}^\sigma. \quad (5)$$

Finally, the equilibrium distribution is computed as follows,

$$f_i^{\text{eq},\sigma} = w_i \rho^\sigma \left(1 + \frac{\mathbf{u} \cdot \mathbf{c}_i}{c_s^2} + \frac{(\mathbf{u} \cdot \mathbf{c}_i)^2}{2c_s^4} - \frac{|\mathbf{u}|^2}{2c_s^2} \right). \quad (6)$$

B. The Color-Gradient Method

The Lattice Boltzmann Equation is usually split in a collision and streaming step,

$$\begin{aligned} f_i^{*,\sigma}(\mathbf{x}, t) &= f_i^\sigma(\mathbf{x}, t) - \frac{1}{\tau^\sigma} (f_i^\sigma - f_i^{\text{eq},\sigma}), \\ f_i^\sigma(\mathbf{x}, t+1) &= f_i^{*,\sigma}(\mathbf{x} - \mathbf{c}_i, t). \end{aligned} \quad (7)$$

The Color-Gradient method introduces two additional steps after the collision step to introduce interface tension and phase separation. The equilibrium distribution is adapted to support separate speeds of sound in the fluids [9],

$$f_i^{\text{eq},\sigma} = \rho_w^\sigma \left[\phi_i^\sigma + w_i \left(\frac{\mathbf{u} \cdot \mathbf{c}_i}{c_s^2} + \frac{(\mathbf{u} \cdot \mathbf{c}_i)^2}{2c_s^4} - \frac{|\mathbf{u}|^2}{2c_s^2} \right) \right] + \Phi_i^\sigma, \quad (8)$$

where the values for ϕ_i^σ are given in Tab. (I).

$ \mathbf{c}_i ^2$	0	1	2	3
D2Q9	α^σ	$(1 - \alpha^\sigma)/5$	$(1 - \alpha^\sigma)/20$	-
D3Q19	α^σ	$(1 - \alpha^\sigma)/12$	$(1 - \alpha^\sigma)/24$	-
D3Q27	α^σ	$2(1 - \alpha^\sigma)/19$	$(1 - \alpha^\sigma)/38$	$(1 - \alpha^\sigma)/152$

TABLE I. Values for ϕ_i^σ for different lattices [9].

$ \mathbf{c}_i ^2$	0	1	2	3
D2Q9	-8/3	-1/6	1/12	-
D3Q19	-5/2	-1/6	1/24	-
D3Q27	-20/9	-2/9	1/36	1/36

TABLE II. Values for ψ_i for different lattices [9].

$ \mathbf{c}_i ^2$	0	1	2	3
D2Q9	0	1/2	1/8	-
D3Q19	0	1/4	1/8	-
D3Q27	0	1/3	1/12	1/48

TABLE III. Values for ξ_i for different lattices [9].

The values for α^σ depend on the initial density ratio between the fluids,

$$\gamma = \frac{\rho_0^\sigma}{\rho_0^{\tilde{\sigma}}} = \frac{1 - \alpha^{\tilde{\sigma}}}{1 - \alpha^\sigma}. \quad (9)$$

We choose $\alpha^{\tilde{\sigma}} = 0.2$ [15], where $\tilde{\sigma}$ corresponds to the low-density component. This gives $\alpha^\sigma = 1 - (1 - \alpha^{\tilde{\sigma}})/\gamma$. The pressure is now computed as follows,

$$p = \sum_\sigma p^\sigma = \sum_\sigma \rho_w^\sigma \zeta (1 - \alpha^\sigma), \quad (10)$$

where ζ is a parameter depending on the lattice. For the D2Q9, D3Q19 and D3Q27, we have $\zeta = 3/5$, $\zeta = 1/2$ and $\zeta = 9/19$, respectively [9]. Finally, the Equilibrium enhancement Φ_i^σ is defined as follows,

$$\Phi_i^\sigma = \bar{\nu} \left[\psi_i u_\alpha \partial_\alpha \rho^\sigma + \xi_i c_{i\alpha} c_{i\beta} (u_\alpha \partial_\beta \rho^\sigma + u_\beta \partial_\alpha \rho^\sigma) \right], \quad (11)$$

where we sum over repeated Greek indices. The stencil-dependent constants ψ_i and ξ_i are given in Tabs. (II) and (III), respectively.

We will also need the effective relaxation parameter on the interface. This is computed as follows [9],

$$\begin{aligned} \frac{1}{\bar{\nu}} &= \frac{\rho^\sigma}{\rho} \frac{1}{\nu^\sigma} + \frac{\rho^{\tilde{\sigma}}}{\rho} \frac{1}{\nu^{\tilde{\sigma}}}, \\ \omega^{\text{eff}} &= \frac{2}{6\bar{\nu} + 1}. \end{aligned} \quad (12)$$

Note that this effective collision frequency ω^{eff} will also be used in place of $1/\tau^\sigma$ in the BGK collision operator for both components [16].

The distribution after the original collision step in Eq. (7) is relabeled as $f_i^{\text{coll},\sigma}$. Next, we perform the perturbation step [9],

$$f_i^{\text{pert},\sigma} = f_i^{\text{coll},\sigma} + A |\mathbf{G}| \left(w_i \frac{(\mathbf{G} \cdot \mathbf{c}_i)^2}{|\mathbf{G}|^2} - B_i \right), \quad (13)$$

where $A = \frac{9}{8} \omega^{\text{eff}} \sigma$, with σ as the surface tension. The factors B_i are stencil dependent and are given in Tab. (IV).

$ \mathbf{c}_i ^2$	0	1	2	3
D2Q9	-4/27	2/27	5/108	-
D3Q19	-2/9	1/54	1/27	-
D3Q27	-16/81	2/81	2/81	7/648

TABLE IV. Values for B_i for different lattices [9].

Lastly, we introduce the color gradient $\mathbf{G}$ [9],

$$\mathbf{G} = \nabla \rho^N \approx \frac{1}{c_s^2} \sum_i w_i \rho^N (\mathbf{x} + \mathbf{c}_i) \mathbf{c}_i, \quad (14)$$

with $\rho^N = (\rho^\sigma - \rho^{\tilde{\sigma}})/\rho$. Note that the density gradients in the equilibrium distribution are computed in the same way. Finally, we will perform the recoloring step [17],

$$\begin{aligned} f_i^{*,\sigma} &= \frac{\rho^\sigma}{\rho} \sum_\sigma f_i^{\text{pert},\sigma} + \beta \frac{\rho^\sigma \rho^{\tilde{\sigma}}}{\rho^2} \frac{\mathbf{G} \cdot \mathbf{c}_i}{|\mathbf{G}| |\mathbf{c}_i|} \sum_\sigma f_i^{\text{eq},\sigma} |_{\mathbf{u}=0}, \\ f_i^{*,\tilde{\sigma}} &= \frac{\rho^{\tilde{\sigma}}}{\rho} \sum_\sigma f_i^{\text{pert},\sigma} - \beta \frac{\rho^\sigma \rho^{\tilde{\sigma}}}{\rho^2} \frac{\mathbf{G} \cdot \mathbf{c}_i}{|\mathbf{G}| |\mathbf{c}_i|} \sum_\sigma f_i^{\text{eq},\sigma} |_{\mathbf{u}=0}, \end{aligned} \quad (15)$$

where $\tilde{\sigma}$ is again the low density component. Additionally, the parameter β tunes the interface thickness, for which $\beta = 0.7$ [15] is chosen.

III. MULTI-COMPONENT BOUNDARY CONDITION

The Non-Equilibrium Bounce-Back scheme [2] is a boundary condition based on the wet-node approach. Instead of the more common Half-way Bounce-Back scheme where the boundary fluid nodes are half a node away from the physical wall, the boundary fluid nodes are infinitesimally close to the physical wall in the wet-node approach. The NEBB scheme leaves the populations streaming out of the domain unchanged after streaming. The unknown populations streaming into the domain can be found using the non-equilibrium parts of the populations streaming out of the domain. Additionally, momentum corrections N_α , where α is the spatial component, are introduced [3]. This gives the following boundary condition for the unknown incoming populations i ,

$$\begin{aligned} f_i^{\text{neq},\sigma} &= f_q^{\text{neq},\sigma} - w_i c_{i\alpha} N_\alpha^\sigma, \\ f_i^\sigma &= f_q^\sigma + (f_i^{\text{eq},\sigma} - f_q^{\text{eq},\sigma}) - w_i c_{i\alpha} N_\alpha^\sigma, \end{aligned} \quad (16)$$

where the index q is given by $\mathbf{c}_i = -\mathbf{c}_q$. Furthermore, repeated Greek indices indicate sums. Note that the incoming populations are defined by $\mathbf{c}_i \cdot \hat{\mathbf{n}}_w > 0$, where $\hat{\mathbf{n}}_w$ is the normal vector to the boundary pointing into the domain. The density ρ and the velocity $\mathbf{u}$ are the imposed boundary density and velocity. To conserve mass, we will satisfy the condition that the amount of mass being removed from the domain is equal to the mass added to the domain at every grid point. During the streaming step, the values of the outgoing populations f_q will be overwritten by populations from the bulk, leading to mass loss. The mass gain is given by Eq. (16). This gives the net mass loss at the boundary due to the NEBB method,

$$\begin{aligned} \Delta m^\sigma &= \sum_i^{\text{out}} (f_i^{*,\sigma} - f_i^\sigma) + \sum_i^{\text{in}} w_i c_{i\alpha} N_\alpha^\sigma \\ &= \sum_i^{\text{out}} (f_i^{*,\sigma} - f_i^\sigma) - \rho^\sigma u_n + \frac{1}{2} c_s^2 N_n^\sigma, \end{aligned} \quad (17)$$

where outgoing populations are defined by $\mathbf{c}_i \cdot \hat{\mathbf{n}}_w < 0$. Furthermore, the index n indicates the component normal to the boundary. For a set velocity boundary condition, the densities can be found using the bare velocity components,

$$\begin{aligned} \rho^\sigma u_n^\sigma &= \sum_i^{\text{in}} f_i^\sigma - \sum_i^{\text{out}} f_i^\sigma + \frac{1}{2} F_n^\sigma \\ &= \rho^\sigma - f_0^\sigma - 2 \sum_i^{\text{out}} f_i^\sigma - \sum_i^{\text{par}} f_i^\sigma + \frac{1}{2} F_n^\sigma \\ \rho^\sigma &= \frac{f_0^\sigma + 2 \sum_i^{\text{out}} f_i^\sigma + \sum_i^{\text{par}} f_i^\sigma - \frac{1}{2} F_n^\sigma}{1 - u_n^\sigma}, \end{aligned} \quad (18)$$

where parallel populations are defined as $\mathbf{c}_i \cdot \hat{\mathbf{n}}_w = 0$ with $i \neq 0$. Furthermore, we assume that $|\hat{\mathbf{c}}_i \cdot \hat{\mathbf{n}}_w| = 1$ for $i \neq 0$. The momentum corrections N_α^σ can be computed by plugging the incoming populations from Eq. (16) back into the bare velocity components,

$$\begin{aligned} \rho^\sigma u_\alpha^\sigma &= \sum_i^{\text{in}} f_i^\sigma c_{i\alpha} + \sum_i^{\text{out}} f_i^\sigma c_{i\alpha} + \sum_i^{\text{par}} f_i^\sigma c_{i\alpha} + \frac{1}{2} F_\alpha^\sigma \\ &= \sum_i^{\text{in}} \left(2 w_i \rho^\sigma \frac{\mathbf{u} \cdot \mathbf{c}_i}{c_s^2} - w_i c_{i\beta} N_\beta^\sigma \right) c_{i\alpha} \\ &\quad + \sum_i^{\text{par}} f_i^\sigma c_{i\alpha} + \frac{1}{2} F_\alpha^\sigma. \end{aligned} \quad (19)$$

The normal and parallel components of the momentum corrections can be found,

$$N_\alpha^\sigma = \frac{2}{c_s^2 A_\alpha} \left[\sum_j^{\text{par}} c_{j\alpha} f_j^\sigma + A_\alpha \rho^\sigma u_\alpha - \rho^\sigma u_\alpha^\sigma + \frac{1}{2} F_\alpha^\sigma \right], \quad (20)$$

with $A_\alpha = \frac{2}{c_s^2} \sum_i^{\text{in}} w_i c_{i\alpha}^2$. For the D2Q9, D3Q19 and D3Q27 lattices we have $A_\alpha = \delta_{\alpha n} + \frac{1}{3}(1 - \delta_{\alpha n})$. To correct for the mass loss given in Eq. (17), we add this back to the zero-velocity component before computing the density,

$$\begin{aligned} f_0^\sigma &= f_0^{*,\sigma} + \Delta m^\sigma + \rho^\sigma u_n \\ &= f_0^{*,\sigma} + \sum_i^{\text{out}} (f_i^{*,\sigma} - f_i^\sigma) + \frac{1}{2} F_n^\sigma. \end{aligned} \quad (21)$$

Note that we have a mass loss given by $-\rho^\sigma u_n$. As this is the expected mass flux at the boundary, we do not correct for it. This simplifies the computation of the densities,

$$\rho_w^\sigma = \frac{f_0^{*,\sigma} + \sum_i^{\text{out}} (f_i^{*,\sigma} + f_i^\sigma) + \sum_i^{\text{par}} f_i^\sigma}{1 - u_n^\sigma}. \quad (22)$$

A. Corner Nodes

Corners between two perpendicular NEBB boundaries have to be handled separately. It is not possible to implement the corner node between two velocity boundaries without extrapolating the density. The corner node between a velocity and density boundary can be implemented. Both the incoming and buried populations are now governed by Eq. (16). The incoming populations are given by $(\hat{\mathbf{n}}_1 + \hat{\mathbf{n}}_2) \cdot \mathbf{c}_i > 0$ and the buried populations are given by $(\hat{\mathbf{n}}_1 + \hat{\mathbf{n}}_2) \cdot \mathbf{c}_i = 0$, where the normal vectors of the two intersecting walls are given by $\hat{\mathbf{n}}_1$ and $\hat{\mathbf{n}}_2$. The following equations are obtained after plugging Eq. (16)

into the bare velocity components again,

$$\begin{aligned}\rho^\sigma u_\alpha^\sigma &= \sum_i^{\text{in}} f_i^\sigma c_{i\alpha} + \sum_i^{\text{out}} f_i^\sigma c_{i\alpha} + \sum_i^{\text{buried}} f_i^\sigma c_{i\alpha} + \frac{1}{2} F_\alpha^\sigma \\ &= \rho^\sigma u_\alpha - \frac{1}{2} c_s^2 N_\alpha^\sigma + \frac{1}{2} F_\alpha^\sigma\end{aligned}\quad (23)$$

The momentum corrections are given as follows,

$$N_\alpha^\sigma = \frac{2}{c_s^2} \left[\rho^\sigma (u_\alpha - u_\alpha^\sigma) + \frac{1}{2} F_\alpha^\sigma \right] \quad (24)$$

The buried populations will be used to set the desired wall density,

$$\begin{aligned}\rho^{\text{buried},\sigma} &= \rho^\sigma - \left(f_0^\sigma + \sum_i^{\text{in}} f_i^\sigma + \sum_i^{\text{out}} f_i^\sigma \right), \\ f_i^\sigma &= \frac{w_i}{\sum_j^{\text{buried}} w_j} \rho^{\text{buried},\sigma} + w_i \rho^\sigma \frac{\mathbf{u} \cdot \mathbf{c}_i}{c_s^2} \\ &\quad - \frac{1}{2} w_i c_{i\alpha} N_\alpha^\sigma.\end{aligned}\quad (25)$$

IV. PRESCRIBED CONTACT ANGLE MODELS

To test the new multi-component boundary condition, we will perform a test case of a static droplet on a flat surface. This will test the momentum corrections taking care of external forcing on the surface and the mass corrections are examined.

A. Virtual Density Scheme for Shan-Chen

The Shan-Chen force given in Eq. (3) reaches out of the domain at the boundary nodes. The virtual densities in the solid can be computed using an averaging over the nearby fluid nodes and the contact angle is then controlled using the parameter χ^σ , [18],

$$\rho^{\text{solid},\sigma} = \chi^\sigma \frac{\sum_i^{\text{in}} w_i \rho^\sigma (\mathbf{x} + \mathbf{c} G_i)}{\sum_i^{\text{in}} w_i}, \quad (26)$$

where the incoming directions are defined by $\mathbf{c}_i \cdot \hat{\mathbf{n}}_w > 0$, with the wall normal vector pointing inside the domain. The wetting parameter is given as $\chi^\sigma = 1 - \xi$ and $\chi^{\tilde{\sigma}} = 1 + \xi$, where σ is the fluid making up the droplet. The surface will be hydrophilic for negative ξ and hydrophobic for positive ξ .

B. Geometric Schemes for Color-Gradient

Like for the Shan-Chen method, the computation of the Color-Gradient in Eq. (14) reaches outside the domain. The densities inside the solid are again averaged

from the nearby fluid nodes [19],

$$\rho^{\text{solid},\sigma} = \frac{\sum_i^{\text{in}} w_i \rho^\sigma (\mathbf{x} + \mathbf{c}_i)}{\sum_i^{\text{in}} w_i}. \quad (27)$$

These solid densities are used to compute a preliminary Color Gradient $\mathbf{G}^*$. To impose a given contact angle θ_c at the boundary, we need to change the angle of this vector with respect to the boundary. This can be either changing only the angle of the color gradient while keeping the norm of $\mathbf{G}$ unchanged [10], or by only changing the component of $\mathbf{G}$ normal to the wall [20][21],

$$\begin{aligned}\mathbf{G} &= |\mathbf{G}^*| \hat{\mathbf{n}}(\theta_c), \\ G_{\text{norm}} &= -\tan\left(\theta_c - \frac{1}{2}\phi\right) \sqrt{\sum_\alpha G_{\text{par},\alpha}^2}.\end{aligned}\quad (28)$$

V. ASYMPTOTIC EXPANSION OF LBE

To test the validity of the mass corrected NEBB method, we will need to apply an asymptotic expansion in Knudsen number [22]. The Knudsen number is given as $Kn = \lambda/L$, where λ is the mean free path that decreases with relaxation time τ , and L is the characteristic length scale of the system. For simplicity, we apply the expansion to the single-component Lattice Boltzmann Equation, but now in explicitly dimensional form,

$$\begin{aligned}&\tilde{f}_i(\tilde{\mathbf{x}} + \tilde{\mathbf{c}}_i \Delta \tilde{t}, \tilde{t} + \Delta \tilde{t}) - \tilde{f}_i(\tilde{\mathbf{x}}, \tilde{t}) \\ &= -\frac{\Delta \tilde{t}}{\tilde{\tau}} \left(\tilde{f}_i(\tilde{\mathbf{x}}, \tilde{t}) - \tilde{f}_i^{\text{eq}}(\tilde{\rho}, \tilde{\mathbf{u}}) \right) + \Delta \tilde{t} \tilde{S}_i,\end{aligned}\quad (29)$$

where the dimensional source term is given as follows,

$$\tilde{S}_i = \left(1 - \frac{\Delta \tilde{t}}{2\tilde{\tau}} \right) w_i \left(\frac{\tilde{\mathbf{c}}_i - \tilde{\mathbf{u}}}{\tilde{c}_s^2} + \frac{\tilde{\mathbf{c}}_i \cdot \tilde{\mathbf{u}}}{\tilde{c}_s^4} \tilde{\mathbf{c}}_i \right) \cdot \tilde{\mathbf{F}}. \quad (30)$$

We will now nondimensionalize this equation the length scale $\tilde{L}$, the velocity scale $\tilde{c}$, the timescale $\tilde{t}_0$ and the density scale $\tilde{\rho}_0$. Note that $\tilde{c} = \Delta \tilde{x} / \Delta \tilde{t}$. Furthermore, we introduce the Strouhal number $Sh = \tilde{L} / (\tilde{t}_0 \tilde{c}) = \Delta t / \Delta x$. This gives the nondimensional version of the previous equations,

$$\begin{aligned}&f_i(\mathbf{x} + \mathbf{c}_i \Delta x, t + \Delta t) - f_i(\mathbf{x}, t) \\ &= -\frac{\Delta t}{\tau} \left(f_i(\mathbf{x}, t) - f_i^{\text{eq}}(\rho, \mathbf{u}) \right) + \Delta x S_i, \\ S_i &= \left(1 - \frac{\Delta t}{2\tau} \right) w_i \left(\frac{\mathbf{c}_i - \mathbf{u}}{c_s^2} + \frac{\mathbf{c}_i \cdot \mathbf{u}}{c_s^4} \mathbf{c}_i \right) \cdot \mathbf{F},\end{aligned}\quad (31)$$

where we defined $\tilde{\mathbf{F}} = \tilde{\rho}_0 \tilde{c}^2 / \tilde{L} \mathbf{F}$. We will now introduce diffusive scaling, such that $\Delta t = \mathcal{O}(Kn^2)$ and $\Delta x = \mathcal{O}(Kn)$, implying $Sh = \mathcal{O}(Kn)$. Furthermore, if we choose a finite Reynolds number $\tilde{Re} = \tilde{U} \tilde{L} / \tilde{\nu} = \mathcal{O}(1)$, we get the Mach number $Ma = \tilde{U} / \tilde{c}_s = \mathcal{O}(Kn)$ from the equation $Ma \propto Kn \cdot Re$. Lastly, $\tau = \mathcal{O}(Kn^2)$, which we

will show is required to recover the equilibrium at leading order in Knudsen number. We will now perform a Taylor expansion on the dimensionless LBE,

$$\sum_{n=1}^{\infty} \frac{1}{n!} \left(\Delta x c_{i\alpha} \partial_{\alpha} + \Delta t \partial_t \right)^n f_i = -\frac{\Delta t}{\tau} (f_i - f_i^{\text{eq}}) + \Delta x S_i, \quad (32)$$

We will continue by expanding this equation in order of Knudsen number. We will expand the distribution function, the equilibrium distribution, the density, and the velocity in orders of Knudsen. Note that from the Mach number, we can state that $\mathbf{u}^{(0)} = \mathbf{0}$. Sorted by order in Knudsen, we recover the following equations,

$$\begin{aligned} f_i^{(0)} &= f_i^{\text{eq},(0)}, \\ f_i^{(1)} &= f_i^{\text{eq},(1)} - \frac{\tau}{\Delta t} \left(\Delta x c_{i\alpha} \partial_{\alpha} f_i^{(0)} - \Delta x S_i^{(0)} \right), \\ f_i^{(2)} &= f_i^{\text{eq},(2)} - \frac{\tau}{\Delta t} \left(\Delta x c_{i\alpha} \partial_{\alpha} f_i^{(1)} + \frac{1}{2} \Delta x^2 c_{i\alpha} c_{i\beta} \partial_{\alpha} \partial_{\beta} f_i^{(0)} \right. \\ &\quad \left. + \Delta t \partial_t f_i^{(0)} - \Delta x S_i^{(1)} \right), \\ f_i^{(3)} &= f_i^{\text{eq},(3)} - \frac{\Delta t}{\tau} \left(\Delta x c_{i\alpha} \partial_{\alpha} f_i^{(2)} + \frac{1}{2} \Delta x^2 c_{i\alpha} c_{i\beta} \partial_{\alpha} \partial_{\beta} f_i^{(1)} \right. \\ &\quad \left. + \Delta t \partial_t f_i^{(1)} + \Delta x c_{i\alpha} \partial_{\alpha} \Delta t \partial_t f_i^{(0)} \right. \\ &\quad \left. + \frac{1}{6} \Delta x^3 c_{i\alpha} c_{i\beta} c_{i\mu} \partial_{\alpha} \partial_{\beta} \partial_{\mu} f_i^{(0)} - \Delta x S_i^{(2)} \right). \end{aligned} \quad (33)$$

Here, we expanded the source term and the equations for density and velocity,

$$\begin{aligned} \rho^{(n)} &= \sum_i f^{(n)}, \\ (\rho \mathbf{u})^{(n)} &= \sum_i c_i f_i^{(n)} + \frac{\Delta x}{2} \mathbf{F}^{(n-1)} \end{aligned} \quad (34)$$

The macroscopic equations can be obtained by taking the zeroth and first moments of the expansion in Eq. (33). For simplicity, we will derive these macroscopic equations for $\rho^{(0)} = \text{const}$ and $\mathbf{F}^{(0)} = \mathbf{0}$. We can now compute the zeroth and first moments of the equation for $f^{(2)}$,

$$\begin{aligned} \rho^{(0)} \nabla \cdot \mathbf{u}^{(1)} &= 0, \\ \mathbf{0} &= -\nabla \left(c_s^2 \rho^{(1)} \right) + \mathbf{F}^{(1)} \end{aligned} \quad (35)$$

We can do the same for $f^{(3)}$,

$$\begin{aligned} Sh \partial_t \rho^{(1)} + \nabla \cdot \left(\rho^{(0)} \mathbf{u}^{(2)} + \rho^{(1)} \mathbf{u}^{(1)} \right) &= 0, \\ Sh \rho^{(0)} \partial_t \mathbf{u}^{(1)} + \rho^{(0)} \nabla \cdot \left(\mathbf{u}^{(1)} \mathbf{u}^{(1)} \right) &= \\ -\nabla \left(c_s^2 \rho^{(2)} \right) + \frac{\rho^{(0)}}{Sh} \left[\nu \left(\nabla \mathbf{u}^{(1)} + \left(\nabla \mathbf{u}^{(1)} \right)^T \right) \right] &+ \mathbf{F}^{(2)} \end{aligned} \quad (36)$$

with $\nu = c_s^2(\tau - 1/2)$.

VI. ANALYSIS OF NEBB

To analyze the accuracy of the force-corrected and mass-corrected NEBB method, previous literature usually assumes the lack of a Knudsen layer [7]. This means that this method is used to find out up until which order in Knudsen number the bulk equations for the distribution function fulfill the boundary condition.

However, this method can be shown to be insufficient to assess the accuracy of this boundary condition. To show this, we can for instance show this by inserting the zero-order Knudsen part of the distribution function in Eq. (16), where we now switch to a single-component formulation for simplicity,

$$f_i^{(0)} = f_q^{(0)} - w_i c_{i\alpha} N_i^{(0)}. \quad (37)$$

We can fill in the bulk equation that we got from the asymptotic expansion of the bulk LBE in Eq. (33),

$$0 = -w_i c_{i\alpha} \frac{1}{c_s^2 A_{\alpha}} F_{\alpha}^{(0)}. \quad (38)$$

This equation does not hold for arbitrary forcing, meaning that this method shows that we already have a Knudsen layer at order zero in Knudsen number. However, it is possible that this Knudsen layer only adds to the higher non-hydrodynamic moments. This can be analyzed using a full Knudsen layer analysis. This entails adding a Knudsen layer correction to the total distribution function [22],

$$f_i = f_i^{\text{bulk}} + f_i^{Kn}. \quad (39)$$

We also define the following stretched coordinate,

$$\eta \equiv \frac{\mathbf{x} \cdot \hat{\mathbf{n}}}{Kn}, \quad (40)$$

which is defined to be zero at the boundary. We now impose the matching condition, which states that the Knudsen correction f_i^{Kn} and its moments go to zero faster than any negative power of η [23]. This is done because we expect f_i to approach f_i^{bulk} far away from the boundary. To find the equations for this Knudsen correction to the distribution function close to the boundary, we insert Eq. (39) into Eq (32). We know that f_i^{bulk} satisfies this equation, so we are left with the following equation,

$$\begin{aligned} \sum_{n=1}^{\infty} \frac{1}{n!} \left(\Delta x c_{i\alpha} \partial_{\alpha} + \Delta t \partial_t \right)^n f_i^{Kn} &= -\frac{\Delta t}{\tau} \left(f_i^{Kn} - g_i^{\text{eq}} \right) \\ &\quad + \Delta x T_i, \\ g_i^{\text{eq}} &\equiv f_i^{\text{eq}}(\rho, \mathbf{u}) - f_i^{\text{eq}}(\rho^{\text{bulk}}, \mathbf{u}^{\text{bulk}}), \\ T_i &\equiv S_i(\rho, \mathbf{u}) - S_i(\rho^{\text{bulk}}, \mathbf{u}^{\text{bulk}}). \end{aligned} \quad (41)$$

We defined the densities as follows,

$$\begin{aligned}\rho^{\text{bulk}} &\equiv \sum_i f_i^{\text{bulk}}, \\ \rho^{Kn} &\equiv \sum_i f_i^{Kn}, \\ \rho &\equiv \rho^{\text{bulk}} + \rho^{Kn}.\end{aligned}\quad (42)$$

Furthermore, the velocities are defined as follows,

$$\begin{aligned}\rho^{\text{bulk}} \mathbf{u}^{\text{bulk}} &\equiv \sum_i c_i f_i^{\text{bulk}} + \frac{1}{2} \mathbf{F}, \\ \rho^{Kn} \mathbf{u}^{Kn} &\equiv \sum_i c_i f_i^{Kn}, \\ \rho \mathbf{u} &\equiv \rho^{\text{bulk}} \mathbf{u}^{\text{bulk}} + \rho^{Kn} \mathbf{u}^{Kn}.\end{aligned}\quad (43)$$

For the expansion in Eq. (41), we have to take into account that the spatial derivatives along the boundary normal scale differently and have to be rewritten,

$$\begin{aligned}\sum_{n=1}^{\infty} \frac{1}{n!} \left(\frac{\Delta x}{Kn} c_{in} \partial_\eta + \Delta x c_{ip} \partial_p + \Delta t \partial_t \right)^n f_i^{Kn} = \\ - \frac{\Delta t}{\tau} \left(f_i^{Kn} - g_i^{\text{eq}} \right) + \Delta x T_i.\end{aligned}\quad (44)$$

Like for the bulk distribution function, we can find the zero-order equation,

$$\sum_{n=1}^{\infty} \frac{1}{n!} \left(\frac{\Delta x}{Kn} c_{in} \partial_\eta \right)^n f_i^{Kn,(0)} = - \frac{\Delta t}{\tau} \left(f_i^{Kn,(0)} - g_i^{\text{eq},(0)} \right) \quad (45)$$

Note that the infinite sum in this equation is now exactly equal to a discrete step in space,

$$f_i^{Kn,(0)} \left(\eta + c_{in} \frac{\Delta x}{Kn} \right) - f_i^{Kn,(0)} = - \frac{\Delta t}{\tau} \left(f_i^{Kn,(0)} - g_i^{\text{eq},(0)} \right) \quad (46)$$

We can split this equation up in an equation for the incoming populations ($c_{in} > 0$), outgoing populations ($c_{in} < 0$), and the zero-velocity and parallel populations ($c_{in} = 0$). This gives the following equations,

$$\begin{aligned}f_{i,j+1}^{Kn,(0)} - f_{i,j}^{Kn,(0)} &= - \frac{\Delta t}{\tau} \left(f_{i,j}^{Kn,(0)} - g_{i,j}^{\text{eq},(0)} \right), \quad c_{in} > 0, \\ f_{i,j-1}^{Kn,(0)} - f_{i,j}^{Kn,(0)} &= - \frac{\Delta t}{\tau} \left(f_{i,j}^{Kn,(0)} - g_{i,j}^{\text{eq},(0)} \right), \quad c_{in} < 0, \\ f_{i,j}^{Kn,(0)} &= g_{i,j}^{\text{eq},(0)}, \quad c_{in} = 0,\end{aligned}\quad (47)$$

where we defined $f_{i,j} \equiv f_i \left(j |c_{in}| \frac{\Delta x}{Kn} \right)$. We can also write this in sum form by making use of the boundary condi-

tions at $\eta = 0$ and $\eta \rightarrow \infty$,

$$\begin{aligned}f_{i,j}^{Kn,(0)} &= \frac{\omega}{(1-\omega)} \sum_{k=0}^{j-1} (1-\omega)^{|k-j|} g_{i,k}^{\text{eq},(0)} \\ &\quad + (1-\omega)^j f_{i,0}^{Kn,(0)}, \quad c_{in} > 0, \\ f_{i,j}^{Kn,(0)} &= \frac{\omega}{(1-\omega)} \sum_{k=j+1}^{\infty} (1-\omega)^{|k-j|} g_{i,k}^{\text{eq},(0)}, \quad c_{in} < 0,\end{aligned}\quad (48)$$

with $\omega \equiv \Delta t / \tau$. We now want to plug in the NEBB boundary condition into the incoming populations at $\eta = 0$. The boundary condition for a single fluid component is given as follows,

$$\begin{aligned}f_i &= f_q + (f_i^{\text{eq}} - f_q^{\text{eq}}) - w_i c_{i\alpha} N_\alpha, \\ N_\alpha &= \frac{2}{c_s^2 A_\alpha} \left[\sum_j^{\text{par}} c_{j\alpha} f_j + (A_\alpha - 1) \rho u_\alpha + \frac{1}{2} F_\alpha \right].\end{aligned}\quad (49)$$

We can plug in Eq. (39) into this equation,

$$f_i^{Kn} = f_q^{Kn} - (f_i^{\text{bulk}} - f_q^{\text{bulk}}) + (f_i^{\text{eq}} - f_q^{\text{eq}}) - w_i c_{i\alpha} N_\alpha. \quad (50)$$

At zeroth order in Knudsen number, we are left with the following boundary condition,

$$\begin{aligned}f_i^{Kn,(0)} &= f_q^{Kn,(0)} + \left(g_i^{\text{eq},(0)} - g_q^{\text{eq},(0)} \right) - w_i c_{i\alpha} N_\alpha^{(0)}, \\ N_\alpha^{(0)} &= \frac{1}{c_s^2 A_\alpha} F_\alpha^{(0)}.\end{aligned}\quad (51)$$

A. Mass correction

Furthermore, we need to look at the mass correction step. For a single-component fluid, this is given as follows,

$$\begin{aligned}f_0(t + \Delta t) &= f_0^{\text{LBE}}(t + \Delta t) + \sum_i^{\text{out}} \left(f_i^*(t) - f_i(t + \Delta t) \right) \\ &\quad + \frac{1}{2} F_n(t + \Delta t),\end{aligned}\quad (52)$$

where the star indicates after-collision populations,

$$f_i(\mathbf{x} + \mathbf{c}_i \Delta x, t + \Delta t) = f_i^* \equiv f_i - \frac{\Delta t}{\tau} (f_i - f_i^{\text{eq}}). \quad (53)$$

This gives the following,

$$f_i^*(t) - f_i(t + \Delta t) = \sum_{n=1}^{\infty} \frac{1}{n!} \left(\Delta x c_{i\alpha} \partial_\alpha \right)^n f_i(t + \Delta t). \quad (54)$$

We can rewrite the mass correction,

$$f_0 = f_0^{\text{LBE}} + \sum_i \sum_{n=1}^{\infty} \frac{1}{n!} \left(\Delta x c_{i\alpha} \partial_\alpha \right)^n f_i + \frac{1}{2} F_n. \quad (55)$$

We choose to attribute this change to the distribution solely to the Knudsen layer part f_0^{Kn} , while keeping f_i^{bulk} constant as Navier-Stokes is derived from this. This gives the following equation for the zero-velocity component of the zeroth order Knudsen distribution function at $\eta = 0$,

$$\begin{aligned} f_0^{Kn,(0)} &= g_0^{\text{eq},(0)} + \sum_i^{\text{out}} \sum_{n=1}^{\infty} \frac{1}{n!} \left(\frac{\Delta x}{Kn} c_{in} \partial_\eta \right)^n f_i^{Kn,(0)} + \frac{1}{2} F_n^{(0)} \\ &= g_0^{\text{eq},(0)} - \frac{\Delta t}{\tau} \sum_i^{\text{out}} \left(f_i^{Kn,(0)} - g_i^{\text{eq},(0)} \right) + \frac{1}{2} F_n^{(0)}. \end{aligned} \quad (56)$$

VII. TEST

This can be seen as adding a mass source to the LBE in Eq. (32) for the zero-velocity component,

$$\begin{aligned} f_0(t + \Delta t) - f_0 &= -\frac{\Delta t}{\tau} (f_0 - f_0^{\text{eq}}) + \Delta x S_i + S^{\text{mc}}, \\ S^{\text{mc}} &= \sum_i^{\text{out}} \left(f_i^*(t) - f_i(t + \Delta t) \right) + \frac{1}{2} F_n(t + \Delta t). \end{aligned} \quad (57)$$

This can be written in continuous form,

$$\begin{aligned} \sum_{n=1}^{\infty} \frac{1}{n!} (\Delta t \partial_t)^n f_0 &= -\frac{\Delta t}{\tau} (f_0 - f_0^{\text{eq}}) + \Delta x S_i + S^{\text{mc}}, \\ S^{\text{mc}} &= \sum_i^{\text{out}} \sum_{n=1}^{\infty} \frac{1}{n!} (\Delta x c_{i\alpha} \partial_\alpha)^n f_i + \sum_{n=0}^{\infty} \frac{1}{n!} (\Delta t \partial_t)^n F_n. \end{aligned} \quad (58)$$

We can now write down the boundary condition for the zero-velocity component at zeroth order,

$$f_0^{(0)} = f_0^{\text{eq},(0)} - \frac{\tau}{\Delta t} S^{\text{mc},(0)}. \quad (59)$$

It is obvious that the bulk solution cannot solve this at zeroth order, so we add the Knudsen distribution,

$$\begin{aligned} f_0^{Kn,(0)} &= g_0^{\text{eq},(0)} - \frac{\tau}{\Delta t} \left(\sum_i^{\text{out}} \sum_{n=1}^{\infty} \frac{1}{n!} \left(\frac{\Delta x}{Kn} c_{in} \partial_\eta \right)^n f_i^{Kn,(0)} \right. \\ &\quad \left. + F_n^{(0)} \right) \end{aligned} \quad (60)$$

- [1] J. Latt, B. Chopard, O. Malaspinas, M. Deville, and A. Michler, Straight velocity boundaries in the lattice Boltzmann method, *Physical Review E* **77**, 056703 (2008).
- [2] Q. Zou and X. He, On pressure and velocity boundary conditions for the lattice Boltzmann BGK model, *Physics of Fluids* **9**, 1591 (1997).
- [3] T. Krüger, H. Kusumaatmaja, A. Kuzmin, O. Shardt, G. Silva, and E. M. Viggen, *The Lattice Boltzmann Method: Principles and Practice*, Graduate Texts in

This gives the following equations for the bulk,

$$\begin{aligned} f_0^{\text{bulk},(0)} &= f_0^{\text{bulk,eq},(0)} - \frac{\tau}{\Delta t} S^{\text{mc},(0)}, \\ f_0^{\text{bulk},(1)} &= f_0^{\text{bulk,eq},(1)} - \frac{\tau}{\Delta t} \left(S^{\text{mc},(1)} - \Delta x S_0^{(0)} \right). \end{aligned} \quad (61)$$

With the following expansion for the mass conserving source term,

$$\begin{aligned} S^{\text{mc},(0)} &= \frac{1}{2} F_n^{(0)} (\rho^{\text{bulk}}, \mathbf{u}^{\text{bulk}}), \\ S^{\text{mc},(1)} &= \Delta x c_{i\alpha} \partial_\alpha f_i^{\text{bulk},(0)} + \frac{1}{2} F_n^{(1)} (\rho^{\text{bulk}}, \mathbf{u}^{\text{bulk}}). \end{aligned} \quad (62)$$

The Knudsen layer equation for the zero-velocity population can be found similarly,

$$\begin{aligned} f_0^{Kn,(0)} &= g_0^{\text{eq},(0)} - \frac{\tau}{\Delta t} T^{\text{mc},(0)}, \\ T^{\text{mc},(0)} &= \frac{1}{2} \left[F_n^{(0)} (\rho, \mathbf{u}) - F_n^{(0)} (\rho^{\text{bulk}}, \mathbf{u}^{\text{bulk}}) \right] \\ &\quad + \sum_i^{\text{out}} \sum_{n=1}^{\infty} \frac{1}{n!} \left(\frac{\Delta x}{Kn} c_{in} \partial_\eta \right)^n f_i^{Kn,(0)}. \end{aligned} \quad (63)$$

The issue here is that even though we can transform the infinite sum to a discrete step in space, this step will go outside the domain. Instead, we can write it as follows,

$$\sum_{n=1}^{\infty} \frac{1}{n!} \left(\frac{\Delta x}{Kn} c_{in} \partial_\eta \right)^n f_i^{Kn,(0)} = -\frac{\Delta t}{\tau} \left(f_i^{Kn,(0)} - g_i^{\text{eq},(0)} \right). \quad (64)$$

- Physics (Springer International Publishing, Cham, 2017).
- [4] F. Klass, A. Gabbana, and A. Bartel, A non-equilibrium bounce-back boundary condition for thermal multispeed LBM, *Journal of Computational Science* **53**, 101364 (2021).
- [5] S. Khajepour, J. Cui, M. Dewar, and B. Chen, A study of wall boundary conditions in pseudopotential lattice Boltzmann models, *Computers & Fluids* **193**, 103896 (2019).

- [6] Z. Wang, M. Soomro, C. Peng, L. F. Ayala, and O. M. Ayala, Two pressure boundary conditions for multi-component multiphase flow simulations using the pseudopotential lattice Boltzmann model, *Computers & Fluids* **248**, 105672 (2022).
- [7] M. Junk and Z. Yang, Asymptotic Analysis of Lattice Boltzmann Boundary Conditions, *Journal of Statistical Physics* **121**, 3 (2005).
- [8] X. Shan and H. Chen, Lattice Boltzmann model for simulating flows with multiple phases and components, *Physical Review E* **47**, 1815 (1993).
- [9] S. Leclaire, A. Parmigiani, O. Malaspinas, B. Chopard, and J. Latt, Generalized three-dimensional lattice Boltzmann color-gradient method for immiscible two-phase pore-scale imbibition and drainage in porous media, *Physical Review E* **95**, 033306 (2017).
- [10] Y. Yu, H. Liu, Y. Zhang, and D. Liang, Color-gradient lattice Boltzmann modeling of immiscible two-phase flows on partially wetting surfaces, *Proceedings of the Institution of Mechanical Engineers, Part C: Journal of Mechanical Engineering Science* **232**, 416 (2018).
- [11] S. Chibbaro, L. Biferale, F. Diotallevi, and S. Succi, Capillary filling for multicomponent fluid using the pseudopotential Lattice Boltzmann method, *The European Physical Journal Special Topics* **171**, 223 (2009).
- [12] T. Akai, B. Bijeljic, and M. J. Blunt, Wetting boundary condition for the color-gradient lattice Boltzmann method: Validation with analytical and experimental data, *Advances in Water Resources* **116**, 56 (2018).
- [13] P. L. Bhatnagar, E. P. Gross, and M. Krook, A Model for Collision Processes in Gases. I. Small Amplitude Processes in Charged and Neutral One-Component Systems, *Physical Review* **94**, 511 (1954).
- [14] Z. Guo, C. Zheng, and B. Shi, Discrete lattice effects on the forcing term in the lattice Boltzmann method, *Physical Review E* **65**, 046308 (2002).
- [15] K. P. N. Datadien, *Directional instabilities in micro-droplet jetting: a numerical approach*, Phd Thesis 1 (Research TU/e / Graduation TU/e), Eindhoven University of Technology, Eindhoven (2024), ISBN: 9789038659213.
- [16] J. Tölke, Lattice Boltzmann simulations of binary fluid flow through porous media, *Philosophical Transactions of the Royal Society of London. Series A: Mathematical, Physical and Engineering Sciences* **360**, 535 (2002).
- [17] S. Leclaire, M. Reggio, and J.-Y. Trépanier, Numerical evaluation of two recoloring operators for an immiscible two-phase flow lattice Boltzmann model, *Applied Mathematical Modelling* **36**, 2237 (2012).
- [18] R. C. V. Coelho, C. B. Moura, M. M. Telo da Gama, and N. A. M. Araújo, Wetting boundary conditions for multicomponent pseudopotential lattice Boltzmann, *International Journal for Numerical Methods in Fluids* **93**, 2570 (2021), eprint: <https://onlinelibrary.wiley.com/doi/pdf/10.1002/flid.4988>.
- [19] S. Zhang, J. Tang, and H. Wu, Simplified wetting boundary scheme in phase-field lattice Boltzmann model for wetting phenomena on curved boundaries, *Physical Review E* **108**, 025303 (2023).
- [20] H. Ding and P. D. M. Spelt, Wetting condition in diffuse interface simulations of contact line motion, *Physical Review E* **75**, 046708 (2007).
- [21] S. Zhang, J. Tang, and H. Wu, Wetting boundary schemes in modified phase-field lattice Boltzmann method for binary fluids with large density ratios, *Computers & Mathematics with Applications* **113**, 243 (2022).
- [22] T. Inamuro, M. Yoshino, and F. Ogino, Accuracy of the lattice Boltzmann method for small Knudsen number with finite Reynolds number, *Physics of Fluids* **9**, 3535 (1997).
- [23] Y. Sone, *Kinetic Theory and Fluid Dynamics*, edited by N. Bellomo, Modeling and Simulation in Science, Engineering and Technology (Birkhäuser, Boston, MA, 2002).