

TW-006 STUDENT VERSION



CLARUSWAY
WAY TO REINVENT YOURSELF

Meeting Agenda

- ▶ Icebreaking
- ▶ Questions
- ▶ Interview Questions
- ▶ Coding Challenge
- ▶ Video of the week
- ▶ Retro meeting
- ▶ Case study / project

Teamwork Schedule

Ice-breaking

5m

- Personal Questions (Study Environment, Kids etc.)
- Any challenges (Classes, Coding, studying, etc.)
- Ask how they're studying, give personal advice.
- Remind that practice makes perfect.

Team work

5m

- Ask what exactly each student does for the team, if they know each other, if they care for each other, if they follow and talk with each other etc.

Ask Questions

15m

1. In the code below, what is the purpose of the *id* attribute?

```
<p id="warning">Be careful when installing this product.</p>
```

- A. It establishes that id is a unique identifier in the document, used for styling CSS, scripting, and linking within a webpage.
- B. It establishes that id is a unique identifier in the document, used for styling CSS and with Javascript code.
- C. It establishes that id may be used for styling CSS several times per page.
- D. It establishes that id is a unique identifier in the website, used for styling CSS, scripting, and linking within a webpage.

2. What do media queries allow us to do?

- A. Stream video on our site.
- B. Use different CSS based on screen size.
- C. Do responsive design.
- D. Changes all document sizes and feature.

3. What is the difference between `<input type="submit" value="click me">` and `<button type="submit">Click me</button>`?

- A. There is no difference. Both will render a button that submits a form.
- B. Both will submit a form. However, the `<button>` can have content other than text, like an image or nested HTML elements, while the `<input>` cannot.
- C. `<input type="button">` has been deprecated in HTML5. You should use the `<button>` tag instead.
- D. Both will submit a form. However, the `<input>` can have content other than text, like an image or nested HTML elements, while the `<button>` cannot.

4. You're adding error handling to the code shown. Which code would you include within the if statement to specify an error message?

```
function addNumbers(x, y){  
  if (isNaN(x) || isNaN(y)) {  
    }  
}
```

- A. `exception('One or both parameters are not numbers')`
- B. `catch('One or both parameters are not numbers')`
- C. `error('One or both parameters are not numbers')`
- D. `throw('One or both parameters are not numbers')`

5. Review the code below. Which statement calls the `addTax` function and passes 50 as an argument?

```
function addTax(total) {  
  return total * 1.05;  
}
```

- A. `addTax = 50;`
- B. `return addTax 50;`
- C. `addTax(50);`
- D. `addTax 50;`

6. Which of the following operators can be used to do a short-circuit evaluation?

- A. `++`
- B. `--`
- C. `.-+`
- D. `||`

7. Which variable is an implicit parameter for every function in JavaScript?

- A. Arguments
- B. args
- C. argsArray
- D. argsList

Interview Questions**15m****1. Can you tell us some limitations of JavaScript?****2. Can you tell us about the errors in JavaScript?****3. Is JavaScript case-sensitive?****4. How to use a prompt box in JS?****5. What are all the looping structures in JavaScript?****6. Explain the difference between "==" and "==="?****Coding Challenge****20m**

- [Coding Challenge: CC-03 Merge Arrays](#)

**Coffee Break****10m**

Video of the Week

5m

- [JavaScript Frameworks](#)

Retro Meeting on a personal and team level

5m

Ask the questions below:

- What went well?
- What could be improved?
- What will we commit to do better in the next week?

Case study/Project

15m

Case study should be explained to the students during the weekly meeting and has to be completed in one weeks by the students. Students should work in small teams to complete the case study.

- [Web site Page Design](#)

JavaScript Projects will be introduced at the project week startup session on Friday 11th, Feb.

Closing

5m

-Next week's plan

-QA Session
