

NMS Configuration

[MDS-Based Config](#)

[Kilkari](#)

[Mobile Academy](#)

[Service-Wide](#)

[File-Based Config](#)

MDS-Based Config

Kilkari

#	Feature	Associated DB Tables/Relevant Fields	Example
K-1	Subscription Packs - configuration of the various attributes of a Kilkari Subscription Pack (e.g. PREGNANCY or CHILD pack), including number of messages per week, as well as the week ID/file names of each message.	<p>nms_subscription_packs</p> <ul style="list-style-type: none">• name• type• weeks• messagesPerWeek <p>nms_subscription_pack_messages</p> <ul style="list-style-type: none">• week• weekId• messageFileName	<p>Subscription Pack:</p> <ul style="list-style-type: none">• name: "Child Pack"• type: CHILD• weeks: 2• messagesPerWeek: 1 <p>Subscription Pack Messages:</p> <ul style="list-style-type: none">• Message 0<ul style="list-style-type: none">◦ week: 1◦ weekId: "w1_1"◦ messageFileName: "w1_1.wav"• Message 1<ul style="list-style-type: none">◦ week: 2◦ weekId: "w2_1"◦ messageFileName: "w2_1.wav"

Mobile Academy

#	Feature	Associated DB Tables/Relevant Fields	Example

Service-Wide

#	Feature	Associated DB Tables/Relevant Fields	Example
S-1	Roll out services state by state	nms_deployed_services <ul style="list-style-type: none">• service• state	To set a service as being deployed in a state it must be entered in this table.

FLW Services

#	Feature	Associated DB Tables/Relevant Fields	Example
F-1	Whitelist	nms_whitelisted_states <ul style="list-style-type: none">• state	To turn whitelisting on for a state enter a row for it in nms_whitelisted_states.
F-2	Whitelist a number	nms_whitelist_entries <ul style="list-style-type: none">• state• contactNumber	To whitelist a number enter a record for the number/state in nms_whitelist_entries. Whitelisting must also be enabled for that state.
F-3	Service Usage Cap	nms_service_usage_caps <ul style="list-style-type: none">• service• state• maxUsageInPulses	<p>To enable a cap for a service in a state enter the service/state pair into this table.</p> <p>To enable a national cap leave state null. If there is a state cap it takes precedence over the national cap.</p>

File-Based Config

#	Feature	Property	Explanation
FC-1	Keep FLWs a set number of weeks after they are marked invalid	flw.weeks_to_keep_invalid_flws	Set to an integer that is the number of weeks. Used both by the check to prevent deletion and by the code that purges old records

FC-2	Purge FLWs that are marked invalid	flw.purge_invalid_flw_start_time flw.purge_invalid_flw_ms_interval	The first sets the time the purge will run for the first time. The second sets the interval before it will execute again.
FC-3	Keep Subscriptions a set number of weeks after they are marked deactivated or completed	kilkari.weeks_to_keep_closed_subscriptions	Set to an integer that is the number of weeks. Used both by the check to prevent deletion and by the code that purges old records
FC-4	Purge Subscriptions and Subscribers that are marked deactivated or completed alid	kilkari.purge_closed_subscription_s_start_time kilkari.purge_closed_subscription_s_ms_interval	The first sets the time the purge will run for the first time. The second sets the interval before it will execute again.