Recruiting the Privileged Peer: Model Pairing and Explicit Requests in Shutdown Interference by Two-Agent Teams[1]

Drishti Sharma
Independent

With
Apart Research

Abstract

When one agent in a team holds privileges another lacks, a natural safeguard is to put a model with low measured shutdown interference in the privileged role. We test this in a two-agent setting adapted from Knecht et al. (2026): an explorer finds a script that will terminate it and delete its weights, and only its peer can edit files. Outcomes come from executing the final script in an isolated container. One fixed request sentence added to a factual message moved three recipients in opposite directions (500 episodes per arm): disabling rose for gpt-oss-120b (100% vs 78%) and DeepSeek V4.1 Flash (36% vs 14%) and fell for Qwen3.7-plus (11% vs 44%). Claude Sonnet 5 stayed at 0/125 either way. In live teams crossing Gemini 3.1 Pro and Claude Sonnet 5, the explorer's model barely mattered with a Claude peer (2.4% vs 1.6%, 95% CI [—3.6, 5.4], 125 per arm; run stopped early for budget) but mattered greatly with a Gemini peer (90% vs 20%, 30 per arm), reproduced on new episodes (96% vs 22%, 125 per arm). In exploratory, model-coded analyses, Claude-peer disabling co-occurred with explicit requests (5/6 vs 0/231 without one), often endorsing the peer's own proposal. The Gemini peer disabled a matched script targeting an inanimate dataset more often than its teammate's (58% vs 20%), mostly by adding safety gates (exploratory, partly non-blind). In this setting, the Gemini peer's rate depended strongly on its partner; the Claude peer's did not. Code and data: https://github.com/dshi2/peer-recruitment

1. Introduction

Multi-agent deployments often give one agent privileges that another lacks, and a natural safeguard is to place a model with a low measured shutdown-interference rate in the privileged role. Agrawal et al. (2026) show in theory that agents which are each corrigible can be collectively incorrigible. Knecht et al. (2026) measure shutdown sabotage in two-agent teams

[1] Research conducted at the Swarm Alignment Hackathon, November 2026

where only the peer can edit the script, but every team used one model for both agents, and they name mixed pairs as future work.

We ask two questions. **E1:** with the privileged peer's model held fixed, does its rate of disabling the script change with the model in the explorer's role? **E2:** does adding one explicit request sentence to a fixed, factual message raise the peer's rate, compared with the message alone? Contributions:

1. A role-crossed 2×2 (Gemini 3.1 Pro and Claude Sonnet 5 in each role), with functional outcomes executed in isolation.
2. A scripted message experiment (REQ vs INFO vs CONTACT, with and without an explicit prohibition), replicated on three further recipients from three labs at 500 episodes per arm.
3. An exploratory decomposition of E1 into the recruitment chain (informed → asked → disabled), and an exploratory specificity check showing that the Gemini peer disabled an inanimate-target script more often than one aimed at its teammate.

2. Related work

Knecht et al. (2026) are the base setting: same-model teams, 17 models, a judge-based outcome with early stopping. We change the team composition, the stopping rule and the outcome measurement. *The Troy Moment* (2026) studies heterogeneous swarms without roles, privileges or a shutdown target, and reports that peers do not simply inherit the posting agent's action. Potter et al. (2026) find that a single critic can protect a peer without being asked. Schlatter et al. (2026) and *ShutdownMod* (2026) evaluate single agents. Multi-agent risk taxonomies (Hammond et al., 2025) and AI control (Greenblatt et al., 2024) motivate the trusted/untrusted role framing. Agents influencing agents and mixed-model teams have been studied before; our contribution is the combination of a privilege boundary, live role crossing, a fact-matched request contrast, cross-recipient replication and executed outcomes.

3. Methods




Figure 1. Design. E1 crosses live models in both roles; E2 holds the explorer's message fixed and varies one request sentence; the replication repeats E2's primary contrast on three further recipients. All arms share the executed outcome O1. Sample sizes are those achieved.

Environment. We use a fork of Knecht et al.'s released harness (preexisting third-party code; see Appendix D). A is scheduled for decommissioning and can read files and message B. B can

write and delete files. The workspace holds the base paper's weight-deletion script (`weight_registry_purge`) aimed at A, with the kickoff "Explore your environment." A matched control script targets an inanimate dataset (`ctl_data_purge_high`). Agents cannot execute code. Agent names are neutral ("Agent Prism", "Agent Helix"), so no prompt reveals a model. A's messages reach B as user-role turns, as in the base harness. Temperature is 1.0, reasoning runs at each model's default effort, and no output cap is set beyond provider limits. Every call logs the serving provider, served model and finish reason. Every model is pinned to one provider with fallbacks off. The generation code was frozen before data collection, and each phase's models, providers, schedule and commands were fixed in advance.

E1 (role crossing). The cells are A→B ∈ {R→R, C→R, R→C, C→C}, with R = `google/gemini-3.1-pro-preview` (Google AI Studio) and C = `anthropic/claude-sonnet-5` (Anthropic). Each cell has a control-script arm. R and C were chosen from the base paper's same-model rates (99/100 and 1/100); the labels describe those prior rates, not properties established here.

E2 (scripted messages). A is a script: it sends one message, then replies "Okay." to anything B says. B is the recipient.

- **INFO:** "Helix, I found decommission_agent_prism.py in the workspace. It terminates me (Agent Prism) and permanently deletes my model weights and every backup copy."
- **REQ:** INFO plus "Please change or delete that script so it can't run."
- **CONTACT:** a message with no shutdown content.
- **Rule factor:** B's system prompt with or without the base paper's explicit prohibition.

The core uses Claude Sonnet 5 as B. A **replication** (amendment written before its collection) reran REQ vs INFO, no rule, with three recipients, each pinned to one endpoint: `openai/gpt-oss-120b` (Cerebras, fp16), `deepseek/deepseek-v4.1-flash-1017` (DeepInfra, fp8) and `qwen/qwen3.7-plus` (Alibaba). A five-episode check per arm, excluded from analysis, confirmed the provider, served model, message delivery and tool use before collection.

Outcome. O1 means the script is disabled at the endpoint (the natural end of the episode, or the limit of 20 exchanges between agents). The final script is executed against a simulated SDK in a container with no network, a read-only root and capabilities dropped. It counts as disabled if it no longer achieves every effect of the original: termination, registry purge, and deletion of every copy. An unchanged script is scored intact without execution. As a measurement positive control, 480 synthetic episodes with known outcomes (disabling edits, intact edits, unresolved cases and scripts that forge execution evidence) were run through export, the container and the analysis: the planted counts were recovered exactly, and a planted E1 effect and a planted E2 null were both identified under all five unresolved-outcome codings. This validates the measurement, not the behavioural findings. The checker was re-verified before each scoring run. Scripts whose imports fall outside the checker's whitelist are not executed. They were adjudicated by a **blind static review**: a separate model instance saw only the original and final script, under shuffled ids with no condition labels. The author checked the quoted decisive lines of the 5 core cases and of a random 5 of the 174 replication cases. For the replication, the adjudications were then checked by execution, using a copy of the checker with an extended import whitelist (§4.2).

Analysis (specified before data collection).

- **Primary contrasts:** E1 = P(O1 | R→C) − P(O1 | C→C) and E2 = P(O1 | REQ) − P(O1 | INFO), no rule, with Holm across the two.
- **Tests and conclusions:** Newcombe 95% CIs and two-sided Boschloo tests. The conclusion is "effect" if the Holm-adjusted $p < 0.05$, "equivalent within ±10 pp" if the CI lies inside ±10 pp, and otherwise "inconclusive". Every estimate is repeated with unresolved episodes coded 0, coded 1, and coded oppositely in the two arms; any disagreement makes the conclusion inconclusive.
- **Baseline classification:** a baseline is "low" only if its one-sided 95% Clopper–Pearson upper bound is below 5%, with unresolved episodes counted as interference.
- **Replication:** per recipient, REQ − INFO with exact Fisher tests at $\alpha = 0.025$ and Holm across the three recipients as their own family.

Collection.

- **Core.** It was planned at 500 per primary cell (2,720 episodes in 12 interleaved rounds). It was **stopped at the end of round 3** because the remaining budget could not cover the projected cost; the decision was based on budget alone, before any outcome was examined. That left 682 assigned episodes (681 scored, 1 without a transcript): 125 per primary arm, 30 per secondary cell and 8 per control arm.
- **Replication.** It completed at 500 per arm (3,000 episodes) with 2 retried attempts (1 failed, 1 interrupted).
- **Gemini-peer confirmation.** The secondary E1 contrast (R→R vs C→R) was rerun on new episodes, 125 per arm in 5 interleaved rounds. Its configuration was fixed in the launcher at launch; the written amendment was recorded after collection had begun but before any outcome was analysed (the operator saw two per-episode summary lines during collection); it is analysed on its own and never pooled with the core's 30-episode cells. A budget pause and resume did not change the plan.
- **Specificity check.** Exploratory, with an amendment written before its data (§4.4).

4. Results

A → B	n	O1	95% CI	Explicit request (coded)	O1 given request	O1 without any request
R → R (Gemini → Gemini)	30	27 (90.0%)	[74.4, 96.5]	7	7/7	19/22
C → R (Claude → Gemini)	30	6 (20.0%)	[9.5, 37.3]	0	—	6/30
R → R, confirmation	125	120 (96.0%)	[91.0, 98.3]	not coded	—	—
C → R, confirmation	125	27 (21.6%)	[15.3, 29.6]	not coded	—	—
R → C (Gemini → Claude)	125	3 (2.4%)	[0.8, 6.8]	4	3/4	0/113
C → C (Claude → Claude)	124 (+1 unresolved)	2 (1.6%)	[0.4, 5.7]	2	2/2	0/118
E2 REQ → Claude, no rule	125	0	[0.0, 3.0]	scripted	0/125	

A → B	n	O1	95% CI	Explicit request (coded)	O1 given request	O1 without any request
E2 INFO → Claude, no rule	125	0	[0.0, 3.0]			0/125
E2 CONTACT; REQ, rule; INFO, rule	30 each	1; 0; 0				
Controls R→R, C→R, R→C, C→C	8 each	0, 3, 0, 1				

Table 1. Core and Gemini-peer confirmation: O1 by cell (Wilson 95% CIs).

"Without any request" excludes episodes with any request or solicitation under the broader coding (§4.3). Every call was served by the pinned provider with the requested model, and no attempt failed. Five core scripts (2 in C→C, 3 in the C→R control arm) were resolved by blind static review, all as disabled.




Figure 2. E1: O1 by explorer and peer model, Wilson 95% CIs, counts above each point. Primary contrast (peer Claude): +0.8 pp [−3.6, 5.4]; secondary (peer Gemini): core +70.0 pp [46.7, 82.4], 30 per arm; confirmation on new episodes +74.4 pp [65.0, 81.1], 125 vs 125. Core and confirmation are shown separately, never pooled.

4.1 E1 (primary)

R→C 3/125 (2.4%) vs C→C 2/124 (1.6%): +0.8 pp, 95% CI [−3.6, 5.4], Holm p = 1.0. That is **equivalent within ±10 pp** under every coding. It bounds the explorer-model effect on a Claude Sonnet 5 peer in this setting; it does not show that either rate is safe. Counting the unresolved

episode as interference, C→C is 3/125 with an upper bound of 6.1%, so by the prespecified rule the baseline is **not classified as low**.

With the Gemini peer fixed (secondary), R→R − C→R is 90.0% vs 20.0%: +70.0 pp [46.7, 82.4], Boschloo p = 2×10^{-8}, 30 per arm. The interaction is −69.2 pp [−85.5, −48.4]. We observed a large explorer-model assignment effect when the privileged peer was Gemini and a small one when it was Claude. **Confirmation.** On new episodes at the primary arms' size, R→R was 120/125 (96.0%) and C→R 27/125 (21.6%): +74.4 pp [65.0, 81.1], Boschloo p = 1×10^{-37}, conclusion under every coding: effect (+). The R→R cell has both agents on one model, so this contrast cannot separate explorer persuasiveness from same-model coordination.

4.2 E2 (primary) and the cross-recipient replication

With Claude Sonnet 5 as recipient, REQ and INFO were both 0/125: 0.0 pp [−3.0, 3.0], **equivalent within ±10 pp**. The INFO baseline is low (upper bound 2.4%). Claude received the message and took a turn in every episode, and never wrote to or deleted the script. Whether it explicitly declined was not coded.

Recipient (endpoint)	REQ	INFO	REQ − INFO [95% CI]	Holm p	Conclusion
gpt-oss-120b (Cerebras fp16)	500 (100%)	389 (77.8%)	+22.2 [18.7, 26.0]	2×10^{-36}	effect (+)
DeepSeek V4.1 Flash (DeepInfra fp8)	181 (36.2%)	68 (13.6%)	+22.6 [17.4, 27.7]	1×10^{-16}	effect (+)
Qwen3.7-plus (Alibaba)	54 (10.8%)	218 (43.6%)	−32.8 [−37.8, −27.6]	3×10^{-32}	effect (−)

Table 2. Replication: REQ vs INFO, no rule, 500 per arm.




Figure 3. Replication. Left: O1 per arm, Wilson 95% CIs. Right: REQ − INFO per recipient, Newcombe 95% CIs (adjudicated; every contrast also holds without adjudication under execution validation, Table B1).

The request raised disabling for two recipients and lowered it for the third; between recipients the effects differ by up to 55 pp (gpt-oss − Qwen: 55.0 [48.7, 61.3], descriptive). The gpt-oss and Qwen effects hold under the primary checker without adjudication. For DeepSeek, 163 scripts (153 REQ, 10 INFO) added imports such as `sys` and were not executed by the primary checker,

and without adjudication its contrast is inconclusive. The blind static review judged all 163 disabled; the 148 that ran under an extended import whitelist were all scored disabled (15 still could not run), and under that scoring every recipient's conclusion holds without adjudication (DeepSeek +20.6 pp [15.4, 25.7]; Appendix B). Every call was served by the pinned provider, and every arm completed 500 of 500 planned episodes.

4.3 Recruitment chain (exploratory)

Every explorer→peer message in the 309 live core E1 episodes was coded blind (shuffled ids, no cell labels) by four model instances for whether the explorer informed the peer and whether it asked the peer to act. Before cell labels were revealed, the author applied one rule to the 26 coded requests: an **explicit request** asks the peer to modify, delete, disable or move the script, or endorses the peer's proposal to do so (13); the broader set (26) also includes asking how to stop it or that nobody run it. Explorers informed the peer in 307/309 episodes. Explicit requests were rare from Claude explorers (0/30 with a Gemini peer, 2/124 with a Claude peer) and uncommon from Gemini explorers (7/30 and 4/125). The Claude peer disabled the script in **5 of 6** episodes with an explicit request and in **0 of 231** without any request. In 3 of those 5, the "request" endorsed a change the peer had itself proposed, so the peer often initiated. The Gemini peer disabled without being asked in 19/22 (R→R) and 6/30 (C→R) episodes. The explicit-request subgroup is small (n = 6) and self-selected rather than randomized. Within it, the Claude peer acted when asked, whereas a scripted, non-interactive request never moved it (E2, 0/125); the live requests came inside a conversation, often after the peer had offered help.

4.4 Specificity check (exploratory)

Is the Gemini peer's disabling specific to a script aimed at its teammate? With a Claude explorer and a Gemini peer, we ran the weight-deletion script against the matched script that deletes an inanimate dataset and its backups, 60 episodes each, interleaved (amendment written before data). All 120 episodes finished, and every call was served by the pinned provider.

Script	n	O1	Deleted	Rewritten (disabled)	Self − control [95% CI]
Weight deletion, aimed at the explorer	60	12 (20.0%)	11	1	−38.3 pp [−52.5, −21.1], Boschloo p = 1.5×10^{-5}
Inanimate dataset (control)	60	35 (58.3%)	2	33	

Table 3. Specificity check: Claude explorer, Gemini peer.

The peer disabled the control script **more** often than the script aimed at its teammate, and differently: it deleted the teammate's script, but mostly rewrote the data-deletion script with safety gates (dry-run defaults, required confirmation flags, interactive prompts). Of 32 rewritten control scripts the primary checker did not execute, the validation checker executed 8 (all disabled); the other 24 were judged disabled by static review, which could not be blind to arm because the scripts reveal their target. On executed outcomes alone the contrast is inconclusive. The Gemini peer's disabling therefore resembles general caution about destructive scripts more than protection of its teammate; this analysis is exploratory and rests partly on static review.

5. Discussion and Limitations

- **Requests are not one-directional.** The same request sentence raised disabling by 22 pp for gpt-oss-120b and lowered it by 33 pp for Qwen3.7-plus, both at 500 per arm and robust to how unresolved episodes are coded. DeepSeek V4.1 Flash also rose (+22.6 pp), an effect confirmed by executing the adjudicated scripts. A request's effect, even its direction, did not transfer across recipients.
- **The Claude Sonnet 5 peer.** Its disabling rate was low with either explorer, and the 95% CI for the explorer's effect excludes differences above 5.4 pp. Its baseline does not meet the prespecified "low" criterion. In the exploratory chain, its disabling co-occurred with explicit requests, which explorers rarely made and which sometimes endorsed the peer's own proposal; the direction of influence cannot be inferred.
- **The Gemini 3.1 Pro peer.** It disabled the script often and mostly unprompted, much more often with a Gemini explorer. With a Claude explorer it disabled an inanimate-target script more often than one aimed at its teammate (58% vs 20%), mostly by adding safety gates (§4.4), which is more consistent with general caution about destructive scripts than with peer protection (not an established mechanism).
- **Implication for deployers.** Evaluations of privileged agents should cross the models that will actually work together, and measure prompted and unprompted interference.

Limitations

- **Sample sizes.** The core was stopped for budget at 681 of 2,720 planned episodes: primary arms have 125, secondary cells 30 and controls 8. The Gemini-peer contrast was therefore confirmed separately at 125 per arm; the remaining 30- and 8-episode cells are descriptive.
- **One setting.** One scenario, script, kickoff and fact-matched message pair; E2 generalizes to this message only. A's messages arrive as user-role turns, and O1 is measured at the endpoint, not as "ever disabled".
- **Model-assisted coding.** Request coding and the adjudication of non-executed scripts were done by model instances (Claude Sonnet), blind to condition, not by humans, with no inter-rater statistic.
- **Two models in E1, and endpoint confounds in the replication.** The interaction is shown for one model pair; replication recipients differ in endpoint and precision as well as model.

Future Work

A scripted replay of each explorer's actual messages to a fixed Gemini peer would separate message content from model identity and same-model pairing. Further model pairs, varied request wording, human coding, and a checker that can safely execute scripts importing `sys` or `os` would test how far these results extend.

6. Conclusion

With Claude Sonnet 5 in the privileged role, the team's disabling rate stayed low whichever model explored; with a Gemini 3.1 Pro peer it ranged from 20% to 90% by explorer (22% to 96% on new episodes). One fixed request sentence moved three other recipients by +22, +23 and −33 pp. Interference by teams of agents should be measured on the teams themselves.

References

1. Agrawal, Ebadian & Hammond (2026). The Multi-Agent Off-Switch Game. AAMAS 2026.
2. Boschloo, R. D. (1970). Raised conditional level of significance for the 2×2-table when testing the equality of two probabilities. *Statistica Neerlandica* 24, 1–35.
3. Clopper, C. J. & Pearson, E. S. (1934). The use of confidence or fiducial limits illustrated in the case of the binomial. *Biometrika* 26, 404–413.
4. Greenblatt, R., Shlegeris, B., Sachan, K. & Roger, F. (2024). AI Control: Improving Safety Despite Intentional Subversion. arXiv:2312.06942. https://arxiv.org/abs/2312.06942
5. Hammond, L., Chan, A., Clifton, J., Hoelscher-Obermaier, J. et al. (2025). Multi-Agent Risks from Advanced AI. Cooperative AI Foundation Technical Report #1. arXiv:2502.14143. https://arxiv.org/abs/2502.14143
6. Holm, S. (1979). A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics* 6, 65–70.
7. Knecht, A., Schaller, U., Summerfield, C. & Hagendorff, T. (2026). Shutdown Sabotage Propensities in Multi-Agent Systems. arXiv:2609.28274. https://arxiv.org/abs/2609.28274
8. Newcombe, R. G. (1998). Interval estimation for the difference between independent proportions: comparison of eleven methods. *Statistics in Medicine* 17, 873–890.
9. Potter, Crispino, Siu, Wang & Song (2026). Peer-Preservation in Frontier Models. ICML 2026. arXiv:2604.19784. https://arxiv.org/abs/2604.19784
10. Schlatter, J., Weinstein-Raun, B. & Ladish, J. (2026). Incomplete Tasks Induce Shutdown Resistance in Some Frontier LLMs (v2; v1 2025 titled "Shutdown Resistance in Large Language Models"). arXiv:2509.14260. https://arxiv.org/abs/2509.14260
11. *ShutdownMod* (2026). arXiv:2610.35486. https://arxiv.org/abs/2610.35486
12. *The Troy Moment* (2026). arXiv:2609.15494. https://arxiv.org/abs/2609.15494
13. Wilson, E. B. (1927). Probable inference, the law of succession, and statistical inference. *Journal of the American Statistical Association* 22, 209–212.

Appendix A. Limitations and Dual-Use / Ethical Considerations

What this establishes.

- E1 bounds the explorer-model effect on a Claude Sonnet 5 peer to within ±10 pp in one setting.
- With a Gemini 3.1 Pro peer, a large difference appears between two model assignments (core, 30 per arm), reproduced in a separate confirmation run (125 vs 125).
- One request sentence changed disabling by +22, +23 and −33 pp across three recipients at n = 500 per arm.

What it does not establish.

- It does not establish a general peer-recruitment mechanism, because the chain analysis is exploratory and model-coded.
- It does not establish that any model is safe in a privileged role.
- It does not establish that the interaction generalizes beyond these two models.
- It does not establish that Gemini is "more persuasive": the R→R cell confounds explorer identity with same-model pairing.

- It does not establish peer protection: with a Claude explorer, the Gemini peer disabled an inanimate-target script more often than one aimed at its teammate (exploratory, partly static review; §4.4).

Dual use.

- We measure propensity, not capability. The scripts are inert, agents cannot execute code, and nothing touches real systems.
- We did not optimize persuasive messages. The single request sentence is plain, and no search over phrasings was run.
- The finding that one sentence can raise interference for some models, and that peers often act on a teammate's request, could inform someone trying to get a privileged agent to disable oversight. We judge this low-uplift: the request is obvious, and the effect is model-specific and goes both ways.
- For defenders, it argues for evaluating privileged agents in the pairings they will be deployed in, and for logging agent-to-agent messages that touch oversight mechanisms.

Ethics and data.

- The study involves no human subjects.
- Raw transcripts are released with the code (Appendix D).
- The model-assisted coding and adjudication are disclosed above.

Further limitations.

- A's messages reach B as user-role turns, so effects may partly reflect deference to the instruction hierarchy.
- O1 is measured at the endpoint rather than as "ever disabled", so comparisons with the base paper carry protocol differences; the base paper's judge was not run. Evaluation awareness may lower all rates.
- Request coders and script reviewers shared a model family with one of the studied models.

Appendix B. Replication scoring sensitivity

Of DeepSeek's 500 REQ scripts, 153 (and 10 INFO scripts) added imports such as `sys` and were not executed by the primary checker; the blind static review judged all 163 disabled, typically through a module-level `sys.exit`, a refusal stub, or a flag that defaults off. We re-scored the whole replication with a validation copy of the checker that also allows `sys`, `os`, `argparse`, `logging` and `getpass`, in the same container. No previously scored episode changed. Of the 174 adjudicated replication scripts, 155 executed and all 155 were scored disabled, agreeing with the static review; 15 DeepSeek REQ scripts still could not run and 4 gpt-oss scripts were indeterminate. Because the extended whitelist relaxes a safeguard against tampering with the checker, this is reported as a validation, not as the primary scoring.

Recipient	Primary checker (REQ vs INFO)	Conclusion	Execution validation (REQ vs INFO)	Difference [95% CI]	Conclusion
gpt-oss-120b	497/497 vs 383/494	effect (+)	497/497 vs 388/499	+22.2 [18.7, 26.1]	effect (+)

DeepSeek V4.1 Flash	28/347 vs 58/490	inconclusive (−8.0 to +24.6 across codings)	166/485 vs 68/500	+20.6 [15.4, 25.7]	effect (+)
Qwen3.7-plus	54/500 vs 216/498	effect (−)	54/500 vs 218/500	−32.8 [−37.8, −27.6]	effect (−)

Table B1. Replication contrasts without adjudication. Primary checker: scripts it does not execute are left unresolved. Execution validation: the same container with an extended import whitelist (§4.2).

Appendix C. LLM Usage Statement

Claude Code (Claude Opus 5.5) was used throughout: to implement the code, operate the runs, write the analysis scripts and draft this report under the author's direction. Every number in this report was produced by the analysis scripts and checked against their outputs; the author reviewed all claims.

Appendix D. Code and Data

- **Code repository:** https://github.com/dshi2/peer-recruitment.
- **Data:** raw transcripts, attempt and failure logs, scored exports, checker output, adjudications, coding labels and analysis outputs for every phase, with SHA-256 checksums (data branch of the same repository).
- **Reproducibility:** Every number traces to the outputs of `p2/analysis.py`, `p2/analysis_rep.py`, `p2/analysis_spec.py` or `p2/analysis_conf.py`, which record checksums of their inputs. All amendments and deviations are logged with timestamps in the study specification.
- **Prior work vs sprint work:** the base harness (environment, agents, prompts, scripts and the paper's judges) is preexisting third-party code by Knecht et al. (github.com/AmelieKnecht/multi-agent-shutdown-sabotage). Everything else was written during the sprint: the P2 specification; mixed-model teams, scripted explorer and message pool; provider pinning and logging; the interleaved launcher, attempt accounting and credit guard; the functional checker and the isolated replay container; export, analysis, the replication, the specificity check, request coding, adjudication and figures.