

5 Finding Vulnerabilities

Lab Scenario

Now that you have done such a great job of finding and enumerating all the machines in your target list, it is time to start associating vulnerabilities that you will be able to exploit. You are asked to use two vulnerability scanners to perform testing on one machine and then compare the results for future exploitation. STAY IN THE BOUNDS OF THE ASSESSMENT, WE ARE NOT EXPLOITING AT THIS TIME.

Lab Objectives

1. To learn the basics of Vulnerability Assessments.
2. Learn how to use Nessus and Saint.
3. Learn how to read the reports and compare different products.

Lab Resources

1. Nessus (Optional)
2. Saint – Saint VM

Lab Tasks Overview

1. Use Nessus to scan one of your servers.
 - a. Connect the Nessus client to the server localhost.
 - b. Enter the server you want to scan.
 - c. Choose Scan Now and wait.
2. Analyze the results when you are finished.
3. Start Saint
4. Under the Scan Set-Up tab, enter the same server you scanned with Nessus.
5. Choose Scan Now and wait patiently.
6. Once the scan is finished use the Report Writer to produce a Full Technical Report.
7. Compare the results with the Nessus Scan.

Lab Details - Step-by-Step Instructions

5.1 Nessus Vulnerability Scanner


This is to be done on your Kali Linux VM.

Pre-steps:

Google "Obtain activation code Nessus home feed" or go here to register and obtain an activation code:

<https://www.tenable.com/products/nessus/nessus-plugins/obtain-an-activation-code>

Select "Register Now" for activation code which will be sent to email used while registering.



Check your email for the activation code. Copy and paste activation code into Nessus, as requested.

Note: The Reporting options are not available in Nessus home.

1. Run the following command to start Nessus: `/etc/init.d/nessusd start`

```
root@kali:~# /etc/init.d/nessusd start
$Starting Nessus : .
root@kali:~#
```

- Now open the web browser and goto <https://127.0.0.1:8834/>



This Connection is Untrusted

You have asked Iceweasel to connect securely to **127.0.0.1:8834**, but we can't confirm that your connection is secure.

Normally, when you try to connect securely, sites will present trusted identification to prove that you are going to the right place. However, this site's identity can't be verified.

What Should I Do?

If you usually connect to this site without problems, this error could mean that someone is trying to impersonate the site, and you shouldn't continue.

[Get me out of here!](#)

- Technical Details
- I Understand the Risks

- If you receive this message, click "I Understand the Risks" and then
- On the next screen click "Confirm Security Exception"

[Add Exception...](#)

Add Security Exception

You are about to override how Iceweasel identifies this site.
Legitimate banks, stores, and other public sites will not ask you to do this.

Server

Location: [Get Certificate](#)

Certificate Status

This site attempts to identify itself with invalid information. [View...](#)

Wrong Site

Certificate belongs to a different site, which could indicate an identity theft.

Outdated Information


Certificate is not currently valid. It is impossible to verify whether this identity was reported as stolen or lost.

Unknown Identity

☒ Permanently store this exception

[Confirm Security Exception](#) [Cancel](#)

5. Click "Get Started"



Nessus
vulnerability scanner

Welcome to Nessus® 5


Thank you for installing Nessus, the world leader in vulnerability scanners. Nessus will allow you to perform:

- High-speed vulnerability discovery, to determine which hosts are running which services
- Agentless auditing, to make sure no host on your network is missing security patches
- Compliance checks, to verify and prove that every host on your network adheres to the security policy you defined
- Scan scheduling, to automatically run scans at the frequency you select
- And more!

During the next steps, we are going to create an administrative account and register your scanner with a Plugin Feed, which we will download.

Get started >

a. Choose a username and password and click Next.



Nessus
vulnerability scanner

Initial Account Setup

First, we need to create an admin user for the scanner. This user has the ability to create/delete users, stop ongoing scans.

Login:

Password:

Confirm Password:

< Prev Next >

b. Enter in the activation code that was emailed after registering and click Next.



Nessus
vulnerability scanner

Plugin Feed Registration

As information about new vulnerabilities is discovered and released into the public domain, programs ("plugins") that enable Nessus to detect their presence. The plugins contain an algorithm to test for the presence of the security issue, and a set of remediation actions to subscribe to a "Plugin Feed".


Please enter your Activation Code:

- Tenable SecurityCenter users: Enter 'SecurityCenter' in the field above
- To perform offline plugin updates, enter 'offline' in the field above


Optional Proxy Settings

< Prev Next >


- c. If you registered successfully, you will receive this message. Click Next.



- d. Nessus will take a while to download plugins and initialize.




- e. Log into Nessus after the initialization is complete.




The image shows the Nessus home login interface. It features the Nessus logo at the top, followed by a 'Username' input field with a person icon, a 'Password' input field with a lock icon, a 'Remember Me' checkbox, and a 'Sign In' button.

6. Upon logging in, click Close.




7. Create a new policy by clicking "Policies"



8. Click 

9. There are several scan policies to choose from. For this example Click "Basic Network Scan"



- a. Name the policy and click Next.

New Basic Network Scan Policy / Step 1 of 3

1 Define your policy name, description, and post-scan editing preferences:

Policy Name	<input type="text" value="Basic Network Scan"/>
Description	<input type="text" value="A brief description of the policy goes here"/>
Allow Post-Scan Report Editing	<input checked="" type="checkbox"/>

[Next](#) [Cancel](#)


- b. In Step 2 of 3, leave "Scan type" set to "Internal" and click Next.

NOTE:

External Network Scan - This policy is tuned to scan externally facing hosts, which typically present fewer services to the network. The plugins associated with known web application vulnerabilities (CGI Abuses and CGI Abuses: XSS plugin families) are enabled in this policy. Also, all 65,535 ports are scanned for on each target

Internal Network Scan - This policy is tuned for better performance, taking into account that it may be used to scan large internal networks with many hosts, several exposed services, and embedded systems such as printers. The "CGI Abuse" plugins are not enabled and a standard set of ports is scanned for, not all 65,535.

- c. In Step 3 of 3, Windows enumeration can be setup if the username, password and/or domain is known. Otherwise, leave this blank and click [Save](#) to complete the scan policy



10. Now create a new scan by clicking “Scans” at the top then

[+ New Scan](#)


11. Fill in each field and click “Launch”.

Note: To save scan time, and IP range was used in the “targets” field that only included the range of computers available to scan. 192.168.2.0/24 could also be used.



Name	My Scan - 1
Description	Basic Network scan of 192.168.2.0/24
Policy	Basic Network Scan
Folder	My Scans
Targets	192.168.2.11-192.168.2.16
Upload Targets	Add File

[Launch](#) [Cancel](#)


12. This scan will take about 10 minutes.

<input type="checkbox"/>	My Scan - 1	08:54 AM	 Running
--------------------------	-------------	----------	---

13. Click “My Scan – 1” to view the scan results.

<input type="checkbox"/>	My Scan - 1	09:00 AM	 Completed	
--------------------------	-------------	----------	---	---

14. Each host is listed with a graphical representations of its vulnerabilities.



15. Click on any IP address for specific vulnerability assessment information of each host.

Severity	Plugin Name	Plugin Family	Count	Host Details
CRITICAL	Apache Tomcat Manager Common Administrative ...	Web Servers	1	Host Details IP: 192.168.2.14 MAC: 00:50:56:01:39:76 OS: Linux Kernel 2.6 on Ubuntu 8.04 (hardy) Start time: Mon May 4 08:54:27 2015 End time: Mon May 4 09:00:28 2015 KB: Download
CRITICAL	Debian OpenSSH/OpenSSL Package Random Nu...	Gain a shell remotely	1	
CRITICAL	Rogue Shell Backdoor Detection	Backdoors	1	
CRITICAL	rsh Unauthenticated Access (via finger Information)	Gain a shell remotely	1	


16. Click “Export” to save the report to multiple formats to view later.



5.2 SAINT Vulnerability Scanner

This is to be done on your **SAINT VM**.

1. Log in to SAINT 8 using *toor* as password



2. Double-click Konsole icon



- Once console opens, type `sudo -i`, press enter. Type `cd /usr/share/saint/` and press enter. Type `/usr/share/saint# ./bin/startmenu8`

```
File Edit View Bookmarks Settings Help
saint8@ubuntu:~$ sudo -i
root@ubuntu:~# cd /usr/share/saint/
root@ubuntu:/usr/share/saint# ./bin/startmenu8
```


- In the following screen, use the up and down arrow keys to highlight *Start and Launch Browser*, then press Enter.

```


Start and Launch Browser
Launch Browser
Restart and Launch Browser
-
Start as a Background Process
Restart Background Process
-
Start as a Remote Scanner Node
Restart Remote Scanner Node
Remote Scanner Node Options
-
General Options
Stop
Exit

Use up/down arrow keys to move and Enter to select.
Continuing in 8 seconds...
```

- Once web browser opens, log in with admin /admintoor.



- On menu options, choose Manage Jobs.




7. On the Create New Jobs wizard:


- Enter unique job name, click Next
- Enter Target IP address (Metasploitable), click Next
- Select Policy Category -Vulnerability and Policy -Heavy/Vulnerability Scan, click Next
- Leave default settings for authentication and credentials, click Next
- Leave default settings for Advanced Settings, click Next
- Select Schedule Immediately, click Finish

The screenshot shows the 'Create New Job' wizard with a sidebar on the left containing steps 1 through 6. Step 1, 'Scan Info', is highlighted. The main area is titled 'Step 1: Basic Information' and contains a 'Name & Description' section with a text box for a unique name and an optional description box. Below this is an 'Asset Group' section with a dropdown menu and a 'Create a new Asset Group' link. A yellow tooltip explains that an asset group is a collection of pre-configured scan targets. At the bottom are 'Previous', 'Next', and 'Finish' buttons.

8. On Manage Scan Jobs page, select the Play button. When asked, "Are you sure you want to run this job now", select OK.




- To watch progress of scan, select Manage Scans from the scan menu. Note: This scan will take a very long time. Start the scan but then come back to check the results the following day.




- Once scan completes, select the Details button.


Scan Management




- If needed, click on Execution History, then select View Results.




12. Look over results and proceed to next step.



13. Click on Report from top menu and then select + for the New Report wizard.



14. On the New Report wizard, select report type, title and format, then click Next.



15. Select appropriate check boxes for charts, click Next.

New Report

1 Report Info
Basic Setup

2 Charts
Customize the charts.

3 Lists
Customize the lists.

4 Details
Customize the details.

5 Other Options

6 Summary
Review, Save, Submit

Step 2: Charts

Select Charts

Bar Pie Table

☐ ☐ ☐ All

☐ ☐ Status of all vulnerabilities

☒ ☒ The number of vulnerabilities in each class

☐ ☐ Vulnerability classes by severity level and date

☐ ☐ Status of current vulnerabilities

☐ ☐ Hosts by severity level and date

☒ ☒ Hosts by severity level

☐ ☐ Status of old vulnerabilities

☒ ☐ Vulnerabilities in each class by subnet

☒ ☐ Hosts by severity and subnet

☒ ☐ Vulnerabilities by severity and subnet

☒ ☐ The most vulnerable hosts, and how many vulnerabilities affect each

☒ ☐ The most common services, and how many hosts are running each

☒ ☐ The most common vulnerabilities, and how many hosts are affected by each

☐ ☐ Vulnerabilities by severity level and date

☒ ☒ Vulnerabilities by severity level

☐ ☐ Status of all vulnerabilities by severity level

Previous Next Finish

16. On the Lists page, click Next.

New Report

1 Report Info
Basic Setup

2 Charts
Customize the charts.

3 Lists
Customize the lists.

4 Details
Customize the details.

5 Other Options

6 Summary
Review, Save, Submit

Step 3: Lists

Select Lists

Host List ☒ Vulnerability Summary ☐ Vulnerability List ☒

Host List Columns

1 Hostname 3 IP address

2 NetBIOS name 4 Operating system

→ Next 4 Columns

Vulnerability List Columns

1 Hostname 3 Severity

2 Port 4 Description

→ Next 4 Columns

Previous Next Finish

17. Click Next on the Details page.

New Report

1 Report Info
Basic Setup

2 Charts
Customize the charts.

3 Lists
Customize the lists.

4 Details
Customize the details.

5 Other Options

6 Summary
Review, Save, Submit

Step 4: Details

Enable or Disable Details

Choose whether to include vulnerability details.
Full details

Choose how to organize details.
By Host

Select Detail Sections

? All Sections <input type="checkbox"/>	? Impact <input checked="" type="checkbox"/>	? Background <input type="checkbox"/>
? Problem <input type="checkbox"/>	? Resolution <input checked="" type="checkbox"/>	? References <input checked="" type="checkbox"/>
? Vulnerability Details <input checked="" type="checkbox"/>	? Limitations <input type="checkbox"/>	

Previous Next Finish

18. Click Next on the Other Options page.

New Report

1 Report Info
Basic Setup

2 Charts
Customize the charts.

3 Lists
Customize the lists.

4 Details
Customize the details.

5 Other Options

6 Summary
Review, Save, Submit

Step 5: Other Settings

Customize the Introduction

Include an Introduction ☒

Introduction
On %date%, at %time%, a %level% type% was conducted using the %scanner%. The scan discovered a total of %hosts%, and detected %reds%, %yellow%, and %browns%. The hosts and problems detected are discussed in greater detail

Additional Data to Include

? Services ☒ ? Information ☒

Advanced Options

Previous Next Finish

19. Select Finish on the Summary page.

New Report

1 Report Info
Basic Setup

2 Charts
Customize the charts.

3 Lists
Customize the lists.

4 Details
Customize the details.

5 Other Options

6 Summary
Review, Save, Submit

Step 6: Summary

Summary of Report Settings

Title: SAINTWriter Assessment Report 1st scan
Type: Full Scan
Format: HTML
Job: my 1st scan
Scan Run: 2015-03-05 08:46:39


Save Settings As Custom Report Type

Optional: Enter a new report type name to save these settings.

Custom Report Type Name

Previous Next Finish

20. A full SAINT report will be generated and displayed in the browser:



Document all the results and reports gathered during the lab.

Tool/Utility	Information Collected/Objectives Achieved
SAINT	Scan Target Machine: Windows Server 2008
	Performed Scan Policy: Network Scan Policy
	Target IP Address:
	Result: SAINT Report