


Status and Control Registers

0.5

Features

- Up to 8-bit Status Register
- Up to 8-bit Control Register



General Description

The status register allows the firmware to read digital signals. The control register allows the firmware to output digital signals.

When to use a status or control register

The status register should be used when the firmware needs to query the state of internal digital signals.

The control register should be used when the firmware needs to interact with a digital system. The control register may be used as a configuration register, allowing the firmware to specify the desired behavior of the digital system.

Input/Output Connections

This section describes the various input and output connections for the status and control registers. An asterisk (*) in the list of I/O's states that the I/O may be hidden on the symbol under the conditions listed in the description of that I/O.

clock – Input (Status Register Only)

Status register clock (status register only).

status_0 - status_7 – Input *

Status register input (status register only). The firmware queries the input signals by reading the status register. The number of inputs depends on the NumInputs parameter.

control_0 - control_7 – Output *

Control register output (control register only). The firmware sets the values of the output terminals by writing to the control register. The number of outputs depends on the NumOutputs parameter.

PRELIMINARY

Transparent Status Read

By default, a CPU read of this register will transparently read the state of the associated routing net. This mode can be used for transient state that is computed and registered internally in the UDB.


Sticky Status, with Clear on Read

In this mode, the associated routing net is sampled on each cycle of the status and control clock and if the signal is high in a given sample, it is captured in the status bit and remains high, regardless of the subsequent state of the associated route. When CPU firmware reads the status register, the bit is cleared. The status register clearing is independent of mode and will occur even if the block clock is disabled, it is based on the bus clock and occurs as part of the read operation.

Component Parameters

Drag a status register or control register onto your design and double-click it to open the Configure dialog.

Figure 1 Configure Status Register Dialog



ModeMask

The ModeMask parameter is used to set specific bits of the Status Register to be held high after being registered, until a read is executed. That read clears all registered values.


PRELIMINARY



NumInputs

Number of input terminals (1-8). The default value is 8.

Figure 2 Configure Control Register Dialog



NumOutputs

Number of output terminals (1-8). The default value is 8. bit0 is the LSB and corresponds to the control_0 terminal.

Placement

There are no placement restrictions for the status or control registers.

Resources

The status register requires one UDB status register.

The control register requires one UDB control register.

Application Programming Interface

Application Programming Interface (API) routines allow you to configure the component using software. The following tables list and describe the interface to each function. The subsequent sections cover each function in more detail.

By default, PSoC Creator assigns the instance name "Status_Reg_1" to the first instance of a status register and "Control_Reg_1" to the first instance of a control register in any given design. You can rename the component to any unique value that follows the syntactic rules for identifiers. The instance name becomes the prefix of every global function name, variable, and constant symbol. For readability, the instance names used in the following tables are "StatusReg" and "ControlReg".

Status Register

Function	Description
StatusReg_Read	Get the state of the status register's inputs (status register only).

uint8 StatusReg_Read (void)

Description: Read the value of a status register.

Parameters: None

Return Value: uint8: State of the status register's inputs.

Side Effects:

Control Register

Function	Description
ControlReg_Write	Set the state of the control register's outputs (control register only).
ControlReg_Read	Get the state of the control register's outputs (control register only).

void ControlReg_Write (uint8)

Description: Set the state of the control register's outputs.

Parameters: uint8: Control register value.

Return Value: None

Side Effects: Sets the state of the control register's outputs.

PRELIMINARY



uint8 ControlReg_Read (void)

Description: Read the value of a control register.

Parameters: None

Return Value: uint8: State of the control register's inputs.

Side Effects: None

Sample Firmware Source Code

Status Register

The following is a C language example demonstrating the basic functionality of the status register component. This example assumes the component has been placed in a design with the default name "Status_Reg_1."

Note If you rename your component you must also edit the example code as appropriate to match the component name you specify.

```
#include <device.h>
#include "Status_Reg_1.h"

void main()
{
    uint8 value;
    value = Status_Reg_1_Read();
}
```

Control Register

The following is a C language example demonstrating the basic functionality of the control register component. This example assumes the component has been placed in a design with the default name "Control_Reg_1."

Note If you rename your component you must also edit the example code as appropriate to match the component name you specify.

```
#include <device.h>
#include "Control_Reg_1.h"

void main()
{
    uint8 value;
    Control_Reg_1_Write(0x3E);
    value = Control_Reg_1_Read();
}
```



PRELIMINARY

Interrupt Service Routine

Not Applicable

Functional Description

DC and AC Electrical Characteristics

The following values are indicative of expected performance and based on initial characterization data.

5.0V/3.3V DC and AC Electrical Characteristics

Parameter	Typical	Min	Max	Units	Conditions and Notes
Input					
Maximum Clock Rate	---		67	MHz	

© Cypress Semiconductor Corporation, 2009. The information contained herein is subject to change without notice. Cypress Semiconductor Corporation assumes no responsibility for the use of any circuitry other than circuitry embodied in a Cypress product. Nor does it convey or imply any license under patent or other rights. Cypress products are not warranted nor intended to be used for medical, life support, life saving, critical control or safety applications, unless pursuant to an express written agreement with Cypress. Furthermore, Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress products in life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

PSoC® Creator™, Programmable System-on-Chip™, and PSoC Express™ are trademarks and PSoC® is a registered trademark of Cypress Semiconductor Corp. All other trademarks or registered trademarks referenced herein are property of the respective corporations.

Any Source Code (software and/or firmware) is owned by Cypress Semiconductor Corporation (Cypress) and is protected by and subject to worldwide patent protection (United States and foreign), United States copyright laws and international treaty provisions. Cypress hereby grants to licensee a personal, non-exclusive, non-transferable license to copy, use, modify, create derivative works of, and compile the Cypress Source Code and derivative works for the sole purpose of creating custom software and or firmware in support of licensee product to be used only in conjunction with a Cypress integrated circuit as specified in the applicable agreement. Any reproduction, modification, translation, compilation, or representation of this Source Code except as specified above is prohibited without the express written permission of Cypress.

Disclaimer: CYPRESS MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Cypress reserves the right to make changes without further notice to the materials described herein. Cypress does not assume any liability arising out of the application or use of any product or circuit described herein. Cypress does not authorize its products for use as critical components in life-support systems where a malfunction or failure may reasonably be expected to result in significant injury to the user. The inclusion of Cypress' product in a life-support systems application implies that the manufacturer assumes all risk of such use and in doing so indemnifies Cypress against all charges.

Use may be limited by and subject to the applicable Cypress software license agreement.

PRELIMINARY

