```
PAINTER PK: {NAME, SURNAME}
PAINTING PK: {TITLE, STYLE}
PAINTS PK: TUTTI GLI ATTRIBUTI
PAINTS FKs:   {PAINTS.PAINTER_NAME,   }  →  {PAINTER.NAME,   }
              {PAINTS.PAINTER_SURNAME}     {PAINTER.SURNAME}
              {PAINTS.PAINTING_STYLE,}  →  {PAINTING.STYLE,}
              {PAINTS.PAINTING_TITLE}      {PAINTING.TITLE}


SELECT *
FROM PAINTER
WHERE NOT EXISTS (SELECT *
                 FROM PAINTS
                 WHERE PAINTS.PAINTING_STYLE != 'SURREALIST'
                 AND PAINTS.PAINTER_NAME = PAINTER.NAME
                 AND PAINTS.PAINTER_SURNAME = PAINTER.SURNAME) ;


WITH N_PAINTINGS AS (
        SELECT PAINTER_NAME, PAINTER_SURNAME, COUNT(*) AS N
        FROM PAINTS
        GROUP BY PAINTER_NAME, PAINTER_SURNAME
)

SELECT PAINTER_NAME, PAINTER_SURNAME
FROM N_PAINTINGS
WHERE N >= ALL (SELECT N
               FROM N_PAINTINGS ) ;
```