Операционные системы

Анализ файловой структуры UNIX. Команды для работы с файлами и каталогами

Матиев Даниэль Саматович

2026-03-13

Содержание (i)

Цели и задачи работы

Процесс выполнения лабораторной работы

Выводы по проделанной работе

1. Цели и задачи работы

Цель лабораторной работы

Ознакомление с файловой системой Linux, её структурой, именами и содержанием каталогов. Приобретение практических навыков по применению команд для работы с файлами и каталогами, по управлению процессами, по проверке использования диска и обслуживанию файловой системы.

Задачи лабораторной работы

1 Выполнить приимеры

2 Выполнить дествия по работе с каталогами и файлами

3 Выполнить действия с правами доступа

4 Получить дополнительные сведения при помощи справки по командам.

2. Процесс выполнения лабораторной работы

Выполнение примеров

```
dsmatiev@dsmatiev:~$
dsmatiev@dsmatiev:~$ cd
dsmatiev@dsmatiev:~$ touch abc1
dsmatiev@dsmatiev:~$ cp abc1 april
dsmatiev@dsmatiev:~$ cp abc1 may
dsmatiev@dsmatiev:~$ mkdir monthly
dsmatiev@dsmatiev:~$ cp april may monthly
dsmatiev@dsmatiev:~$ cp monthly/may monthly/june
dsmatiev@dsmatiev:~$ ls monthly
april  june  may
dsmatiev@dsmatiev:~$ mkdir monthly.00
dsmatiev@dsmatiev:~$ cp -r monthly monthly.00
dsmatiev@dsmatiev:~$ cp -r monthly.00 /tmp
dsmatiev@dsmatiev:~$
```

Рисунок 1: Выполнение примеров

Выполнение примеров

```
dsmatiev@dsmatiev:~$ mv april july
dsmatiev@dsmatiev:~$ mv july monthly.00
dsmatiev@dsmatiev:~$ ls monthly.00
july  monthly
dsmatiev@dsmatiev:~$ mv monthly.00 monthly.01
dsmatiev@dsmatiev:~$ mkdir reports
dsmatiev@dsmatiev:~$ mv monthly.01 reports
dsmatiev@dsmatiev:~$ mv reports/monthly.01 reports/monthly
dsmatiev@dsmatiev:~$
```

Рисунок 2: Выполнение примеров

Выполнение примеров

```
dsmatiev@dsmatiev:~$
dsmatiev@dsmatiev:~$ touch may
dsmatiev@dsmatiev:~$ ls -l may
-rw-r--r--. 1 dsmatiev dsmatiev 0 Mar 13 16:52 may
dsmatiev@dsmatiev:~$ chmod u+x may
dsmatiev@dsmatiev:~$ ls -l may
-rwxr--r--. 1 dsmatiev dsmatiev 0 Mar 13 16:52 may
dsmatiev@dsmatiev:~$ chmod u-x may
dsmatiev@dsmatiev:~$ ls -l may
-rw-r--r--. 1 dsmatiev dsmatiev 0 Mar 13 16:52 may
dsmatiev@dsmatiev:~$ chmod g-r,o-r monthly
dsmatiev@dsmatiev:~$ chmod g+w abc1
dsmatiev@dsmatiev:~$
```

Рисунок 3: Выполнение примеров

Создание директорий и копирование файлов

```
dsmatiev@dsmatiev:~$
dsmatiev@dsmatiev:~$ cp /usr/include/linux/sysinfo.h ~
dsmatiev@dsmatiev:~$ mv sysinfo.h equipment
dsmatiev@dsmatiev:~$ mkdir ski.plases
dsmatiev@dsmatiev:~$ mv equipment ski.plases/
dsmatiev@dsmatiev:~$ mv ski.plases/equipment ski.plases/equiplist
dsmatiev@dsmatiev:~$ touch abc1
dsmatiev@dsmatiev:~$ cp abc1 ski.plases/equiplist2
dsmatiev@dsmatiev:~$ cd ski.plases/
dsmatiev@dsmatiev:~/ski.plases$ mkdir equipment
dsmatiev@dsmatiev:~/ski.plases$ mv equiplist equipment/
dsmatiev@dsmatiev:~/ski.plases$ mv equiplist2 equipment/
dsmatiev@dsmatiev:~/ski.plases$ cd
dsmatiev@dsmatiev:~$ mkdir newdir
dsmatiev@dsmatiev:~$ mv newdir ski.plases/
dsmatiev@dsmatiev:~$ mv ski.plases/newdir/ ski.plases/plans
dsmatiev@dsmatiev:~$
```

Рисунок 4: Работа с каталогами

Работа с командой chmod

```
dsmatiev@dsmatiev:~$ mkdir australia play
dsmatiev@dsmatiev:~$ touch my_os feathers
dsmatiev@dsmatiev:~$ chmod 744 australia/
dsmatiev@dsmatiev:~$ chmod 711 play/
dsmatiev@dsmatiev:~$ chmod 544 my_os
dsmatiev@dsmatiev:~$ chmod 664 feathers
dsmatiev@dsmatiev:~$ ls -l
total 0
-rw-rw-r--. 1 dsmatiev dsmatiev  0 Mar 13 16:53 abc1
drwxr--r--. 1 dsmatiev dsmatiev  0 Mar 13 16:54 australia
drwxr-xr-x. 1 dsmatiev dsmatiev  0 Feb 25 15:22 Desktop
drwxr-xr-x. 1 dsmatiev dsmatiev  0 Feb 25 15:22 Documents
drwxr-xr-x. 1 dsmatiev dsmatiev 44 Mar  8 15:54 Downloads
-rw-rw-r--. 1 dsmatiev dsmatiev  0 Mar 13 16:54 feathers
drwxr-xr-x. 1 dsmatiev dsmatiev 74 Feb 25 15:40 git-extended
-rw-r--r--. 1 dsmatiev dsmatiev  0 Mar 13 16:52 may
drwx--x--x. 1 dsmatiev dsmatiev 24 Mar 13 16:52 monthly
drwxr-xr-x. 1 dsmatiev dsmatiev  0 Feb 25 15:22 Music
-r-xr--r--. 1 dsmatiev dsmatiev  0 Mar 13 16:54 my_os
drwxr-xr-x. 1 dsmatiev dsmatiev  0 Feb 25 15:22 Pictures
drwx--x--x. 1 dsmatiev dsmatiev  0 Mar 13 16:54 play
drwxr-xr-x. 1 dsmatiev dsmatiev  0 Feb 25 15:22 Public
drwxr-xr-x. 1 dsmatiev dsmatiev 14 Mar 13 16:52 reports
drwxr-xr-x. 1 dsmatiev dsmatiev 44 Feb 25 15:47 site
drwxr-xr-x. 1 dsmatiev dsmatiev 28 Mar 13 16:54 ski.plases
drwx------. 1 dsmatiev dsmatiev  8 Feb 25 15:49 snap
drwxr-xr-x. 1 dsmatiev dsmatiev  0 Feb 25 15:22 Templates
drwxr-xr-x. 1 dsmatiev dsmatiev  0 Feb 25 15:22 Videos
drwxr-xr-x. 1 dsmatiev dsmatiev 10 Feb 25 15:30 work
```

Файл /etc/passwd

```
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/spool/mail:/usr/sbin/nologin
operator:x:11:0:operator:/root:/usr/sbin/nologin
games:x:12:100:games:/usr/games:/usr/sbin/nologin
ftp:x:14:50:FTP User:/var/ftp:/usr/sbin/nologin
nobody:x:65534:65534:Kernel Overflow User:/:/usr/sbin/nologin
dbus:x:81:81:System Message Bus:/:/usr/sbin/nologin
tss:x:59:59:Account used for TPM access:/:/usr/sbin/nologin
systemd-oom:x:999:999:systemd Userspace OOM Killer:/:/usr/sbin/nologin
polkitd:x:114:114:User for polkitd:/:/sbin/nologin
systemd-coredump:x:998:998:systemd Core Dumper:/:/usr/sbin/nologin
systemd-timesync:x:997:997:systemd Time Synchronization:/:/usr/sbin/nologin
chrony:x:996:996:chrony system user:/var/lib/chrony:/sbin/nologin
systemd-network:x:192:192:systemd Network Management:/:/usr/sbin/nologin
systemd-resolve:x:193:193:systemd Resolver:/:/usr/sbin/nologin
avahi:x:70:70:Avahi mDNS/DNS-SD Stack:/var/run/avahi-daemon:/usr/sbin/nologin
unbound:x:993:993:Unbound DNS resolver:/var/lib/unbound:/sbin/nologin
clevis:x:992:992:Clevis Decryption Framework unprivileged user:/var/cache/clevis:/usr/sbin/no
login
usbmuxd:x:113:113:usbmuxd user:/:/usr/sbin/nologin
gluster:x:991:991:GlusterFS daemons:/run/gluster:/usr/sbin/nologin
qemu:x:107:107:qemu user:/:/usr/sbin/nologin
apache:x:48:48:Apache:/usr/share/httpd:/sbin/nologin
/etc/passwd
```

Рисунок 6: Файл /etc/passwd

Работа с файлами и правами доступа

```
dsmatiev@dsmatiev:~$
dsmatiev@dsmatiev:~$ cp feathers file.old
dsmatiev@dsmatiev:~$ mv file.old play/
dsmatiev@dsmatiev:~$ mkdir fun
dsmatiev@dsmatiev:~$ cp -R play/ fun/
dsmatiev@dsmatiev:~$ mv fun/ play/games
dsmatiev@dsmatiev:~$ chmod u-r feathers
dsmatiev@dsmatiev:~$ cat feathers
cat: feathers: Permission denied
dsmatiev@dsmatiev:~$ cp feathers feathers2
cp: cannot open 'feathers' for reading: Permission denied
dsmatiev@dsmatiev:~$ chmod u+r feathers
dsmatiev@dsmatiev:~$ chmod u-x play/
dsmatiev@dsmatiev:~$ cd play/
bash: cd: play/: Permission denied
dsmatiev@dsmatiev:~$ chmod +x play/
dsmatiev@dsmatiev:~$
```

Рисунок 7: Работа с файлами и правами доступа

Справка по командам

```
MOUNT(8)                                System Administration                                MOUNT(8)

NAME
       mount - mount a filesystem

SYNOPSIS
       mount [-h|-V]

       mount [-l] [-t fstype]

       mount -a [-fFnrsvw] [-t fstype] [-O optlist]

       mount [-fnrsvw] [-o options] device|mountpoint

       mount [-fnrsvw] [-t fstype] [-o options] device mountpoint

       mount --bind|--rbind|--move olddir newdir

       mount --make-[shared|slave|private|unbindable|rshared|rslave|rprivate|runbindable] mountpoint

DESCRIPTION
       All files accessible in a Unix system are arranged in one big tree, the file hierarchy, rooted at /.
       These files can be spread out over several devices. The mount command serves to attach the filesystem
       found on some device to the big file tree. Conversely, the umount(8) command will detach it again. The
       filesystem is used to control how data is stored on the device or provided in a virtual way by network
       or other services.

       The standard form of the mount command is:

          mount -t type device dir

       This tells the kernel to attach the filesystem found on device (which is of type type) at the
       directory dir. The option -t type is optional. The mount command is usually able to detect a
       filesystem. The root permissions are necessary to mount a filesystem by default. See section
 Manual page mount(8) line 1 (press h for help or q to quit)
```

Рисунок 8: Команда mount

Справка по командам

```
FSCK(8)                                System Administration                                FSCK(8)

NAME
       fsck - check and repair a Linux filesystem

SYNOPSIS
       fsck [-lsAVRTMNP] [-r [fd]] [-C [fd]] [-t fstype] [filesystem...] [--] [fs-specific-options]

DESCRIPTION
       fsck is used to check and optionally repair one or more Linux filesystems. filesystem can be a device
       name (e.g., /dev/hdc1, /dev/sdb2), a mount point (e.g., /, /usr, /home), or a filesystem label or UUID
       specifier (e.g., UUID=8868abf6-88c5-4a83-98b8-bfc24057f7bd or LABEL=root). Normally, the fsck program
       will try to handle filesystems on different physical disk drives in parallel to reduce the total
       amount of time needed to check all of them.

       If no filesystems are specified on the command line, and the -A option is not specified, fsck will
       default to checking filesystems in /etc/fstab serially. This is equivalent to the -As options.

       The exit status returned by fsck is the sum of the following conditions:

       0
           No errors

       1
           Filesystem errors corrected

       2
           System should be rebooted

       4
           Filesystem errors left uncorrected

       8
           Operational error
 Manual page fsck(8) line 1 (press h for help or q to quit)
```

Рисунок 9: Команда fsck

Справка по командам

```
MKFS(8)                                System Administration                                MKFS(8)

NAME
       mkfs - build a Linux filesystem

SYNOPSIS
       mkfs [options] [-t type] [fs-options] device [size]

DESCRIPTION
       This mkfs frontend is deprecated in favour of filesystem specific mkfs.<type> utils.

       mkfs is used to build a Linux filesystem on a device, usually a hard disk partition. The device
       argument is either the device name (e.g., /dev/hda1, /dev/sdb2), or a regular file that shall contain
       the filesystem. The size argument is the number of blocks to be used for the filesystem.

       The exit status returned by mkfs is 0 on success and 1 on failure.

       In actuality, mkfs is simply a front-end for the various filesystem builders (mkfs.fstype) available
       under Linux. The filesystem-specific builder is searched for via your PATH environment setting only.
       Please see the filesystem-specific builder manual pages for further details.

OPTIONS
       -t, --type type
           Specify the type of filesystem to be built. If not specified, the default filesystem type
           (currently ext2) is used.

       fs-options
           Filesystem-specific options to be passed to the real filesystem builder.

       -V, --verbose
           Produce verbose output, including all filesystem-specific commands that are executed. Specifying
           this option more than once inhibits execution of any filesystem-specific commands. This is really
           only useful for testing.

 Manual page mkfs(8) line 1 (press h for help or q to quit)
```

Рисунок 10: Команда mkfs

Справка по командам

```
KILL(1)                                User Commands                                KILL(1)

NAME
       kill - terminate a process

SYNOPSIS
       kill  [-signal|-s signal|-p]  [-q value] [-a] [--timeout milliseconds signal] [--] pid|name...

       kill -l [number|0xsigmask] | -L

       kill -d pid

DESCRIPTION
       The command kill sends the specified signal to the specified processes or process groups.

       If no signal is specified, the TERM signal is sent. The default action for this signal is to terminate
       the process. This signal should be used in preference to the KILL signal (number 9), since a process
       may install a handler for the TERM signal in order to perform clean-up steps before terminating in an
       orderly fashion. If a process does not terminate after a TERM signal has been sent, then the KILL
       signal may be used; be aware that the latter signal cannot be caught, and so does not give the target
       process the opportunity to perform any clean-up before terminating.

       Most modern shells have a builtin kill command, with a usage rather similar to that of the command
       described here. The --all, --pid, and --queue options, and the possibility to specify processes by
       command name, are local extensions.

       If signal is 0, then no actual signal is sent, but error checking is still performed.

ARGUMENTS
       The list of processes to be signaled can be a mixture of names and PIDs.

       pid
           Each pid can be expressed in one of the following ways:

 Manual page kill(1) line 1 (press h for help or q to quit)
```

Рисунок 11: Команда kill

3. Выводы по проделанной работе

Вывод

В ходе данной работы мы ознакомились с файловой системой Linux, её структурой, именами и содержанием каталогов. Научились совершать базовые операции с файлами, управлять правами их доступа для пользователя и групп. Ознакомились с Анализом файловой системы. А также получили базовые навыки по проверке использования диска и обслуживанию файловой системы.