

UnifyComply API — Frontend Integration Guide

Every HTTP endpoint core-platform exposes today — what each one is for, who can call it, a real request and a real response, and the gotchas a generated schema will not tell you.

Generated 2026-10-01

Base URL `{API_BASE}/v1` — core-platform is the only service a frontend ever calls. It fans out to compliance-domain, provider-gateway, risk-decisioning, transaction-monitoring and investigation-sar; none of those are reachable directly.

How the examples were made Every request and response below was captured live on 2026-10-01 against a fresh sandbox tenant ("Docs Demo Fintech Ltd") created for this guide. IDs are real but belong to that throwaway tenant. Tokens, API secrets, webhook secrets and OTP secrets are redacted; long arrays are shortened with `/* ... N more */`.

Interactive schema Swagger is served live by core-platform at `/v1/docs` — use it for exact validator rules; use this guide for behaviour.

Contents

- | | |
|--|--|
| 0. How to read this | 9. Verifications |
| 1. Fundamentals — auth, headers, envelope, errors, limits | 10. Verification review tabs |
| 2. Authentication & account | 11. Dashboard & webhooks |
| 3. Tenant onboarding & user profile | 12. Transactions — ingestion, detail, statement |
| 4. Apps & API keys | 13. Transaction-monitoring settings & Re-KYC triggers |
| 5. App configuration — risk, PEP, compliance rules, webhooks | 14. Transaction-monitoring dashboard & queues |
| 6. Team, roles, business information, domain | 15. Investigations — reporting actions & case management |
| 7. Public option sets (enum lookups) | 16. PND watchlist & SAR reports |
| 8. Customers — KYC (individuals) & KYB (businesses) | 17. What's left — known gaps |

0. How to read this

Every endpoint card carries a status badge and the credential types it accepts:

LIVE endpoint exists, was called for this guide, and behaves as documented. **PARTIAL** endpoint works, but one or more fields are always `null` / empty by design today, or a dependency is missing in some environments.

NOT BUILT nothing exists yet.

SESSION a signed-in user's JWT. **API KEY** an app-scoped secret `sk_...`. **PUBLIC** no credentials.

Method colours: **GET** blue, **POST** green, **PUT** purple, **PATCH** amber, **DELETE** red. Paths are shown with the `/v1` prefix exactly as you send them.

1. Fundamentals — auth, headers, envelope, errors, limits

TWO CREDENTIAL TYPES

Credential	How to send it	Use it for
Session JWT	<code>Authorization: Bearer <token></code> from sign-in / onboarding / refresh, plus <code>x-app-id: <appId></code> to pick which of the tenant's apps you act on (omit → the tenant's default app)	Everything a human does in the dashboard: settings, team, investigations, verification review tabs.
API key	<code>Authorization: Bearer sk_<domain>--<random></code> . App and domain are baked into the key; <code>x-app-id</code> is ignored.	Server-to-server integration: customers, documents, verifications, transactions, webhooks, dashboard reads.

Routes guarded by `CombinedAuthGuard` accept either credential. Routes guarded only by `PermissionsGuard` are **session-only** — an API key gets `401 Unauthorized`, not `403` (see 1.4). Session routes also check the signed-in user's **role permissions** (`dashboard:access`, `tenant-settings:update`, `case:resolve`, `case:escalate`, `pnd:manage`, `sar:file`, ...); a role without the permission gets `403`.

API-KEY SCOPES

Scope	Grants
<code>customers:read</code> / <code>customers:write</code>	Customer roster, profile CRUD, account purpose, TM subscription, flags, approve/reject, offboard
<code>documents:write</code>	Uploading or replacing documents (customer and shareholder)
<code>verifications:read</code> / <code>verifications:write</code>	Starting/reading verifications, available checks, the <code>/dashboard/*</code> reads
<code>webhooks:read</code> / <code>webhooks:write</code>	Reading webhook deliveries / requeueing one
<code>transactions:read</code> / <code>transactions:write</code>	Transaction ingestion and reads, TM dashboard/queues, account statement

A key missing the scope a route needs gets **403** (the key is valid, it just isn't allowed).

HEADERS & CORS

Allowed request headers: `Authorization`, `Content-Type`, `x-app-id`. Allowed methods: `GET` `POST` `PUT` `DELETE` `PATCH` `OPTIONS`. Your origin must be in core-platform's `CORS_ORIGINS`. Bodies are `application/json`; files travel as base64 data URLs inside JSON (never multipart).

RESPONSE ENVELOPE

```
{
  "status": true,           // false on any error
  "message": "...",        // human-readable, safe to toast
  "data": { ... } | [ ... ] | null,
  "meta"? : { "totalItems", "itemsCount", "itemsPerPage", "totalPages", "currentPage" }, // paginated lists only
  "summary"? : { ... }     // list screens that also need tile counts (TM queues, PND, SAR, statement)
}
```

Paginated lists accept `page` (1-based) and `limit` (default 20).

ERRORS — REAL EXAMPLES

400 — validation failure (one message string listing every failed rule)

```
// request — PUT /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/notification-preferences
{"eventCallbackUrl": "http://localhost:4999/webhooks/unifycomply", "webhookEnabled": true}
// response — HTTP 400
{"status": false, "message": "eventCallbackUrl must be a URL address"}
```

401 — bad credentials

```
// response — HTTP 401
{"status": false, "message": "User authentication failed. Invalid username or password"}
```

401 — API key on a session-only route

```
// response — HTTP 401
{"status": false, "message": "Unauthorized"}
```

404 — unknown id

```
// response — HTTP 404
{
  "status": false,
  "message": "No SAR filing found with a matching id: 00000000000000000000000000000000"
}
```

429 — rate limited

```
// response — HTTP 429
{"status": false, "message": "ThrottlerException: Too Many Requests", "data": null}
```

Rate limits are per client and stacked: 10 requests / second, 40 / 10 seconds, 200 / minute. A burst (e.g. firing every dashboard tile plus a table at once) can hit the 10/s window — fetch lazily, debounce search inputs, and retry 429s with backoff.

DOMAIN — SANDBOX VS PRODUCTION

Every tenant has two isolated domains. A sandbox customer is invisible to a production request. API keys are bound to one domain at issue (`sk_sandbox-...` / `sk_production-...`). A session switches with `POST /v1/tenants/settings/domain/switch` (§6.4), which re-issues the token. Sandbox calls deterministic provider simulators — nothing billed, nothing sent to a real watchlist; the AML simulator flags any name containing "sanction" or "pep".

2. Authentication & account

Sign-up → verify email → sign-in → onboard the tenant (\$3). All `/v1/auth/*` sign-in style routes take `?platform=app|admin`.

2.1 Sign up LIVE PUBLIC

POST `/v1/auth/sign-up`

```
// request - POST /v1/auth/sign-up
{
  "firstName": "Ada", "lastName": "Okafor", "email": "docs.demo.1790894194091@unifycomply.test",
  "countryCode": "NG", "password": "<redacted>"
}
// response - HTTP 201
{
  "status": true, "message": "Sign up successful.",
  "data": {
    "id": "f0e9c73b09f1448a94175812f9f2f4ed", "createdAt": "2026-10-01T22:36:34.146Z",
    "updatedAt": "2026-10-01T22:36:34.146Z", "email": "docs.demo.1790894194091@unifycomply.test",
    "phone": null, "firstName": "Ada", "lastName": "Okafor", "countryCode": "NG",
    "status": "created", "lastActivityAt": null, "language": "en-US", "timezone": "Africa/Lagos",
    "imageUrl": null
  }
}
```

Creates the user only (status `created`). They cannot sign in until the email is verified. Password must be "strong" (upper, lower, digit, symbol, 8+).

2.2 Email verification — send code, then confirm LIVE PUBLIC

POST `/v1/auth/email/verify`

POST `/v1/auth/email/verify/:token?platform=app`

```
// request - POST /v1/auth/email/verify
{"email": "docs.demo.1790894194091@unifycomply.test"}
// response - HTTP 201
{
  "status": true, "message": "Verification email sent successfully.",
  "data": {"email": "docs.demo.1790894194091@unifycomply.test", "expires": 300}
}
```

```
// request - POST /v1/auth/email/verify/:token?platform=app
{"email": "docs.demo.1790894194091@unifycomply.test"}
// response - HTTP 201
{
  "status": true, "message": "Email verified successfully.",
  "data": {
    "user": {
      "id": "f0e9c73b09f1448a94175812f9f2f4ed",
      "email": "docs.demo.1790894194091@unifycomply.test", "phone": null, "firstName": "Ada",
      "lastName": "Okafor", "countryCode": "NG", "status": "created", "lastActivityAt": null,
      "language": "en-US", "timezone": "Africa/Lagos", "imageUrl": null
    },
    "access": {"token": "<jwt>", "refreshToken": "<jwt>"}
  }
}
```

```
}  
}
```

Confirming returns a full session (same shape as sign-in) — the user is signed in immediately.

The code is 4 characters and expires after 300 seconds. Show a countdown from `expires` and a resend button that calls the first route again.

2.3 Sign in LIVE PUBLIC

POST `/v1/auth/sign-in?platform=app`

```
// request - POST /v1/auth/sign-in?platform=app  
{  
  "email": "docs.demo.1790894194091@unifycomply.test",  
  "password": "<redacted>"  
}  
// response - HTTP 200  
{  
  "status": true, "message": "Sign in successful",  
  "data": {  
    "user": {  
      "id": "f0e9c73b09f1448a94175812f9f2f4ed",  
      "email": "docs.demo.1790894194091@unifycomply.test",  
      "phone": null, "firstName": "Ada",  
      "lastName": "Okafor", "countryCode": "NG", "status": "active",  
      "lastActivityAt": "2026-10-01T22:38:31.477Z",  
      "language": "en-US",  
      "timezone": "Africa/Lagos",  
      "imageUrl": null  
    },  
    "userAccess": [  
      {  
        "id": "34bfd0c7b0b24af9913abd453024ee04",  
        "tenantName": "Docs Demo Fintech Ltd",  
        "status": "active",  
        "roleId": "0f4e5a4603234018bb80791780ac9295"  
      }  
    ],  
    "currentAccess": {  
      "id": "34bfd0c7b0b24af9913abd453024ee04",  
      "tenantName": "Docs Demo Fintech Ltd",  
      "status": "active",  
      "roleId": "0f4e5a4603234018bb80791780ac9295"  
    },  
    "access": {  
      "token": "<jwt>",  
      "refreshToken": "<jwt>"  
    }  
  }  
}
```

`access.token` is the bearer for every session call; keep `access.refreshToken` for §2.4. `currentAccess` is the tenant the token acts as — `null` until the user has onboarded or been invited to a tenant.

When MFA is enabled — continue with §2.8 `mfa/validate` using `data.userId`

```
// request - POST /v1/auth/sign-in?platform=app  
{  
  "email": "docs.demo.1790894194091@unifycomply.test",  
  "password": "<redacted>"  
}  
// response - HTTP 401  
{  
  "status": false, "message": "Multifactor Authentication required.",  
  "data": {  
    "userId": "f0e9c73b09f1448a94175812f9f2f4ed"  
  }  
}
```

2.4 Refresh the access token

LIVEREFRESH TOKENPOST /v1/auth/refresh

Send the **refresh token** (not the access token) as `Authorization: Bearer <refreshToken>` . No body.

```
// response - HTTP 201
{
  "status": true, "message": "Token refresh successful",
  "data": {
    "currentAccess": {
      "id": "34bfd0c7b0b24af9913abd453024ee04", "tenantName": "Docs Demo Fintech Ltd",
      "status": "active", "roleId": "0f4e5a4603234018bb80791780ac9295"
    },
    "currentRole": {
      "id": "0f4e5a4603234018bb80791780ac9295", "name": "Administrator", "department": null,
      "description": null, "isDefault": true, "riskLevelMinimum": 0, "riskLevelMaximum": 4,
      "permissions": ["dashboard:access", "team-member:create", "team-member:update", "... 12 more"]
    },
    "access": {"token": "<jwt>", "refreshToken": null}
  }
}
```

`access.refreshToken` comes back `null` . Refresh issues a new access token only — keep using the refresh token you already hold. `currentRole.permissions` is the list to gate UI actions on.

2.5 Current user & tenant access

LIVESESSIONGET /v1/auth/userGET /v1/auth/accessPOST /v1/auth/access/switch

```
// response - HTTP 200
{
  "status": true, "message": "User auth profile retrieved successfully.",
  "data": {
    "id": "f0e9c73b09f1448a94175812f9f2f4ed", "createdAt": "2026-10-01T22:36:34.146Z",
    "updatedAt": "2026-10-01T22:36:47.579Z", "email": "docs.demo.1790894194091@unifycomply.test",
    "phone": null, "firstName": "Ada", "lastName": "Okafor", "countryCode": "NG",
    "status": "active", "lastActivityAt": "2026-10-01T22:36:47.579Z", "language": "en-US",
    "timezone": "Africa/Lagos", "imageUrl": null
  }
}
```

```
// response - HTTP 200
{
  "status": true, "message": "User access information retrieved successfully",
  "data": {
    "userAccess": [
      {
        "id": "34bfd0c7b0b24af9913abd453024ee04", "tenantName": "Docs Demo Fintech Ltd",
        "status": "active", "roleId": "0f4e5a4603234018bb80791780ac9295"
      }
    ],
    "currentAccess": {
      "id": "34bfd0c7b0b24af9913abd453024ee04", "tenantName": "Docs Demo Fintech Ltd",
      "status": "active", "roleId": "0f4e5a4603234018bb80791780ac9295"
    }
  }
}
```

```
}  
}  
}
```

```
// request - POST /v1/auth/access/switch  
{  
  "accessToken": "34bfd0c7b0b24af9913abd453024ee04"  
}  
// response - HTTP 201  
{  
  "status": true, "message": "User access switched successfully",  
  "data": {  
    "currentAccess": {  
      "id": "34bfd0c7b0b24af9913abd453024ee04", "tenantName": "Docs Demo Fintech Ltd",  
      "status": "active", "roleId": "0f4e5a4603234018bb80791780ac9295"  
    },  
    "access": {"token": "<jwt>", "refreshToken": "<jwt>"}  
  }  
}
```

Switching tenants returns a new token — replace the stored one.

2.6 Change password

LIVE

SESSION

PUT /v1/auth/password

```
// request - PUT /v1/auth/password  
{  
  "password": "<redacted>"  
}  
// response - HTTP 200  
{  
  "status": true, "message": "User password updated successfully", "data": null  
}
```

2.7 Forgot password

LIVE

PUBLIC

POST /v1/auth/forgot-password

POST /v1/auth/forgot-password/:token?platform=app

```
// request - POST /v1/auth/forgot-password  
{  
  "email": "docs.demo.1790894194091@unifycomply.test"  
}  
// response - HTTP 201  
{  
  "status": true, "message": "Forgot password initiated successfully",  
  "data": {"email": "docs.demo.1790894194091@unifycomply.test", "expires": 300}  
}
```

```
// request - POST /v1/auth/forgot-password/:token?platform=app  
{  
  "email": "docs.demo.1790894194091@unifycomply.test"  
}  
// response - HTTP 201  
{  
  "status": true, "message": "Account retrieved successfully",  
  "data": {  
    "user": {  
      "id": "f0e9c73b09f1448a94175812f9f2f4ed",  
      "email": "docs.demo.1790894194091@unifycomply.test", "phone": "+2348020000001",  
      "firstName": "Ada", "lastName": "Okafor", "countryCode": "NG", "status": "active",  
      "lastActivityAt": "2026-10-01T22:38:43.379Z", "language": "en-US",  
      "timezone": "Africa/Lagos", "imageUrl": null  
    },  
    "access": {"token": "<jwt>", "refreshToken": "<jwt>"}  
  }  
}
```

```
}  
}
```

Completing the reset signs the user in — it does not take a new password. Route straight to a "set new password" screen and call §2.6 `PUT /v1/auth/password` with the returned session.

2.8 Multi-factor authentication (TOTP)

LIVESESSION

GET /v1/auth/mfa/status

POST /v1/auth/mfa/setup

PUT /v1/auth/mfa/enable

POST /v1/auth/mfa/validate?platform=app

PUT /v1/auth/mfa/disable

```
// response – HTTP 200  
{"status": true, "message": "User MFA status retrieved successfully", "data": {"MFAEnabled": false}}
```

```
// request – POST /v1/auth/mfa/setup  
// response – HTTP 201  
{  
  "status": true, "message": "User MFA setup initiated successfully",  
  "data": {  
    "secret": "<redacted>",  
    "keyUri": "otpauth://totp/unifycomply:docs.demo.1790894194091%40unifycomply.test?secret=  
<redacted>&period=30&digits=6&algorithm=SHA1&issuer=unifycomply"  
  }  
}
```

Render `keyUri` as a QR code for authenticator apps; show `secret` as the manual-entry fallback.

Enable — body is a current 6-digit code from the authenticator

```
// request – PUT /v1/auth/mfa/enable  
{"token": "401946"}  
// response – HTTP 200  
{"status": true, "message": "User MFA enabled successfully", "data": {"MFAEnabled": true}}
```

Validate — public; completes a sign-in that returned 401 "Multifactor Authentication required"

```
// request – POST /v1/auth/mfa/validate?platform=app  
{"userId": "f0e9c73b09f1448a94175812f9f2f4ed", "token": "401946"}  
// response – HTTP 201  
{  
  "status": true, "message": "Validation completed",  
  "data": {  
    "user": {  
      "id": "f0e9c73b09f1448a94175812f9f2f4ed",  
      "email": "docs.demo.1790894194091@unifycomply.test", "phone": "+234802000001",  
      "firstName": "Ada", "lastName": "Okafor", "countryCode": "NG", "status": "active",  
      "lastActivityAt": "2026-10-01T22:38:45.867Z", "language": "en-US",  
      "timezone": "Africa/Lagos", "imageUrl": null  
    },  
    "access": {"token": "<jwt>", "refreshToken": "<jwt>"  
  }  
}
```

```
}  
}
```

```
// request - PUT /v1/auth/mfa/disable  
{ "token": "843575" }  
// response - HTTP 200  
{ "status": true, "message": "User MFA disabled successfully", "data": { "MFAEnabled": false } }
```

2.9 Google sign-in LIVE PUBLIC

GET /v1/auth/google/sign-in?redirect=<your-callback-url>

GET /v1/auth/google/callback

POST /v1/auth/sign-in/intent

Navigate the browser (not `fetch`) to `/v1/auth/google/sign-in`. It answers **302** to Google's consent screen (captured: HTTP 302 → `https://accounts.google.com/o/oauth2/v2/auth?...`). Google returns to `/v1/auth/google/callback`, which redirects to your `redirect` URL with a one-time `intent`. Exchange it:

```
POST /v1/auth/sign-in/intent?platform=app  
{ "intent": "<intent from the redirect>" }  
// → same session shape as §2.3
```

Not captured live. The callback and intent exchange need a real Google account; shapes are from the controller.

3. Tenant onboarding & user profile

3.1 Onboard a tenant LIVE SESSION

POST /v1/tenants/onboarding

```
// request - POST /v1/tenants/onboarding  
{  
  "name": "Docs Demo Fintech Ltd", "registrationNumber": "RC-1029384", "countryCode": "NG",  
  "timezone": "Africa/Lagos", "website": "https://docs-demo.unifycomply.test",  
  "industry": "fintech", "companySize": "11-50"  
}  
// response - HTTP 201  
{  
  "status": true, "message": "Tenant created successfully",  
  "data": {  
    "tenant": {  
      "id": "7c9e91f81e064c6a9eada352ffeaf9c7", "name": "Docs Demo Fintech Ltd",  
      "registrationNumber": "RC-1029384", "tin": null, "industry": "fintech",  
      "website": "https://docs-demo.unifycomply.test", "yearFounded": null,  
      "companySize": "11-50", "countryCode": "NG", "timezone": "Africa/Lagos",  
      "address": {  
        "city": null, "state": null, "street": null, "country": null, "houseNo": null,  
        "zipCode": null, "formatted": "()", "stateCode": null,  
        "coordinates": { "lat": null, "lng": null }, "countryCode": null  
      }  
    }  
  },  
}
```

```

    "userAccess": [
      {
        "id": "34bfd0c7b0b24af9913abd453024ee04", "tenantName": "Docs Demo Fintech Ltd",
        "status": "active", "roleId": "0f4e5a4603234018bb80791780ac9295"
      }
    ],
    "access": {"token": "<jwt>", "refreshToken": "<jwt>"}
  }
}

```

Call once, right after the first sign-in. Required: `name`, `registrationNumber`, `countryCode`, `timezone`. Provisions everything a first verification needs: a default app, sandbox + production API keys, an Administrator role, risk/PEP/compliance defaults, default transaction-monitoring rules and the nine Re-KYC triggers.

Swap the token. `data.access.token` is now tenant-scoped; the sign-in token you used to call this has no tenant.

3.2 My profile

LIVE

SESSION

GET `/v1/users/me/profiles`

PUT `/v1/users/me/profiles`

```

// response - HTTP 200
{
  "status": true, "message": "User profile retrieved successfully",
  "data": {
    "personalInformation": {
      "firstName": "Ada", "lastName": "Okafor",
      "email": "docs.demo.1790894194091@unifycomply.test", "phone": null,
      "role": "Administrator", "department": null
    },
    "preferences": {"timezone": "Africa/Lagos", "language": "en-US"}
  }
}

```

```

// request - PUT /v1/users/me/profiles
{
  "personalInformation": {"firstName": "Ada", "lastName": "Okafor", "phone": "+2348020000001"},
  "preferences": {"language": "en-US", "timezone": "Africa/Lagos"}
}
// response - HTTP 200
{
  "status": true, "message": "User profile updated successfully",
  "data": {
    "personalInformation": {
      "firstName": "Ada", "lastName": "Okafor",
      "email": "docs.demo.1790894194091@unifycomply.test", "phone": "+2348020000001",
      "role": "Administrator", "department": null
    },
    "preferences": {"timezone": "Africa/Lagos", "language": "en-US"}
  }
}

```

Distinct from `GET /v1/auth/user` (bare user record) — this is the profile-settings screen's data.

4. Apps & API keys

Session only, permission `tenant-settings:update`. An app is a separately-configured integration under one tenant (its own keys, webhook URL, rules). Everything customer- or transaction-related is scoped to an app.

4.1 Apps — list, read, create, rename, disable

LIVESESSIONGET `/v1/tenants/apps`GET `/v1/tenants/apps/:appId`POST `/v1/tenants/apps`PUT `/v1/tenants/apps/:appId`DELETE `/v1/tenants/apps/:appId`

```
// response — HTTP 200
{
  "status": true, "message": "Apps retrieved successfully",
  "data": [
    {
      "id": "1f62a4c6854e404385bf807eea9a7b5e", "name": "Default",
      "description": "Created with the tenant", "status": "active", "isDefault": true
    }
  ],
  "meta": {"totalItems": 1, "itemsCount": 1, "itemsPerPage": 25, "totalPages": 1, "currentPage": 1}
}
```

```
// request — POST /v1/tenants/apps
{"name": "Docs Demo — Payouts", "description": "Second app used to demonstrate app CRUD"}
// response — HTTP 201
{
  "status": true, "message": "App created successfully",
  "data": {
    "id": "56110b2661184dab96a2c9f33781b075", "createdAt": "2026-10-01T22:36:51.229Z",
    "updatedAt": "2026-10-01T22:36:51.229Z", "name": "Docs Demo — Payouts",
    "description": "Second app used to demonstrate app CRUD", "status": "active",
    "isDefault": false, "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

```
// request — PUT /v1/tenants/apps/56110b2661184dab96a2c9f33781b075
{"name": "Docs Demo — Payouts (renamed)"}
// response — HTTP 200
{
  "status": true, "message": "App updated successfully",
  "data": {
    "id": "56110b2661184dab96a2c9f33781b075", "createdAt": "2026-10-01T22:36:51.229Z",
    "updatedAt": "2026-10-01T22:36:51.626Z", "name": "Docs Demo — Payouts (renamed)",
    "description": "Second app used to demonstrate app CRUD", "status": "active",
    "isDefault": false, "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

```
// request — DELETE /v1/tenants/apps/56110b2661184dab96a2c9f33781b075
// response — HTTP 200
{
  "status": true, "message": "App disabled successfully",
  "data": {
    "id": "56110b2661184dab96a2c9f33781b075", "createdAt": "2026-10-01T22:36:51.229Z",
```

```

    "updatedAt": "2026-10-01T22:36:52.000Z", "name": "Docs Demo - Payouts (renamed)",
    "description": "Second app used to demonstrate app CRUD", "status": "disabled",
    "isDefault": false, "tenantId": "7c9e91f81e064c6a9eada352ffef9c7"
  }
}

```

Delete is a soft disable (`status: "disabled"`): customers and verdicts are kept. Creating an app seeds its TM rules and Re-KYC triggers automatically.

4.2 API keys — list, issue, rotate, revoke LIVE SESSION

GET `/v1/tenants/apps/:appId/keys`

POST /v1/tenants/apps/:appId/keys

POST /v1/tenants/apps/:appId/keys/:keyId/rotate

DELETE /v1/tenants/apps/:appId/keys/:keyId

```
// request - POST /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/keys
{"name": "Docs demo integration", "scopes": ["customers:read", "customers:write", "... 7 more"]}
// response - HTTP 201
{
  "status": true,
  "message": "Key issued successfully. Copy the secret now - it is not shown again.",
  "data": {
    "id": "6fd6d4ef168e4181a5060ad4b129e1bb", "createdAt": "2026-10-01T22:36:49.174Z",
    "updatedAt": "2026-10-01T22:36:49.174Z", "publicKey": "pk_sandbox-YBWsJoTdgbbq...",
    "secretKey": "sk_sandbox-<redacted>", "domain": "sandbox", "lastUsedAt": null,
    "name": "Docs demo integration",
    "scopes": ["customers:read", "customers:write", "... 7 more"],
    "tenantId": "7c9e91f81e064c6a9eada352ffef9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e"
  }
}
```

secretKey is returned exactly once — on create and on rotate. Show it in a copy-once dialog. Lists return the record without a usable secret. Rotating kills the old secret immediately — warn before confirming.

```
// response - HTTP 200
{
  "status": true, "message": "Keys retrieved successfully",
  "data": [
    {
      "id": "ab1243ffea424c728053e065912ee6a3", "publicKey": "pk_sandbox-PD0ATkLTdCn...",
      "lastUsedAt": null, "name": "Default key",
      "scopes": ["customers:read", "customers:write", "... 7 more"]
    }
  ]
}
```

```
// response - HTTP 201
{
  "status": true, "message": "Key rotated successfully. The previous secret no longer works.",
  "data": {
    "id": "489b9ed234d540eda9cccbdbdfef68b26", "createdAt": "2026-10-01T22:36:49.557Z",
    "updatedAt": "2026-10-01T22:36:49.940Z", "publicKey": "pk_sandbox-eNPTKUBKMqJ...",
    "secretKey": "sk_sandbox-<redacted>", "domain": "sandbox", "lastUsedAt": null,
    "name": "Read-only dashboard key", "scopes": ["verifications:read"],
    "tenantId": "7c9e91f81e064c6a9eada352ffef9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e"
```

```
}  
}
```

```
// response – HTTP 200  
{  
  "status": true, "message": "Key revoked successfully",  
  "data": {"id": "489b9ed234d540eda9ccdbdfef68b26"}  
}
```

Available scopes are the nine in §1. Keys are issued in the caller's current domain.

4.3 App's primary API key

LIVESESSION

GET /v1/tenants/apps/:appId/api-key

POST /v1/tenants/apps/:appId/api-key/rotate

```
// response – HTTP 200  
{  
  "status": true, "message": "App API keys retrieved successfully",  
  "data": {  
    "id": "ab1243ffea424c728053e065912ee6a3", "createdAt": "2026-10-01T22:36:34.547Z",  
    "updatedAt": "2026-10-01T22:36:34.547Z", "publicKey": "pk_sandbox-PD0ATkLTdCn...",  
    "secretKey": "sk_sandbox-<redacted>", "domain": "sandbox", "lastUsedAt": null,  
    "name": "Default key",  
    "scopes": ["customers:read", "customers:write", "... 7 more"],  
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e"  
  }  
}
```

The key provisioned at onboarding. `rotate` behaves like §4.2's rotate.

4.4 App-scope backfill (operational)

LIVESESSION

GET /v1/tenants/apps/scope/status

POST /v1/tenants/apps/scope/backfill

```
// response – HTTP 200  
{  
  "status": true, "message": "App scope status retrieved successfully",  
  "data": {"compliance": {"scopable": 0, "orphaned": 0}, "risk": {"scopable": 0, "orphaned": 0}}  
}
```

```
// response – HTTP 201  
{  
  "status": true, "message": "App scope backfill completed",  
  "data": {  
    "tenants": 5, "workflows": 0, "complianceRows": 0, "riskRows": 0,  
    "unscoped": {"compliance": {"scopable": 0, "orphaned": 0}, "risk": {"scopable": 0, "orphaned":  
0}}  
  }  
}
```

Assigns legacy rows that pre-date apps to the tenant's default app. Not something a normal settings screen needs.

5. App configuration — risk, PEP, compliance rules, webhooks

Session only, `tenant-settings:update`. Each is a GET/PUT pair under `/v1/tenants/apps/:appId/...`. This is the configuration snapshotted onto every verification run.

5.1 Risk factor configurations

LIVE

SESSION

GET `/v1/tenants/apps/:appId/risk-factor-configurations`

PUT `/v1/tenants/apps/:appId/risk-factor-configurations/:slug`

```
// response - HTTP 200
{
  "status": true, "message": "App risk factor configurations retrieved successfully",
  "data": [
    {
      "name": "Politically Exposed Person (PEP) Association",
      "description": "Name similarity or known association with politically exposed persons",
      "type": "regulatory", "slug": "pep-association", "riskWeight": 1, "enabled": true
    },
    {
      "name": "Sanctions List Match",
      "description": "Name appears on international sanctions lists (OFAC, EU, UN)",
      "type": "regulatory", "slug": "sanctions-list-match", "riskWeight": 1, "enabled": true
    },
    "... 4 more"
  ]
}
```

```
// request - PUT /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/risk-factor-configurations/pep-association
{"riskWeight": 2, "enabled": true}
// response - HTTP 200
{
  "status": true, "message": "App risk factor configurations updated successfully",
  "data": {
    "createdAt": "2026-10-01T22:36:34.547Z", "updatedAt": "2026-10-01T22:36:55.858Z",
    "name": "Politically Exposed Person (PEP) Association",
    "description": "Name similarity or known association with politically exposed persons",
    "type": "regulatory", "slug": "pep-association", "riskWeight": 2, "enabled": true,
    "domain": "sandbox", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

5.2 Risk score threshold

LIVESESSION

GET /v1/tenants/apps/:appId/risk-score-threshold

PUT /v1/tenants/apps/:appId/risk-score-threshold

```
// request - PUT /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/risk-score-threshold
{"warningThreshold": 2, "blockThreshold": 3}
// response - HTTP 200
{
  "status": true, "message": "App risk score thresholds updated successfully",
  "data": {
    "createdAt": "2026-10-01T22:36:34.547Z", "updatedAt": "2026-10-01T22:36:56.232Z",
    "warningThreshold": 2, "blockThreshold": 3, "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

On the KYC/KYB 0–4 scale: at or above `warningThreshold` a run goes to review; at or above `blockThreshold` it is blocked.

5.3 PEP tier configurations

LIVESESSION

GET /v1/tenants/apps/:appId/pep-tier-configurations

PUT /v1/tenants/apps/:appId/pep-tier-configurations/:tier

```
// request - PUT /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/pep-tier-configurations/tier-1
{"riskScoreImpact": 4, "requiresApproval": true, "autoEscalation": true}
// response - HTTP 200
{
  "status": true, "message": "App PEP tier configurations updated successfully",
  "data": {
    "createdAt": "2026-10-01T22:36:34.549Z", "updatedAt": "2026-10-01T22:36:56.609Z",
    "name": "Senior Foreign PEP", "tier": "tier-1",
    "description": "Heads of state, government ministers, senior officials",
    "riskScoreImpact": 4, "requiresApproval": true, "autoEscalation": true,
    "positionDescription": "Holds the highest offices of state, operates in high-corruption jurisdictions, or has adve...",
    "positionExamples": ["President", "Prime Minister", "... 2 more"], "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

5.4 Compliance rules

LIVESESSION

GET /v1/tenants/apps/:appId/compliance-rules

PUT /v1/tenants/apps/:appId/compliance-rules

```
// request - PUT /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/compliance-rules
{"flaggedCountryCodes": ["IR", "KP"], "kycExpiryDays": 365}
// response - HTTP 200
{
  "status": true, "message": "App compliance rules updated successfully",
  "data": {
    "createdAt": "2026-10-01T22:36:34.549Z", "updatedAt": "2026-10-01T22:36:57.364Z",

```

```

    "kycExpiryDays": 365, "kybExpiryDays": 365,
    "kycDocuments": ["id-document", "liveness-check", "... 1 more"],
    "kybDocuments": ["certificate-of-incorporation", "directors-id", "... 2 more"],
    "flaggedCountryCodes": ["IR", "KP"], "activityBreachMultiplier": 2, "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}

```

`kycDocuments` / `kybDocuments` drive each customer's document requirements (§8.9). `flaggedCountryCodes` blocks onboarding from those countries **and** powers the High-Risk Country transaction check (§12). PUT accepts any subset of fields.

5.5 Webhook settings & signing secret

LIVE

SESSION

GET /v1/tenants/apps/:appId/notification-preferences

PUT /v1/tenants/apps/:appId/notification-preferences

POST /v1/tenants/apps/:appId/webhook/rotate-secret

```

// request - PUT /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/notification-preferences
{"eventCallbackUrl": "https://example.com/webhooks/unifycomply", "webhookEnabled": true}
// response - HTTP 200
{
  "status": true, "message": "App developer config updated successfully",
  "data": {
    "id": "849b46839a254d6a874b972dd4e13d0b", "createdAt": "2026-10-01T22:36:34.547Z",
    "updatedAt": "2026-10-01T22:37:00.826Z", "domain": "sandbox",
    "eventCallbackUrl": "https://example.com/webhooks/unifycomply",
    "webhookSecret": "whsec_<redacted>", "webhookEnabled": true, "ipWhitelistEnabled": false,
    "allowedIps": [], "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}

```

Rejected: a callback URL that resolves to a private address

```

// request - PUT /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/notification-preferences
{
  "eventCallbackUrl": "http://webhooks.docs-demo.localhost:4999/unifycomply",
  "webhookEnabled": true
}
// response - HTTP 400
{
  "status": false,
  "message": "Webhook host webhooks.docs-demo.localhost resolves to a non-public address (::1)"
}

```

Callback URLs must resolve to a public address. `localhost`, `127.0.0.1`, `*.localhost` and private ranges are refused (SSRF protection). For local development use a public tunnel (ngrok, Cloudflare Tunnel).

```

// response - HTTP 201
{
  "status": true, "message": "Webhook signing secret rotated successfully",
  "data": {
    "id": "849b46839a254d6a874b972dd4e13d0b", "createdAt": "2026-10-01T22:36:34.547Z",
    "updatedAt": "2026-10-01T22:36:57.748Z", "domain": "sandbox", "eventCallbackUrl": null,
    "webhookSecret": "whsec_<redacted>", "webhookEnabled": true, "ipWhitelistEnabled": false,
    "allowedIps": [], "appId": "1f62a4c6854e404385bf807eea9a7b5e",
  }
}

```

```
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"  
  }  
}
```

Rotation invalidates signatures made with the old secret immediately, including retries already queued.

6. Team, roles, business information, domain

Session only, `tenant-settings:update` . Tenant-wide by design — teams and roles are not per-app.

6.1 Team invites

LIVE

SESSION

- GET** `/v1/tenants/settings/teams`
- POST** `/v1/tenants/settings/teams`
- POST** `/v1/tenants/settings/teams/resend`
- DELETE** `/v1/tenants/settings/teams/:inviteId/revoke`

```
// request - POST /v1/tenants/settings/teams
{
  "fullName": "Bola Analyst", "email": "bola.analyst.1790894322184@unifycomply.test",
  "roleId": "0f4e5a4603234018bb80791780ac9295"
}
// response - HTTP 201
{
  "status": true, "message": "Tenant team invite created successfully",
  "data": {
    "id": "515dbf7316a14b7a826148716b658ab4", "createdAt": "2026-10-01T22:38:42.599Z",
    "updatedAt": "2026-10-01T22:38:42.599Z", "fullName": "Bola Analyst",
    "email": "bola.analyst.1790894322184@unifycomply.test", "status": "pending",
    "expiryDate": "2026-10-04T22:38:42.595Z", "roleId": "0f4e5a4603234018bb80791780ac9295",
    "userId": null, "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

```
// request - POST /v1/tenants/settings/teams/resend
{"id": "515dbf7316a14b7a826148716b658ab4"}
// response - HTTP 201
{
  "status": true, "message": "Tenant team invite resend successfully",
  "data": {
    "id": "515dbf7316a14b7a826148716b658ab4", "createdAt": "2026-10-01T22:38:42.599Z",
    "updatedAt": "2026-10-01T22:38:43.005Z", "fullName": "Bola Analyst",
    "email": "bola.analyst.1790894322184@unifycomply.test", "status": "pending",
    "expiryDate": "2026-10-04T22:38:43.005Z", "roleId": "0f4e5a4603234018bb80791780ac9295",
    "userId": null, "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

`id` goes in the JSON body, not the query string.

```
// response - HTTP 200
{
  "status": true, "message": "Tenant team information retrieved successfully",
  "data": [
    {
      "email": "bola.analyst.1790894322184@unifycomply.test",
      "id": "515dbf7316a14b7a826148716b658ab4", "name": "Bola Analyst", "imageUrl": null,
      "status": "pending", "lastActivityAt": null, "roleName": "Administrator"
    },
    {
      "email": "bola.analyst.1790894315945@unifycomply.test",
      "id": "1b35dbd6213641928667128c190bcfd9", "name": "Bola Analyst", "imageUrl": null,
      "status": "revoked", "lastActivityAt": null, "roleName": "Administrator"
    }
  ]
}
```

```
}  
}
```

```
// response – HTTP 200  
{  
  "status": true, "message": "Tenant team invite revoked successfully",  
  "data": {  
    "id": "1b35dbd6213641928667128c190bcfd9", "createdAt": "2026-10-01T22:38:36.331Z",  
    "updatedAt": "2026-10-01T22:38:37.494Z", "fullName": "Bola Analyst",  
    "email": "bola.analyst.1790894315945@unifycomply.test", "status": "revoked",  
    "expiryDate": "2026-10-04T22:38:36.330Z", "roleId": "0f4e5a4603234018bb80791780ac9295",  
    "userId": null, "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"  
  }  
}
```

6.2 Roles & permissions

LIVESESSION

```
GET /v1/tenants/settings/roles-permissions  
POST /v1/tenants/settings/roles-permissions  
GET /v1/tenants/settings/roles-permissions/options  
GET /v1/tenants/settings/roles-permissions/:roleId  
PUT /v1/tenants/settings/roles-permissions/:roleId  
DELETE /v1/tenants/settings/roles-permissions/:roleId
```

Single-role routes are spelled `roles-permissions` (missing "i"). That is the real path; the collection routes use the correct spelling.

```
// response – HTTP 200  
{  
  "status": true, "message": "Tenant role permission options retrieved successfully",  
  "data": [  
    {  
      "value": "team-member:create", "label": "Can Add Team Members",  
      "description": "Allow this role to invite and add new team members to the tenant"  
    },  
    {  
      "value": "team-member:update", "label": "Can Update Team Members",  
      "description": "Allow this role to update team member details and assignments"  
    },  
    {  
      "value": "role-permission:create", "label": "Can Create Roles & Permissions",  
      "description": "Allow this role to create new roles and assign permissions to them"  
    },  
    "... 9 more"  
  ]  
}
```

The permission vocabulary — render it as the checkbox list. 12 permissions today.

```
// request – POST /v1/tenants/settings/roles-permissions  
{  
  "name": "Compliance Analyst", "description": "Works cases and drafts SARs",  
  "department": "Compliance", "riskLevelMinimum": 0, "riskLevelMaximum": 2,  
  "permissions": ["dashboard:access", "customers:retrieve", "... 3 more"]  
}  
// response – HTTP 201
```

```
{
  "status": true, "message": "Tenant roles and permissions created successfully",
  "data": {
    "id": "746aaacf52f84b828659d2da624efd5e", "createdAt": "2026-10-01T22:38:37.872Z",
    "updatedAt": "2026-10-01T22:38:37.872Z", "name": "Compliance Analyst",
    "department": "Compliance", "description": "Works cases and drafts SARs", "isDefault": false,
    "riskLevelMinimum": 0, "riskLevelMaximum": 2,
    "permissions": ["dashboard:access", "customers:retrieve", "... 3 more"],
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

```
// request - PUT /v1/tenants/settings/roles-permissions/746aaacf52f84b828659d2da624efd5e
{
  "name": "Compliance Analyst", "riskLevelMinimum": 0, "riskLevelMaximum": 3,
  "permissions": ["dashboard:access", "customers:retrieve", "... 4 more"]
}
// response - HTTP 200
{
  "status": true, "message": "Tenant roles permissions updated successfully",
  "data": {
    "id": "746aaacf52f84b828659d2da624efd5e", "createdAt": "2026-10-01T22:38:37.872Z",
    "updatedAt": "2026-10-01T22:38:38.630Z", "name": "Compliance Analyst",
    "department": "Compliance", "description": "Works cases and drafts SARs", "isDefault": false,
    "riskLevelMinimum": 0, "riskLevelMaximum": 3,
    "permissions": ["dashboard:access", "customers:retrieve", "... 4 more"],
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

```
// response - HTTP 200
{"status": true, "message": "Tenant roles permissions deleted successfully", "data": null}
```

400 — `riskLevelMinimum` must be ≤ `riskLevelMaximum` (0–4 scale)

```
// request - POST /v1/tenants/settings/roles-permissions
{"name": "Broken", "riskLevelMinimum": 3, "riskLevelMaximum": 1, "permissions": ["dashboard:access"]}
// response - HTTP 400
{
  "status": false,
  "message": "`role.riskLevelMinimum` should be less than or equals to `role.riskLevelMaximum` value."
}
```

6.3 Business information

LIVE

SESSION

GET /v1/tenants/settings/business-information

PUT /v1/tenants/settings/business-information

```
// request - PUT /v1/tenants/settings/business-information
{"website": "https://docs-demo.unifycomply.test", "tin": "TIN-0099887"}
// response - HTTP 200
{
  "status": true, "message": "Tenant business information updated successfully",
  "data": {
    "name": "Docs Demo Fintech Ltd", "registrationNumber": "RC-1029384", "tin": "TIN-0099887",
    "industry": "fintech", "website": "https://docs-demo.unifycomply.test", "yearFounded": null,
    "companySize": "11-50",
    "address": {
```

```

    "city": null, "state": null, "street": null, "country": null, "houseNo": null,
    "zipCode": null, "formatted": "()", "stateCode": null,
    "coordinates": {"lat": null, "lng": null}, "countryCode": null
  }
}
}

```

6.4 Switch domain (sandbox ↔ production)

LIVE

SESSION

POST /v1/tenants/settings/domain/switch

```

// request - POST /v1/tenants/settings/domain/switch
{"domain": "production"}
// response - HTTP 201
{
  "status": true, "message": "User access switched successfully",
  "data": {
    "currentAccess": {
      "id": "34bfd0c7b0b24af9913abd453024ee04", "tenantName": "Docs Demo Fintech Ltd",
      "status": "active", "roleId": "0f4e5a4603234018bb80791780ac9295"
    },
    "access": {"token": "<jwt>", "refreshToken": "<jwt>"}
  }
}

```

Same customer list, now in production — empty, because sandbox data is isolated

```

// response - HTTP 200
{
  "status": true, "message": "Customers kyc retrieved successfully", "data": [],
  "meta": {"totalItems": 0, "itemsCount": 0, "itemsPerPage": 5, "totalPages": 0, "currentPage": 1}
}

```

Store the returned token; every subsequent call operates in the new domain.

6.5 Deprecated tenant-wide settings routes

LIVE

SESSION

GET /v1/tenants/settings/{api-key | risk-factor-configurations | risk-score-threshold | pep-tier-configurations | notification-preferences | compliance-rules | webhook/deliveries}

```

// response - HTTP 200
{
  "status": true, "message": "Tenant compliance rules retrieved successfully",
  "data": {
    "createdAt": "2026-10-01T22:36:34.549Z", "updatedAt": "2026-10-01T22:36:57.364Z",
    "kycExpiryDays": 365, "kybExpiryDays": 365,
    "kycDocuments": ["id-document", "liveness-check", "... 1 more"],
    "kybDocuments": ["certificate-of-incorporation", "directors-id", "... 2 more"],
    "flaggedCountryCodes": ["IR", "KP"], "activityBreachMultiplier": 2, "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}

```

These still work and read/write the tenant's **default** app, but are marked deprecated in Swagger. Build against the `/v1/tenants/apps/:appId/...` equivalents in §4–§5. Includes their PUT / rotate / redeliver siblings.

7. Public option sets (enum lookups)

7.1 Option sets

LIVEPUBLIC

GET `/v1/public/misc/options/keys`

GET `/v1/public/misc/options?keys=a,b`

GET `/v1/public/misc/options/:key`

Every closed vocabulary the API validates against, served as data. Load once per session and cache; never hardcode dropdown values that can drift from the server.

```
// response – HTTP 200
{
  "status": true, "message": "Items retrieved successfully",
  "data": [
    "countries",
    "profile-types",
    "domains",
    "genders",
    "business-types",
    "business-industries",
    "employee-counts",
    "shareholder-types",
    "individual-verification-types",
    "business-verification-types",
    "shared-verification-types",
    "kyc-document-categories",
    "kyb-document-categories",
    "individual-document-types",
    "business-document-types",
    "workflow-statuses",
    "workflow-priorities",
    "verification-run-statuses",
    "verification-outcomes",
    "verification-provider-keys",
    "verification-reason-severities",
    "document-statuses",
    "customer-lifecycle-statuses",
    "risk-bands",
    "risk-decisions",
    "risk-priorities",
    "risk-factor-types",
    "pep-tiers",
    "role-permissions",
    "team-invite-statuses",
    "transaction-types",
    "transaction-directions",
    "tm-categories",
    "tm-rule-severities",
    "tm-rule-statuses",
    "tm-risk-levels",
    "tm-condition-operators",
    "tm-condition-fields",
    "transaction-risk-statuses",
    "transaction-timeline-events"
  ]
}
```

```
]
}
```

```
// response – HTTP 200
{
  "status": true, "message": "Items retrieved successfully",
  "data": {
    "key": "<redacted>",
    "description": "Comparison a transaction-monitoring rule's condition applies",
    "options": [{"value": "equals", "label": "Equals"}, {"value": "not-equals", "label": "Not
Equals"}, "... 4 more"]
  }
}
```

```
// response – HTTP 200
{
  "status": true, "message": "Items retrieved successfully",
  "data": {
    "sets": [
      {
        "key": "<redacted>", "description": "Whether a customer is a person or a company",
        "options": [{"value": "individual", "label": "Individual"}, {"value": "business", "label":
"Business"}]
      },
      {
        "key": "genders", "description": "Gender values on an individual customer",
        "options": [{"value": "male", "label": "Male"}, {"value": "female", "label": "Female"}]
      },
      {
        "key": "<redacted>",
        "description": "Which of the four transaction-monitoring queues a matched rule routes to",
        "options": [
          {"value": "tm-not-blocked", "label": "TM Not Blocked"},
          {"value": "stop-payment", "label": "Stop Payment"},
          {"value": "cumulative-frequency", "label": "Cumulative Frequency"},
          "... 1 more"
        ]
      }
    ],
    "constants": {"riskScore": {"min": 0, "max": 4}}
  }
}
```

Investigation vocabularies are not registered here yet. Case resolution types, case actions-taken, PND resolution types and investigation risk levels must be hardcoded from §15–§16 for now (see §17).

8. Customers — KYC (individuals) & KYB (businesses)

Two parallel trees, `/v1/customers/kyc` and `/v1/customers/kyb`, with the same shape. Session or API key. `tenantId`, `appId` and `domain` are always resolved from the credential — never send them.

8.1 Create an individual

LIVESESSIONAPI KEYPOST `/v1/customers/kyc`

```
// request - POST /v1/customers/kyc
{
  "firstName": "Chidinma", "lastName": "Eze", "dob": "1991-04-12", "gender": "female",
  "email": "chidinma.eze@example.com", "phone": "+2348031234567", "countryCode": "NG",
  "address": {
    "houseNo": "12", "street": "Admiralty Way", "city": "Lekki", "state": "Lagos",
    "stateCode": "LA", "country": "Nigeria", "countryCode": "NG", "zipCode": "105102"
  }
}
// response - HTTP 201
{
  "status": true, "message": "Customer kyc created successfully",
  "data": {
    "id": "33c479186e2741be98bce2af145959af", "createdAt": "2026-10-01T22:37:01.390Z",
    "updatedAt": "2026-10-01T22:37:01.390Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffef9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "firstName": "Chidinma", "lastName": "Eze", "middleName": null,
    "email": "chidinma.eze@example.com", "phone": "+2348031234567", "countryCode": "NG",
    "dob": "1991-04-12",
    "address": {
      "city": "Lekki", "state": "Lagos", "street": "Admiralty Way", "country": "Nigeria",
      "houseNo": "12", "zipCode": "105102",
      "formatted": "12 Admiralty Way, Lekki, Lagos LA, 105102, Nigeria (NG)", "stateCode": "LA",
      "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
    },
    "gender": "female", "emailChangedAt": null, "phoneChangedAt": null, "addressChangedAt": null,
    "status": "pending", "statusReasons": [], "statusChangedAt": null, "statusRunId": null,
    "riskScore": null, "lastReviewedAt": null, "nextReviewAt": null, "flags": [],
    "documentTypes": []
  }
}
```

Required: `firstName`, `lastName`, `dob` (ISO date), `gender` (`male|female`), `email`, `phone`, `countryCode` (ISO-2), `address` (object; every field optional). New customers start `status: "pending"` with `nextReviewAt` set by the app's `kycExpiryDays`. Creation from a country in `flaggedCountryCodes` is refused.

Requires: `customers:write`

8.2 Create a business

LIVESESSIONAPI KEYPOST `/v1/customers/kyb`

```
// request - POST /v1/customers/kyb
{
  "businessName": "Kora Logistics Limited", "registrationDate": "2018-03-15",
  "contactEmail": "compliance@koralogistics.example", "contactPhone": "+2348091234567",
  "countryCode": "NG", "industry": "technology", "website": "https://koralogistics.example",
  "address": {
    "houseNo": "27", "street": "Adeola Odeku Street", "city": "Victoria Island",
    "state": "Lagos", "stateCode": "LA", "country": "Nigeria", "countryCode": "NG",
    "zipCode": "101241"
  }
}
```

```

}
}
// response – HTTP 201
{
  "status": true, "message": "Customer kyb created successfully",
  "data": {
    "id": "eab4159c3215435d9b12806cdd629c96", "createdAt": "2026-10-01T22:37:12.339Z",
    "updatedAt": "2026-10-01T22:37:12.339Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "businessName": "Kora Logistics Limited", "businessType": null, "countryCode": "NG",
    "address": {
      "city": "Victoria Island", "state": "Lagos", "street": "Adeola Odeku Street",
      "country": "Nigeria", "houseNo": "27", "zipCode": "101241",
      "formatted": "27 Adeola Odeku Street, Victoria Island, Lagos LA, 101241, Nigeria (NG)",
      "stateCode": "LA",
      "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
    },
    "registrationDate": "2018-03-15", "industry": "technology",
    "contactEmail": "compliance@koralogistics.example", "contactPhone": "+2348091234567",
    "website": "https://koralogistics.example", "contactEmailChangedAt": null,
    "contactPhoneChangedAt": null, "addressChangedAt": null, "status": "pending",
    "statusReasons": [], "statusChangedAt": null, "statusRunId": null, "riskScore": null,
    "lastReviewedAt": null, "nextReviewAt": null, "flags": [], "documentTypes": []
  }
}
}

```

Required: `businessName`, `registrationDate`, `contactEmail`, `contactPhone`, `countryCode`, `address`.

Optional: `industry`, `website`.

Requires: `customers:write`

8.3 Read, list & stats

LIVE

SESSION

API KEY

GET `/v1/customers/kyc/:customerId`

GET `/v1/customers/kyc`

GET `/v1/customers/kyc/stats`

GET `/v1/customers/kyb/:customerId`

GET `/v1/customers/kyb`

GET `/v1/customers/kyb/stats`

Query: `page`, `limit`, `status` (`pending|onboarded|review|blocked|offboarded`; omitted → offboarded excluded), `search` (name, email, phone), `dateFrom`, `dateTo`.

```

// response – HTTP 200
{
  "status": true, "message": "Customer retrieved successfully",
  "data": {
    "id": "33c479186e2741be98bce2af145959af", "createdAt": "2026-10-01T22:37:01.390Z",
    "updatedAt": "2026-10-01T22:37:30.296Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "firstName": "Chidinma", "lastName": "Eze", "middleName": null,
    "email": "chidinma.eze@example.com", "phone": "+2348031234500", "countryCode": "NG",
    "dob": "1991-04-12",
    "address": {
      "city": "Lekki", "state": "Lagos", "street": "Admiralty Way", "country": "Nigeria",
      "houseNo": "12", "zipCode": "105102",
      "formatted": "12 Admiralty Way, Lekki, Lagos LA, 105102, Nigeria (NG)", "stateCode": "LA",
      "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
    },
    "gender": "female", "emailChangedAt": null, "phoneChangedAt": "2026-10-01T22:37:11.865Z",
  }
}

```

```

"addressChangedAt": null, "status": "onboarded", "statusReasons": [],
"statusChangedAt": "2026-10-01T22:37:30.294Z",
"statusRunId": "081e121f775f4b53bf0a7758f4f474a5", "riskScore": 0,
"lastReviewedAt": "2026-10-01T22:37:30.294Z", "nextReviewAt": "2027-10-01T22:37:30.296Z",
"flags": [],
"documentTypes": ["passport", "selfie-photo", "utility-bill"],
"lifecycle": [
  {
    "id": "72f15473453b4afc950cc8622491358b", "profileType": "individual",
    "fromStatus": "pending", "toStatus": "onboarded", "actor": "risk-decisioning",
    "reasons": [], "riskScore": 0,
    "detail": {
      "band": "low", "workflowId": "7a10d4b1895741a48674bbe4769d05df", "blockThreshold": 3,
      "warningThreshold": 2
    },
    "customerId": "33c479186e2741be98bce2af145959af",
    "runId": "081e121f775f4b53bf0a7758f4f474a5"
  }
]
}

```

Individual detail additionally carries `lifecycle` (status history). `flags` holds monitoring findings (§8.7); `documentTypes` lists what has been uploaded.

```

// response – HTTP 200
{
  "status": true, "message": "Customers kyc retrieved successfully",
  "data": [
    {
      "id": "ac906f738a7647668077edd4b9105234", "firstName": "Tunde", "lastName": "Bakare",
      "middleName": null, "email": "tunde.bakare@example.com", "phone": "+2348039876543",
      "countryCode": "NG", "dob": "1986-09-02",
      "address": {
        "city": "Ikoyi", "state": "Lagos", "street": "Awolowo Road", "country": "Nigeria",
        "houseNo": "4", "zipCode": "105102",
        "formatted": "4 Awolowo Road, Ikoyi, Lagos LA, 105102, Nigeria (NG)", "stateCode": "LA",
        "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
      },
      "gender": "male", "emailChangedAt": null, "phoneChangedAt": null, "addressChangedAt": null,
      "status": "pending", "statusReasons": [], "statusChangedAt": null, "statusRunId": null,
      "riskScore": null, "lastReviewedAt": null, "nextReviewAt": null, "flags": [],
      "documentTypes": []
    },
    "... 1 more"
  ],
  "meta": {"totalItems": 2, "itemsCount": 2, "itemsPerPage": 10, "totalPages": 1, "currentPage": 1}
}

```

```

// response – HTTP 200
{
  "status": true, "message": "Customers kyc stats retrieved successfully",
  "data": {"successful": 0, "pending": 2, "highRisk": 0, "rejected": 0}
}

```

Counts derive from each customer's latest verification, not the customer row.

Roster vs queue. This is the roster (who). Priority, assignee and time-in-queue live on the verification queue (§9.4). Join on `customerId` when a screen needs both.

Requires: `customers:read`

8.4 Update (full replace)

LIVESESSIONAPI KEYPUT /v1/customers/kyc/:customerIdPUT /v1/customers/kyb/:customerId

```
// request - PUT /v1/customers/kyc/33c479186e2741be98bce2af145959af
{
  "firstName": "Chidinma", "lastName": "Eze", "dob": "1991-04-12", "gender": "female",
  "email": "chidinma.eze@example.com", "phone": "+2348031234500", "countryCode": "NG",
  "address": {
    "houseNo": "12", "street": "Admiralty Way", "city": "Lekki", "state": "Lagos",
    "stateCode": "LA", "country": "Nigeria", "countryCode": "NG", "zipCode": "105102"
  }
}
// response - HTTP 200
{
  "status": true, "message": "Customer kyc updated successfully",
  "data": {
    "id": "33c479186e2741be98bce2af145959af", "createdAt": "2026-10-01T22:37:01.390Z",
    "updatedAt": "2026-10-01T22:37:11.865Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "firstName": "Chidinma", "lastName": "Eze", "middleName": null,
    "email": "chidinma.eze@example.com", "phone": "+2348031234500", "countryCode": "NG",
    "dob": "1991-04-12",
    "address": {
      "city": "Lekki", "state": "Lagos", "street": "Admiralty Way", "country": "Nigeria",
      "houseNo": "12", "zipCode": "105102",
      "formatted": "12 Admiralty Way, Lekki, Lagos LA, 105102, Nigeria (NG)", "stateCode": "LA",
      "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
    },
    "gender": "female", "emailChangedAt": null, "phoneChangedAt": "2026-10-01T22:37:11.865Z",
    "addressChangedAt": null, "status": "pending", "statusReasons": [], "statusChangedAt": null,
    "statusRunId": null, "riskScore": null, "lastReviewedAt": null, "nextReviewAt": null,
    "flags": [],
    "documentTypes": ["passport", "... 2 more"]
  }
}
```

400 — sending only the changed field

```
// request - PUT /v1/customers/kyc/33c479186e2741be98bce2af145959af
{"phone": "+2348031234500"}
// response - HTTP 400
{
  "status": false,
  "message": "firstName must be a string, lastName must be a string, email must be a string,
countryCode ($value) is not a valid ISO 3166-1 alpha-2 country code rec..."
}
```

PUT is a full replace. Send every required field, pre-filled from the current record, even to change one value.

Changing two of email / phone / address within 72 hours on an onboarded customer raises a suspected account-takeover Re-KYC trigger. The customer's verified workflow flips to `in-review` (configurable in §13).

Requires: `customers:write`

8.5 Approve / reject after review

LIVESESSIONAPI KEY

POST /v1/customers/{kyc|kyb}/:customerId/approve

POST /v1/customers/{kyc|kyb}/:customerId/reject

```
// request - POST /v1/customers/kyb/eab4159c3215435d9b12806cdd629c96/approve
{"reason": "Directors cleared on manual review; CAC records match."}
// response - HTTP 201
{
  "status": true, "message": "Customer kyb onboarding approved",
  "data": {"customerId": "eab4159c3215435d9b12806cdd629c96", "status": "onboarded"}
}
```

```
// request - POST /v1/customers/kyc/12c1a2ae64ec4a29882031494f7f21f7/reject
{"reason": "Confirmed sanctions match against OFAC SDN list."}
// response - HTTP 201
{
  "status": true, "message": "Customer kyc onboarding rejected",
  "data": {"customerId": "12c1a2ae64ec4a29882031494f7f21f7", "status": "blocked"}
}
```

400 — reject without a reason

```
// request - POST /v1/customers/kyc/ac906f738a7647668077edd4b9105234/reject
{}
// response - HTTP 400
{
  "status": false,
  "message": "reason must not be blank, reason should not be empty, reason must be a string"
}
```

reason is required on reject, optional on approve. Rejecting blocks the customer and fails their verification, so it must say why (blank or whitespace-only is refused). Make it a required field in the reject dialog.

A compliance officer's manual decision on a customer the engine left in review/blocked. Approve also settles the customer's latest verification to `verified`; reject settles it to `failed`. Both write a `customer.review.approved|rejected` audit event (actor = the signed-in user's email, or `api-key`) and fire the matching `workflow.verified` / `workflow.failed` webhook (§11.2), with the reason recorded on both.

Requires: `customers:write`

8.6 Offboard (soft delete)

LIVESESSIONAPI KEY

DELETE /v1/customers/{kyc|kyb}/:customerId

```
// request - DELETE /v1/customers/kyc/ac906f738a7647668077edd4b9105234
{"reason": "Customer closed their account"}
// response - HTTP 200
{
  "status": true, "message": "Customer kyc offboarded successfully",
  "data": {"customerId": "ac906f738a7647668077edd4b9105234", "status": "offboarded"}
}
```

Moves the customer to `offboarded`; nothing is deleted and a later clean run never re-onboards them. Find them again with `?status=offboarded`.

Requires: `customers:write`

8.7 Flags (monitoring findings)

PARTIAL

SESSION

API KEY

PATCH `/v1/customers/{kyc|kyb}/:customerId/flags/:flagId`

```
// request
{ "status": "investigating", "note": "Reviewing adverse media" } // warning → investigating → revised
```

404 — unknown flag id (real response; the demo customer had no flags)

```
// response — HTTP 404
{
  "status": false,
  "message": "No flag flg_does_not_exist on customer 33c479186e2741be98bce2af145959af"
}
```

Flags move forward only (`warning` → `investigating` → `revised`); skipping or going backwards returns 400, and `note` is required for `revised` .

Field	Status	Why
<code>customer.flags</code>	empty after onboarding runs	Flags are raised only from ongoing-monitoring observations (e.g. a new AML hit after onboarding), not from the onboarding verification itself. A sandbox run with a sanctions hit blocks the customer but raises no flag.

Requires: `customers:write`

8.8 Upload & replace documents

LIVE

SESSION

API KEY

POST `/v1/customers/{kyc|kyb}/:customerId/documents`

PUT `/v1/customers/{kyc|kyb}/:customerId/documents/:documentId`

GET `/v1/customers/{kyc|kyb}/:customerId/documents`

```
// request — POST /v1/customers/kyc/33c479186e2741be98bce2af145959af/documents
{
  "type": "passport", "idNumber": "A09876543", "issueDate": "2021-03-01",
  "expiryDate": "2031-02-28",
  "file": "data:application/pdf;base64,JVBERi0xLjQKMSAwIG9iajw8L1R5cGUv..."
}
// response — HTTP 201
{
  "status": true, "message": "Customer kyc document created successfully",
  "data": {
    "id": "31ffc8f5f501420aab65d78325778d84", "createdAt": "2026-10-01T22:37:03.108Z",
    "updatedAt": "2026-10-01T22:37:03.632Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffef9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "type": "passport", "category": "id-document",
    "url": "http://blobs.rokswood.com/unifycomply/compliance-
documents/t7c9e91f81e064c6a9eada352ffef9c7/individual/c33c479186e2741be98bce2af145959af/id-
document",
    "idNumber": "A09876543", "issueDate": "2021-03-01", "expiryDate": "2031-02-28",
    "status": "validated", "reKycNotifiedAt": null, "key": "<redacted>",
    "contentType": "application/pdf", "customerId": "33c479186e2741be98bce2af145959af",
    "customerType": "individual", "shareholderId": null,
```

```

    "verification": {
      "documentId": "31ffc8f5f501420aab65d78325778d84", "type": "passport", "valid": true,
      "reasons": [
        {
          "code": "document.ok", "severity": "info", "message": "passport accepted",
          "field": "passport"
        }
      ]
    }
  }
}

```

`file` is a base64 data URI. Max 2 MB decoded; allowed types `application/pdf`, `image/jpeg`, `image/png`, `image/webp`, `image/heic`, `image/tiff`. Uploading a second document of the same type updates the existing one. Individual types include `passport`, `national-identity`, `driver-license`, `selfie-photo`, `utility-bill`, `bank-statement`; business types include `certificate-of-incorporation`, `tin`, `proof-of-business-address`.

400 — PUT without `file`

```

// request — PUT
/v1/customers/kyc/33c479186e2741be98bce2af145959af/documents/31ffc8f5f501420aab65d78325778d84
{"type": "passport", "idNumber": "A09876543", "issueDate": "2021-03-01", "expiryDate": "2031-03-01"}
// response — HTTP 400
{
  "status": false,
  "message": "passport requires a file upload; attach it as a base64 data URI on \"file\""
}

```

PUT must resend the file. Document types that require an upload reject a PUT without `file`. Changing an expiry date means re-sending the file too. Passports also require `issueDate`.

```

// response — HTTP 200
{
  "status": true, "message": "Customer kyc documents retrieved successfully",
  "data": [
    {
      "id": "5680310515d444d191de24f9d39034a1", "type": "selfie-photo",
      "category": "liveness-check",
      "url": "http://blobs.rokswood.com/unifycomply/compliance-
documents/t7c9e91f81e064c6a9eada352ffeaf9c7/individual/c33c479186e2741be98bce2af145959af/liveness-
che...",
      "idNumber": null, "issueDate": null, "expiryDate": null, "status": "validated",
      "reKycNotifiedAt": null, "key": "<redacted>", "contentType": "image/png",
      "customerId": "33c479186e2741be98bce2af145959af", "customerType": "individual",
      "shareholderId": null
    },
    "... 2 more"
  ]
}

```

`url` points at a private bucket and does not fetch on its own; use the review tabs (§10) for time-limited `signedUrl`s.

Requires: `documents:write` (writes), `customers:read` (reads)

8.9 Document requirements checklist

LIVESESSIONAPI KEYGET

/v1/customers/{kyc|kyb}/:customerId/documents/requirements

Before any upload

```
// response – HTTP 200
{
  "status": true, "message": "Document requirements retrieved successfully",
  "data": [
    {
      "category": "id-document",
      "acceptedTypes": ["national-identity", "passport", "... 1 more"], "satisfied": false,
      "documentIds": []
    },
    {
      "category": "liveness-check", "acceptedTypes": ["selfie-photo"], "satisfied": false,
      "documentIds": []
    },
    "... 1 more"
  ]
}
```

After uploading passport, selfie and utility bill

```
// response – HTTP 200
{
  "status": true, "message": "Document requirements retrieved successfully",
  "data": [
    {
      "category": "id-document",
      "acceptedTypes": ["national-identity", "passport", "... 1 more"], "satisfied": true,
      "documentIds": ["31ffc8f5f501420aab65d78325778d84"]
    },
    {
      "category": "liveness-check", "acceptedTypes": ["selfie-photo"], "satisfied": true,
      "documentIds": ["5680310515d444d191de24f9d39034a1"]
    },
    "... 1 more"
  ]
}
```

Driven by the app's `kycDocuments` / `kybDocuments` (\$5.4). Render it before letting someone start a verification so a missing document surfaces early.

Requires: `customers:read`

8.10 Shareholders / directors (KYB only)

LIVESESSIONAPI KEYGET /v1/customers/kyb/:customerId/shareholdersPOST /v1/customers/kyb/:customerId/shareholdersPUT /v1/customers/kyb/:customerId/shareholders/:shareholderIdGET /v1/customers/kyb/:customerId/shareholders/:shareholderId/documentsPOST /v1/customers/kyb/:customerId/shareholders/:shareholderId/documentsPUT /v1/customers/kyb/:customerId/shareholders/:shareholderId/documents/:documentId

```
// request - POST /v1/customers/kyb/eab4159c3215435d9b12806cdd629c96/shareholders
{
  "firstName": "Ngozi", "lastName": "Adeyemi", "countryCode": "NG", "shareCountTotal": 60000,
  "sharePercentage": 60, "type": "individual", "email": "ngozi@koralogistics.example",
  "phone": "+2348052345678",
  "address": {
    "houseNo": "27", "street": "Adeola Odeku Street", "city": "Victoria Island",
    "state": "Lagos", "stateCode": "LA", "country": "Nigeria", "countryCode": "NG",
    "zipCode": "101241"
  },
  "dateAppointed": "2018-03-15", "role": "Managing Director / CEO"
}
// response - HTTP 201
{
  "status": true, "message": "Customer kyb shareholder created successfully",
  "data": {
    "id": "8d0e4ae691fe411cafaf609b41e21711", "createdAt": "2026-10-01T22:37:12.735Z",
    "updatedAt": "2026-10-01T22:37:12.735Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "firstName": "Ngozi", "lastName": "Adeyemi", "sharePercentage": 60, "shareCountTotal": 60000,
    "type": "individual", "dateAppointed": "2018-03-15", "role": "Managing Director / CEO",
    "email": "ngozi@koralogistics.example", "phone": "+2348052345678", "countryCode": "NG",
    "address": {
      "city": "Victoria Island", "state": "Lagos", "street": "Adeola Odeku Street",
      "country": "Nigeria", "houseNo": "27", "zipCode": "101241",
      "formatted": "27 Adeola Odeku Street, Victoria Island, Lagos LA, 101241, Nigeria (NG)",
      "stateCode": "LA",
      "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
    },
    "customerId": "eab4159c3215435d9b12806cdd629c96"
  }
}
```

Every shareholder is sanctions- and PEP-screened alongside the business on each KYB run. Shareholder PUT is a full replace, like §8.4.

```
// request - POST
/v1/customers/kyb/eab4159c3215435d9b12806cdd629c96/shareholders/8d0e4ae691fe411cafaf609b41e21711/docu
ments
{
  "type": "passport", "idNumber": "B01234567", "issueDate": "2020-01-02",
  "expiryDate": "2030-01-01", "file": "data:application/pdf;base64,JVBERi0xLjQKJSVFT0Y="
}
// response - HTTP 201
{
  "status": true, "message": "Shareholder document created successfully",
  "data": {
    "id": "14fd000373c24b9494352a0a53f05cdc", "createdAt": "2026-10-01T22:37:21.705Z",
    "updatedAt": "2026-10-01T22:37:22.215Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "type": "passport", "category": "id-document",
  }
}
```

```

    "url": "http://blobs.rokswood.com/unifycomply/compliance-
documents/t7c9e91f81e064c6a9eada352ffea9c7/business/ceab4159c3215435d9b12806cdd629c96/8d0e4ae691fe41
...",
    "idNumber": "B01234567", "issueDate": "2020-01-02", "expiryDate": "2030-01-01",
    "status": "validated", "reKycNotifiedAt": null, "key": "<redacted>",
    "contentType": "application/pdf", "customerId": "eab4159c3215435d9b12806cdd629c96",
    "customerType": "business", "shareholderId": "8d0e4ae691fe411cafaf609b41e21711",
    "verification": {
      "documentId": "14fd000373c24b9494352a0a53f05cdc", "type": "passport", "valid": true,
      "reasons": [
        {
          "code": "document.ok", "severity": "info", "message": "passport accepted",
          "field": "passport"
        }
      ]
    }
  }
}
}

```

```

// response - HTTP 200
{
  "status": true, "message": "Shareholder documents retrieved successfully",
  "data": [
    {
      "id": "14fd000373c24b9494352a0a53f05cdc", "type": "passport", "category": "id-document",
      "url": "http://blobs.rokswood.com/unifycomply/compliance-
documents/t7c9e91f81e064c6a9eada352ffea9c7/business/ceab4159c3215435d9b12806cdd629c96/8d0e4ae691fe41
...",
      "idNumber": "B01234567", "issueDate": "2020-01-02", "expiryDate": "2030-06-01",
      "status": "validated", "reKycNotifiedAt": null, "key": "<redacted>",
      "contentType": "application/pdf", "customerId": "eab4159c3215435d9b12806cdd629c96",
      "customerType": "business", "shareholderId": "8d0e4ae691fe411cafaf609b41e21711"
    }
  ]
}

```

Fixed during this guide's capture run. Shareholder document uploads previously failed with 404 "No individual customer found". They now attach to the business customer (`customerType: "business"` , `shareholderId` set), as shown above.

Requires: `customers:write` , `documents:write`

8.11 Account purpose & transaction-monitoring subscription

LIVE

SESSION

API KEY

GET /v1/customers/{kyc|kyb}/:customerId/account-purpose

PUT /v1/customers/{kyc|kyb}/:customerId/account-purpose

POST /v1/customers/{kyc|kyb}/:customerId/transaction-monitoring/subscribe

POST /v1/customers/{kyc|kyb}/:customerId/transaction-monitoring/unsubscribe

```

// request - PUT /v1/customers/kyc/33c479186e2741be98bce2af145959af/account-purpose
{
  "purpose": "personal-banking", "sourceOfFunds": "salary",
  "purposeDetail": "Salary account, bills and family support", "expectedMonthlyTransactions": 20,
  "expectedMonthlyValue": 1500000, "expectedSingleTransactionValue": 300000, "currency": "NGN",
  "expectedCorridors": ["NG", "GB"],
  "expectedChannels": ["bank-transfer", "card"]
}
// response - HTTP 200
{

```

```

"status": true, "message": "Account purpose recorded successfully",
"data": {
  "id": "729ff97fe0ae424e9f01348ef5f60a15", "createdAt": "2026-10-01T22:37:08.111Z",
  "updatedAt": "2026-10-01T22:37:08.111Z", "domain": "sandbox",
  "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
  "profileType": "individual", "purpose": "personal-banking",
  "purposeDetail": "Salary account, bills and family support", "sourceOfFunds": "salary",
  "sourceOfWealth": null, "expectedMonthlyTransactions": 20, "expectedMonthlyValue": 1500000,
  "expectedSingleTransactionValue": 300000, "currency": "NGN",
  "expectedCorridors": ["NG", "GB"],
  "expectedChannels": ["bank-transfer", "card"], "anticipatedCounterparties": null,
  "declaredBy": "api-key", "declaredAt": "2026-10-01T22:37:08.111Z",
  "monitoringEnabled": false, "subscribedAt": null,
  "customerId": "33c479186e2741be98bce2af145959af"
}
}

```

What the customer said they would use the account for. Required: `purpose` , `sourceOfFunds` . The `expected*` fields are what real activity is compared against: a trailing-30-day breach (by the app's `activityBreachMultiplier`) raises a monitoring alert.

subscribe takes the same body as **PUT** and switches declared-vs-actual monitoring on

```

// response - HTTP 201
{
  "status": true, "message": "Customer kyc subscribed to transaction monitoring successfully",
  "data": {
    "id": "729ff97fe0ae424e9f01348ef5f60a15", "createdAt": "2026-10-01T22:37:08.111Z",
    "updatedAt": "2026-10-01T22:37:56.101Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "profileType": "individual", "purpose": "personal-banking",
    "purposeDetail": "Salary account, bills and family support", "sourceOfFunds": "salary",
    "sourceOfWealth": null, "expectedMonthlyTransactions": 20, "expectedMonthlyValue": 1500000,
    "expectedSingleTransactionValue": 300000, "currency": "NGN",
    "expectedCorridors": ["NG", "GB"],
    "expectedChannels": ["bank-transfer", "card"], "anticipatedCounterparties": null,
    "declaredBy": "api-key", "declaredAt": "2026-10-01T22:37:56.101Z", "monitoringEnabled": true,
    "subscribedAt": "2026-10-01T22:37:56.099Z", "customerId": "33c479186e2741be98bce2af145959af"
  }
}

```

```

// response - HTTP 201
{
  "status": true,
  "message": "Customer kyb unsubscribed from transaction monitoring successfully",
  "data": {
    "id": "13be91e3c4ad4b5f92adeb4ed7529798", "createdAt": "2026-10-01T22:37:19.390Z",
    "updatedAt": "2026-10-01T22:38:40.500Z", "domain": "sandbox",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "profileType": "business", "purpose": "business-operations", "purposeDetail": null,
    "sourceOfFunds": "business-income", "sourceOfWealth": null,
    "expectedMonthlyTransactions": 400, "expectedMonthlyValue": 85000000,
    "expectedSingleTransactionValue": 5000000, "currency": "NGN",
    "expectedCorridors": ["NG", "GH", "... 1 more"], "expectedChannels": ["bank-transfer"],
    "anticipatedCounterparties": null, "declaredBy": "api-key",
    "declaredAt": "2026-10-01T22:37:56.875Z", "monitoringEnabled": false,
    "subscribedAt": "2026-10-01T22:37:56.874Z", "customerId": "eab4159c3215435d9b12806cdd629c96"
  }
}

```

404 — unsubscribing a customer that never declared a purpose

```

// response - HTTP 404
{

```

```
"status": false,  
"message": "No account purpose declared for customer: ac906f738a7647668077edd4b9105234 – nothing to  
unsubscribe"  
}
```

Rules-based monitoring needs no subscription. The detection rules in §13 run on every transaction for every customer; subscription only controls the declared-vs-actual comparison.

Requires: `customers:read` / `customers:write`

9. Verifications

A verification (workflow) runs a set of checks for one customer and settles to `verified`, `in-review` or `failed`.
Session or API key.

9.1 Available checks for a country

LIVESESSIONAPI KEYGET `/v1/verifications/available-checks?countryCode=NG&profileType=individual`

```
// response – HTTP 200
{
  "status": true, "message": "Available checks retrieved successfully",
  "data": {
    "countryCode": "NG", "profileType": "individual",
    "checks": [
      {
        "type": "national-id", "label": "National Identity Number",
        "authority": "National Identity Management Commission",
        "eligibleProviders": ["dojah", "qoreid", "interswitch", "... 2 more"]
      },
      {
        "type": "bank-account", "label": "Bank Verification Number",
        "authority": "Nigeria Inter-Bank Settlement System",
        "eligibleProviders": ["dojah", "interswitch", "sandbox", "... 1 more"]
      },
      {
        "type": "passport", "label": "Passport", "authority": null,
        "eligibleProviders": ["dojah", "qoreid", "sandbox", "... 1 more"]
      },
      "... 5 more"
    ]
  }
}
```

Call before rendering a check picker. A check absent for a country genuinely is not offerable there and would be rejected at start.

Requires: `verifications:read`

9.2 Start a verification

LIVESESSIONAPI KEYPOST `/v1/verifications/kyc`POST `/v1/verifications/kyb`

```
// request – POST /v1/verifications/kyc
{
  "customerId": "33c479186e2741be98bce2af145959af",
  "verificationTypes": [{"type": "passport"}, {"type": "selfie"}]
}
// response – HTTP 201
{
  "status": true, "message": "Customer kyc verification started successfully",
  "data": {
    "workflowId": "7a10d4b1895741a48674bbe4769d05df",
    "workflow": {
      "id": "7a10d4b1895741a48674bbe4769d05df", "timeInQueueMs": 0, "riskScore": 0,
      "assignedTo": null, "status": "processing", "priority": "standard",
      "verificationTypes": ["passport", "selfie", "... 2 more"], "profileType": "individual",
      "providerKey": null, "providerSubjectId": null, "providerRejectLabels": [],

```

```

    "providerReviewedAt": null, "lastProviderEventAt": null,
    "customerId": "33c479186e2741be98bce2af145959af"
  },
  "run": {
    "run": {
      "id": "081e121f775f4b53bf0a7758f4f474a5", "status": "processing", "outcome": "pending",
      "profileType": "individual",
      "configSnapshot": {
        "pepTiers": [
          {
            "name": "Senior Foreign PEP", "tier": "tier-1", "autoEscalation": true,
            "riskScoreImpact": 4, "requiresApproval": true
          },
          {
            "name": "Domestic Senior PEP", "tier": "tier-2", "autoEscalation": true,
            "riskScoreImpact": 3, "requiresApproval": true
          },
          "... 2 more"
        ],
        "riskFactors": [
          {
            "name": "Sanctions List Match", "slug": "sanctions-list-match",
            "type": "regulatory", "enabled": true, "riskWeight": 1
          },
          {
            "name": "Warnings and Regulatory Enforcement",
            "slug": "warnings-regulatory-enforcement", "type": "regulatory", "enabled": true,
            "riskWeight": 1
          },
          "... 4 more"
        ],
        "kybDocuments": ["certificate-of-incorporation", "directors-id", "... 2 more"],
        "kycDocuments": ["id-document", "liveness-check", "... 1 more"], "kybExpiryDays": 365,
        "kycExpiryDays": 365,
        "riskScoreThreshold": {"blockThreshold": 3, "warningThreshold": 2},
        "flaggedCountryCodes": ["IR", "KP"], "activityBreachMultiplier": 2
      },
      "reasons": [], "startedAt": "2026-10-01T22:37:25.563Z", "completedAt": null,
      "resultPublishedAt": null, "workflowId": "7a10d4b1895741a48674bbe4769d05df",
      "customerId": "33c479186e2741be98bce2af145959af"
    },
    "tasks": [
      {
        "id": "b21dd60eb29f44e3bcb7efdc748a8d4b", "verificationType": "passport",
        "outcome": "pending", "reasons": [], "preferredProviderKey": null, "providerKey": null,
        "providerReference": null, "attempts": 1, "lastError": null, "completedAt": null,
        "runId": "081e121f775f4b53bf0a7758f4f474a5", "shareholderId": null
      },
      {
        "id": "22b6578dba6845e2a2f53f877aa7c53b", "verificationType": "selfie",
        "outcome": "pending", "reasons": [], "preferredProviderKey": null, "providerKey": null,
        "providerReference": null, "attempts": 1, "lastError": null, "completedAt": null,
        "runId": "081e121f775f4b53bf0a7758f4f474a5", "shareholderId": null
      },
      "... 2 more"
    ]
  },
  "mandatoryAdded": ["sanctions-screening", "pep-screening"]
}

```

Omit `providerKey` to run every eligible provider and reconcile (any real `failed` wins, then `review-required`; unreachable providers do not vote). `mandatoryAdded` lists checks the server added (sanctions + PEP are always run). The response returns while checks are still `processing`.

400 — a type the country/profile does not offer

```
// request — POST /v1/verifications/kyc
{
  "customerId": "ac906f738a7647668077edd4b9105234",
  "verificationTypes": [{"type": "national-id-card"}]
}
// response — HTTP 400
{
  "status": false,
  "message": "verificationTypes.0.type must be one of the following values: national-id, bank-account, passport, driver-license, address-verification, selfie, sanct..."
}
```

Requires: `verifications:write`

9.3 Read one verification (poll until settled)

LIVE

SESSION

API KEY

GET /v1/verifications/:workflowId

A sandbox run against "Pep Sanction" — blocked on a sanctions + PEP hit

```
// response — HTTP 200
{
  "status": true, "message": "Verification retrieved successfully",
  "data": {
    "workflow": {
      "id": "d2f3cecb18fb48d6a3746df20fcb65b7", "timeInQueueMs": 5001, "riskScore": 4,
      "assignedTo": null, "status": "failed", "priority": "standard",
      "verificationTypes": ["sanctions-screening", "pep-screening"], "profileType": "individual",
      "providerKey": null, "providerSubjectId": null,
      "providerRejectLabels": ["screening.sanctions-hit", "screening.pep-hit"],
      "providerReviewedAt": null, "lastProviderEventAt": "2026-10-01T22:37:50.116Z",
      "customerId": "12c1a2ae64ec4a29882031494f7f21f7"
    },
    "run": {
      "run": {
        "id": "b7529c22ff6848b08c14f2c4865b241d", "status": "completed", "outcome": "failed",
        "profileType": "individual",
        "configSnapshot": {
          "pepTiers": [
            {
              "name": "Senior Foreign PEP", "tier": "tier-1", "autoEscalation": true,
              "riskScoreImpact": 4, "requiresApproval": true
            },
            {
              "name": "Domestic Senior PEP", "tier": "tier-2", "autoEscalation": true,
              "riskScoreImpact": 3, "requiresApproval": true
            },
            "... 2 more"
          ],
          "riskFactors": [
            {
              "name": "Sanctions List Match", "slug": "sanctions-list-match",
              "type": "regulatory", "enabled": true, "riskWeight": 1
            },
            {
              "name": "Warnings and Regulatory Enforcement",
              "slug": "warnings-regulatory-enforcement", "type": "regulatory", "enabled": true,
              "riskWeight": 1
            },
            "... 4 more"
          ]
        }
      }
    }
  }
}
```

```

    "kybDocuments": ["certificate-of-incorporation", "directors-id", "... 2 more"],
    "kycDocuments": ["id-document", "liveness-check", "... 1 more"], "kybExpiryDays": 365,
    "kycExpiryDays": 365,
    "riskScoreThreshold": {"blockThreshold": 3, "warningThreshold": 2},
    "flaggedCountryCodes": ["IR", "KP"], "activityBreachMultiplier": 2
  },
  "reasons": [
    {
      "code": "screening.match", "field": "sandbox-sanction-1",
      "message": "Matched \"Pep Sanction\" on sanctions list at 98% confidence – list:
sandbox_default · programme: SANDBOX-PROGRA...",
      "evidence": {
        "score": 98, "aliases": [], "datasets": ["sandbox_default"], "countries": ["NG"],
        "positions": [], "categories": ["sanction"], "lastChange": null, "sourceUrls": [],
        "matchedName": "Pep Sanction", "matchSeverity": "exact",
        "providerEntityId": "sandbox-sanction-1", "sanctionPrograms": ["SANDBOX-PROGRAM"]
      },
      "severity": "blocking"
    },
    {
      "code": "screening.review-match", "field": "sandbox-pep-1",
      "message": "Matched \"Pep Sanction\" on politically exposed person at 85% confidence –
list: sandbox_default · position: San...",
      "evidence": {
        "score": 85, "aliases": [], "datasets": ["sandbox_default"], "countries": ["NG"],
        "positions": ["Sandbox Minister"], "categories": ["pep"], "lastChange": null,
        "sourceUrls": [], "matchedName": "Pep Sanction", "matchSeverity": "high",
        "providerEntityId": "sandbox-pep-1", "sanctionPrograms": []
      },
      "severity": "warning"
    }
  ],
  "startedAt": "2026-10-01T22:37:45.124Z", "completedAt": "2026-10-01T22:37:50.077Z",
  "resultPublishedAt": "2026-10-01T22:37:50.083Z",
  "workflowId": "d2f3cecb18fb48d6a3746df20fcb65b7",
  "customerId": "12c1a2ae64ec4a29882031494f7f21f7"
},
"tasks": [
  {
    "id": "ccec41e1037e4569b462e496d17abd47", "verificationType": "sanctions-screening",
    "outcome": "failed",
    "reasons": [
      {
        "code": "screening.match", "field": "sandbox-sanction-1",
        "message": "Matched \"Pep Sanction\" on sanctions list at 98% confidence – list:
sandbox_default · programme: SANDBOX-PROGRA...",
        "evidence": {
          "score": 98, "aliases": [], "datasets": ["sandbox_default"], "countries": ["NG"],
          "positions": [], "categories": ["sanction"], "lastChange": null,
          "sourceUrls": [], "matchedName": "Pep Sanction", "matchSeverity": "exact",
          "providerEntityId": "sandbox-sanction-1",
          "sanctionPrograms": ["SANDBOX-PROGRAM"]
        },
        "severity": "blocking"
      }
    ]
  },
  {
    "id": "0b87332111694d0ab79963208f91a92e", "verificationType": "pep-screening",
    "outcome": "review-required",
    "reasons": [
      {
        "code": "screening.review-match", "field": "sandbox-pep-1",
        "message": "Matched \"Pep Sanction\" on politically exposed person at 85% confidence –
list: sandbox_default · position: San...",

```

```

        "evidence": {
            "score": 85, "aliases": [], "datasets": ["sandbox_default"], "countries": ["NG"],
            "positions": ["Sandbox Minister"], "categories": ["pep"], "lastChange": null,
            "sourceUrls": [], "matchedName": "Pep Sanction", "matchSeverity": "high",
            "providerEntityId": "sandbox-pep-1", "sanctionPrograms": []
        },
        "severity": "warning"
    }
},
    "preferredProviderKey": null, "providerKey": "sandbox-aml", "providerReference": null,
    "attempts": 1, "lastError": null, "completedAt": "2026-10-01T22:37:50.047Z",
    "runId": "b7529c22ff6848b08c14f2c4865b241d", "shareholderId": null
}
]
},
    "risk": {
        "runId": "b7529c22ff6848b08c14f2c4865b241d",
        "workflowId": "d2f3cecb18fb48d6a3746df20fcb65b7",
        "customerId": "12c1a2ae64ec4a29882031494f7f21f7", "profileType": "individual", "score": 4,
        "band": "high", "priority": "urgent", "canApprove": false, "requiresEscalation": true,
        "decision": "block",
        "contributions": [
            {
                "code": "screening.sanctions-hit", "points": 1, "source": "screening",
                "message": "Matched a sanctions, terrorism or asset-freeze list",
                "evidence": {
                    "taskId": "ccec41e1037e4569b462e496d17abd47",
                    "reasons": [
                        {
                            "code": "screening.match", "field": "sandbox-sanction-1",
                            "message": "Matched \"Pep Sanction\" on sanctions list at 98% confidence – list:
sandbox_default · programme: SANDBOX-PROGRA...",
                            "evidence": {
                                "score": 98, "aliases": [], "datasets": ["sandbox_default"],
                                "countries": ["NG"], "positions": [], "categories": ["sanction"],
                                "lastChange": null, "sourceUrls": [], "matchedName": "Pep Sanction",
                                "matchSeverity": "exact", "providerEntityId": "sandbox-sanction-1",
                                "sanctionPrograms": ["SANDBOX-PROGRAM"]
                            },
                            "severity": "blocking"
                        }
                    ],
                    "shareholderId": null
                },
                "factorSlug": "sanctions-list-match"
            },
            {
                "code": "screening.pep-hit", "points": 4, "source": "pep-tier",
                "message": "Politically exposed person matching Senior Foreign PEP",
                "evidence": {
                    "tier": "tier-1", "taskId": "0b87332111694d0ab79963208f91a92e",
                    "reasons": [
                        {
                            "code": "screening.review-match", "field": "sandbox-pep-1",
                            "message": "Matched \"Pep Sanction\" on politically exposed person at 85% confidence
– list: sandbox_default · position: San...",
                            "evidence": {
                                "score": 85, "aliases": [], "datasets": ["sandbox_default"],
                                "countries": ["NG"], "positions": ["Sandbox Minister"], "categories": ["pep"],
                                "lastChange": null, "sourceUrls": [], "matchedName": "Pep Sanction",
                                "matchSeverity": "high", "providerEntityId": "sandbox-pep-1",
                                "sanctionPrograms": []
                            },
                            "severity": "warning"
                        }
                    ],
                    "shareholderId": null, "requiresApproval": true
                },
            },
        ],
    },

```

```

        "factorSlug": "pep-association"
    }
},
"warningThreshold": 2, "blockThreshold": 3, "decidedAt": "2026-10-01T22:37:50.103Z"
},
"events": [
    {
        "id": "844bf388f8fb4d26954138bc4ce8b3d3", "action": "risk.decision",
        "actor": "risk-decisioning", "fromStatus": "processing", "toStatus": "failed",
        "detail": {
            "band": "high", "runId": "b7529c22ff6848b08c14f2c4865b241d", "score": 4,
            "decision": "block", "messageId": "decision:b7529c22ff6848b08c14f2c4865b241d",
            "contributions": [
                {
                    "code": "screening.sanctions-hit", "points": 1, "source": "screening",
                    "message": "Matched a sanctions, terrorism or asset-freeze list",
                    "evidence": {
                        "taskId": "ccec41e1037e4569b462e496d17abd47",
                        "reasons": [
                            {
                                "code": "screening.match", "field": "sandbox-sanction-1",
                                "message": "Matched \"Pep Sanction\" on sanctions list at 98% confidence - list:
sandbox_default · programme: SANDBOX-PROGRA...",
                                "evidence": {
                                    "score": 98, "aliases": [], "datasets": ["sandbox_default"],
                                    "countries": ["NG"], "positions": [], "categories": ["sanction"],
                                    "lastChange": null, "sourceUrls": [], "matchedName": "Pep Sanction",
                                    "matchSeverity": "exact", "providerEntityId": "sandbox-sanction-1",
                                    "sanctionPrograms": ["SANDBOX-PROGRAM"]
                                },
                                "severity": "blocking"
                            }
                        ]
                    },
                    "shareholderId": null
                },
                {
                    "code": "screening.pep-hit", "points": 4, "source": "pep-tier",
                    "message": "Politically exposed person matching Senior Foreign PEP",
                    "evidence": {
                        "tier": "tier-1", "taskId": "0b87332111694d0ab79963208f91a92e",
                        "reasons": [
                            {
                                "code": "screening.review-match", "field": "sandbox-pep-1",
                                "message": "Matched \"Pep Sanction\" on politically exposed person at 85%
confidence - list: sandbox_default · position: San...",
                                "evidence": {
                                    "score": 85, "aliases": [], "datasets": ["sandbox_default"],
                                    "countries": ["NG"], "positions": ["Sandbox Minister"],
                                    "categories": ["pep"], "lastChange": null, "sourceUrls": [],
                                    "matchedName": "Pep Sanction", "matchSeverity": "high",
                                    "providerEntityId": "sandbox-pep-1", "sanctionPrograms": []
                                },
                                "severity": "warning"
                            }
                        ]
                    },
                    "shareholderId": null, "requiresApproval": true
                },
                {
                    "factorSlug": "pep-association"
                }
            ],
            "blockThreshold": 3, "warningThreshold": 2
        },
        "customerName": "Pep Sanction", "workflowId": "d2f3cecb18fb48d6a3746df20fcb65b7"
    },
    {
        "id": "a9720c24384640fc846457f333994752", "action": "verification.completed",

```

```

"actor": "compliance-domain", "fromStatus": "processing", "toStatus": null,
"detail": {
  "runId": "b7529c22ff6848b08c14f2c4865b241d",
  "tasks": [
    {
      "outcome": "failed",
      "reasons": [
        {
          "code": "screening.match", "field": "sandbox-sanction-1",
          "message": "Matched \"Pep Sanction\" on sanctions list at 98% confidence – list:
sandbox_default · programme: SANDBOX-PROGRA...",
          "evidence": {
            "score": 98, "aliases": [], "datasets": ["sandbox_default"],
            "countries": ["NG"], "positions": [], "categories": ["sanction"],
            "lastChange": null, "sourceUrls": [], "matchedName": "Pep Sanction",
            "matchSeverity": "exact", "providerEntityId": "sandbox-sanction-1",
            "sanctionPrograms": ["SANDBOX-PROGRAM"]
          },
          "severity": "blocking"
        }
      ],
      "providerKey": "sandbox-aml", "verificationType": "sanctions-screening"
    },
    {
      "outcome": "review-required",
      "reasons": [
        {
          "code": "screening.review-match", "field": "sandbox-pep-1",
          "message": "Matched \"Pep Sanction\" on politically exposed person at 85%
confidence – list: sandbox_default · position: San...",
          "evidence": {
            "score": 85, "aliases": [], "datasets": ["sandbox_default"],
            "countries": ["NG"], "positions": ["Sandbox Minister"],
            "categories": ["pep"], "lastChange": null, "sourceUrls": [],
            "matchedName": "Pep Sanction", "matchSeverity": "high",
            "providerEntityId": "sandbox-pep-1", "sanctionPrograms": []
          },
          "severity": "warning"
        }
      ],
      "providerKey": "sandbox-aml", "verificationType": "pep-screening"
    }
  ],
  "outcome": "failed", "messageId": "run:b7529c22ff6848b08c14f2c4865b241d"
},
"customerName": "Pep Sanction", "workflowId": "d2f3cecb18fb48d6a3746df20fcb65b7"
},
"... 1 more"
]
}
}

```

There is no push to the browser — poll. Re-fetch every ~3 s until `workflow.status` is `verified`, `in-review` or `failed` and `risk` is non-null (about 6–12 s in sandbox). Your backend can listen for the `workflow.verified` / `workflow.failed` webhooks (§11.2) instead.

`events` is the audit trail a compliance officer reads ("why is this in review"). Every task carries `reasons[]`, even on a pass.

Requires: `verifications:read`

9.4 Verification queues LIVE

SESSIONAPI KEYGET /v1/verificationsGET /v1/verifications/kycGET /v1/verifications/kyb

Query: `page`, `limit`, `status`, `priority`, `verificationType` (matches if included), `dateFrom`, `dateTo`, `search` (workflow id / displayId / provider subject id — not customer name).

```
// response – HTTP 200
{
  "status": true, "message": "Kyc verifications retrieved successfully",
  "data": [
    {
      "id": "7a10d4b1895741a48674bbe4769d05df", "timeInQueueMs": 4659, "riskScore": 0,
      "assignedTo": null, "status": "verified", "priority": "standard",
      "verificationTypes": ["passport", "... 3 more"], "profileType": "individual",
      "providerKey": null, "providerSubjectId": null, "providerRejectLabels": [],
      "providerReviewedAt": null, "lastProviderEventAt": "2026-10-01T22:37:30.204Z",
      "customerId": "33c479186e2741be98bce2af145959af", "displayId": "9D05DF",
      "customerName": "Chidinma Eze", "country": "NG",
      "documentType": "Passport + Selfie + Sanctions Screening + PEP Screening"
    }
  ],
  "meta": {"totalItems": 1, "itemsCount": 1, "itemsPerPage": 10, "totalPages": 1, "currentPage": 1}
}
```

/kyc and /kyb add `displayId`, `customerName`, `country` and a friendly `documentType` label.

/verifications is the profile-agnostic version without that enrichment.

Requires: `verifications:read`

10. Verification review tabs

The data behind one verification's review screen. Session only (`dashboard:access`) — an API key gets 401. Fetch each tab lazily when opened; hitting the KYC path for a business workflow (or vice versa) returns 404.

404 — KYB path with a KYC workflow id

```
// response – HTTP 404
{
  "status": false,
  "message": "No kyb verification found with a matching workflowId: 7a10d4b1895741a48674bbe4769d05df"
}
```

10.1 KYC — documents LIVE

SESSIONGET /v1/verifications/kyc/:workflowId/documents

```
// response – HTTP 200
{
  "status": true, "message": "Documents tab retrieved successfully",
  "data": {
    "workflowId": "7a10d4b1895741a48674bbe4769d05df",
    "documents": [
```

```

{
  "id": "693776d544504a098824df5efda2e7c9", "type": "utility-bill",
  "category": "proof-of-address",
  "url": "http://blobs.rokswood.com/unifycomply/compliance-
documents/t7c9e91f81e064c6a9eada352ffeaf9...",
  "idNumber": null, "issueDate": "2026-08-15", "expiryDate": null, "status": "validated",
  "reKycNotifiedAt": null, "key": "<redacted>", "contentType": "application/pdf",
  "customerId": "33c479186e2741be98bce2af145959af", "customerType": "individual",
  "shareholderId": null,
  "signedUrl": "http://minio-api.apps.rokswood.com:9000/unifycomply/compliance-
documents/t7c9e91f81e064c6a...",
  "extractedInformation": null
},
"... 2 more"
],
"riskScore": 0, "riskBand": "low",
"timeline": [
  {
    "id": "5a0c9ca3f2b54d88bc74cc332f903f21", "action": "risk.decision",
    "actor": "risk-decisioning", "fromStatus": "processing", "toStatus": "verified",
    "detail": {
      "band": "low", "runId": "081e121f775f4b53bf0a7758f4f474a5", "score": 0,
      "decision": "onboard", "messageId": "decision:081e121f775f4b53bf0a7758f4f474a5",
      "contributions": [], "blockThreshold": 3, "warningThreshold": 2
    },
    "customerName": "Chidinma Eze", "workflowId": "7a10d4b1895741a48674bbe4769d05df"
  },
  "... 2 more"
]
}

```

Use `signedUrl` (valid about an hour) to display/download; it is `null` when no file was stored.
`extractedInformation` is always `null` — no OCR yet.

10.2 KYC / KYB — risk score

LIVE

SESSION

GET /v1/verifications/kyc/:workflowId/risk-score

GET /v1/verifications/kyb/:workflowId/risk-score

```

// response – HTTP 200
{
  "status": true, "message": "Risk score analysis tab retrieved successfully",
  "data": {
    "available": true,
    "risk": {
      "runId": "081e121f775f4b53bf0a7758f4f474a5",
      "workflowId": "7a10d4b1895741a48674bbe4769d05df",
      "customerId": "33c479186e2741be98bce2af145959af", "profileType": "individual", "score": 0,
      "band": "low", "priority": "standard", "canApprove": true, "requiresEscalation": false,
      "decision": "onboard", "contributions": [], "warningThreshold": 2, "blockThreshold": 3,
      "decidedAt": "2026-10-01T22:37:30.186Z"
    }
  }
}

```

Score is on the 0–4 KYC/KYB scale. No narrative sentence is generated — template one from `contributions` if the design needs it.

10.3 KYC — AML screening

LIVESESSIONGET

/v1/verifications/kyc/:workflowId/aml-screening

```
// response – HTTP 200
{
  "status": true, "message": "AML screening tab retrieved successfully",
  "data": {
    "tasks": [
      {
        "id": "41be267fa4fa4475962a17ce6766bf56", "verificationType": "sanctions-screening",
        "outcome": "passed",
        "reasons": [
          {
            "code": "screening.clear", "message": "No sanctions match across 1 dataset(s)",
            "evidence": {"threshold": 70, "totalCandidates": 0, "datasetsSearched":
["sandbox_default"]},
            "severity": "info"
          }
        ],
        "preferredProviderKey": null, "providerKey": "sandbox-aml", "providerReference": null,
        "attempts": 1, "lastError": null, "completedAt": "2026-10-01T22:37:30.112Z",
        "runId": "081e121f775f4b53bf0a7758f4f474a5", "shareholderId": null
      },
      {
        "id": "5541018378ae4ee08e596d3dbd7cb1ba", "verificationType": "pep-screening",
        "outcome": "passed",
        "reasons": [
          {
            "code": "screening.clear",
            "message": "No PEP, warning or adverse media match across 1 dataset(s)",
            "evidence": {"threshold": 70, "totalCandidates": 0, "datasetsSearched":
["sandbox_default"]},
            "severity": "info"
          }
        ],
        "preferredProviderKey": null, "providerKey": "sandbox-aml", "providerReference": null,
        "attempts": 1, "lastError": null, "completedAt": "2026-10-01T22:37:30.082Z",
        "runId": "081e121f775f4b53bf0a7758f4f474a5", "shareholderId": null
      }
    ]
  }
}
```

10.4 KYC — device information

PARTIALSESSIONGET

/v1/verifications/kyc/:workflowId/device-information

```
// response – HTTP 200
{
  "status": true, "message": "Device information tab retrieved successfully",
  "data": {
    "available": false, "ip": null, "geolocation": null, "device": null, "vpnDetected": null,
    "proxyDetected": null, "reason": "IP and device capture is not implemented (see TODO D10)"
  }
}
```

Field	Status	Why
every field	always null	No IP or device capture exists anywhere in the platform. Render a permanent empty state using <code>reason</code> .

10.5 KYC — liveness

PARTIAL

SESSION

GET /v1/verifications/kyc/:workflowId/liveness

```
// response – HTTP 200
{
  "status": true, "message": "Liveness detection tab retrieved successfully",
  "data": {
    "available": true, "livenessDetection": "skipped", "matchScoreRate": null,
    "providerKey": null, "providerReference": null, "attempts": 1,
    "completedAt": "2026-10-01T22:37:27.490Z",
    "reasons": [
      {
        "code": "verification.unsupported", "message": "\"selfie\" is not offerable in NG",
        "severity": "warning"
      }
    ]
  }
}
```

Field	Status	Why
matchScoreRate	usually null	A <code>selfie</code> check runs through the generic identity path; the dedicated biometric liveness capability is never invoked. Do not build UI expecting confidence %, face/mask/eyes checks.

10.6 KYB — business overview

LIVE

SESSION

GET /v1/verifications/kyb/:workflowId/business-overview

```
// response – HTTP 200
{
  "status": true, "message": "Business overview tab retrieved successfully",
  "data": {
    "workflowId": "a20726b6d31b4f6bb2b6bcd201a91e6b",
    "business": {
      "id": "eab4159c3215435d9b12806cdd629c96", "businessName": "Kora Logistics Limited",
      "businessType": null, "countryCode": "NG",
      "address": {
        "city": "Victoria Island", "state": "Lagos", "street": "Adeola Odeku Street",
        "country": "Nigeria", "houseNo": "27", "zipCode": "101241",
        "formatted": "27 Adeola Odeku Street, Victoria Island, Lagos LA, 101241, Nigeria (NG)",
        "stateCode": "LA",
        "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
      },
      "registrationDate": "2018-03-15", "industry": "technology",
      "contactEmail": "compliance@koralogistics.example", "contactPhone": "+2348091234500",
      "website": "https://koralogistics.example", "contactEmailChangedAt": null,
      "contactPhoneChangedAt": "2026-10-01T22:37:19.781Z", "addressChangedAt": null,
      "status": "review", "statusReasons": [], "statusChangedAt": "2026-10-01T22:37:30.314Z",
      "statusRunId": "b0fc875f3328424b98b221d5fc4f3b04", "riskScore": 0,
    }
  }
}
```

```

    "lastReviewedAt": "2026-10-01T22:37:30.314Z", "nextReviewAt": null, "flags": [],
    "documentTypes": ["certificate-of-incorporation", "tin"]
  },
  "registrationNumber": "RC-23456789", "tin": "TIN-12345678-0001", "activities": null,
  "status": "in-review", "riskScore": 0
}
}

```

`registrationNumber` and `tin` are read off the uploaded certificate-of-incorporation / TIN documents' `idNumber` (null if not uploaded). `business.status` is the customer lifecycle; top-level `status` is the workflow — different fields.

10.7 KYB — directors & officers, shareholders LIVE SESSION

GET `/v1/verifications/kyb/:workflowId/directors-officers`

GET `/v1/verifications/kyb/:workflowId/shareholders`

```

// response — HTTP 200
{
  "status": true, "message": "Directors and officers tab retrieved successfully",
  "data": {
    "directors": [
      {
        "id": "74c08fd820f94e4b8e9b9bdce84ebc60", "firstName": "Emeka", "lastName": "Obi",
        "sharePercentage": 40, "shareCountTotal": 40000, "type": "individual",
        "dateAppointed": "2019-06-01", "role": "Director",
        "email": "emeka@koralogistics.example", "phone": "+2348057654321", "countryCode": "NG",
        "address": {
          "city": "Victoria Island", "state": "Lagos", "street": "Adeola Odeku Street",
          "country": "Nigeria", "houseNo": "27", "zipCode": "101241",
          "formatted": "27 Adeola Odeku Street, Victoria Island, Lagos LA, 101241, Nigeria (NG)",
          "stateCode": "LA",
          "coordinates": {"lat": null, "lng": null}, "countryCode": "NG"
        },
        "customerId": "eab4159c3215435d9b12806cdd629c96", "nationality": null, "idType": null,
        "idNumber": null, "riskLevel": "low", "needsReview": false,
        "screening": [
          {
            "verificationType": "sanctions-screening", "outcome": "passed",
            "reasons": [
              {
                "code": "screening.clear", "message": "No sanctions match across 1 dataset(s)",
                "evidence": {"threshold": 70, "totalCandidates": 0, "datasetsSearched":
["sandbox_default"]},
                "severity": "info"
              }
            ]
          },
          "... 1 more"
        ]
      },
      "... 1 more"
    ]
  }
}

```

`screening[]` is each director's own live sanctions/PEP result. `nationality`, `idType`, `idNumber` (and `shareClass` on `/shareholders`) are always `null` — not captured.

10.8 KYB — documents, compliance checks

LIVESESSION

GET /v1/verifications/kyb/:workflowId/document

GET /v1/verifications/kyb/:workflowId/compliance-checks

```
// response – HTTP 200
{
  "status": true, "message": "Compliance checks tab retrieved successfully",
  "data": {
    "tasks": [
      {
        "id": "d8f84b49cfd4df096ec621717739bde", "verificationType": "sanctions-screening",
        "outcome": "passed",
        "reasons": [
          {
            "code": "screening.clear", "message": "No sanctions match across 1 dataset(s)",
            "evidence": {"threshold": 70, "totalCandidates": 0, "datasetsSearched":
["sandbox_default"]},
            "severity": "info"
          }
        ],
        "preferredProviderKey": null, "providerKey": "sandbox-aml", "providerReference": null,
        "attempts": 1, "lastError": null, "completedAt": "2026-10-01T22:37:30.250Z",
        "runId": "b0fc875f3328424b98b221d5fc4f3b04", "shareholderId": null
      },
      {
        "id": "0381e691cfbe4bfdaa9aba2be40a1027", "verificationType": "pep-screening",
        "outcome": "passed",
        "reasons": [
          {
            "code": "screening.clear",
            "message": "No PEP, warning or adverse media match across 1 dataset(s)",
            "evidence": {"threshold": 70, "totalCandidates": 0, "datasetsSearched":
["sandbox_default"]},
            "severity": "info"
          }
        ],
        "preferredProviderKey": null, "providerKey": "sandbox-aml", "providerReference": null,
        "attempts": 1, "lastError": null, "completedAt": "2026-10-01T22:37:30.158Z",
        "runId": "b0fc875f3328424b98b221d5fc4f3b04", "shareholderId": null
      }
    ]
  }
}
```

Note the singular `/document`. `compliance-checks` is the business entity's own screening only; directors' results are on §10.7.

11. Dashboard & webhooks

11.1 Dashboard tiles & feeds

LIVESESSIONAPI KEYGET /v1/dashboard/summaryGET /v1/dashboard/high-risk-alertsGET /v1/dashboard/verification-typesGET /v1/dashboard/activityGET /v1/dashboard/api-calls?year=2026

```
// response – HTTP 200
{
  "status": true, "message": "Dashboard summary retrieved successfully",
  "data": {"total": 2, "successRate": 50, "failureRate": 0, "pendingReviewRate": 50}
}
```

```
// response – HTTP 200
{
  "status": true, "message": "Verification type breakdown retrieved successfully",
  "data": [
    {"type": "pep-screening", "label": "PEP Screening", "count": 2, "percentage": 28.6},
    {"type": "sanctions-screening", "label": "Sanctions Screening", "count": 2, "percentage": 28.6},
    {"type": "passport", "label": "Passport Verification", "count": 1, "percentage": 14.3},
    "... 2 more"
  ]
}
```

```
// response – HTTP 200
{
  "status": true, "message": "Recent activity retrieved successfully",
  "data": [
    {
      "id": "937e7873802d4cbaabfec90312413e09", "message": "Risk decision recorded: review",
      "customerName": "Kora Logistics Limited", "workflowId": "a20726b6d31b4f6bb2b6bcd201a91e6b"
    },
    {
      "id": "df4870bdd94a4411a0ccde33d922f795", "message": "Verification failed",
      "customerName": "Kora Logistics Limited", "workflowId": "a20726b6d31b4f6bb2b6bcd201a91e6b"
    },
    "... 4 more"
  ],
  "meta": {"totalItems": 6, "itemsCount": 6, "itemsPerPage": 10, "totalPages": 1, "currentPage": 1}
}
```

```
// response – HTTP 200
{
  "status": true, "message": "API call counts retrieved successfully",
  "data": [
    {"month": 1, "successful": 0, "failed": 0},
    {"month": 2, "successful": 0, "failed": 0},
    {"month": 3, "successful": 0, "failed": 0},
    "... 9 more"
  ]
}
```

`high-risk-alerts` and `activity` are paginated. A workflow with three checks counts toward all three in `verification-types`.

Requires: `verifications:read`

11.2 Webhook deliveries

LIVE

SESSION

API KEY

GET `/v1/webhooks/deliveries`

GET `/v1/webhooks/deliveries/:id`

POST `/v1/webhooks/deliveries/:id/redeliver`

GET `/v1/tenants/apps/:appId/webhook/deliveries`

POST `/v1/tenants/apps/:appId/webhook/deliveries/:id/redeliver`

Query: `workflowId`, `status` (`pending|delivered|failed|dead`), `page`, `limit`.

```
// response – HTTP 200
{
  "status": true, "message": "Webhook delivery retrieved successfully",
  "data": {
    "id": "c7417ca429db4eb7886d8874f9ef3a42", "createdAt": "2026-10-01T22:37:30.241Z",
    "updatedAt": "2026-10-01T22:37:40.524Z", "domain": "sandbox", "event": "workflow.verified",
    "url": "https://example.com/webhooks/unifycomply",
    "payload": {
      "data": {
        "run": {
          "id": "081e121f775f4b53bf0a7758f4f474a5", "status": "completed", "outcome": "passed",
          "reasons": [
            {
              "code": "identity.field-match", "field": "firstName",
              "message": "firstName matches the record", "evidence": {"score": 100},
              "severity": "info"
            },
            "... 5 more"
          ],
          "startedAt": "2026-10-01T22:37:25.563Z", "completedAt": "2026-10-01T22:37:30.126Z"
        },
        "risk": {
          "band": "low", "score": 0, "decision": "onboard", "priority": "standard",
          "canApprove": true, "contributions": [], "blockThreshold": 3, "warningThreshold": 2,
          "requiresEscalation": false
        },
        "tasks": [
          {
            "outcome": "passed",
            "reasons": [
              {
                "code": "identity.field-match", "field": "firstName",
                "message": "firstName matches the record", "evidence": {"score": 100},
                "severity": "info"
              },
              "... 2 more"
            ],
            "providerKey": "sandbox", "verificationType": "passport", "providerReference": null
          },
          "... 3 more"
        ],
        "customer": {
          "email": "chidinma.eze@example.com", "phone": "+2348031234500", "gender": "female",
          "address": {
            "city": "Lekki", "state": "Lagos", "street": "Admiralty Way", "zipCode": "105102",
            "formatted": "12 Admiralty Way, Lekki, Lagos LA, 105102, Nigeria (NG)",
            "countryCode": "NG"
          },
          "website": null, "industry": null, "lastName": "Eze", "firstName": "Chidinma",
          "customerId": "33c479186e2741be98bce2af145959af", "middleName": null,

```

```

    "countryCode": "NG", "dateOfBirth": "1991-04-12", "profileType": "individual",
    "businessName": null, "businessType": null, "registrationDate": null
  },
  "workflow": {
    "id": "7a10d4b1895741a48674bbe4769d05df", "status": "verified", "priority": "standard",
    "riskScore": 0, "profileType": "individual", "providerKey": null,
    "providerSubjectId": null,
    "verificationTypes": ["passport", "... 3 more"]
  },
  "manualReview": null
},
"event": "workflow.verified", "timestamp": "2026-10-01T22:37:30.239Z",
"workflowId": "7a10d4b1895741a48674bbe4769d05df"
},
"signature": "t=1790894250,v1=1be3e4102adbc0105ea7857609d3a22168d71dc337c6df471185ac4848de4c5",
"status": "failed", "attempts": 1, "availableAt": "2026-10-01T22:37:42.524Z",
"deliveredAt": null, "responseStatus": 405,
"responseBody": "<!doctype html><html lang='en'><head><title>Example Domain</title><link
rel='ico...'>
",
"lastError": "HTTP 405", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7",
"appId": "1f62a4c6854e404385bf807eea9a7b5e",
"workflowId": "7a10d4b1895741a48674bbe4769d05df"
}
}

```

The demo app pointed at `https://example.com/...`, which answers 405 — so this delivery shows a real failure after 3 attempts with `responseStatus` and `lastError` filled. Redeliver re-sends the exact original payload. The `/tenants/apps/:appId/...` pair is the session-side mirror of the same data.

EVENTS & SIGNATURE

Two events today: `workflow.verified` and `workflow.failed`, fired when a workflow reaches that status — by the risk engine or by a manual approve/reject (§8.5) — never for `in-review`. A manual decision adds `data.manualReview: { decision, actor, reason, decidedAt }` (null for engine decisions) while `data.risk` still carries the engine's original verdict, so the receiver can see what was overridden. Every delivery carries `x-unifycomply-signature: t=<unix-seconds>,v1=<hex-hmac-sha256> over ${t}.${rawBody}` with the app's webhook secret. Verify against the raw body (not re-serialised JSON), compare in constant time, and reject stale timestamps.

Requires: `webhooks:read` / `webhooks:write`

12. Transactions — ingestion, detail, statement

Feeding transactions in powers every transaction-monitoring screen. Each transaction is evaluated against the app's detection and risk-score rules (§13) within a second or two of ingestion.

12.1 Record a transaction

LIVE

SESSION

API KEY

POST /v1/transactions

```

// request - POST /v1/transactions
{
  "customerId": "33c479186e2741be98bce2af145959af", "profileType": "individual",
  "currency": "USD", "direction": "inbound", "amount": 2500, "channel": "bank-transfer",
  "transactionType": "deposit", "reference": "DOCS-CLEAN-1790894286780",
  "occurredAt": "2026-10-01T21:18:06.780Z",
  "counterparty": {"name": "Acme Payroll Ltd", "accountNumber": "0123456789", "countryCode": "NG",
  "bic": "GTBINGLA"},

```

```

"paymentPurpose": "Salary", "sourceCountryCode": "NG", "destinationCountryCode": "NG",
"deviceInfo": {"device": "iPhone 15", "ipAddress": "102.89.1.20", "isNewDevice": false},
"debit": null, "credit": 2500, "balance": 502500
}
// response – HTTP 201
{
  "status": true, "message": "Transaction recorded successfully",
  "data": {
    "id": "1e73ff91f0a14e86b52748fb21d02b88", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "domain": "sandbox",
    "customerId": "33c479186e2741be98bce2af145959af", "profileType": "individual",
    "direction": "inbound", "amount": 2500, "currency": "USD", "channel": "bank-transfer",
    "transactionType": "deposit", "corridorCountryCode": null, "payerDeclaredName": null,
    "counterparty": {"name": "Acme Payroll Ltd", "accountNumber": "0123456789", "countryCode": "NG",
    "bic": "GTBINGLA"},
    "sourceCountryCode": "NG", "destinationCountryCode": "NG", "paymentPurpose": "Salary",
    "merchant": null,
    "deviceInfo": {"device": "iPhone 15", "ipAddress": "102.89.1.20", "isNewDevice": false},
    "debit": null, "credit": 2500, "balance": 502500, "reference": "DOCS-CLEAN-1790894286780",
    "occurredAt": "2026-10-01T21:18:06.780Z", "metadata": {},
    "createdAt": "2026-10-01T22:38:07.213Z"
  }
}

```

Field	Required	Notes
customerId , profileType , direction , amount , currency , channel , reference , occurredAt	yes	direction : inbound outbound . channel : free text payment rail (bank-transfer , card , crypto , ...).
transactionType	no	transfer withdrawal deposit payment recall-debit — rule filters and the Recall Debit rule key off it.
counterparty	no	{ name , accountNumber , countryCode , bic }
sourceCountryCode , destinationCountryCode , corridorCountryCode	no	Destination/source feed the High-Risk Country check (§5.4 flaggedCountryCodes).
payerDeclaredName	no	Name on the payment instruction. Compared with the customer's registered name → BACS Mismatch.
deviceInfo , merchant , paymentPurpose , metadata	no	metadata keys are readable by rules (e.g. geo_mismatch , geo_mismatch_distance).
debit , credit , balance	no	Tenant-supplied ledger values. UnifyComply never computes a balance; send them if you want the Account Statement (§12.4) to render.

Retrying with the same `reference` returns the original row (same `id`) — no duplicate

```

// response – HTTP 201
{
  "status": true, "message": "Transaction recorded successfully",
  "data": {
    "id": "1e73ff91f0a14e86b52748fb21d02b88", "amount": 2500,
    "reference": "DOCS-CLEAN-1790894286780", "createdAt": "2026-10-01T22:38:07.213Z"
  }
}

```

reference is the idempotency key. Generate it once per real transaction, not per HTTP attempt.

400 — missing required fields

```
// request — POST /v1/transactions
{"customerId": "33c479186e2741be98bce2af145959af", "amount": 10}
// response — HTTP 400
{
  "status": false,
  "message": "profileType must be one of the following values: individual, business, direction must be one of the following values: inbound, outbound, currency must..."
}
```

Requires: `transactions:write`

12.2 List & read

LIVE

SESSION

API KEY

GET /v1/transactions

GET /v1/transactions/:id

Query: `customerId`, `dateFrom`, `dateTo`, `page`, `limit`.

```
// response — HTTP 200
{
  "status": true, "message": "Transactions retrieved successfully",
  "data": [
    {
      "id": "05ea12fc43d347a9adbc6b7edc2cfd06", "customerId": "33c479186e2741be98bce2af145959af",
      "profileType": "individual", "direction": "outbound", "amount": 6000, "currency": "USD",
      "channel": "crypto", "transactionType": "withdrawal", "corridorCountryCode": null,
      "payerDeclaredName": null, "counterparty": null, "sourceCountryCode": null,
      "destinationCountryCode": null, "paymentPurpose": null, "merchant": null,
      "deviceInfo": null, "debit": 6000, "credit": null, "balance": 397300,
      "reference": "D0CS-CRY-1790894286780", "occurredAt": "2026-10-01T22:28:06.780Z",
      "metadata": {}
    },
    "... 4 more"
  ],
  "meta": {"totalItems": 8, "itemsCount": 5, "itemsPerPage": 5, "totalPages": 2, "currentPage": 1}
}
```

Requires: `transactions:read`

12.3 Transaction detail (composed)

PARTIAL

SESSION

API KEY

GET /v1/transactions/:id/detail

A 75,000 USD transfer — tripped High Value Transaction and Threshold Breach, auto-blocked

```
// response — HTTP 200
{
  "status": true, "message": "Transaction detail retrieved successfully",
  "data": {
    "transaction": {
      "id": "03ee00beed0e4bc2a0c9a043ccb98da0", "customerId": "33c479186e2741be98bce2af145959af",
      "profileType": "individual", "direction": "outbound", "amount": 75000, "currency": "USD",
      "channel": "bank-transfer", "transactionType": "transfer", "corridorCountryCode": null,
      "payerDeclaredName": null,
      "counterparty": {"name": "Lekki Properties", "accountNumber": "1122334455", "countryCode":
"NG", "bic": null},
      "sourceCountryCode": null, "destinationCountryCode": null, "paymentPurpose": null,

```

```

    "merchant": null, "deviceInfo": null, "debit": 75000, "credit": null, "balance": 412500,
    "reference": "D0CS-THR-1790894286780", "occurredAt": "2026-10-01T21:38:06.780Z",
    "metadata": {}
  },
  "customer": {"name": "Chidinma Eze", "maskedAccount": null},
  "risk": {
    "category": "tm-blocked", "riskScore": 0, "riskLevel": "low", "status": "blocked",
    "rulesTriggerCount": 2,
    "matchedRules": [
      {
        "reason": "Flags transactions above $10,000 for review (transaction amount 75000 exceeds
10000)",
        "ruleId": "ab4687262e07448cbb7fe8463068ca8f", "ruleName": "High Value Transaction",
        "ruleType": "detection", "description": "Flags transactions above $10,000 for review",
        "severityOrScore": "medium",
        "matchedConditions": [{"field": "transaction_amount", "value": "10000", "operator":
"greater-than"}]
      },
      {
        "reason": "Transfer value exceeds the configured transaction threshold (transaction amount
75000 exceeds 50000)",
        "ruleId": "24faf45dc8864ad4852ddf9a59ec3a4f", "ruleName": "Threshold Breach",
        "ruleType": "detection",
        "description": "Transfer value exceeds the configured transaction threshold.",
        "severityOrScore": "critical",
        "matchedConditions": [{"field": "transaction_amount", "value": "50000", "operator":
"greater-than"}]
      }
    ],
    "decidedAt": "2026-10-01T22:38:08.406Z"
  },
  "analystStatus": null, "riskNarrative": null,
  "timeline": [
    {"kind": "initiated", "message": null, "occurredAt": "2026-10-01T22:38:08.394Z"},
    {"kind": "analysis-complete", "message": null, "occurredAt": "2026-10-01T22:38:08.408Z"},
    {
      "kind": "flagged-for-review",
      "message": "Blocked (tm-blocked): High Value Transaction – Flags transactions above $10,000
for review (transaction amount 75000 exceeds 10000); Threshold Breach – Transfer value exceeds the
configured transaction threshold (transaction amount 75000 exceeds 50000)",
      "occurredAt": "2026-10-01T22:38:08.409Z"
    }
  ]
}

```

Every matched rule says why it fired. Each `matchedRules[]` entry carries `description` (what the rule catches) and `reason` (that description plus this transaction's actual values, e.g. "Transfer value exceeds the configured transaction threshold (transaction amount 75000 exceeds 50000)"). The `flagged-for-review` timeline entry lists the outcome and every reason. Show `reason` wherever a hold or block is displayed. Transactions assessed before 2026-10-01 have no `reason` .

A blocked transaction can show `riskScore: 0` / `riskLevel: "low"` . Score and level come only from risk-score rules (§13.2); detection rules set `category` and `status` . Lead the UI with `status` and `category` , and show the score as secondary.

Field	Status	Why
<code>customer.maskedAccount</code>	always null	No customer account-number concept exists; only the counterparty's.

Field	Status	Why
riskNarrative	always null	No narrative generation on the transaction side.
risk	null briefly	Null for the second or two before evaluation completes.
timeline	grows	initiated , analysis-complete , flagged-for-review (only if a rule matched), then the case status once an action from §15 has been taken.

Every demo transaction produced the expected outcome:

Demo transaction	Result	Rules matched
Inbound 2,500 deposit	cleared , no category	none
Outbound 15,000 transfer	stop-payment · pending	High Value Transaction
Outbound 75,000 transfer	tm-blocked · blocked	High Value Transaction + Threshold Breach
1,200 recall-debit	tm-blocked · blocked	Recall Debit Payment
3,000 to Iran	stop-payment · pending , score 40	High-Risk Country List + Cross-border transfer (risk-score rule)
800 with payerDeclaredName: "John Smith"	stop-payment · pending	BACS Mismatch
4,200 card, geo_mismatch_distance: 6100	tm-blocked · blocked	Suspicious Geo-Location Pattern
6,000 crypto withdrawal	tm-blocked · blocked	Large Crypto Payout (custom rule from §13.1)

Requires: transactions:read

12.4 Account statement

LIVE

SESSION

API KEY

GET /v1/customers/:id/statement

Query: page , limit .

```
// response – HTTP 200
{
  "status": true, "message": "Account statement retrieved successfully",
  "data": [
    {
      "id": "05ea12fc43d347a9adbc6b7edc2cfd06", "customerId": "33c479186e2741be98bce2af145959af",
      "profileType": "individual", "direction": "outbound", "amount": 6000, "currency": "USD",
      "channel": "crypto", "transactionType": "withdrawal", "corridorCountryCode": null,
      "payerDeclaredName": null, "counterparty": null, "sourceCountryCode": null,
      "destinationCountryCode": null, "paymentPurpose": null, "merchant": null,
      "deviceInfo": null, "debit": 6000, "credit": null, "balance": 397300,
      "reference": "DOCS-CRY-1790894286780", "occurredAt": "2026-10-01T22:28:06.780Z",
      "metadata": {}
    },
    "... 4 more"
  ],
}
```

```
"summary": {
  "currentBalance": 397300, "totalCredit": 2500, "totalDebit": 105200, "totalTransactions": 8,
  "accountOpeningDate": "2026-10-01T21:18:06.780Z", "openingBalance": 500000
},
"meta": {"totalItems": 8, "itemsCount": 5, "itemsPerPage": 5, "totalPages": 2, "currentPage": 1}
}
```

`openingBalance` / `accountOpeningDate` derive from the customer's earliest transaction. A customer whose transactions never carried `balance` gets `null` summary values — render an empty state, not 0.

Requires: `transactions:read`

13. Transaction-monitoring settings & Re-KYC triggers

Session only, `tenant-settings:update`. Base path `/v1/tenants/apps/:appId/transaction-monitoring`. Two independent entities: a **detection rule** routes a transaction to a queue (and can auto-block); a **risk-score rule** adds points to its 0–100 score.

13.1 Detection rules

LIVESESSIONGET `/v1/tenants/apps/:appId/transaction-monitoring/rules`POST `/v1/tenants/apps/:appId/transaction-monitoring/rules`PATCH `/v1/tenants/apps/:appId/transaction-monitoring/rules/:ruleId`DELETE `/v1/tenants/apps/:appId/transaction-monitoring/rules/:ruleId`

```
// request - POST /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/transaction-monitoring/rules
{
  "name": "Large Crypto Payout", "description": "Outbound crypto payouts above 5,000",
  "severityLevel": "high", "tmCondition": "stop-payment", "autoBlock": false, "sendAlerts": true,
  "conditions": [
    {"field": "channel", "operator": "equals", "value": "crypto"},
    {"field": "transaction_amount", "operator": "greater-than", "value": "5000"}
  ],
  "transactionTypes": ["withdrawal", "transfer"], "status": "active"
}
// response - HTTP 201
{
  "status": true, "message": "Rule created successfully",
  "data": {
    "id": "311a11887924411badf3b37bcf510c03", "createdAt": "2026-10-01T22:37:59.079Z",
    "updatedAt": "2026-10-01T22:37:59.079Z", "name": "Large Crypto Payout",
    "description": "Outbound crypto payouts above 5,000", "severityLevel": "high",
    "tmCondition": "stop-payment", "autoBlock": false, "sendAlerts": true,
    "conditions": [
      {"field": "channel", "value": "crypto", "operator": "equals"},
      {"field": "transaction_amount", "value": "5000", "operator": "greater-than"}
    ],
    "transactionTypes": ["withdrawal", "transfer"], "status": "active", "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffef9c7"
  }
}
```

```
// request - PATCH /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/transaction-
monitoring/rules/311a11887924411badf3b37bcf510c03
{"severityLevel": "critical", "autoBlock": true, "tmCondition": "tm-blocked"}
// response - HTTP 200
{
  "status": true, "message": "Rule updated successfully",
  "data": {
    "id": "311a11887924411badf3b37bcf510c03", "createdAt": "2026-10-01T22:37:59.079Z",
    "updatedAt": "2026-10-01T22:37:59.471Z", "name": "Large Crypto Payout",
    "description": "Outbound crypto payouts above 5,000", "severityLevel": "critical",
    "tmCondition": "tm-blocked", "autoBlock": true, "sendAlerts": true,
    "conditions": [
      {"field": "channel", "value": "crypto", "operator": "equals"},
      {"field": "transaction_amount", "value": "5000", "operator": "greater-than"}
    ],
    "transactionTypes": ["withdrawal", "transfer"], "status": "active", "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffef9c7"
  }
}
```

Conditions are AND-only. `field` and `operator` are closed enums — build the condition builder from `/v1/public/misc/options/tm-condition-fields` and `tm-condition-operators`. `tmCondition` is the queue (`tm-not-blocked|stop-payment|cumulative-frequency|tm-blocked`); `transactionTypes: null` means all types.

400 — a field outside the enum

```
// request — POST /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/transaction-monitoring/rules
{
  "name": "Bad", "severityLevel": "low", "tmCondition": "tm-blocked",
  "conditions": [{"field": "customer_age", "operator": "equals", "value": "1"}]
}
// response — HTTP 400
{
  "status": false,
  "message": "conditions.0.field must be one of the following values: transaction_amount, currency,
channel, transaction_type, direction, profile_type, corridor_cou..."
}
```

Every new app starts with 8 rules (6 Fintech suite + Recall Debit + Threshold Breach)

```
// response — HTTP 200
{
  "status": true, "message": "Rules retrieved successfully",
  "data": [
    {
      "id": "efad88fc444c4ec285d10e4ab8fa74f4", "name": "Suspicious Geo-Location Pattern",
      "description": "Detects transactions with significant geo-location mismatch (>5000km)",
      "severityLevel": "critical", "tmCondition": "tm-blocked", "autoBlock": true,
      "sendAlerts": true,
      "conditions": [
        {"field": "geo_mismatch", "value": "true", "operator": "equals"},
        {"field": "geo_mismatch_distance", "value": "5000", "operator": "greater-than"}
      ],
      "transactionTypes": [], "status": "active"
    },
    {
      "id": "952d79db5cc24bcc8050a519eb21e9a8", "name": "High ML Fraud Probability",
      "description": "AI model detected high fraud probability (>80%)",
      "severityLevel": "critical", "tmCondition": "tm-blocked", "autoBlock": true,
      "sendAlerts": true, "conditions": [], "transactionTypes": [], "status": "active"
    },
    "... 6 more"
  ],
  "meta": {"totalItems": 8, "itemsCount": 8, "itemsPerPage": 20, "totalPages": 1, "currentPage": 1}
}
```

4 of the 8 seeded rules have no conditions and never fire. High ML Fraud Probability, Large Withdrawal Pattern, New Device High Amount and Velocity Spike Detection describe patterns over time, which the single-transaction engine cannot express yet. Show them, but consider marking them "not evaluated".

```
// response — HTTP 200
{
  "status": true, "message": "Rule deleted successfully",
  "data": {"id": "b38b6d52e29c4c458e193bc1504822af"}
}
```

13.2 Risk-score rules

LIVESESSION

GET /v1/tenants/apps/:appId/transaction-monitoring/risk-score-rules

POST /v1/tenants/apps/:appId/transaction-monitoring/risk-score-rules

PATCH /v1/tenants/apps/:appId/transaction-monitoring/risk-score-rules/:ruleId

DELETE /v1/tenants/apps/:appId/transaction-monitoring/risk-score-rules/:ruleId

```
// request - POST /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/transaction-monitoring/risk-score-rules
{
  "name": "Cross-border transfer", "description": "Any transfer leaving Nigeria", "score": 35,
  "riskLevel": "medium", "transactionTypes": ["transfer"],
  "conditions": [{"field": "destination_country", "operator": "not-equals", "value": "NG"}],
  "status": "active"
}
// response - HTTP 201
{
  "status": true, "message": "Risk score rule created successfully",
  "data": {
    "id": "058a180990f64b38a7d82579676a2562", "createdAt": "2026-10-01T22:38:00.220Z",
    "updatedAt": "2026-10-01T22:38:00.220Z", "name": "Cross-border transfer",
    "description": "Any transfer leaving Nigeria", "score": 35, "riskLevel": "medium",
    "conditions": [{"field": "destination_country", "value": "NG", "operator": "not-equals"}],
    "transactionTypes": ["transfer"], "status": "active", "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

```
// request - PATCH /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/transaction-monitoring/risk-score-rules/058a180990f64b38a7d82579676a2562
{"score": 40}
// response - HTTP 200
{
  "status": true, "message": "Risk score rule updated successfully",
  "data": {
    "id": "058a180990f64b38a7d82579676a2562", "createdAt": "2026-10-01T22:38:00.220Z",
    "updatedAt": "2026-10-01T22:38:00.603Z", "name": "Cross-border transfer",
    "description": "Any transfer leaving Nigeria", "score": 40, "riskLevel": "medium",
    "conditions": [{"field": "destination_country", "value": "NG", "operator": "not-equals"}],
    "transactionTypes": ["transfer"], "status": "active", "domain": "sandbox",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}
```

score 0–100 (TM's own scale, unrelated to KYC 0–4). Scores of all matched rules add up; the total buckets into **low** (<40), **medium** (<70), **high** .

13.3 Rule templates

LIVESESSION

GET /v1/tenants/apps/:appId/transaction-monitoring/rule-templates

POST /v1/tenants/apps/:appId/transaction-monitoring/rule-templates/:templateId/adopt

```
// response - HTTP 200
{
  "status": true, "message": "Rule templates retrieved successfully",
  "data": [
```

```

{
  "id": "fintech-tm-detection-suite", "name": "Fintech TM Detection Suite",
  "industryLabel": "Fintech and Payment Processing Industry",
  "description": "Comprehensive fraud detection rules specifically designed for fintech companies
and payment processors. Includes high-value transaction monitoring.",
  "popular": true,
  "keyFeatures": ["Withdrawal Monitoring", "Cross border Monitoring", "... 1 more"],
  "ruleCount": 6
},
{
  "id": "banking-financial-services-suite", "name": "Banking & Financial Services Suite",
  "industryLabel": "Banking and Financial Services",
  "description": "Comprehensive fraud detection rules specifically designed for fintech companies
and payment processors. Includes high-value transaction monitoring.",
  "popular": true,
  "keyFeatures": ["Withdrawal Monitoring", "Cross border Monitoring", "... 1 more"],
  "ruleCount": 6
},
"... 4 more"
]
}

```

```

// response – HTTP 201
{
  "status": true, "message": "Adopted 6 rule(s) from \"E-Commerce Protection Package\"",
  "data": [
    {
      "id": "b38b6d52e29c4c458e193bc1504822af", "name": "Suspicious Geo-Location Pattern",
      "description": "Detects transactions with significant geo-location mismatch (>5000km)",
      "severityLevel": "critical", "tmCondition": "tm-blocked", "autoBlock": true,
      "sendAlerts": true,
      "conditions": [{"field": "geo_mismatch", "value": "true", "operator": "equals"}, "... 1 more"],
      "transactionTypes": [], "status": "active"
    },
    "... 5 more"
  ]
}

```

Adopting is additive and does not de-duplicate. Adopting a package you already have doubles its rules (and their trigger counts). Only the Fintech package has distinct content today — the other five carry the same six rules under their own names.

13.4 Re-KYC triggers PARTIAL SESSION

GET /v1/tenants/apps/:appId/re-kyc/trigger-rules

PATCH /v1/tenants/apps/:appId/re-kyc/trigger-rules/:kind

A fixed catalogue of nine kinds per app — enable, disable or tune `config`; no create or delete.

```

// response – HTTP 200
{
  "status": true, "message": "Re-KYC trigger rules retrieved successfully",
  "data": [
    {
      "id": "aad5a9e225d14a7f9e7d7c5c0549889f", "kind": "high-risk-jurisdiction",
      "status": "active", "config": {}
    },
    {
      "id": "2869a89e649b474faa3bb995f9e094a1", "kind": "pep-sanctions", "status": "active",
      "config": {}
    }
  ]
}

```

```

    },
    "... 7 more"
  ]
}

```

```

// request - PATCH /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/re-kyc/trigger-rules/suspected-ato
{"status": "inactive"}
// response - HTTP 200
{
  "status": true, "message": "Re-KYC trigger rule updated successfully",
  "data": {
    "id": "f807f26f4a844ce39543714ea52ac9c2", "createdAt": "2026-10-01T22:36:34.556Z",
    "updatedAt": "2026-10-01T22:38:02.873Z", "kind": "suspected-ato", "status": "inactive",
    "config": {}, "domain": "sandbox", "appId": "1f62a4c6854e404385bf807eea9a7b5e",
    "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7"
  }
}

```

400 — unknown kind

```

// request - PATCH /v1/tenants/apps/1f62a4c6854e404385bf807eea9a7b5e/re-kyc/trigger-rules/velocity-spike
{"status": "inactive"}
// response - HTTP 400
{
  "status": false,
  "message": "kind must be one of the following values: high-risk-jurisdiction, pep-sanctions, transaction-monitoring-escalation, basic-kyc, expired-id, forged-id, ..."
}

```

A Re-KYC audit event — every escalation carries `trigger` and `reason`

```

// response - HTTP 200
{
  "status": true, "message": "Verification retrieved successfully",
  "data": {
    "events": [
      {
        "id": "11ac8993b9464cfd80c6b62d9990b69f", "action": "transaction.monitoring.alert",
        "actor": "risk-decisioning", "fromStatus": "in-review", "toStatus": null,
        "detail": {
          "reason": "Transaction-monitoring activity identifies risk requiring renewed customer due diligence. Activity used crypto, direct-debit, not among the declared channels.",
          "trigger": "transaction-monitoring-escalation",
          "messageId": "monitoring:05ea12fc43d347a9adbc6b7edc2cfd06",
          "contributions": [
            {
              "code": "activity.channel-not-declared", "points": 1, "source": "verification",
              "message": "Activity used crypto, direct-debit, not among the declared channels",
              "evidence": {"channels": ["crypto", "... 1 more"], "declared": ["bank-transfer", "... 1 more"]},
              "factorSlug": "activity-inconsistent-with-purpose"
            }
          ],
          "transactionId": "05ea12fc43d347a9adbc6b7edc2cfd06"
        },
        "customerName": "Chidinma Eze", "workflowId": "7a10d4b1895741a48674bbe4769d05df"
      },
      "... 7 more"
    ]
  }
}

```

Every Re-KYC escalation writes an audit event whose `detail` carries `trigger` (the kind below) and `reason` — the rules document's Trigger / Criteria wording followed by the specific finding (the expired document and date, the AML match, the changed fields, the monitoring finding). Render `detail.reason` as the "why is this in review" line.

Kind	Status	Disabling it...
pep-sanctions	live	stops a new AML match from flipping a verified customer to <code>in-review</code> (the match is still recorded)
transaction-monitoring-escalation	live	stops a monitoring alert from flipping the workflow
basic-kyc	live	skips the periodic re-screen for this app
expired-id , proof-of-address	live	stops expiry of an ID / proof-of-address document from flipping the workflow
suspected-ato	live	stops 2+ sensitive-field changes within 72 h from flipping the workflow
high-risk-jurisdiction , forged-id , immigration-check	no-op	nothing evaluates these yet — the toggle changes nothing

14. Transaction-monitoring dashboard & queues

14.1 Overview

PARTIAL

SESSION

API KEY

GET

/v1/transaction-monitoring/overview

Query: `windowStart` , `windowEnd` (ISO; default the trailing 24 h).

```
// response – HTTP 200
{
  "status": true, "message": "Overview retrieved successfully",
  "data": {
    "windowStart": "2026-09-30T22:38:22.704Z", "windowEnd": "2026-10-01T22:38:22.704Z",
    "totalVolume": 9, "totalValue": 155700, "activeUsers": 2, "avgRiskScore": 9,
    "highRiskAlerts": 0, "activityChart": {"21": 5, "22": 4},
    "riskDistribution": {"low": 7, "medium": 2, "high": 0},
    "tmConditions": {"tm-not-blocked": 0, "stop-payment": 4, "cumulative-frequency": 0, "tm-blocked":
4},
    "monthlyVolume": null
  }
}
```

Field	Status	Why
monthlyVolume	always null	No day/month bucketed aggregation exists yet.
activityChart	hour-of-day	Keys are hours 0–23 within the window, not a time series.

Requires: `transactions:read`

14.2 The four category queues PARTIAL SESSION API KEY

- GET** /v1/transaction-monitoring/tm-blocked
- GET** /v1/transaction-monitoring/stop-payment
- GET** /v1/transaction-monitoring/cumulative-frequency
- GET** /v1/transaction-monitoring/tm-not-blocked

Query: `status` (`pending|cleared|blocked`), `page` , `limit` .

```
// response – HTTP 200
{
  "status": true, "message": "Transactions retrieved successfully",
  "data": [
    {
      "id": "c9f6ae4512774176944c1dc05283b641",
      "transactionId": "88c0b44452304148bf0d6922ba869340",
      "customerId": "eab4159c3215435d9b12806cdd629c96", "riskScore": 40, "riskLevel": "medium",
      "category": "stop-payment", "status": "pending", "rulesTriggerCount": 2,
      "matchedRules": [
        {
          "reason": "Flags transactions above $10,000 for review (transaction amount 48000 exceeds
10...",
          "ruleId": "ab4687262e07448cbb7fe8463068ca8f", "ruleName": "High Value Transaction",
          "ruleType": "detection", "description": "Flags transactions above $10,000 for review",
          "severityOrScore": "medium",
          "matchedConditions": [{"field": "transaction_amount", "value": "10000", "operator":
"greater-than"}]
        },
        "... 1 more"
      ],
      "decidedAt": "2026-10-01T22:38:10.760Z"
    },
    "... 3 more"
  ],
  "summary": {
    "category": "stop-payment", "totalTransactions": 4, "totalAmount": 66800, "pendingReview": 4,
    "resolved": 0
  },
  "meta": {"totalItems": 4, "itemsCount": 4, "itemsPerPage": 5, "totalPages": 1, "currentPage": 1}
}
```

`summary` always carries all four tile values; screens that show fewer simply ignore the rest. The category is fixed by the route.

Queue	Status	Why
TM Not-Blocked	empty for clean traffic	Only transactions whose matched rule routes to <code>tm-not-blocked</code> appear. A transaction that matched nothing gets <code>category: null</code> and appears in no queue — so "cleared for processing" volume is not listed here today.

Requires: `transactions:read`

15. Investigations — reporting actions & case management

The "Reporting Actions" menu on Transaction Detail and the Account Statement. Session only — an API key gets 401. `:id` is the transaction id; the server resolves the customer. The first action on a transaction creates its case.

401 — called with an API key

```
// request — POST /v1/transactions/fef5460c015b4b8081ca8e4df24497ff/actions/escalate-case
{"notes": "x"}
// response — HTTP 401
{"status": false, "message": "Unauthorized"}
```

15.1 Resolve case

LIVE

SESSION

POST

/v1/transactions/:id/actions/resolve-case

```
// request — POST /v1/transactions/bb8ff7844f2d4af685499be5ceb589d5/actions/resolve-case
{
  "resolutionType": "cleared-no-issues",
  "outcomeSummary": "Vehicle purchase confirmed with invoice from Bright Motors",
  "actionsTaken": ["customer-verification-completed", "source-of-funds-verified", "... 1 more"],
  "resolutionNotes": "Customer supplied dealer invoice INV-2209; amount matches."
}
// response — HTTP 201
{
  "status": true, "message": "Case resolved successfully",
  "data": {
    "id": "cf5d7d443cf44538bbb10384787c4fdd", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "domain": "sandbox",
    "transactionId": "bb8ff7844f2d4af685499be5ceb589d5",
    "customerId": "33c479186e2741be98bce2af145959af", "status": "resolved",
    "resolutionType": "cleared-no-issues",
    "outcomeSummary": "Vehicle purchase confirmed with invoice from Bright Motors",
    "actionsTaken": ["customer-verification-completed", "source-of-funds-verified", "... 1 more"],
    "resolutionNotes": "Customer supplied dealer invoice INV-2209; amount matches.",
    "assignedTo": null, "resolvedAt": "2026-10-01T22:38:25.500Z",
    "resolvedBy": "docs.demo.1790894194091@unifycomply.test",
    "createdAt": "2026-10-01T22:38:25.495Z", "updatedAt": "2026-10-01T22:38:25.500Z"
  }
}
```

Field	Values
resolutionType (required)	cleared-no-issues, false-positive, escalated-to-authorities, resolved-after-contact, documentation-provided-cleared, risk-closed-insufficient-grounds
actionsTaken (multi-select)	customer-verification-completed, source-of-funds-verified, pep-screening-cleared, enhanced-due-diligence-performed, transaction-pattern-analyzed, adverse-media-check-completed, business-relationship-reviewed, sanctions-screening-passed

Requires: permission `case:resolve`

15.2 Escalate case

LIVESESSION

POST /v1/transactions/:id/actions/escalate-case

```
// request - POST /v1/transactions/423ce5a336da4d9b877d0606dcda0188/actions/escalate-case
{"notes": "Payer name on instruction does not match KYC name - escalating to compliance lead."}
// response - HTTP 201
{
  "status": true, "message": "Case escalated successfully",
  "data": {
    "id": "0520804e8b4847e29301123fe1ff254c", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "domain": "sandbox",
    "transactionId": "423ce5a336da4d9b877d0606dcda0188",
    "customerId": "33c479186e2741be98bce2af145959af", "status": "escalated",
    "resolutionType": null, "outcomeSummary": null, "actionsTaken": [],
    "resolutionNotes": "Payer name on instruction does not match KYC name - escalating to compliance lead.",
    "assignedTo": null, "resolvedAt": null, "resolvedBy": null,
    "createdAt": "2026-10-01T22:38:25.885Z", "updatedAt": "2026-10-01T22:38:25.888Z"
  }
}
```

Requires: permission `case:escalate`

15.3 Place PND (Post No Debit) — also files a SAR

LIVESESSION

POST /v1/transactions/:id/actions/place-pnd

```
// request - POST /v1/transactions/03ee00beed0e4bc2a0c9a043ccb98da0/actions/place-pnd
{
  "listType": "internal-watchlist", "entityType": "individual", "fullName": "Chidinma Eze",
  "nationality": "NG", "dateOfBirth": "1991-04-12", "idNumber": "A09876543",
  "idType": "passport", "address": "12 Admiralty Way, Lekki, Lagos", "riskLevel": "high",
  "reasonForListing": "Structuring",
  "narrative": "Single outbound transfer of 75,000 USD against a declared monthly value of 1.5M NGN.",
  "activityTypeTags": ["structuring", "velocity"], "amount": 75000,
  "documentReference": "DOC-7781", "evidenceReference": "EVD-2201",
  "reportingOfficer": "Ada Okafor"
}
// response - HTTP 201
{
  "status": true,
  "message": "Placed on PND watchlist successfully, SAR rationale filed automatically",
  "data": {
    "pndListing": {
      "id": "3080365f4d47473a869c8e3ae20a9ce7",
      "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0",
      "customerId": "33c479186e2741be98bce2af145959af",
      "caseId": "06475155d5d74d77b2a827da1cb9ff09", "status": "active",
      "listType": "internal-watchlist", "entityType": "individual", "fullName": "Chidinma Eze",
      "nationality": "NG", "dateOfBirth": "1991-04-12", "idNumber": "A09876543",
      "idType": "passport", "address": "12 Admiralty Way, Lekki, Lagos", "riskLevel": "high",
      "reasonForListing": "Structuring",
      "narrative": "Single outbound transfer of 75,000 USD against a declared monthly value of 1.5M NGN.",
      "activityTypeTags": ["structuring", "velocity"], "amount": 75000,
      "documentReference": "DOC-7781", "evidenceReference": "EVD-2201",
      "reportingOfficer": "Ada Okafor", "filedBy": "docs.demo.1790894194091@unifycomply.test",
      "resolvedDate": null, "resolutionType": null, "resolutionReason": null,
      "investigationOutcome": null, "resolutionActionsTaken": null, "approvedBy": null
    }
  }
}
```

```

"sarFiling": {
  "id": "dffa675f00b478a953fa52736cedac8", "caseId": "06475155d5d74d77b2a827da1cb9ff09",
  "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0", "status": "pending",
  "subjectFullName": "Chidinma Eze", "entityType": "individual", "accountNumberMasked": null,
  "totalAmount": 75000, "riskLevel": "high", "activityType": null, "detectionDate": null,
  "activityStartDate": null, "activityEndDate": null, "filingJurisdiction": null,
  "filedDate": null, "filedBy": "docs.demo.1790894194091@unifycomply.test",
  "suspiciousActivityCategories": ["structuring", "velocity"], "suspiciousIndicators": [],
  "narrative": {
    "openingStatement": "Single outbound transfer of 75,000 USD against a declared monthly value
of 1.5M ...",
    "whyItsSuspicious": "", "activityDescription": "", "investigationStepsTaken": "",
    "summaryAndRecommendation": ""
  },
  "relatedTransactionIds": ["03ee00beed0e4bc2a0c9a043ccb98da0"]
}
}
}

```

One call creates both a PND listing and a SAR filing. The design's submit button reads "File SAR". Do not also call \$15.4 for the same PND — it would create a second, unrelated filing. Required: `entityType` (`individual|business`), `fullName` , `riskLevel` (`low|medium|high|critical`), `reasonForListing` .

Requires: permission `pnd:manage`

15.4 Generate SAR rationale

LIVE

SESSION

POST `/v1/transactions/:id/sar-rationale`

```

// request - POST /v1/transactions/9e8539c64425421e98d4342efe4508fe/sar-rationale
{
  "subjectFullName": "Chidinma Eze", "entityType": "individual",
  "accountNumberMasked": "*****4567", "totalAmount": 3000, "riskLevel": "high",
  "activityType": "Sanctioned jurisdiction transfer", "detectionDate": "2026-10-01",
  "activityStartDate": "2026-10-01", "activityEndDate": "2026-10-01",
  "filingJurisdiction": "NFIU - NG",
  "suspiciousActivityCategories": ["Sanctions Evasion"],
  "suspiciousIndicators": [
    {
      "title": "Transfer to a sanctioned jurisdiction",
      "description": "Outbound transfer to an Iran-domiciled counterparty"
    }
  ],
  "narrative": {
    "openingStatement": "Chidinma Eze, an individual customer, sent USD 3,000 to Tehran Trading Co (IR).",
    "activityDescription": "One outbound bank transfer on 2026-10-01 to a counterparty domiciled in Iran.",
    "whyItsSuspicious": "Iran is on the tenant's flagged-country list; no declared corridor covers it.",
    "investigationStepsTaken": "Reviewed declared account purpose (NG, GB corridors only) and 90-day history.",
    "summaryAndRecommendation": "File with NFIU and hold further transfers to IR pending review."
  },
  "relatedTransactionIds": ["9e8539c64425421e98d4342efe4508fe"]
}
// response - HTTP 201
{
  "status": true, "message": "SAR rationale generated successfully",
  "data": {
    "id": "2f3354d94b594ab49e51a04b6ed94f29", "tenantId": "7c9e91f81e064c6a9ead352ffef9c7",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "domain": "sandbox",

```

```

"caseId": "e69b624ea2624e8f84c650d9edd9dab8",
"transactionId": "9e8539c64425421e98d4342efe4508fe", "status": "pending",
"subjectFullName": "Chidinma Eze", "entityType": "individual",
"accountNumberMasked": "*****4567", "totalAmount": 3000, "riskLevel": "high",
"activityType": "Sanctioned jurisdiction transfer",
"detectionDate": "2026-10-01T00:00:00.000Z", "activityStartDate": "2026-10-01T00:00:00.000Z",
"activityEndDate": "2026-10-01T00:00:00.000Z", "filingJurisdiction": "NFIU - NG",
"filedDate": null, "filedBy": "docs.demo.1790894194091@unifycomply.test",
"suspiciousActivityCategories": ["Sanctions Evasion"],
"suspiciousIndicators": [
  {
    "title": "Transfer to a sanctioned jurisdiction",
    "description": "Outbound transfer to an Iran-domiciled counterparty"
  }
],
"narrative": {
  "openingStatement": "Chidinma Eze, an individual customer, sent USD 3,000 to Tehran Trading Co (IR).",
  "whyItsSuspicious": "Iran is on the tenant's flagged-country list; no declared corridor covers it.",
  "activityDescription": "One outbound bank transfer on 2026-10-01 to a counterparty domiciled in Iran.",
  "investigationStepsTaken": "Reviewed declared account purpose (NG, GB corridors only) and 90-day history.",
  "summaryAndRecommendation": "File with NFIU and hold further transfers to IR pending review."
},
"relatedTransactionIds": ["9e8539c64425421e98d4342efe4508fe"],
"createdAt": "2026-10-01T22:38:26.681Z", "updatedAt": "2026-10-01T22:38:26.681Z"
}

```

Required: `subjectFullName`, `entityType`, `riskLevel`. `narrative` has five lettered parts (A opening statement ... E summary & recommendation) and `suspiciousIndicators` is the numbered list on the rendered document. Re-post to revise ("Edit Rationale").

Requires: permission `sar:file`

15.5 Case Management tab

LIVE

SESSION

GET `/v1/transactions/:id/case`

No action taken yet — `data: null` (not 404)

```

// response - HTTP 200
{"status": true, "message": "Case retrieved successfully", "data": null}

```

```

// response - HTTP 200
{
  "status": true, "message": "Case retrieved successfully",
  "data": {
    "id": "06475155d5d74d77b2a827da1cb9ff09", "tenantId": "7c9e91f81e064c6a9eada352ffef9c7",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "domain": "sandbox",
    "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0",
    "customerId": "33c479186e2741be98bce2af145959af", "status": "open", "resolutionType": null,
    "outcomeSummary": null, "actionsTaken": [], "resolutionNotes": null, "assignedTo": null,
    "resolvedAt": null, "resolvedBy": null, "createdAt": "2026-10-01T22:38:26.266Z",
    "updatedAt": "2026-10-01T22:38:26.277Z",
    "activity": [
      {
        "id": "371b97ba572d4673afd27a3a98fd316a", "kind": "sar-rationale-generated",
        "message": "SAR rationale generated: high risk",
        "actorId": "docs.demo.1790894194091@unifycomply.test",

```

```

      "occurredAt": "2026-10-01T22:38:26.282Z"
    },
    {
      "id": "9f261bfeec6f4966ba16224979f2d079", "kind": "pnd-placed",
      "message": "Placed on PND watchlist: Structuring",
      "actorId": "docs.demo.1790894194091@unifycomply.test",
      "occurredAt": "2026-10-01T22:38:26.275Z"
    }
  ],
  "pndListings": [
    {
      "id": "3080365f4d47473a869c8e3ae20a9ce7",
      "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0",
      "customerId": "33c479186e2741be98bce2af145959af",
      "caseId": "06475155d5d74d77b2a827da1cb9ff09", "status": "active",
      "listType": "internal-watchlist", "entityType": "individual", "fullName": "Chidinma Eze",
      "nationality": "NG", "dateOfBirth": "1991-04-12", "idNumber": "A09876543",
      "idType": "passport", "address": "12 Admiralty Way, Lekki, Lagos", "riskLevel": "high",
      "reasonForListing": "Structuring",
      "narrative": "Single outbound transfer of 75,000 USD against a declared monthly valu...",
      "activityTypeTags": ["structuring", "velocity"], "amount": 75000,
      "documentReference": "DOC-7781", "evidenceReference": "EVD-2201",
      "reportingOfficer": "Ada Okafor", "filedBy": "docs.demo.1790894194091@unifycomply.test",
      "resolvedDate": null, "resolutionType": null, "resolutionReason": null,
      "investigationOutcome": null, "resolutionActionsTaken": null, "approvedBy": null
    }
  ],
  "sarFilings": [
    {
      "id": "dffaa675f00b478a953fa52736cedac8", "caseId": "06475155d5d74d77b2a827da1cb9ff09",
      "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0", "status": "pending",
      "subjectFullName": "Chidinma Eze", "entityType": "individual",
      "accountNumberMasked": null, "totalAmount": 75000, "riskLevel": "high",
      "activityType": null, "detectionDate": null, "activityStartDate": null,
      "activityEndDate": null, "filingJurisdiction": null, "filedDate": null,
      "filedBy": "docs.demo.1790894194091@unifycomply.test",
      "suspiciousActivityCategories": ["structuring", "velocity"], "suspiciousIndicators": [],
      "narrative": {
        "openingStatement": "Single outbound transfer of 75,000 USD against a declared monthly
valu...",
        "whyItsSuspicious": "", "activityDescription": "", "investigationStepsTaken": "",
        "summaryAndRecommendation": ""
      },
      "relatedTransactionIds": ["03ee00beed0e4bc2a0c9a043ccb98da0"]
    }
  ]
}

```

Requires: permission `dashboard:access`

15.6 AI-assisted SAR draft (chat)

PARTIAL

SESSION

POST /v1/transactions/:id/sar-draft/start

POST /v1/transactions/:id/sar-draft/:conversationId/messages

```

// response - HTTP 201
{
  "status": true, "message": "SAR draft conversation ready",
  "data": {
    "id": "50b9b509b3084d6ab214e37ec16c2205", "caseId": "e69b624ea2624e8f84c650d9edd9dab8",
    "messages": [], "createdAt": "2026-10-01T22:38:27.854Z",
    "updatedAt": "2026-10-01T22:38:27.854Z"
  }
}

```

```
}  
}
```

Sending a message in an environment without an AI key — real response

```
// request – POST /v1/transactions/9e8539c64425421e98d4342efe4508fe/sar-  
draft/50b9b509b3084d6ab214e37ec16c2205/messages  
{  
  "message": "Draft the SAR narrative for this transfer to Iran and list the suspicious indicators."  
}  
// response – HTTP 500  
{"status": false, "message": "Internal server error", "data": null}
```

```
// message response when the AI provider is configured (shape from the contract)  
{ "conversation": { "id": "...", "caseId": "...", "messages": [ { "role": "user", "content": "...", {  
  "role": "assistant", "content": "...", } ] },  
  "draftNarrative": { "narrative": { "openingStatement": "...", "activityDescription": "...",  
    "whyItsSuspicious": "...",  
      "investigationStepsTaken": "...", "summaryAndRecommendation": "..."  
    },  
    "suspiciousIndicators": [ { "title": "...", "description": "...", } ] | null }
```

Never auto-file from `draftNarrative` . Offer a "Use this draft" button that copies it into the §15.4 form; a human submits. `draftNarrative` is null whenever the reply lacks a parseable structured block.

Field	Status	Why
messages	500 without AI key	provider-gateway needs <code>ANTHROPIC_API_KEY</code> . The demo environment has none, and the failure surfaces as a generic 500 rather than a clear "AI not configured" — show a retry/"drafting unavailable" state.

Requires: permission `sar:file`

16. PND watchlist & SAR reports

Session only. Reads need `dashboard:access` ; writes need `pnd:manage` / `sar:file` . These are top-level resources addressed by their own id.

16.1 PND watchlist

LIVE

SESSION

GET /v1/pnd-watchlist

Query: `status` (`active|resolved|under-review`), `riskLevel` (`low|medium|high|critical`), `page` , `limit` .

```
// response – HTTP 200  
{  
  "status": true, "message": "PND watchlist retrieved successfully",  
  "data": [  
    {  
      "id": "3080365f4d47473a869c8e3ae20a9ce7",  
      "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0",  
      "customerId": "33c479186e2741be98bce2af145959af",  
      "caseId": "06475155d5d74d77b2a827da1cb9ff09", "status": "active",  
      "listType": "internal-watchlist", "entityType": "individual", "fullName": "Chidinma Eze",  
      "nationality": "NG", "dateOfBirth": "1991-04-12", "idNumber": "A09876543",  
      "idType": "passport", "address": "12 Admiralty Way, Lekki, Lagos", "riskLevel": "high",
```

```

    "reasonForListing": "Structuring",
    "narrative": "Single outbound transfer of 75,000 USD against a declared monthly valu...",
    "activityTypeTags": ["structuring", "velocity"], "amount": 75000,
    "documentReference": "DOC-7781", "evidenceReference": "EVD-2201",
    "reportingOfficer": "Ada Okafor", "filedBy": "docs.demo.1790894194091@unifycomply.test",
    "resolvedDate": null, "resolutionType": null, "resolutionReason": null,
    "investigationOutcome": null, "resolutionActionsTaken": null, "approvedBy": null
  }
],
"summary": {"totalEntries": 1, "active": 1, "resolved": 0},
"meta": {"totalItems": 1, "itemsCount": 1, "itemsPerPage": 10, "totalPages": 1, "currentPage": 1}
}

```

Requires: `dashboard:access`

16.2 Resolve a PND restriction

LIVE

SESSION

PATCH `/v1/pnd-watchlist/:id/resolve`

```

// request - PATCH /v1/pnd-watchlist/3080365f4d47473a869c8e3ae20a9ce7/resolve
{
  "resolutionType": "investigation-complete-no-issues",
  "resolutionReason": "Customer provided a signed property purchase agreement for the 75,000 USD
transfer.",
  "investigationOutcome": "No suspicious activity confirmed.",
  "resolutionActionsTaken": "Reviewed 90-day history; verified source of funds with employer letter."
}
// response - HTTP 200
{
  "status": true, "message": "PND listing resolved successfully",
  "data": {
    "id": "3080365f4d47473a869c8e3ae20a9ce7", "tenantId": "7c9e91f81e064c6a9eada352ffeaf9c7",
    "appId": "1f62a4c6854e404385bf807eea9a7b5e", "domain": "sandbox",
    "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0",
    "customerId": "33c479186e2741be98bce2af145959af",
    "caseId": "06475155d5d74d77b2a827da1cb9ff09", "status": "resolved",
    "listType": "internal-watchlist", "entityType": "individual", "fullName": "Chidinma Eze",
    "nationality": "NG", "dateOfBirth": "1991-04-12", "idNumber": "A09876543",
    "idType": "passport", "address": "12 Admiralty Way, Lekki, Lagos", "riskLevel": "high",
    "reasonForListing": "Structuring",
    "narrative": "Single outbound transfer of 75,000 USD against a declared monthly valu...",
    "activityTypeTags": ["structuring", "velocity"], "amount": 75000,
    "documentReference": "DOC-7781", "evidenceReference": "EVD-2201",
    "reportingOfficer": "Ada Okafor", "filedBy": "docs.demo.1790894194091@unifycomply.test",
    "resolvedDate": "2026-10-01T22:38:31.112Z",
    "resolutionType": "investigation-complete-no-issues",
    "resolutionReason": "Customer provided a signed property purchase agreement for the 75,000 ...",
    "investigationOutcome": "No suspicious activity confirmed.",
    "resolutionActionsTaken": "Reviewed 90-day history; verified source of funds with employer
letter...",
    "approvedBy": "docs.demo.1790894194091@unifycomply.test",
    "createdAt": "2026-10-01T22:38:26.272Z", "updatedAt": "2026-10-01T22:38:31.112Z"
  }
}

```

`resolutionType` (required): `investigation-complete-no-issues`, `investigation-complete-issues-resolved`, `case-closed`, `false-positive`, `customer-cleared-by-authorities` — a different list from case resolution. `resolutionReason`, `investigationOutcome`, `resolutionActionsTaken` are required; `approvedBy` defaults to the signed-in user's email.

Requires: permission `pnd:manage`

16.3 SAR reports — list, read, status, export LIVE SESSION

GET /v1/sar-reports

GET /v1/sar-reports/:id

PATCH /v1/sar-reports/:id/status

GET /v1/sar-reports/:id/export

Query: `status` (`pending|under-review|submitted`), `page` , `limit` .

```
// response — HTTP 200
{
  "status": true, "message": "SAR reports retrieved successfully",
  "data": [
    {
      "id": "dffaa675f00b478a953fa52736cedac8", "caseId": "06475155d5d74d77b2a827da1cb9ff09",
      "transactionId": "03ee00beed0e4bc2a0c9a043ccb98da0", "status": "pending",
      "subjectFullName": "Chidinma Eze", "entityType": "individual", "accountNumberMasked": null,
      "totalAmount": 75000, "riskLevel": "high", "activityType": null, "detectionDate": null,
      "activityStartDate": null, "activityEndDate": null, "filingJurisdiction": null,
      "filedDate": null, "filedBy": "docs.demo.1790894194091@unifycomply.test",
      "suspiciousActivityCategories": ["structuring", "... 1 more"], "suspiciousIndicators": [],
      "narrative": {
        "openingStatement": "Single outbound transfer of 75,000 USD against a declared monthly
valu...",
        "whyItsSuspicious": "", "activityDescription": "", "investigationStepsTaken": "",
        "summaryAndRecommendation": ""
      },
      "relatedTransactionIds": ["03ee00beed0e4bc2a0c9a043ccb98da0"]
    },
    "... 1 more"
  ],
  "summary": {"totalFiles": 2, "pendingReview": 2, "submitted": 0, "underInvestigation": 0},
  "meta": {"totalItems": 2, "itemsCount": 2, "itemsPerPage": 10, "totalPages": 1, "currentPage": 1}
}
```

```
// request — PATCH /v1/sar-reports/2f3354d94b594ab49e51a04b6ed94f29/status
{"status": "under-review"}
// response — HTTP 200
{
  "status": true, "message": "SAR filing status updated successfully",
  "data": {
    "id": "2f3354d94b594ab49e51a04b6ed94f29", "status": "under-review",
    "subjectFullName": "Chidinma Eze", "riskLevel": "high",
    "updatedAt": "2026-10-01T22:38:30.305Z"
  }
}
```

```
// response — HTTP 200
Content-Type: application/pdf
Content-Disposition: attachment; filename="sar-filing-2f3354d94b594ab49e51a04b6ed94f29.pdf"
// 2750 bytes of PDF
```

Export is a real PDF, not JSON. Fetch as a blob and trigger a download using the filename from `Content-Disposition` . The document renders Basic Information, numbered Suspicious Indicators and the five-part narrative.

Requires: `dashboard:access` (reads/export), `sar:file` (status)

17. What's left — known gaps

Real behaviour observed while building this guide. None blocks integration, but each needs a deliberate UI state.

AI SAR drafting returns a bare 500 when no AI key is configured

provider-gateway needs `ANTHROPIC_API_KEY`. Without it, §15.6 messages fail with "Internal server error" instead of a clear 503. Configure the key per environment and/or map this failure to a friendly error.

Clean transactions appear in no queue

A transaction that matches no rule gets `category: null`, so TM Not-Blocked ("cleared for processing") never lists it (§14.2).

Investigation enums are not in the public option registry

Case resolution types, actions-taken, PND resolution types, entity type and investigation risk level must be hardcoded from §15–§16 until they are registered in `/v1/public/misc/options`.

Four seeded detection rules never fire

High ML Fraud Probability, Large Withdrawal Pattern, New Device High Amount and Velocity Spike need windowed/velocity evaluation that does not exist yet (§13.1).

Three Re-KYC triggers are no-ops

`high-risk-jurisdiction`, `forged-id`, `immigration-check` (§13.4).

Always-null fields

`monthlyVolume` (§14.1), `customer.maskedAccount` and `riskNarrative` (§12.3), every device-information field (§10.4), most liveness detail (§10.5), director nationality/ID and share class (§10.7), `extractedInformation` (§10.1).

Flags only come from ongoing monitoring

Onboarding runs never raise flags (§8.7); the flag workflow UI will look empty until a post-onboarding AML observation arrives.

Webhooks cover two events

Only `workflow.verified` and `workflow.failed` (engine or manual decision). Re-KYC escalations to `in-review`, transaction alerts and investigation actions are not pushed — poll the relevant endpoints.

Source of truth: core-platform controllers under `apps/core-platform/src/**/controllers`, live Swagger at `/v1/docs`. Companion docs: `docs/ui-contracts/transaction-monitoring-endpoints.md`, `docs/ui-contracts/verification-detail-tabs.md`, `docs/rekyc-tm-rules-rollout.md`.