Tables (13)

Nom	Туре	Schéma
avatar		CREATE TABLE "avatar" ("id" INTEGER, "v" INTEGER, "st" INTEGER, "vcv" INTEGER, "dds" INTEGER, "cva" BLOB, "lctk" BLOB, PRIMARY KEY("id")) WITHOUT ROWID
id	INTEGER	"id" INTEGER
V	INTEGER	"v" INTEGER
st	INTEGER	"st" INTEGER
VCV	INTEGER	"vcv" INTEGER
dds	INTEGER	"dds" INTEGER
cva	BLOB	"cva" BLOB
lctk	BLOB	"lctk" BLOB
avgrvq		CREATE TABLE "avgrvq" ("id" INTEGER, "q1" INTEGER, "q2" INTEGER, "qm1" INTEGER, "qm2" INTEGER, "v1" INTEGER, "v2" INTEGER, "vm1" INTEGER, "vm2" INTEGER, PRIMARY KEY("id")) WITHOUT ROWID
id	INTEGER	"id" INTEGER
q1	INTEGER	"q1" INTEGER
q2	INTEGER	"q2" INTEGER
qm1	INTEGER	"qm1" INTEGER
qm2	INTEGER	"qm2" INTEGER
v1	INTEGER	"v1" INTEGER
v2	INTEGER	"v2" INTEGER
vm1	INTEGER	"vm1" INTEGER
vm2	INTEGER	"vm2" INTEGER
avrsa		CREATE TABLE "avrsa" ("id" INTEGER, "clepub" BLOB, PRIMARY KEY("id")) WITHOUT ROWID
id	INTEGER	"id" INTEGER
clepub	BLOB	"clepub" BLOB
compte		CREATE TABLE "compte" ("id" INTEGER, "v" INTEGER, "dds" INTEGER, "dpbh" INTEGER, "pcbh" INTEGER, "kx" BLOB, "mack" BLOB, "mmck" BLOB, PRIMARY KEY("id")) WITHOUT ROWID
id	INTEGER	"id" INTEGER
v	INTEGER	"v" INTEGER
dds	INTEGER	"dds" INTEGER
dpbh	INTEGER	"dpbh" INTEGER
pcbh	INTEGER	"pcbh" INTEGER
kx	BLOB	"kx" BLOB
mack	BLOB	"mack" BLOB
mmck	BLOB	"mmck" BLOB
contact		CREATE TABLE "contact" ("id" INTEGER, "ic" INTEGER, "v" INTEGER, "st" INTEGER, "q1" INTEGER, "q2" INTEGER, "qm1" INTEGER, "qm2" INTEGER, "ardc" BLOB, "icbc" BLOB "datak" BLOB, PRIMARY KEY("id", "ic"))
id	INTEGER	"id" INTEGER
ic	INTEGER	"ic" INTEGER
v	INTEGER	"v" INTEGER
st	INTEGER	"st" INTEGER
q1	INTEGER	"q1" INTEGER
q2	INTEGER	"q2" INTEGER
qm1	INTEGER	"qm1" INTEGER
qm2	INTEGER	"qm2" INTEGER
ardc	BLOB	"ardc" BLOB
icbc	BI OB datak BI OB	"icbc" BLOB datak BLOB

Туре	CREATE TABLE "groupe" ("id" INTEGER, "v" INTEGER, "dds" INTEGER, "st" INTEGER, "cvg" BLOB, "mcg" BLOB, "lstmg" BLOB, PRIMARY
	"et" INTECED "Cya" BIOR "mca" BIOR "letma" BIOR DDIMADY
	KEY("id")) WITHOUT ROWID
INTEGER	"id" INTEGER
INTEGER	"v" INTEGER
INTEGER	"dds" INTEGER
INTEGER	"st" INTEGER
BLOB	"cvg" BLOB
BLOB	"mcg" BLOB
BLOB	"Istmg" BLOB
	CREATE TABLE "invitct" ("id" INTEGER, "ni" INTEGER, "dlv" INTEGER, "st" INTEGER, "datap" BLOB, "datak" BLOB, "ardc" BLOB, PRIMARY KEY ("id", "ni"))
INTEGER	"id" INTEGER
INTEGER	"ni" INTEGER
INTEGER	"dlv" INTEGER
INTEGER	"st" INTEGER
BLOB	"datap" BLOB
BLOB	"datak" BLOB
BLOB	"ardc" BLOB
	CREATE TABLE "invitgr" ("id" INTEGER, "ni" INTEGER, "v" INTEGER, "dlv" INTEGER, "st" INTEGER, "datap" BLOB, "datak" BLOB, PRIMARY KEY ("id", "ni"))
INTEGER	"id" INTEGER
INTEGER	"ni" INTEGER
INTEGER	"v" INTEGER
INTEGER	"dlv" INTEGER
INTEGER	"st" INTEGER
BLOB	"datap" BLOB
BLOB	"datak" BLOB
	CREATE TABLE "membre" ("id" INTEGER, "im" INTEGER, "v" INTEGER, "st" INTEGER, "vote" INTEGER, "dlv" INTEGER, "datag" BLOB, "ardg" BLOB, PRIMARY KEY("id", "im"))
INTEGER	"id" INTEGER
INTEGER	"im" INTEGER
INTEGER	"v" INTEGER
INTEGER	"st" INTEGER
INTEGER	"vote" INTEGER
INTEGER	"dlv" INTEGER
BLOB	"datag" BLOB
BLOB	"ardg" BLOB
	CREATE TABLE "parrain" ("pph" INTEGER, "id" INTEGER, "nc" INTEGER, "dlv" INTEGER, "st" INTEGER, "q1" INTEGER, "q2" INTEGER, "qm1" INTEGER, "qm2" INTEGER, "datak" BLOB, "datax" BLOB, "ardc" BLOB, PRIMARY KEY("pph")) WITHOUT ROWID
INTEGER	"pph" INTEGER
INTEGER	"id" INTEGER
INTEGER	"nc" INTEGER
INTEGER	"dlv" INTEGER
INTEGER	"st" INTEGER
INTEGER	"q1" INTEGER
INTEGER	"q2" INTEGER
	INTEGER BLOB BLOB INTEGER INTEGER INTEGER INTEGER BLOB BLOB INTEGER

Nom	Туре	Schéma
qm1	INTEGER	"qm1" INTEGER
qm2	INTEGER	"qm2" INTEGER
datak	BLOB	"datak" BLOB
datax	BLOB	"datax" BLOB
ardc	BLOB	"ardc" BLOB
rencontre		CREATE TABLE "rencontre" ("prh" INTEGER, "id" INTEGER, "v" INTEGER, "dlv" INTEGER, "st" INTEGER, "datak" BLOB, "nomcx" BLOB, PRIMARY KEY("prh")) WITHOUT ROWID
prh	INTEGER	"prh" INTEGER
id	INTEGER	"id" INTEGER
v	INTEGER	"v" INTEGER
dlv	INTEGER	"div" INTEGER
st	INTEGER	"st" INTEGER
datak	BLOB	"datak" BLOB
nomcx	BLOB	"nomcx" BLOB
secret		CREATE TABLE "secret" ("id" INTEGER, "ns" INTEGER, "ic" INTEGER, "v" INTEGER, "st" INTEGER, "txts" BLOB, "mcs" BLOB, "aps" BLOB, "dups" BLOB, PRIMARY KEY("id", "ns"))
id	INTEGER	"id" INTEGER
ns	INTEGER	"ns" INTEGER
ic	INTEGER	"ic" INTEGER
v	INTEGER	"v" INTEGER
st	INTEGER	"st" INTEGER
txts	BLOB	"txts" BLOB
mcs	BLOB	"mcs" BLOB
aps	BLOB	"aps" BLOB
dups	BLOB	"dups" BLOB
versions		CREATE TABLE "versions" ("id" INTEGER, "v" BLOB, PRIMARY KEY("id")) WITHOUT ROWID
id	INTEGER	"id" INTEGER
v	BLOB	"v" BLOB

Index (17)

Nom	Туре	Schéma
dds_avatar		CREATE INDEX "dds_avatar" ON "avatar" ("dds")
dds		"dds"
dds_compte		CREATE INDEX "dds_compte" ON "compte" ("dds")
dds		"dds"
dds_groupe		CREATE INDEX "dds_groupe" ON "groupe" ("dds")
dds		"dds"
dlv_invitct		CREATE INDEX "dlv_invitct" ON "invitct" ("dlv")
dlv		"dlv"
dlv_invitgr		CREATE INDEX "dlv_invitgr" ON "invitgr" ("dlv")
dlv		"dlv"
dlv_parrain		CREATE INDEX "dlv_parrain" ON "parrain" ("dlv")
dlv		"dlv"
dlv_rencontre		CREATE INDEX "dlv_rencontre" ON "rencontre" ("dlv")
dlv		"dlv"

Nom	Туре	Schéma
dpbh_compte		CREATE UNIQUE INDEX "dpbh_compte" ON "compte" ("dpbh")
dpbh		"dpbh"
id_parrain		CREATE INDEX "id_parrain" ON "parrain" ("id")
id id		"id"
id_rencontre		CREATE INDEX "id_rencontre" ON "rencontre" ("id")
id		"id"
id_v_avatar		CREATE INDEX "id_v_avatar" ON "avatar" ("id", "v")
id		"id"
v		"v"
id_v_contact		CREATE INDEX "id_v_contact" ON "contact" ("id", "v")
id		"id"
v		"v"
id_v_groupe		CREATE INDEX "id_v_groupe" ON "groupe" ("id", "v")
id		"id"
V		"v"
id_v_membre		CREATE INDEX "id_v_membre" ON "membre" ("id", "v")
id		"id"
v		"v"
id_v_secret		CREATE INDEX "id_v_secret" ON "secret" ("id", "v")
id		"id"
V		"v"
id_vcv_avatar		CREATE INDEX "id_vcv_avatar" ON "avatar" ("id", "vcv")
id		"id"
vcv		"vcv"
st_secret		CREATE INDEX "st_secret" ON "secret" ("st")
st		"st"

Vues (0) Nom Type Schéma

Déclencheurs (0) Nom Type Schéma