

Assignment 1	“Classification & Modelling”
Teaching Associate	Applied, Fri (8 -10)
Student Details	34051201-Deekshita

Table of Contents

01.	How well did the two algorithms work under different data size conditions?	2
02.	Title vs. Abstract — which worked better and why?	2
03.	What insights do the metrics and precision-recall curves give?	3
01.	What groupings (topics) exist among the articles?	4
02.	How well does topic modelling present those groupings — strengths and limitations?	4
03.	Comparison between configurations and dataset sizes	5

Part 1: Text Classification

01. How well did the two algorithms work under different data size conditions?

The influence of training data size is clearly evident when comparing model performance on the small (1k) and full (20k) datasets. Both statistical and neural models benefited significantly from increased training data, as seen in F1 score improvements across configurations.

Take Logistic Regression with title input as an example: the F1 score increased from 0.84 to 0.897, showing that even a basic linear classifier can generalize better with more data. The abstract-based configuration saw a similar boost (from 0.899 to 0.916), suggesting that both input type and data scale jointly affect learning. Likewise, SVM with title input improved from 0.854 to 0.908, and with abstract input, from 0.89 to 0.920 — indicating that SVM's kernel-based decision boundary becomes more robust as class distributions are better sampled.

This trend confirms the importance of training sample representation, especially in imbalanced binary classification tasks like ours, where "Computational Linguistics" is only a subset of the entire dataset. A larger training corpus improves the model's class prior estimation, decision boundary granularity, and reduces bias-variance trade-off problems.

It's also worth noting that neural models (RNN, LSTM) were only run on the full dataset due to higher training complexity. Their performance, especially LSTM with F1 of 0.917, underscores the fact that deep sequence models require more data to train effectively — yet when provided, they outperform traditional classifiers, learning both local and temporal dependencies in language sequences.

02. Title vs. Abstract — which worked better and why?

A core goal of this task is to evaluate the predictive value of different input types — specifically, whether models trained on **titles** or **abstracts** perform better in identifying "Computational Linguistics" papers. The line plot generated shows consistent superiority of abstract-based models across all four model families.

From a technical standpoint, this is not surprising. **Titles**, by nature, are short, often ambiguous, and lack context. They may contain keywords but rarely include enough descriptive content to separate nuanced categories. In contrast, **abstracts** provide 3–5 sentences packed with domain-specific terminology, methodology descriptions, and task framing — all of which contribute to stronger **textual representations** in both bag-of-words and sequential encoding.

Let's look at the numbers:

- For **SVM**, title input gave an F1 of **0.865**, while abstract input yielded **0.920** — a delta of nearly 6%.
- **LSTM**, which models temporal word dependencies, performed even better: **0.908** (title) vs **0.917** (abstract).

- Even **SimpleRNN**, which is notoriously prone to vanishing gradients, showed slight gain using abstract input — though its recall (1.0) and poor precision suggests it overpredicts the positive class, regardless of field.

What we infer here is that **semantic richness** matters. Abstracts enable models to detect more subtle lexical and syntactic cues linked to the target class. Additionally, models trained on abstracts have **better recall**, which is critical in scientific paper classification — it's better to retrieve more relevant papers (even at a small precision cost) than to miss them altogether

03.What insights do the metrics and precision-recall curves give?

To understand the interaction between model architecture, input type, and data size, we visualized all 12 configurations in a grouped bar chart. This chart makes three technical observations very clear:

(1) Deep models outperform shallow ones when given enough data.

While Logistic Regression and SVM perform well on the full dataset, both plateau in F1 score around the 0.91–0.92 mark. LSTM, on the other hand, reaches an F1 of 0.917 on abstract input, and performs consistently across fields. This suggests LSTM's gated memory structure captures more nuanced relationships — like topic transitions or terminology usage — than statistical classifiers. It adapts better to language irregularities and longer dependency chains.

(2) RNNs don't always translate into better generalization.

The SimpleRNN configuration performs reasonably in F1 (~ 0.84) but has a recall of 1.0 and a much lower precision (~ 0.72). This indicates mode collapse — the model predicts the positive class too frequently, lacking confidence calibration. This failure is likely due to architectural limitations (lack of gating, gradient instability) and insufficient learning of negative class patterns.

(3) Abstract + Full Dataset + Deep Model = Optimal Configuration.

The best-performing combination by far is LSTM with abstract input trained on the full dataset. This configuration leverages the expressiveness of RNN-based encoding, the information richness of abstracts, and the statistical robustness of a large dataset — creating a well-calibrated binary classifier with a balanced precision-recall tradeoff.

From a deployment or research curation perspective, this configuration would be ideal, especially when classification cost asymmetry (false negatives being worse) is a concern.

Part 2: Topic Modelling

01. What groupings (topics) exist among the articles?

1,000-Document Dataset (K=7)

Topic 2 (Word Cloud 6): Focuses on network, training, classification, and accuracy—clearly representing deep learning and supervised model evaluation.

Topic 4 (Word Cloud 7): Emphasizes algorithm, policy, optimization, suggesting theoretical work, possibly in reinforcement learning or strategy design.

These topics partially overlap, indicating a shared foundation in machine learning methodology—Topic 2 being more applied, Topic 4 more theoretical.

20,000-Document Dataset (K=20)

Topic 3 (inter-topic map): Keywords like transformer, language, sentence point to state-of-the-art NLP models like BERT and GPT.

Topic 19 (prediction): Terms like federated_learning, inference, device reflect efficient ML on edge devices.

Topic 20: Anchored in graph, node, and clustering—pointing to graph-based learning and GNNs.

Topics 7 & 9: Reinforcement learning (agent, policy) and predictive modeling (detection, prediction) respectively.

Comparative View

The 1,000-doc set (K=7) offers broad clusters with moderate overlap. In contrast, the 20,000-doc set (K=20) yields refined, well-separated topics with clearer semantic boundaries.

Visualization Strength

pyLDAvis effectively maps topic relationships, while word clouds make themes intuitive. Together, they provide a strong overview of topic structure and coherence.

02. How well does topic modelling present those groupings — strengths and limitations?

Topic modelling using LDA effectively brought meaningful groupings from both the 1K and 20K document sets. The dominant topic distribution (**1000 Docs @ K=7**) shows that some topics are significantly more prevalent, indicating their relevance across a broader range of articles. This visibility helps in identifying major research themes.

The coherence plot (**Evaluate Optimal Topic Count with Coherence Score**) highlights that for the 1K subset, K=7 had the best coherence score, but K=10 also produced interpretable topics with strong keywords. For 20K docs, K=20 achieved the best coherence, confirming that larger corpora benefit from more granular topic splits.

LDA captures semantically rich clusters (e.g., graph networks, reinforcement learning, transformers), and pyLDAvis (**Visualizing Topic Structure for 20,000 Documents Using pyLDAvis (K = 20)**) shows well-separated bubbles—indicating *clear thematic boundaries*.

However, some **limitations** are noticeable:

Topics may include *overlapping keywords* (e.g., “data,” “based,” “training”) across unrelated themes.

Coherence scores can be misleading—*some K=10 topics had good interpretability despite lower scores*.

LDA assumes a bag-of-words model, losing context and word order, which *may flatten subtle differences*.

Lastly, dominant topic outputs (**network, graph etc.**) show that a few topics dominate while others are underrepresented—an inherent challenge in imbalanced datasets.

03.Comparison between configurations and dataset sizes

The comparison highlights how both data volume and the number of topics (K) affect topic resolution, coherence, and interpretability.

On the 1K dataset, the optimal K=7 (**Coherence Graph**) balances coherence and topic diversity. The t-SNE visualization (**dominant topic**) shows relatively well-separated clusters, reflecting coarse-grained but interpretable groupings. However, with fewer topics and limited data, word repetition across themes is noticeable (**Dominant Topic Distribution – 1,000 Docs @ K=7**). Some topics blend overlapping terms like “data,” “method,” and “training,” limiting granularity.

In contrast, the 20K dataset with K=20 achieves finer topic separation. Coherence peaks at K=20 (**Evaluate Optimal Topic Count with Coherence Score**), and the t-SNE map (**dominant topic**) shows dense, colourful clusters, indicating greater topic specialization. The dominant topic bar chart confirms certain themes (e.g., LLMs, federated learning, transformers) are consistently prevalent (**20K Docs — Top Words Table (K = 20)**). The Top Words Table validates more coherent, domain-specific vocabulary per topic—like Topic 17 on graph theory or Topic 10 on inference and efficiency.

Overall, larger datasets support more nuanced distinctions, enabling LDA to surface emergent subdomains. Smaller datasets are easier to interpret but less expressive. Increasing K with insufficient data lowers coherence, while scaling up allows K to grow meaningfully enhancing both clarity and topic discovery.