

# Working with factor variables in R

*Amelia McNamara*

*June 7, 2016*

## Introduction

Factors are the data type that R uses for categorical data. For example, a gender variable might include the categories `male`, `female` and `gender non-conforming`. Storing this information as a factor is the alternative to storing it as a series of character strings.

Historically, storing categorical data as a factor variable was more efficient than storing the same data as strings, because factor variables only store the factor labels once Peng (2015). However, R has changed to use hashed versions of all character strings, so the storage issue is no longer valid Peng (2015).

Factors can be very tricky to deal with, which has led to the online `stringsAsFactors = HELLNO` movement. This refers to the default behavior of many of R's data import functions to take any variable composed as strings and automatically convert the variable to a factor. The R community has been moving away from this default behavior, with functions from Hadley Wickham's `readr` package defaulting to leaving strings as-is.

However, factor variables are important when it comes to modeling. When you pass a factor variable into `lm` or `glm`, R automatically creates dummy variables for each of the levels and picks one as a reference group. This behavior is lost if the variable is stored as a character vector.

So, factors are important. But, they can often be hard to deal with. Because of the way the group numbers are stored separately from the factor labels, it can be easy to overwrite data in such a way that the original data is lost. In this paper, we will consider the best practices for working with factor data.

To do this, we will consider data from the General Social Survey.

## Loading the data

We have several options for how to get this data. We could download it in SPSS or Stata formats and use the foreign package to read it in. The GSS download even provides an R file to do the translation for you. Here is the result of that:

```
source('../data/GSS.r')
str(GSS)
```

```
## 'data.frame': 2538 obs. of 17 variables:
## $ YEAR : int 2014 2014 2014 2014 2014 2014 2014 2014 2014 2014 2014 ...
## $ ID_ : int 1 2 3 4 5 6 7 8 9 10 ...
## $ WRKSTAT : int 1 1 4 2 5 1 9 1 8 1 ...
## $ PRESTIGE: int 0 0 0 0 0 0 0 0 0 0 ...
## $ MARITAL : int 3 1 3 1 1 1 1 1 5 1 ...
## $ CHILDS : int 0 0 1 2 3 1 2 2 4 3 ...
## $ AGE : int 53 26 59 56 74 56 63 34 37 30 ...
## $ EDUC : int 16 16 13 16 17 17 12 17 10 15 ...
## $ SEX : int 1 2 1 2 2 2 1 1 2 2 ...
## $ RACE : int 1 1 1 1 1 1 1 1 1 3 ...
## $ INCOM16 : int 2 3 2 2 4 4 2 3 3 1 ...
## $ INCOME : int 12 12 12 12 13 12 13 12 10 12 ...
## $ RINCOME : int 12 12 0 9 0 12 13 12 0 12 ...
## $ INCOME72: int 0 0 0 0 0 0 0 0 0 0 ...
```

```
## $ PARTYID : int  5 5 6 5 3 6 6 8 3 3 ...
## $ FINRELA : int  4 4 2 4 3 4 9 3 2 3 ...
## $ SEXORNT : int  3 3 3 3 3 9 0 0 3 3 ...
## - attr(*, "col.label")= chr  "Gss year for this respondent" "Respondent id number"
```

Obviously, this is less than ideal. Now, all the factor variables are encoded as integers, but their level labels have been lost. We have to look at a codebook to determine if `SEX == 1` indicates male or female. We would rather preserve the integrated level labels. In order to do this, our best option is to download the data as an Excel file and use the `readxl` package to load it.

```
library(readxl)
GSS <- read_excel("../data/GSS.xls")
str(GSS)

## Classes 'tbl_df', 'tbl' and 'data.frame':    2540 obs. of  17 variables:
## $ Gss year for this respondent      : num  2014 2014 2014 2014 2014 ...
## $ Respondent id number              : num   1  2  3  4  5  6  7  8  9 10 ...
## $ Labor force status                : chr   "Working fulltime" "Working fulltime" "Working fulltime" ...
## $ Rs occupational prestige score (1970) : num   0  0  0  0  0  0  0  0  0  0 ...
## $ Marital status                   : chr   "Divorced" "Married" "Divorced" "Married" ...
## $ Number of children                : num   0  0  1  2  3  1  2  2  4  3 ...
## $ Age of respondent                 : chr   "53.000000" "26.000000" "59.000000" "56.000000" ...
## $ Highest year of school completed  : num  16 16 13 16 17 17 12 17 10 15 ...
## $ Respondents sex                   : chr   "Male" "Female" "Male" "Female" ...
## $ Race of respondent                : chr   "White" "White" "White" "White" ...
## $ Rs family income when 16 yrs old  : chr   "Below average" "Average" "Below average" "Above average" ...
## $ Total family income               : chr   "$25000 or more" "$25000 or more" "$25000 or more" "Not applicable" ...
## $ Respondents income                : chr   "$25000 or more" "$25000 or more" "$25000 or more" "Not applicable" ...
## $ Total family income               : chr   "Not applicable" "Not applicable" "Not applicable" "Not applicable" ...
## $ Political party affiliation        : chr   "Not str republican" "Not str republican" "Not str republican" "Not str republican" ...
## $ Opinion of family income          : chr   "Above average" "Above average" "Below average" "Above average" ...
## $ Sexual orientation                 : chr   "Heterosexual or straight" "Heterosexual or straight" "Heterosexual or straight" "Heterosexual or straight" ...

GSS <- GSS[,-14]
```

That's a little better. Now we have preserved the character strings. But, the data is not yet useable in an analysis.

## Renaming the variables

One problem is that the variable names (while human readable) are full of spaces, so are hard to use. But, we can rename them. The `rename()` function in the `dplyr` package is a good way to do this.

```
library(dplyr)

GSS <- GSS %>%
  rename(LaborStatus = `Labor force status`) %>%
  rename(PolParty = `Political party affiliation`) %>%
  rename(Age = `Age of respondent`)
```

## Considering some factor variables

Once we have variable names that are easier to work with, we can begin to think about how the data should be cleaned.

```
GSS <- GSS %>%
  mutate(LaborStatus = factor(LaborStatus)) %>%
  mutate(PolParty = factor(PolParty))

levels(GSS$LaborStatus) # I wish I had a piece of dplyr code for this
```

```
## [1] "Keeping house"      "No answer"          "Other"
## [4] "Retired"            "School"             "Temp not working"
## [7] "Unempl, laid off"   "Working fulltime"   "Working parttime"
```

```
levels(GSS$PolParty)
```

```
## [1] "Don't know"          "Ind,near dem"       "Ind,near rep"
## [4] "Independent"         "No answer"          "Not str democrat"
## [7] "Not str republican"  "Other party"        "Strong democrat"
## [10] "Strong republican"
```

## Changing the labels of factors (base R)

One action you might want to take is just to change the text of one (or more) of the factor labels, so it appears more nicely formatted in a `ggplot2` plot, for example.

Here is how I do that in base R. Typically, I end up ruining something in the process of doing this, so I *always* start with a `summary` call, to check after I have done my attempt.

```
summary(GSS$LaborStatus)
```

```
##      Keeping house      No answer      Other      Retired
##           263           2           76          460
##      School Temp not working Unempl, laid off Working fulltime
##           90           40          104         1230
## Working parttime      NA's
##           273           2
```

```
levels(GSS$LaborStatus) <- c(levels(GSS$LaborStatus)[1:5], "Temporarily not working", "Unemployed, laid off", "Strong republican")
summary(GSS$LaborStatus)
```

```
##      Keeping house      No answer      Other
##           263           2           76
##      Retired      School Temporarily not working
##           460           90           40
## Unemployed, laid off Working full time Working part time
##           104          1230          273
##      NA's
##           2
```

## Changing the labels of factors (dplyr)

In `dplyr`, you can use the `recode` function to do the same thing. There are a few things to remember with `recode`. The first is that it is a vector function, which means it must be used within a `mutate` call or with a variable pulled out using `$`. The second is that you need to tell it which variable to recode, even if you are overwriting an existing variable.

```
GSS <- GSS %>%
  mutate(PolParty = recode(PolParty, `Not str republican` = "Not a strong republican"))
```

## Combining several levels into one

This is another common task. Maybe you want fewer coefficients to interpret in your model, or the process that generated the data makes a finer distinction between categories than your research. For whatever the reason, you want to group together levels that are currently separate.

How I do this in base R:

```
levels(GSS$LaborStatus) <- c("Not employed", "No answer", "Other", "Not employed", "Not employed", "Not  
summary(GSS$LaborStatus)
```

##	Not employed	No answer	Other	Employed	NA's
##	957	2	76	1503	2

## Combining many categories into one

In this data, age is provided as an integer for respondents 18-88, but then also includes the possible answer “89 or older” as well as a possible “No answer” and NA values.

```
GSS <- GSS %>%  
  mutate(Age = factor(Age))  
summary(GSS$Age)
```

##	18.000000	19.000000	20.000000	21.000000	22.000000	23.000000
##	6	25	26	24	28	30
##	24.000000	25.000000	26.000000	27.000000	28.000000	29.000000
##	31	48	47	41	31	51
##	30.000000	31.000000	32.000000	33.000000	34.000000	35.000000
##	57	49	55	47	46	40
##	36.000000	37.000000	38.000000	39.000000	40.000000	41.000000
##	40	54	47	52	46	54
##	42.000000	43.000000	44.000000	45.000000	46.000000	47.000000
##	35	54	39	41	34	43
##	48.000000	49.000000	50.000000	51.000000	52.000000	53.000000
##	32	39	54	45	37	60
##	54.000000	55.000000	56.000000	57.000000	58.000000	59.000000
##	53	52	60	43	60	47
##	60.000000	61.000000	62.000000	63.000000	64.000000	65.000000
##	46	38	44	42	38	40
##	66.000000	67.000000	68.000000	69.000000	70.000000	71.000000
##	35	41	21	23	32	28
##	72.000000	73.000000	74.000000	75.000000	76.000000	77.000000
##	20	22	25	21	24	17
##	78.000000	79.000000	80.000000	81.000000	82.000000	83.000000
##	28	26	16	14	8	11
##	84.000000	85.000000	86.000000	87.000000	88.000000	89 or older
##	13	6	9	8	11	19
##	No answer	NA's				
##	9	2				

We might want to turn this into a factor variable with two levels: 18-65, and over 65. In this case, it would be much easier to deal with a conditional statement about the numeric values, rather than writing out each of the numbers as a character vector.

But, in order to do that we need to make it numeric.

```
# GSS$Age[GSS$Age == "No answer"] <- NA # Do I really need this? Nope!
levels(GSS$Age) <- c(levels(GSS$Age)[1:71], "89", "No answer")
GSS$Age <- as.numeric(as.character(GSS$Age))
```

```
## Warning: NAs introduced by coercion
```

```
summary(GSS$Age)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.   NA's
##      18.00   34.00   49.00   49.01   62.00   89.00    11
```

Of course, we’re cheating a little bit here– if we were going to use this as a numeric variable in an analysis, we wouldn’t necessarily want to turn all the “89 or older” cases into the number “89”. But, we’re just on our way to a two-category factor, so those cases would have gone to the “65 and up” category one way or the other.

```
GSS <- GSS %>%
  mutate(Age = if_else(Age<65, "18-65", "65 and up")) %>%
  mutate(Age = factor(Age))
summary(GSS$Age)
```

```
##      18-65 65 and up      NA's
##      2011      518      11
```

## Acknowledgements

Thanks to my students Kelcie Grenier, Kat Kyuchukov, and Emily Ruppel, whose spring 2016 project in my SDS 291 class formed the inspiration for this paper.

## References

Peng, Roger D. 2015. “stringsAsFactors: An Unauthorized Biography.” <http://simplystatistics.org/2015/07/24/stringsasfactors-an-unauthorized-biography/>.