

HOTHER_ID5

Business Rules	<ul style="list-style-type: none"> • User must be the implementer of record for Handler information. • Handler ID must exist in HBASIC. • Handler ID, Activity Location, and Other ID must be unique. • Use of the HOTHER_ID5 table is optional.
English Name Description Data Type and Length Allowed Values Default Value Notes	EPA Handler ID (Primary Key) Unique RCRA identification number assigned by the implementing State or Region to each RCRA site (e.g., generators; transporters; and treatment, storage, disposal facilities). VARCHAR2 (12) Valid ID as outlined below: The ID can be a minimum of 4 characters and a maximum of 12 characters. The first two characters must be a valid state postal code which corresponds to the state in which the handler is located. Spaces are not allowed. Handlers associated with Navajo Nation should be assigned Handler IDs beginning with 'NN' regardless of where the handler is physically located.
English Name Description Data Type and Length Allowed Values Default Value Notes	Activity Location (Primary Key) Indicates the location of the agency regulating the handler. CHAR (2) State postal code Location associated with the current user ID. For a list of valid state postal codes, refer to the Column Information Report for LU_STATE.
English Name Description Data Type and Length Allowed Values Default Value	Other ID (Primary Key) Additional identification for the handler VARCHAR2 (12) Valid ID as outlined below: The ID can be a minimum of 4 characters and a maximum of 12 characters (defined as a number, letter, space, or dash; however, the ID can not contain all spaces).
English Name Description Data Type and Length Allowed Values Default Value	Relationship Type Owner Indicates the agency that defined the Relationship Type. CHAR (2)

HOTHER_ID5

English Name Relationship Type
Description The relationship between the other ID and the handler ID.
Data Type and Length CHAR (1)
Allowed Values Nationally- or implementer-defined value in LU_RELATIONSHIP.

Existing nationally-defined values:

C	Converted from Second ID
F	Site Fragment
G	ID Before Site Fragment
J	Joined Site
K	ID Before Sites Joined
M	Multiple Occupant
N	Concurrent Ownership
O	Other
P	Previous Id
S	State ID
T	Redundant State Id
Y	Became Brownfields
Z	Pre-Brownfields

Default Value

English Name Same Facility
Description Indicates if the other ID refers to the same facility as the handler ID.
Data Type and Length CHAR (1)
Allowed Values

N	No
U	Unknown
Y	Yes

Default Value

English Name User ID of Last Change
Description Records the user ID of the last person to change the data.
Data Type and Length VARCHAR2 (6)
Allowed Values Valid user ID
Default Value Current user ID

English Name Date of Last Change
Description Records the date that the data was last changed.
Data Type and Length DATE
Allowed Values Valid date/time stamp
Default Value Current date and time

HOTHER_ID5

English Name	Notes
Description	Additional information regarding other IDs for this facility.
Data Type and Length	VARCHAR2 (2000)
Allowed Values	Any value blank Not provided
Default Value	blank

* End of Report *