

CSCD 327 Lab 2

Dustin Randall

January 15, 2026

1 Create Customer table

```
1 CREATE TABLE customer (  
2     customerId int,  
3     first_name varchar(20),  
4     last_name varchar(20),  
5     city varchar(20),  
6     state char(2),  
7     check(state in ('WA', 'OR', 'ID')),  
8     primary key(customerId)  
9 );
```

Time	Status	Command	Exec	Fetch	Rows	Message	SQL/Command
13:12:26	↓ STARTED					Executing current statement for: 'EwuSqlLab' [.	
13:12:26	✓ SUCCESS	CREATE	0.094			0 OK. No rows were affected	CREATE TABLE customer (...)
13:12:26	↓ FINISHED		0.094	0	0	✓ Success: 1	

Figure 1: Creating the customer table

2 Create Orders table

```
1 CREATE TABLE orders (  
2     orderId char(5),  
3     customerId int,  
4     order_date date,  
5     order_value decimal(10,2),  
6     check(order_value > 0.0),  
7     primary key(orderId),  
8     foreign key(customerId) references customer(  
9         customerId)  
10         on update cascade  
11         on delete set null  
12 );
```

13:25:44	↓ STARTED				Executing current statement for: 'EwuSqlLab' [
13:25:45	✓ SUCCESS	CREATE	0.106		0 OK. No rows were affected
13:25:45	↓ FINISHED		0.106	0	0 ✓ Success: 1

Figure 2: Creating the orders table

3 Insert data into tables

```
1 INSERT INTO customer VALUES
2     (1001, 'Jane', 'Eyre', 'Spokane', 'WA'),
3     (1002, 'Harry', 'Potter', 'Boise', 'ID'),
4     (1003, 'James', 'Bond', 'Seattle', 'WA'),
5     (1004, 'Jo', 'March', 'Portland', 'OR'),
6     (1005, 'Sherlock', 'Holmes', 'Salem', 'OR');
```

ts	Status	Command	Exec	Fetch	Rows	Message	SQL/Command
13:29:55	STARTED					Executing current statement for: 'EwuSqlLab' [
13:29:56	SUCCESS	INSERT	0.099		5 OK		INSERT INTO customer VALUES...
13:29:56	FINISHED		0.099	0	5	Success: 1	

Figure 3: Inserting data into the customer table

```
1 INSERT INTO orders VALUES
2     ('DB101', 1001, '2026-01-01', 150.00),
3     ('DB102', 1003, '2026-01-01', 50.50),
4     ('DB103', 1001, '2026-01-03', 25.25),
5     ('DB104', 1005, '2026-01-04', 125.75),
6     ('DB105', 1004, '2026-01-07', 43.25),
7     ('DB106', 1004, '2026-01-08', 11.50),
8     ('DB107', 1001, '2026-01-12', 84.75);
```

13:37:48	STARTED					Executing current statement for: 'EwuSqlLab' [
13:37:48	SUCCESS	INSERT	0.102		7 OK		INSERT INTO orders VALUES...
13:37:48	FINISHED		0.102	0	7	Success: 1	

Figure 4: Inserting data into the orders table

4 Query inserted data

```
1 SELECT * FROM customer;
```


*		customerId	first_name	last_name	city	state
1		1001	Jane	Eyre	Spokane	WA
2		1002	Harry	Potter	Boise	ID
3		1003	James	Bond	Seattle	WA
4		1004	Jo	March	Portland	OR
5		1005	Sherlock	Holmes	Salem	OR

Figure 5: Selecting all data from the customer table

```
1 SELECT * FROM orders;
```


*		orderId	customerId	order_date	order_value
1		DB101	1001	2026-01-01	150.00
2		DB102	1003	2026-01-01	50.50
3		DB103	1001	2026-01-03	25.25
4		DB104	1005	2026-01-04	125.75
5		DB105	1004	2026-01-07	43.25
6		DB106	1004	2026-01-08	11.50
7		DB107	1001	2026-01-12	84.75

Figure 6: Selecting all data from the orders table

5 Attempt insert

The attempt fails because of a foreign key constraint violation (1010 is not a valid customer id).

```
1 INSERT INTO orders VALUES ('DB108', 1010, '2026-01-15', 50.00);
```




Figure 7: Attempting to insert invalid foreign key into orders table

6 Delete Sherlock from customer table

```
1 DELETE from customer WHERE first_name = 'Sherlock';
```

	State	Command	Time	Rows	Message
13:44:39	STARTED				Executing current statement for: 'EwuSqlLab' [
13:44:39	SUCCESS	DELETE	0.093	1	OK
13:44:40	FINISHED		0.093	0	1 ✓ Success: 1

Figure 8: Deleting Sherlock Holmes from customer table and checking orders table

```
1 SELECT * FROM customer;
```


*		customerId	first_name	last_name	city	state
1		1001	Jane	Eyre	Spokane	WA
2		1002	Harry	Potter	Boise	ID
3		1003	James	Bond	Seattle	WA
4		1004	Jo	March	Portland	OR

Figure 9: Customer table after deleting Sherlock Holmes

```
1 SELECT * FROM orders;
```


*	 orderId	customerId	o
1	DB101	1001	2
2	DB102	1003	2
3	DB103	1001	2
4	DB104	(null)	2
5	DB105	1004	2
6	DB106	1004	2
7	DB107	1001	2

Figure 10: Orders table with null customerId after deleting Sherlock Holmes


7 update Harry Potter's customerId to 1006

```
1 UPDATE customer SET customerId = 1006 WHERE first_name  
   = 'Harry' AND last_name = 'Potter';
```

	Status	Command	Exec	Fetch	Rows	Message	SQL/Command
13:47:16	↓ STARTED					Executing current statement for: 'EwuSqlLab' [
13:47:16	✓ SUCCESS	UPDATE	0.112		1	OK	UPDATE customer SET customerId = 1006 WHERE first_na
13:47:16	↓ FINISHED		0.112	0	1	✓ Success: 1	

Figure 11: Updating Harry Potter's customerId to 1006

```
1 SELECT customerId FROM customer WHERE first_name = '
   Harry' AND last_name = 'Potter';
```



customerId	
1006	

Figure 12: Selecting Harry Potter's updated customerId

```
1 SELECT * from orders WHERE customerId = 1006;
```

13:48:58	⬇ STARTED	Executing current statement for: 'EwuSqlL			
13:48:59	✓ SUCCESS	SELECT	0.067	0.022	0 Empty result set fetched
13:48:59	⬇ FINISHED		0.067	0.022	0 ✓ Success: 1

Figure 13: Orders table showing Harry Potter has no orders

8 Find all customers in WA but not in Spokane

```
1 SELECT first_name, last_name from customer WHERE state  
   = 'WA' AND city <> 'Spokane';
```

*	first_name	last_name
1	James	Bond

Figure 14: Selecting all customers in WA but not in Spokane

9 Find orders between 25 and 100 inclusive, ordered by customerId

```
1 SELECT customerId, order_date FROM orders WHERE  
2    order_value BETWEEN 25 AND 100  
3    ORDER BY customerId;
```

*	customerId	order_date
1	1001	2026-01-03
2	1001	2026-01-12
3	1003	2026-01-01
4	1004	2026-01-07

Figure 15: Selecting orders with value between 25 and 100 inclusive, ordered by customerId

10 Find distinct customerIds with orders on or after 2026-01-03

```
1 SELECT DISTINCT customerId FROM orders
2   WHERE order_date >= '2026-01-03';
```

*	customerId
1	1001
2	(null)
3	1004

Figure 16: Selecting distinct customerIds with orders on or after 2026-01-03