

Bagging


CSC 461: Machine Learning

Fall 2021


Prof. Marco Alvarez
University of Rhode Island

Feature space

Alternative view:



Jure Leskovec, Stanford CS246: Mining Massive Datasets, <http://cs246.stanford.edu>



Comprehensive Decision Tree Models in Bioinformatics
Gregor Sligic, Simon Kocbek, Igor Pernek, Peter Kokol
Published: March 30, 2012 • <https://doi.org/10.1371/journal.pone.0033812>

Complicated decision boundaries ==> Overfitting

Trees problems


- Overfitting
- Unstable
 - ✓ slight changes of the data ==> different tree structures

Bias-Variance decomposition


Expected loss

- ✓ **bias**: how wrong the expected prediction is
- ✓ **variance**: the amount of variability in the predictions
- ✓ **Bayes error**: the inherent unpredictability of the targets (e.g. noise)

$$\mathbb{E}[(y - t)^2] = \underbrace{(y^* - \mathbb{E}[y])^2}_{\text{bias}} + \underbrace{\text{Var}(y)}_{\text{variance}} + \underbrace{\text{Var}(t)}_{\text{Bayes error}}$$



The Elements of Statistical Learning, Hastie, Tibshirani, Friedman, 2nd Ed.



<http://scott.fortmann-roe.com/docs/BiasVariance.html>

Ensembles

- Set of hypotheses (e.g. classifiers)
 - ✓ individual predictions are combined into a final prediction, e.g. majority vote
- **Bagging (bootstrap aggregation)**
 - ✓ train models independently (**in parallel**) on random subsets of data
 - ✓ variance-reduction technique
- **Boosting**
 - ✓ train **weak** models **sequentially**, each focusing on examples misclassified by previous models
 - ✓ bias-reduction technique

Netflix prize



Kaggle competitions

Active Competitions

Competition	Prize	Duration
NFL Health & Safety - Helmet Assignment	\$100,000	15 days to go
NFL Big Data Bowl 2022	\$100,000	3 months to go
Sartorius - Cell Instance Segmentation	\$75,000	2 months to go
2021 Kaggle Machine Learning & Data Science...	\$30,000	a month to go
PetFinder.my - Pawpularity Contest	\$25,000	3 months to go
chai - Hindi and Tamil Question Answering	\$10,000	a month to go
Lux AI	\$10,000	2 months to go
Google Brain - Ventilator Pressure Prediction	\$7,500	16 days to go

Bootstrapping

- Assuming a dataset \mathcal{D} with n examples
- Generate m datasets
 - sample n instances from \mathcal{D} **with replacement** (bootstrap samples)
 - some elements will appear multiple times
 - some elements may not appear at all

probability of each element not being selected: $\left(1 - \frac{1}{n}\right)^n$


36.8% for large n

Exercise

- Write a script that generates a random sequence of N elements and creates M bootstrap samples from that sequence
 - can use `random.randint` and `random.choices`


Random Forests

Bootstrapping



https://www.bpesquet.fr/mlhandbook/algorithms/decision_trees_and_random_forests.html

Inference



https://www.bpesquet.fr/mlhandbook/algorithms/decision_trees_and_random_forests.html

Random Forest

- ▶ Ensemble
 - ✓ create m trees trained from bootstrap “samples”
 - ✓ majority vote for prediction
- ▶ Benefits
 - ✓ reduces overfitting — low variance, however it has little effect on bias
- ▶ Combines **example diversity** with **feature diversity**

Algorithm

Algorithm $\text{RandomForest}(D, T, d)$ – train an ensemble of tree models from bootstrap samples and random subspaces.

Input : data set D ; ensemble size T ; subspace dimension d .

Output : ensemble of tree models whose predictions are to be combined by voting or averaging.

for $t = 1$ to T **do**


 build a bootstrap sample D_t from D by sampling $|D|$ data points with replacement;
 select d features at random and reduce dimensionality of D_t accordingly;
 train a tree model M_t on D_t without pruning;

end


return $\{M_t | 1 \leq t \leq T\}$

from: Machine Learning Making Sense of Data, <http://people.cs.bris.ac.uk/~flach/mlbook/>


Regression example



1 tree




10 trees



average

Comparing classifiers



Issues

- ▶ Fitting ensembles can be computationally intensive
 - ✓ can use *max_depth* to alleviate
- ▶ Naively averaging or taking a majority both may not be optimal
 - ✓ stay tuned: **boosting**