

The `vutinfth` class*

Thomas Auzinger
`thomas@auzinger.name`

July 13, 2022

Abstract

This class provides a $\text{\LaTeX 2}_{\epsilon}$ template for theses at the Faculty of Informatics at the TU Wien. In the current version, bachelor and master theses as well as dissertations are supported in both English and German.

*This document corresponds to `vutinfth v1.7`, dated 2017/06/19.

Contents

1	Introduction	3
2	Known Issues	3
3	Usage for Document Authors	3
3.1	Data	3
3.1.1	Textual Data	3
3.1.2	Persons	4
3.1.3	Dates	4
3.1.4	List Data	5
3.1.5	Polylingual Data	6
3.2	Layout	6
4	Usage for Class Writers	7
4.1	Data	7
4.2	Layout	8
5	Implementation	9
5.1	Initialization	9
5.1.1	Class Options	9
5.1.2	Loaded Class and Packages	9
5.1.3	Low-Level Functionality	10
5.1.4	Fonts	10
5.2	Data	11
5.2.1	Dates	11
5.2.2	Textual Data	11
5.2.3	Persons	11
5.2.4	Polylingual Text	13
5.2.5	Thesis Types	16
5.2.6	Declarations	20
5.3	Layout	23
5.3.1	Setup	23
5.3.2	Title Page	24
5.3.3	Front Matter Material	30
5.3.4	Page Style	33
6	Change History	33
	Index	34

1 Introduction

This class provides a L^AT_EX 2_ε template for all theses at the Faculty of Informations at the TU Wien. Further information on the document class and accompanying support can be found at <https://gitlab.cg.tuwien.ac.at/auzinger/vutinfth>. Further guidelines may apply to both the format and structure of certain theses. These can be found at <http://www.informatik.tuwien.ac.at/dekanat>. Thesis authors are advised to consult Section 3 for a documentation of all relevant commands. Information for class developers is provided in Section 4.

2 Known Issues

This class is incompatible with the `minitoc` package as of version 60, due to the incompatibility of the underlying `memoir` class. Use the `titletoc` package as a replacement.

3 Usage for Document Authors

This section contains relevant information for authors of theses that are based on the `vutinfth` document class.

3.1 Data

To allow the generation of the title pages, signature fields, statements, etc., several pieces of information have to be set by the author using the commands in the subsequent sections. We discern several categories of data: *(i)* textual data, which is given by a simple text string, *(ii)* persons, which are defined by their names, optional titles, and their gender, as well as, *(iii)* dates and *(iv)* list data, which allow the selection of one argument from a list of permissible arguments. Several commands have polylingual capabilities and support different languages (see Section 3.1.5). A superscript P, i.e., `\commandP`, indicates such a command.

3.1.1 Textual Data

<code>\setaddress</code>	All commands in this section are called with one mandatory argument, e.g., as <code>\command{<text>}</code> , where <code><text></code> defines the content of the commands. For polylingual commands, given by <code>\command^P</code> , one <code><text></code> argument has to be supplied for each language (see Section 3.1.5). The following textual data can be set:
<code>\setregnumber</code>	
<code>\settitle</code>	
<code>\setsubtitle</code>	
<code>\setcurriculum</code>	
<code>\setfirstreviewerdata</code>	
<code>\setsecondreviewerdata</code>	

Command	Role	Type	Optional
<code>\setaddress</code>	Address of the author	All	No
<code>\setregnumber</code>	Registration number of the author	All	No
<code>\settitle^P</code>	Title of the thesis	All	No
<code>\setsubtitle^P</code>	Subtitle of the thesis	All	Yes
<code>\setcurriculum^P</code>	Name of the curriculum	B, M	No
Types: Bachelor (B), Master (M), Doctoral (D), PhD School (P), All (All)			
Command	Role	Type	Optional
<code>\setfirstreviewerdata</code>	Affiliation and country of first reviewer	P	No
<code>\setsecondreviewerdata</code>	Affiliation and country of second reviewer	P	No
Types: Bachelor (B), Master (M), Doctoral (D), PhD School (P), All (All)			

3.1.2 Persons

`\setauthor` All commands in this section are called with four mandatory arguments, e.g., as
`\setadvisor` `\command{\langle pretitle \rangle}{\langle name \rangle}{\langle posttitle \rangle}{\langle gender \rangle}`, where $\langle name \rangle$ defines both
`\setsecondadvisor` the first name(s) and family name(s) of the person. A title that is placed before
`\setfirstassistant` the name is assigned with $\langle pretitle \rangle$, while a trailing title is given with $\langle posttitle \rangle$.
`\setsecondassistant` Both $\langle pretitle \rangle$ and $\langle posttitle \rangle$ can be left empty, to indicate an absence of such
`\setthirdassistant` a title; the insertion of appropriate glue between titles and names is handled by
`\setfirstreviewer` the `vutinfth` class. The declaration of the persons gender via $\langle gender \rangle$ allows
`\setsecondreviewer` the use of gender-specific terms in languages that support them, e.g., German.
The possible options for $\langle gender \rangle$ are `male` and `female` (see Section 3.1.4). The
following persons can be set:

Command	Role	Type	Optional
<code>\setauthor</code>	Author of the thesis	All	No
<code>\setadvisor</code>	Main advisor of the thesis	All	No
<code>\setsecondadvisor</code>	Second advisor of the thesis	D, P	Yes
<code>\setfirstassistant</code>	First advising assistant	B, M	Yes
<code>\setsecondassistant</code>	Second advising assistant	B, M	Yes
<code>\setthirdassistant</code>	Third advising assistant	B, M	Yes
<code>\setfirstreviewer</code>	First thesis reviewer	D, P	No
<code>\setsecondreviewer</code>	Second thesis reviewer	D, P	No
Types: Bachelor (B), Master (M), Doctoral (D), PhD School (P), All (All)			

3.1.3 Dates

`\setdate` All commands in this section are called with three mandatory arguments, e.g., as
`\command{\langle day \rangle}{\langle month \rangle}{\langle year \rangle}`. The syntax is identical to the last three

arguments of the `\newdate` command of the `datetime` package, from which these commands derive. The following dates can be set:

Command	Role	Type	Optional
<code>\setdate</code>	Signing date	All	No
Types: Bachelor (B), Master (M), Doctoral (D), PhD School (P), All (All)			

3.1.4 List Data

All commands in this section are called with at least one mandatory argument called $\langle list \rangle$, e.g., as `\command...{\langle list \rangle}...`, where $\langle list \rangle$ is given one element from a set of possible arguments.

`\setauthor` When setting a person, the person's gender is specified with a list argument (see
`\setadvisor` Section 3.1.2):
...

Command	Options	Description
<code>\command{\.}{\.}{\.}{\langle list \rangle}</code>	male	Specifies a male person.
	female	Specifies a female person.

`\setthesis` The thesis type is selected from one of the fundamental types:

Command	Options	Description
<code>\setthesis{\langle list \rangle}</code>	bachelor	Specifies a bachelor's thesis.
	master	Specifies a master's thesis.
	doctor	Specifies a dissertation.
	phd-school	Specifies a dissertation at the Vienna PhD school of Informatics.

`\setmasterdegree` With a master's curriculum, different degrees can be achieved and the appropriate type has to be chosen based on the curriculum that the author is enrolled in:

Command	Options	Description
<code>\setmasterdegree{\langle list \rangle}</code>	dipl.	Specifies the degree 'Diplom-Ingenieur(in)'.
	master	Specifies the degree 'Master of Science'.
	rer.nat.	Specifies the degree 'Magist(er/ra) der Naturwissenschaften'.
	rer.soc.oec.	Specifies the degree 'Magist(er/ra) der Sozial- und Wirtschaftswissenschaften'.

`\setdoctordegree` With a doctorate study, different degrees can be achieved and the appropriate type has to be chosen based on the program that the author is enrolled in:

Command	Options	Description
<code>\setdoctordegree{⟨list⟩}</code>	<code>techn.</code>	Specifies the degree ‘Doktor(in) der Technischen Wissenschaften’.
	<code>rer.nat.</code>	Specifies the degree ‘Doktor(in) der Naturwissenschaften’.
	<code>rer.soc.oec.</code>	Specifies the degree ‘Doktor(in) der Sozial- und Wirtschaftswissenschaften’.

3.1.5 Polylingual Data

`\setcurriculum` Used as `\setcurriculum{⟨english⟩}{⟨german⟩}`, it sets the name of the curriculum that the student is enrolled in. The name can be given in English, with `⟨english⟩`, and in German, with `⟨german⟩`. Note that the curriculum name does not need to be supplied for all thesis types, since, e.g., doctoral studies do not have a curriculum per se. If a title page of one of the languages is not used, the corresponding argument can be left empty.

`\settitle` Used as `\settitle{⟨english⟩}{⟨german⟩}`, it sets the title of the thesis. The title can be given both in an English version, with `⟨english⟩`, and in a German version, with `⟨german⟩`. For title pages in a given language, the corresponding title will be used. Unused languages can be supplied as empty brackets and it is possible to use the English or German title for both language versions.

`\setsubtitle` Used as `\setsubtitle{⟨english⟩}{⟨german⟩}`, it sets the subtitle of the thesis. The same specifications as for `\settitle` apply.

`\addtitlepage` The titlepage can be generated in the following languages (see Section 3.2):

Command	Options	Description
<code>\addtitlepage{⟨list⟩}</code>	<code>english</code>	Generates an English title page.
	<code>naustrian</code>	Generates a German title page.

Note that a non-English title page is not available for a dissertation at the Vienna PhD School of Informatics.

3.2 Layout

Most of the data that is supplied with the commands of the previous sections is used to generate the front matter of the thesis. It consists of obligatory items such as the title page(s) and the statement of originality as well as optional items such as the acknowledgements or the abstract in different languages. In the remainder of this section, the available items of the front matter are given.

`\addtitlepage` Used as `\addtitlepage{⟨lang⟩}`, where `⟨lang⟩` is the name of a language as given

in the `babel` package (see Section 3.1.4). The necessary pieces of information have to be set beforehand (as described in Section 3.1). This command is usually used directly after `\begin{document}\frontmatter`.

<code>\addstatementpage</code>	Used as <code>\addstatementpage</code> , it generates a page with the statement of originality.
<code>acknowledgements</code> <code>acknowledgements*</code>	Used as <code>\begin{acknowledgements}\text\end{acknowledgements}</code> , this environment generates a chapter with the English acknowledgements. Use the starred version, i.e., <code>acknowledgements*</code> , to remove the table of content entry of this environment.
<code>danksagung</code> <code>danksagung*</code>	Used as <code>\begin{danksagung}\text\end{danksagung}</code> , this environment generates a chapter with the German acknowledgements. Use the starred version, i.e., <code>danksagung*</code> , to remove the table of content entry of this environment.
<code>abstract</code> <code>abstract*</code>	Used as <code>\begin{abstract}\text\end{abstract}</code> , this environment generates a chapter with the English abstract. Use the starred version, i.e., <code>abstract*</code> , to remove the table of content entry of this environment.
<code>kurzfassung</code> <code>kurzfassung*</code>	Used as <code>\begin{kurzfassung}\text\end{kurzfassung}</code> , this environment generates a chapter with the German abstract. Use the starred version, i.e., <code>kurzfassung*</code> , to remove the table of content entry of this environment.

4 Usage for Class Writers

To accomodate shifting requirements, the `vutinfth` class provides various convenience functions that allow the modification and extension of its functionality.

4.1 Data

To compose several parts of the thesis layout, input from the thesis author is required. For the `vutinfth` class, this is realized by the commands provided in Section 3.1. Additional data can be defined with the the commands in the remainder of this section.

<code>\CreateData</code>	Used as <code>\CreateData{<name>}</code> , it generates a command <code>\set{<name>}</code> . Used as <code>\set{<name>}{<string>}</code> , the newly created command assigns the value <code><string></code> to the internal variable <code>\vutinfth@data@<name></code> . The variable is initialized with an error value to alert the user of the fact that <code><string></code> was not supplied via the <code>\set{<name>}</code> command. Furthermore, a command <code>\vutinfth@data@<name>@def</code> is created, to increase source code readability when verifying the existence of a specific data item. See Section 5.2.6 for examples.
<code>\CreatePerson</code>	Used as <code>\CreatePerson{<name>}</code> , it generates a command <code>\set{<name>}</code> . Used as <code>\set{<name>}{<pretile>}{<personname>}{<posttile>}{<gender>}</code> , the newly created command assigns the supplied values to the corresponding internal variables <code>\vutinfth@person@<name>@...</code> as given in the table below.

Argument	Internal Variable
	<code>\vutinfth@person@⟨name⟩@def</code>
<code>⟨prettitle⟩</code>	<code>\vutinfth@person@⟨name⟩@prettitle</code>
<code>⟨personname⟩</code>	<code>\vutinfth@person@⟨name⟩@name</code>
<code>⟨posttitle⟩</code>	<code>\vutinfth@person@⟨name⟩@posttitle</code>
<code>⟨gender⟩</code>	<code>\vutinfth@person@⟨name⟩@gender</code>

The command `\vutinfth@person@⟨name⟩@def` is created to increase source code readability when verifying the existence of a specific person. Furthermore, the command `\vutinfth@person@⟨name⟩@fullname` returns the person's name together with existing titles and correct whitespace in between. The person's gender is either `\vutinfth@person@male` or `\vutinfth@person@female`, depending on the input. See Section 5.2.6 for examples.

`\AddLanguage` Used as `\AddLanguage{⟨lang⟩}`, it enables the language `⟨lang⟩` to be used by polylingual expressions. `⟨lang⟩` has to be chosen from the languages of the `babel` package that is used by this class. Currently, `vutinfth` uses two languages, i.e., `english` for English expressions and `naustrian` for German expressions.

`\CreatePolylingual` Used as `\CreatePolylingual[⟨expressions⟩]{⟨name⟩}`, it generates a command `\vutinfth@polylingual@⟨name⟩` that selects the appropriate expression based on the current language at the time of use. The argument `⟨expressions⟩` is a list of elements of the form `⟨expri⟩`, where each element defines the expression for a valid language, e.g., `⟨langi⟩=⟨texti⟩`. `⟨langi⟩` has to be chosen from the languages that were defined via `\AddLanguage`. As a convention, text that needs to start with an uppercase letter is assigned to a name that starts with an uppercase letter. The same holds for uppercase words, e.g.,
`\CreatePolylingual[english=advisor,naustrian=Betreuer]{advisor}`
`\CreatePolylingual[english=Advisor,naustrian=Betreuer]{Advisor}`
`\CreatePolylingual[english=ADVISOR,naustrian=BETREUER]{ADVISOR}`.
See Section 5.2.6 for examples.

4.2 Layout

Several key elements in the layout of the frontmatter are encapsulated to allow a convenient extension of this functionality.

`\SignatureFields` Used as `\SignatureFields[⟨mode⟩]{⟨center⟩}{⟨right⟩}`, it creates a place and date description and/or one or two signature fields. `⟨mode⟩` can be set to `y`, which adds an entry with date and place to the left, to `h`, which adds the corresponding whitespace, or to `n`, which adds nothing. If text is supplied to `⟨center⟩`, it is added below a rule, right to the possible date and place entry. If text is supplied to `⟨right⟩`, it is added below a rule, right to the possible signature field created by `⟨center⟩`. This command ensures a uniform width and positioning of the signature fields on both the title pages and the statement of originality.

`\SignatureBlock` Used as `\SignatureBlock`, it generates the signature fields for both author and

advisor.

<code>\ReviewerBlock</code>	Used as <code>\ReviewerBlock</code> , it generates the signature fields for both reviewers.
<code>\AdvisorBlock</code>	Used as <code>\AdvisorBlock</code> , it generates the name fields for both the advisor and the potential assistants.
<code>\AddTitlePage</code>	Used as <code>\AddTitlePage</code> , it generates a title page in the current language. This command contains the placement of the header graphics, the footer, the appropriate blocks, etc.
<code>\AddStatementPage</code>	Used as <code>\AddStatementPage</code> , it generates a chapter with the statement of originality together with the author's signature field.
<code>SFFont</code>	Alters the sans serif font inside the environment. Called with one mandatory argument as <code>\begin{SFFont}{\langle family \rangle}</code> , which determines the sans serif font family that should be used, e.g., <code>phv</code> for Helvetica.

5 Implementation

5.1 Initialization

5.1.1 Class Options

Pass the options to the underlying memoir class.

```
1 \DeclareOption*{%
2   \PassOptionsToClass{\CurrentOption}{memoir}%
3 }%
4 \ProcessOptions\relax
```

5.1.2 Loaded Class and Packages

The `vutinfth` class is based on the `memoir` class.

```
5 \LoadClass[a4paper,11pt]{memoir}%
6 \chapterstyle{veelo}%
```

The following packages are required for the functionality and style of the document class.

```
7 \RequirePackage[scaled]{helvet}%
8 \RequirePackage{lmodern}%
9 \RequirePackage{courier}%
10 \RequirePackage[T1]{fontenc}%
11 \RequirePackage[english,naustrian]{babel}%
12 \RequirePackage[nodayofweek]{datetime}%
13 \RequirePackage{geometry}%
14 \RequirePackage{calc}%
15 \RequirePackage{etoolbox}%
```

```

16 \RequirePackage{graphicx}%
17 \graphicspath{{graphics/}}%

```

5.1.3 Low-Level Functionality

This section provides low-level functionality for macro definitions and macro expansions.

`\@namexdef` Globally defines a control sequence with an expanded argument.

```

18 \newcommand{\@namexdef}[1]{\expandafter\xdef\csname#1\endcsname}%

```

`\ifstrequal` A variant of `\ifstrequal` that fully expands the first two arguments.

```

19 \newcommand{\ifstrequal}[4]{%
20   \begingroup
21     \edef\vutinfth@tempa{{#1}}%
22     \edef\vutinfth@tempb{{#2}}%
23     \expandafter\expandafter\expandafter\ifstrequal
24       \expandafter\vutinfth@tempa\vutinfth@tempb{#3}{#4}%
25   \endgroup
26 }%

```

5.1.4 Fonts

`\vutinfth@HUGE` Initializes the font sizes.

```

\vutinfth@huge
\vutinfth@LARGE
\vutinfth@Large
\vutinfth@large
\vutinfth@normalsize
27 \newcommand{\vutinfth@HUGE}{\fontsize{30}{34}\selectfont}%
28 \newcommand{\vutinfth@huge}{\fontsize{20}{23}\selectfont}%
29 \newcommand{\vutinfth@LARGE}{\fontsize{17}{22}\selectfont}%
30 \newcommand{\vutinfth@Large}{\fontsize{14}{18}\selectfont}%
31 \newcommand{\vutinfth@large}{\fontsize{12}{14.5}\selectfont}%
32 \newcommand{\vutinfth@normalsize}{\fontsize{11}{13.6}\selectfont}%

```

`SFFont` Selects the given font family as sans serif font.

```

33 \newenvironment{SFFont}[1]{%

```

Stores the current sans serif font in `\vutinfth@f@family@tmp` and changes to the given sans serif font.

```

34   \begingroup
35     \sfdefault
36     \global\let\vutinfth@f@family@tmp=\f@family
37   \endgroup
38   \renewcommand{\sfdefault}{#1}%

```

In case the outer scope is already sans serif, the new font has to be activated.

```

39   \ifdefstrequal{\f@family}{\vutinfth@f@family@tmp}{\sfdefault}{}%
40 }%

```

The scope of the font change is the environment itself. Thus, no cleanup code is required in case the outer scope was already sans serif.

```
41 \renewcommand{\sfdefault}{\vutinfth@f@family@tmp}%
42 }%
```

5.2 Data

5.2.1 Dates

`\setdate` Creates the internal storage for the signing date.

```
43 \newcommand{\setdate}[3]{%
44 \newdate{\vutinfth@date@signing}{#1}{#2}{#3}%
45 }%
```

5.2.2 Textual Data

`\vutinfth@def@data` Creates the internal storage for simple data entries.

```
46 \newcommand{\vutinfth@def@data}[2]{%
47 \@namedef{\vutinfth@data@#1@def}{}%
48 \@namedef{\vutinfth@data@#1}{#2}%
49 }%
```

`\vutinfth@def@data@invalid` Initializes the internal storage with error messages.

```
50 \newcommand{\vutinfth@def@data@invalid}[2]{%
51 \@namedef{\vutinfth@data@#1@error}{%
52 \ClassError{\vutinfth}{No #2 issued}{Set #1 with #2.}%
53 }%
54 \@namedef{\vutinfth@data@#1}{\@nameuse{\vutinfth@data@#1@error}}%
55 }%
```

`\CreateData` Issues the construction of a setter function for a data entry given by `\setdate`.

```
56 \newcommand{\CreateData}[1]{%
57 \@namedef{set#1}##1{%
58 \vutinfth@def@data{#1}{##1}%
59 }%
60 \vutinfth@def@data@invalid{#1}{\string\set#1}%
61 }%
```

5.2.3 Persons

`\vutinfth@person@male` Two genders are differentiated for each person: male and female.
`\vutinfth@person@female`

```
62 \newcommand{\vutinfth@person@male}{male}%
63 \newcommand{\vutinfth@person@female}{female}%
```

`\ifmale` Convenience macros to determine the gender of a person.

`\iffemale`

```

64 \newcommand{\ifmale}[2]{%
65   \ifcsstring{vutinfth@person@#1@gender}{\vutinfth@person@male}{#2}{}%
66 }%
67 \newcommand{\iffemale}[2]{%
68   \ifcsstring{vutinfth@person@#1@gender}{\vutinfth@person@female}{#2}{}%
69 }%
```

`\vutinfth@def@person` Creates the internal storage for a person's name, titles and gender.

```

70 \newcommand{\vutinfth@def@person}[5]{%
71   \@namedef{vutinfth@person@#1@def}{}%
72   \@namedef{vutinfth@person@#1@prettitle}{#2}%
73   \@namedef{vutinfth@person@#1@name}{#3}%
74   \@namedef{vutinfth@person@#1@posttitle}{#4}%
75   \ifdefstring{\vutinfth@person@male}{#5}{%
76     \@namedef{vutinfth@person@#1@gender}{\vutinfth@person@male}%
77   }{%
78     \ifdefstring{\vutinfth@person@female}{#5}{%
79       \@namedef{vutinfth@person@#1@gender}{\vutinfth@person@female}%
80     }{%

```

For the full name, additional spaces have to be inserted depending on the presence of pre- or posttitles.

```

81   \ifstrempy{#3}{%
82     \ifstrempy{#2}{%
83       \@namedef{vutinfth@person@#1@fullname}{#4}%
84     }{%
85       \ifstrempy{#4}{%
86         \@namedef{vutinfth@person@#1@fullname}{#2}%
87       }{%
88         \@namedef{vutinfth@person@#1@fullname}{#2 #4}%
89       }%
90     }%
91   }{%
92     \ifstrempy{#2}{%
93       \ifstrempy{#4}{%
94         \@namedef{vutinfth@person@#1@fullname}{#3}%
95       }{%
96         \@namedef{vutinfth@person@#1@fullname}{#3, #4}%
97       }%
98     }{%
99       \ifstrempy{#4}{%
100        \@namedef{vutinfth@person@#1@fullname}{#2 #3}%
101      }{%
102        \@namedef{vutinfth@person@#1@fullname}{#2 #3, #4}%
103      }%
104    }%

```

```

105 }%
106 }%

```

`\vutinfth@def@person@invalid` Initializes the internal storage with error messages.

```

107 \newcommand{\vutinfth@def@person@invalid}[2]{%
108   \@namedef{vutinfth@person@#1@error}{%
109     \ClassError{vutinfth}{No #2 issued}{Set #1 with #2.}%
110   }%
111   \@namedef{vutinfth@person@#1@name}{%
112     \@nameuse{vutinfth@person@#1@error}}%
113   \@namedef{vutinfth@person@#1@prettitle}{%
114     \@nameuse{vutinfth@person@#1@error}}%
115   \@namedef{vutinfth@person@#1@posttitle}{%
116     \@nameuse{vutinfth@person@#1@error}}%
117   \@namedef{vutinfth@person@#1@gender}{%
118     \@nameuse{vutinfth@person@#1@error}}%
119   \@namedef{vutinfth@person@#1@fullname}{%
120     \@nameuse{vutinfth@person@#1@error}}%
121 }%

```

`\CreatePerson` Issues the construction of a setter function for a person given by `\setperson`.

```

122 \newcommand{\CreatePerson}[1]{%
123   \@namedef{set#1}##1##2##3##4{%
124     \vutinfth@def@person{#1}{##1}{##2}{##3}{##4}%
125   }%
126   \vutinfth@def@person@invalid{#1}{\string\set#1}%
127 }%

```

5.2.4 Polylingual Text

This class supports bi- and polylingual text via a key-value mechanism. See the `\CreatePolylingual` command further down for the actual definition of polylingual expressions.

`\AddLanguage` Constructs the temporary variables and the permanent storage for polylingual text in the given language.

```

128 \newcommand{\AddLanguage}[1]{%

```

First, the key for the current language, given by its name in the `babel` package, is created. Keys of the `keyval` package are internally stored as `KV@family@keyname`, where we use `vutinfth` as family name and the argument as key name. The value that is given to this key as part of a function argument is assigned to a temporary storage.

```

129   \@namedef{KV@vutinfth@#1}##1{%
130     \@namedef{vutinfth@current@#1}{##1}%
131   }%

```

The key value is initialized as empty.

```
132 \@nameuse{KV@vutinfth@#1}{}%
```

The transfer from temporary to permanent storage is achieved by adding code to the already existing transfer routine. This causes each new language to issue the transfer for the previously defined language.

```
133 \ifundef{\vutinfth@allocate@polylingual}{%
```

Define the transfer function, if it has not been defined so far.

```
134 \newcommand{\vutinfth@allocate@polylingual}[1]{\@empty}%
135 }{}%
```

Store the current transfer function via `\let` to allow recursion.

```
136 \@namelet{\vutinfth@allocate@polylingual@#1}%
137 \vutinfth@allocate@polylingual
```

Define the transfer function to permanent storage.

```
138 \renewcommand{\vutinfth@allocate@polylingual}[1]{%
```

Call the transfer routine of the previously defined language.

```
139 \@nameuse{\vutinfth@allocate@polylingual@#1}{##1}%
```

To define the permanent storage, `\@namexdef` is used the definition's scope has to be global.

```
140 \@namexdef{\vutinfth###1@#1}{%
141 \ifcempty{\vutinfth@current@#1}{%
```

In draft mode we mark unassigned languages, i.e., polylingual expression that were not defined for a language that is in use when the polylingual expression is called.

```
142 \ifdraftdoc{%
143 [Draft: No '#1' text for polylingual '##1'.]%
144 }%
145 \relax
146 }\fi
147 }{%
```

The use of `\@namexdef` expands the content of the temporary storage before assigning it to the permanent one.

```
148 \@nameuse{\vutinfth@current@#1}%
149 }%
150 }%
151 }%
```

At time of usage, the language, which is given as an argument, is checked against the currently active language.

```
152 \ifundef{\vutinfth@selectlanguage@polylingual}{%
```

Define the language selection function, if it has not been defined so far.

```
153 \newcommand{\vutinfth@selectlanguage@polylingual}[1]{\@empty}%
154 }{}
```

Store the current selection function via `\let` to allow recursion.

```
155 \@namelet{\vutinfth@selectlanguage@polylingual@#1}%
156 \vutinfth@selectlanguage@polylingual
```

Define the selection function.

```
157 \renewcommand{\vutinfth@selectlanguage@polylingual}[1]{%
```

Call the selection routine of the previously defined language.

```
158 \@nameuse{\vutinfth@selectlanguage@polylingual@#1}{##1}%
```

The currently active language is given by `\language`. If it matches the language, which was supplied as the argument, the content of the current permanent storage is returned.

```
159 \ifdefstring{\language}{#1}{\@nameuse{\vutinfth@##1@#1}}{}%
160 }%
161 }
```

`\CreatePolylingual` Creates the actual polylingual expressions.

```
162 \newcommand{\CreatePolylingual}[2][]{%
163 \begingroup
```

The key-value pairs of the optional argument define the text that is returned for the respective languages. We use `vutinfth` as the family name for the keys.

```
164 \setkeys{vutinfth}{#1}%
```

Each key was already assigned a temporary storage, whose content has to be transferred to permanent storage.

```
165 \vutinfth@allocate@polylingual{#2}%
166 \endgroup
```

The mandatory argument `{⟨arg⟩}` is used to define the macro that returns the appropriate text for the currently active language.

```
167 \@namedef{vutinfth@polylingual@#2}{%
168 \vutinfth@selectlanguage@polylingual{#2}}%
169 }
```

5.2.5 Thesis Types

<code>\thesis@basetype@undergraduate</code> <code>\vutinfth@thesis@basetype@graduate</code>	Two thesis categories are differentiated: <code>undergraduate</code> and <code>graduate</code> .
	<pre> 170 \newcommand{\vutinfth@thesis@basetype@undergraduate}{% 171 \vutinfth@undergraduate}% 172 \newcommand{\vutinfth@thesis@basetype@graduate}{% 173 \vutinfth@graduate}% </pre>
<code>\ifundergraduate</code> <code>\ifgraduate</code>	Convenience macros to determine the category of the selected thesis type.
	<pre> 174 \newcommand{\ifundergraduate}[1]{% 175 \ifstrequal{\vutinfth@thesis@basetype}{% 176 \vutinfth@thesis@basetype@undergraduate 177 }{#1}{}% 178 }% 179 \newcommand{\ifgraduate}[1]{% 180 \ifstrequal{\vutinfth@thesis@basetype}{% 181 \vutinfth@thesis@basetype@graduate 182 }{#1}{}% 183 }% </pre>
<code>\vutinfth@thesis@doctortype@doctor</code> <code>\vutinfth@thesis@doctortype@phd</code>	Two doctor thesis categories are differentiated: <code>doctor</code> and <code>phd</code> , where the latter is for dissertation in the context of the Vienna PhD School of Informatics.
	<pre> 184 \newcommand{\vutinfth@thesis@doctortype@doctor}{% 185 \vutinfth@doctor}% 186 \newcommand{\vutinfth@thesis@doctortype@phd}{% 187 \vutinfth@phd}% </pre>
<code>\ifdoctor</code> <code>\ifphd</code>	Convenience macros to determine the category of the selected doctor thesis type. These need to be nested inside <code>\ifgraduate</code> conditions.
	<pre> 188 \newcommand{\ifdoctor}[1]{% 189 \ifstrequal{\vutinfth@thesis@doctortype}{% 190 \vutinfth@thesis@doctortype@doctor 191 }{#1}{}% 192 }% 193 \newcommand{\ifphd}[1]{% 194 \ifstrequal{\vutinfth@thesis@doctortype}{% 195 \vutinfth@thesis@doctortype@phd 196 }{#1}{}% 197 }% </pre>
<code>\vutinfth@thesis@basetype</code> <code>\vutinfth@thesis@doctortype</code> <code>\vutinfth@thesis@thesisname</code> <code>\vutinfth@thesis@degree</code>	Initialize the thesis category, the type and the specific degree with error messages.
	<pre> 198 \newcommand{\vutinfth@thesis@basetype}{% 199 \ClassError{\vutinfth}{No \string\setthesis \space issued}{% 200 Set thesis type with \string\setthesis.}% 201 }% </pre>


```

202 \newcommand{\vutinfth@thesis@doctortype}{%
203   \ClassError{\vutinfth}{No \string\setthesis \space issued}{%
204     Set thesis type with \string\setthesis.}%
205 }%
206 \newcommand{\vutinfth@polylingual@degree@name}{%
207   \ClassError{\vutinfth}{No \string\setthesis \space issued}{%
208     Set thesis type with \string\setthesis.}%
209 }%
210 \newcommand{\vutinfth@polylingual@thesis@name}{%
211   \ClassError{\vutinfth}{No \string\setthesis \space issued}{%
212     Set thesis type with \string\setthesis.}%
213 }%

```

\vutinfth@thesis@bachelor Four main thesis types are differentiated: bachelor, master, doctor, and
\vutinfth@thesis@master phd-school.
\vutinfth@thesis@doctor
\vutinfth@thesis@phd

```

214 \newcommand{\vutinfth@thesis@bachelor}{bachelor}%
215 \newcommand{\vutinfth@thesis@master}{master}%
216 \newcommand{\vutinfth@thesis@doctor}{doctor}%
217 \newcommand{\vutinfth@thesis@phd}{phd-school}%

```

\@setthesisname
\@setdegree@name
\@setgendereddegree@name

Internal convenience macros.

```

218 \newcommand{\@setthesisname}[1]{%
219   \renewcommand{\vutinfth@polylingual@thesis@name}{#1}}%
220 \newcommand{\@setdegree@name}[1]{%
221   \renewcommand{\vutinfth@polylingual@degree@name}{#1}}%
222 \newcommand{\@setgendereddegree@name}[2]{%
223   \ifmale{author}{\@setdegree@name{#1}}%
224   \iffemale{author}{\@setdegree@name{#2}}%
225 }%

```

\setthesis Sets the thesis type.

```

226 \newcommand{\setthesis}[1]{%
227   \ifdefstring{\vutinfth@thesis@bachelor}{#1}{%

```

Initializes bachelor thesis type.

```

228   \renewcommand{\vutinfth@thesis@basetype}{%
229     \vutinfth@thesis@basetype@undergraduate}%
230   \@setthesisname{\vutinfth@polylingual@BACHELORTHESIS}%
231   \@setdegree@name{\vutinfth@polylingual@Bdeg}%
232 }{}%
233   \ifdefstring{\vutinfth@thesis@master}{#1}{%

```

Initializes master thesis type.

```

234   \renewcommand{\vutinfth@thesis@basetype}{%
235     \vutinfth@thesis@basetype@undergraduate}%

```

```

236 \setthesisname{%
237 \ClassError{vutinfth}{No \string\setmasterdegree \space issued}{%
238 Set masterdegree with \string\setmasterdegree.}%
239 }%
240 \setdegreegreename{%
241 \ClassError{vutinfth}{No \string\setmasterdegree \space issued}{%
242 Set master degree with \string\setmasterdegree.}%
243 }%
244 }{}%
245 \ifdefstring{\vutinfth@thesis@doctor}{#1}{%

```

Initializes doctor thesis type.

```

246 \renewcommand{\vutinfth@thesis@basetype}{%
247 \vutinfth@thesis@basetype@graduate}%
248 \renewcommand{\vutinfth@thesis@doctortype}{%
249 \vutinfth@thesis@doctortype@doctor}%
250 \setthesisname{\vutinfth@polylingual@DOCTORTHESIS}%
251 \setdegreegreename{%
252 \ClassError{vutinfth}{No \string\setdoctordegree \space issued}{%
253 Set doctor degree with \string\setdoctordegree.}%
254 }%
255 }{}%
256 \ifdefstring{\vutinfth@thesis@phd}{#1}{%

```

Initializes phd-school thesis type.

```

257 \renewcommand{\vutinfth@thesis@basetype}{%
258 \vutinfth@thesis@basetype@graduate}%
259 \renewcommand{\vutinfth@thesis@doctortype}{%
260 \vutinfth@thesis@doctortype@phd}%
261 \setthesisname{\vutinfth@polylingual@PHDTHESIS}%
262 \setdegreegreename{\vutinfth@polylingual@Pdeg}%
263 }{}%
264 }%

```

```

\vutinfth@thesis@mdeg@dipl Four master degrees can be selected: dipl., master, rer.nat., and
\vutinfth@thesis@mdeg@master rer.soc.oec..
\vutinfth@thesis@mdeg@rernat
\vutinfth@thesis@mdeg@rersocoec
265 \newcommand{\vutinfth@thesis@mdeg@dipl}{dipl.}%
266 \newcommand{\vutinfth@thesis@mdeg@master}{master}%
267 \newcommand{\vutinfth@thesis@mdeg@rernat}{rer.nat.}%
268 \newcommand{\vutinfth@thesis@mdeg@rersocoec}{rer.soc.oec.}%

```

`\setmasterdegree` Sets the specific master degree.

```

269 \newcommand{\setmasterdegree}[1]{%
270 \ifdefstring{\vutinfth@thesis@mdeg@dipl}{#1}{%
271 \setthesisname{\vutinfth@polylingual@DIPLOMATHEESIS}%
272 \setgendereddegreegreename{%

```

```

273     \vutinfth@polylingual@MdegDiplMale
274 }{%
275     \vutinfth@polylingual@MdegDiplFemale
276 }%
277 }{}%
278 \ifdefstring{\vutinfth@thesis@mdeg@master}{#1}{%
279     \@setthesisname{\vutinfth@polylingual@MASTERTHESIS}%
280     \@setdegreegreenname{\vutinfth@polylingual@MdegMaster}%
281 }{}%
282 \ifdefstring{\vutinfth@thesis@mdeg@rernat}{#1}{%
283     \@setthesisname{\vutinfth@polylingual@MASTERTHESIS}%
284     \@setgendereddegreegreenname{%
285         \vutinfth@polylingual@MdegRerNatMale
286     }{%
287         \vutinfth@polylingual@MdegRerNatFemale
288     }%
289 }{}%
290 \ifdefstring{\vutinfth@thesis@mdeg@rersocoec}{#1}{%
291     \@setthesisname{\vutinfth@polylingual@MASTERTHESIS}%
292     \@setgendereddegreegreenname{%
293         \vutinfth@polylingual@MdegRerSocOecMale
294     }{%
295         \vutinfth@polylingual@MdegRerSocOecFemale
296     }%
297 }{}%
298 }%

```

```

\vutinfth@thesis@ddeg@rernat Three doctor degrees can be selected: rer.nat., techn., and rer.soc.oec..
\vutinfth@thesis@ddeg@techn
\vutinfth@thesis@ddeg@rersocoec
299 \newcommand{\vutinfth@thesis@ddeg@rernat}{rer.nat.}%
300 \newcommand{\vutinfth@thesis@ddeg@techn}{techn.}%
301 \newcommand{\vutinfth@thesis@ddeg@rersocoec}{rer.soc.oec.}%

```

`\setdoctordegree` Sets the specific doctor degree.

```

302 \newcommand{\setdoctordegree}[1]{%
303     \ifdefstring{\vutinfth@thesis@ddeg@rernat}{#1}{%
304         \@setgendereddegreegreenname{%
305             \vutinfth@polylingual@DdegRerNatMale
306         }{%
307             \vutinfth@polylingual@DdegRerNatFemale
308         }%
309 }{}%
310 \ifdefstring{\vutinfth@thesis@ddeg@techn}{#1}{%
311     \@setgendereddegreegreenname{%
312         \vutinfth@polylingual@DdegTechnMale
313     }{%
314         \vutinfth@polylingual@DdegTechnFemale
315     }%
316 }{}%

```

```

317 \ifdefstring{\vutinfth@thesis@ddeg@rersocoec}{#1}{%
318 \setgendereddegreename{%
319 \vutinfth@polylingual@ddegRerSocOecMale
320 }{%
321 \vutinfth@polylingual@ddegRerSocOecFemale
322 }%
323 }{%
324 }%

```

5.2.6 Declarations

Textual Data Creates the required textual data entries.

```

325 \CreateData{address}%
326 \CreateData{regnumber}%
327 \CreateData{firstreviewerdata}%
328 \CreateData{secondreviewerdata}%

```

Persons Creates the required person entries.

```

329 \CreatePerson{author}%
330 \CreatePerson{advisor}%
331 \CreatePerson{secondadvisor}%
332 \CreatePerson{firstassistant}%
333 \CreatePerson{secondassistant}%
334 \CreatePerson{thirdassistant}%
335 \CreatePerson{firstreviewer}%
336 \CreatePerson{secondreviewer}%

```

Languages Adds the desired languages to the polylingual expressions. All added languages have to be given as arguments to the `babel` package.

```

337 \AddLanguage{english}%
338 \AddLanguage{naustrian}%

```

PolyLinguals Creates the polylingual expressions.

```

339 \CreatePolylingual[
340 english=Advisor,
341 naustrian=Betreuung]{Advisor}%
342 \CreatePolylingual[
343 english=Second advisor,
344 naustrian=Zweitbetreuung]{Secondadvisor}%
345 \CreatePolylingual[
346 english=submitted in partial fulfillment of the requirements
347 for the degree of,
348 naustrian=zur Erlangung des akademischen Grades]{submission}%
349 \CreatePolylingual[
350 english=in,
351 naustrian=im Rahmen des Studiums]{in}%

```

```

352 \CreatePolylingual[
353   english=within the]{within}%
354 \CreatePolylingual[
355   english=Vienna PhD School of Informatics]{School}%
356 \CreatePolylingual[
357   english=by,
358   naustrian=eingereicht von]{by}%
359 \CreatePolylingual[
360   english=Registration Number,
361   naustrian=Matrikelnummer]{Registrationnumber}%
362 \CreatePolylingual[
363   english=to the Faculty of Informatics,
364   naustrian=an der Fakult\"at f\"ur Informatik]{faculty}%
365 \CreatePolylingual[
366   english=at the TU Wien,
367   naustrian=der Technischen Universit\"at Wien]{university}%
368 \CreatePolylingual[
369   english=Assistance,
370   naustrian=Mitwirkung]{Assistance}%
371 \CreatePolylingual[
372   english=The dissertation has been reviewed by:,
373   naustrian=Diese Dissertation haben begutachtet:]{Reviewed}%
374 \CreatePolylingual[
375   english=External reviewers:]{Reviewers}%
376 \CreatePolylingual[
377   english=Vienna,
378   naustrian=Wien]{Place}%
379 \CreatePolylingual[
380   english=Declaration of Authorship,
381   naustrian=Erkl\"arung zur Verfassung der Arbeit]{StatementChapter}%
382 \CreatePolylingual[
383   english={I hereby declare that I have written this Doctoral Thesis
384     independently, that I have completely specified the utilized
385     sources and resources and that I have definitely marked all parts
386     of the work - including tables, maps and figures - which belong
387     to other works or to the internet, literally or extracted, by
388     referencing the source as borrowed.},
389   naustrian={Hiermit erkl\"are ich, dass ich diese Arbeit
390     selbst\"andig verfasst habe, dass ich die verwendeten Quellen
391     und Hilfsmittel vollst\"andig angegeben habe und dass ich die
392     Stellen der Arbeit -- einschlie{\ss}lich Tabellen, Karten und
393     Abbildungen --, die anderen Werken oder dem Internet im Wortlaut
394     oder dem Sinn nach entnommen sind, auf jeden Fall unter Angabe
395     der Quelle als Entlehnung kenntlich gemacht habe.}]{Statement}%

```

Degree titles.

```

396 \CreatePolylingual[
397   english=Bachelor of Science,
398   naustrian=Bachelor of Science]{Bdeg}%

```

```

399 \CreatePolylingual[
400   english=Master of Science,
401   naustrian=Master of Science]{MdegMaster}%
402 \CreatePolylingual[
403   english=Diplom-Ingenieur,
404   naustrian=Diplom-Ingenieur]{MdegDiplMale}%
405 \CreatePolylingual[
406   english=Diplom-Ingenieurin,
407   naustrian=Diplom-Ingenieurin]{MdegDiplFemale}%
408 \CreatePolylingual[
409   english=Magister der Naturwissenschaften,
410   naustrian=Magister der Naturwissenschaften]{MdegRerNatMale}%
411 \CreatePolylingual[
412   english=Magistra der Naturwissenschaften,
413   naustrian=Magistra der Naturwissenschaften]{MdegRerNatFemale}%
414 \CreatePolylingual[
415   english=Magister der Sozial- und Wirtschaftswissenschaften,
416   naustrian=Magister der Sozial- und Wirtschaftswissenschaften]{%
417   MdegRerSocOecMale}%
418 \CreatePolylingual[
419   english=Magistra der Sozial- und Wirtschaftswissenschaften,
420   naustrian=Magistra der Sozial- und Wirtschaftswissenschaften]{%
421   MdegRerSocOecFemale}%
422 \CreatePolylingual[
423   english=Doktor der Naturwissenschaften,
424   naustrian=Doktor der Naturwissenschaften]{DdegRerNatMale}%
425 \CreatePolylingual[
426   english=Doktorin der Naturwissenschaften,
427   naustrian=Doktorin der Naturwissenschaften]{DdegRerNatFemale}%
428 \CreatePolylingual[
429   english=Doktor der Technischen Wissenschaften,
430   naustrian=Doktor der Technischen Wissenschaften]{DdegTechnMale}%
431 \CreatePolylingual[
432   english=Doktorin der Technischen Wissenschaften,
433   naustrian=Doktorin der Technischen Wissenschaften]{DdegTechnFemale}%
434 \CreatePolylingual[
435   english=Doktor der Sozial- und Wirtschaftswissenschaften,
436   naustrian=Doktor der Sozial- und Wirtschaftswissenschaften]{%
437   DdegRerSocOecMale}%
438 \CreatePolylingual[
439   english=Doktorin der Sozial- und Wirtschaftswissenschaften,
440   naustrian=Doktorin der Sozial- und Wirtschaftswissenschaften]{%
441   DdegRerSocOecFemale}%
442 \CreatePolylingual[
443   english=Doctor of Technical Sciences]{%
444   Pdeg}%

```

Thesis types.

```

445 \CreatePolylingual[

```

```

446   english=BACHELOR'S THESIS,
447   naustrian=BACHELORARBEIT]{BACHELORTHESIS}%
448 \CreatePolylingual[
449   english=MASTER'S THESIS,
450   naustrian=MASTERARBEIT]{MASTERTHESIS}%
451 \CreatePolylingual[
452   english=DIPLOMA THESIS,
453   naustrian=DIPLOMARBEIT]{DIPLOMATHESES}%
454 \CreatePolylingual[
455   english=DISSERTATION,
456   naustrian=DISSERTATION]{DOCTORTHESIS}%
457 \CreatePolylingual[
458   english=PhD THESIS]{PHDTHESIS}%

```

\settitle Sets the title of the thesis.

```

459 \newcommand{\settitle}[2]{%
460   \CreatePolylingual[english=#1,naustrian=#2]{Title}%
461 }%

```

\setsubtitle Sets the subtitle of the thesis.

```

462 \newcommand{\setsubtitle}[2]{%
463   \CreatePolylingual[english=#1,naustrian=#2]{Subtitle}%
464 }%

```

\setcurriculum Sets the curriculum name.

```

465 \newcommand{\setcurriculum}[2]{%
466   \CreatePolylingual[english=#1,naustrian=#2]{Curriculum}%
467 }%

```

5.3 Layout

5.3.1 Setup

\vutinfth@squarebullet Set internal convenience macros.

```

468 \newcommand{\newsetlength}[2]{%
469   \newlength{#1}%
470   \setlength{#1}{#2}%
471 }%
472 \newcommand{\vutinfth@squarebullet}{\rule[0.47ex]{0.4ex}{0.4ex}}%

```

\vutinfth@tmp@parindent Temporary storage for page layout lengths.

```

\vutinfth@tmp@baselineskip
\vutinfth@tmp@parskip
473 \newlength{\vutinfth@tmp@parindent}%
474 \newlength{\vutinfth@tmp@baselineskip}%
475 \newlength{\vutinfth@tmp@parskip}%

```

`\vutinfth@savelayout` Saves and restores relevant page layout lengths.
`\vutinfth@restorelayout`

```

476 \newcommand{\vutinfth@savelayout}{%
477   \setlength{\vutinfth@tmp@parindent}{\parindent}%
478   \setlength{\vutinfth@tmp@baselineskip}{\baselineskip}%
479   \setlength{\vutinfth@tmp@parskip}{\parskip}%
480 }%
481 \newcommand{\vutinfth@restorelayout}{%
482   \setlength{\parindent}{\vutinfth@tmp@parindent}%
483   \setlength{\baselineskip}{\vutinfth@tmp@baselineskip}%
484   \setlength{\parskip}{\vutinfth@tmp@parskip}%
485 }%
```

5.3.2 Title Page

Initialize the header graphics. The vertical placement of the header graphics on the title pages are given by `\vutinfth@header@placement`, while the composition of the graphical elements are determined by the subsequent lengths, which constitute direct measurements of the graphics. If the header graphics are changed, these values have to be adapted.

```

486 \newsetlength{\vutinfth@header@placement}{-41.49731pt}%
487 \newsetlength{\vutinfth@bar@width}{511bp}%
488 \newsetlength{\vutinfth@bar@height}{47bp}%
489 \newsetlength{\vutinfth@bar@pivot@x}{330.71bp}%
490 \newsetlength{\vutinfth@bar@pivot@y}{25.31bp}%
491 \newsetlength{\vutinfth@logo@height}{46bp}%
492 \newsetlength{\vutinfth@logo@pivot@x}{4.57bp}%
493 \newsetlength{\vutinfth@logo@pivot@y}{5.37bp}%
494 \newsetlength{\vutinfth@logo@offset@height}{\vutinfth@logo@height
495   + \vutinfth@bar@pivot@y - \vutinfth@logo@pivot@y}%
496 \newsetlength{\vutinfth@logo@offset@x}{-\vutinfth@bar@width
497   + \vutinfth@bar@pivot@x - \vutinfth@logo@pivot@x}%
498 \newsetlength{\vutinfth@logo@offset@y}{
499   - \vutinfth@bar@pivot@y + \vutinfth@logo@pivot@y}%

```

`\vutinfth@header@titlepage` Initialize header.

```

500 \newcommand{\vutinfth@header@titlepage}{%
501   \centering
502   \begin{minipage}[b][\vutinfth@logo@offset@height][t]{%
503     \vutinfth@bar@width
504   }%
505   \hspace*{\vutinfth@logo@offset@x}%
506   \raisebox{\vutinfth@logo@offset@y}{%
507   }%
508   \end{minipage}%
509 }%
```


`\vutinfth@footer@titlepage` Initialize footer.

```
510 \newcommand{\vutinfth@footer@titlepage}{%
511   \centering
512   \begin{minipage}{\textwidth}%
513     \centering\vutinfth@normalsize\sffamily
514     Technische Universit\{a}t Wien\\
515     A-1040 Wien \vutinfth@squarebullet\space
516     Karlsplatz 13 \vutinfth@squarebullet\space
517     Tel. +43-1-58801-0 \vutinfth@squarebullet\space
518     www.tuwien.ac.at%
519   \end{minipage}%
520 }
```

`vutinfth@pagestyle@titlepage` Generate the title page style.

```
521 \makepagestyle{vutinfth@pagestyle@titlepage}%
522 \makerunningwidth{vutinfth@pagestyle@titlepage}[\textwidth]{%
523   \vutinfth@bar@width}%
524 \makeheadposition{vutinfth@pagestyle@titlepage}{%
525   center}{center}{center}{center}%
526 \makeevenhead{vutinfth@pagestyle@titlepage}{}{%
527   \vutinfth@header@titlepage}{}%
528 \makeoddhead{vutinfth@pagestyle@titlepage}{}{%
529   \vutinfth@header@titlepage}{}%
530 \makefootrule{vutinfth@pagestyle@titlepage}{%
531   \vutinfth@pagestyle@titlepagefootrunwidth}{0.5pt}{\footruleskip}%
532 \makeevenfoot{vutinfth@pagestyle@titlepage}{}{%
533   \vutinfth@footer@titlepage}{}%
534 \makeoddfoot{vutinfth@pagestyle@titlepage}{}{%
535   \vutinfth@footer@titlepage}{}%

```

Set style element specifications.

```
536 \newsetlength{\vutinfth@bigskipamount}{6mm}%

```

Helper functions.

```
537 \newcommand{\vutinfth@bigskip}{\vspace{\vutinfth@bigskipamount}}%

```

`\AdvisorBlock` Generates a block with the advisor's name (and potential assistances' names). An error is thrown, if the advisors are not defined consecutively, starting with the first.

```
538 \newcommand{\AdvisorBlock}{%
539   \ifundergraduate{%
540     \begin{minipage}[t][2.5cm][t]{\textwidth}%
541       \vutinfth@normalsize
542       \begin{tabular}{@{}l@{ }l}%
543         \vutinfth@polylingual@Advisor: &

```

```

544 \vutinfth@person@advisor@fullname\\
545 \ifdef{\vutinfth@person@firstassistant@def}{%
546 \vutinfth@polylingual@Assistance: &
547 \vutinfth@person@firstassistant@fullname\\
548 }{}%
549 \ifdef{\vutinfth@person@secondassistant@def}{%
550 \ifundef{\vutinfth@person@firstassistant@def}{%
551 \vutinfth@person@firstassistant@error
552 }{%
553 & \vutinfth@person@secondassistant@fullname\\
554 }%
555 }{}%
556 \ifdef{\vutinfth@person@thirdassistant@def}{%
557 \ifundef{\vutinfth@person@firstassistant@def}{%
558 \vutinfth@person@firstassistant@error
559 }{%
560 \ifundef{\vutinfth@person@secondassistant@def}{%
561 \vutinfth@person@secondassistant@error
562 }{%
563 & \vutinfth@person@thirdassistant@fullname\\
564 }%
565 }%
566 }{}%
567 \end{tabular}%
568 \end{minipage}%
569 }%
570 \ifgraduate{%
571 \begin{minipage}[t][1.6cm][t]{\textwidth}%
572 \vutinfth@normalsize
573 \vutinfth@polylingual@Advisor:
574 \vutinfth@person@advisor@fullname
575 \ifdef{\vutinfth@person@secondadvisor@def}{%
576 \\
577 \vutinfth@polylingual@Secondadvisor:
578 \vutinfth@person@secondadvisor@fullname
579 }{}%
580 \end{minipage}\par%
581 }%
582 }%

```

```

\vutinfth@signature@height Set lengths of the signature blocks.
\vutinfth@signature@width
\vutinfth@placedate@width 583 \newsetlength{\vutinfth@signature@height}{25mm}%
584 \newsetlength{\vutinfth@signature@width}{51mm}%
585 \newsetlength{\vutinfth@placedate@width}{50mm}%

```

\SignatureFields Generates a block with signatures and an optional place-date entry. The first argument is optional and adds an entry with date and place [y], or adds corresponding whitespace [h] or adds nothing [n], which is also the default value. The

second arguments adds a rule and the given text below it, if a text is given, or the corresponding whitespace, if not. The third argument adds a rule and the given text below it, if a text is given.

```

586 \newcommand{\SignatureFields}[3][n]{%
587   {\vutinfth@normalsize
588     \ifstrequal{#1}{y}{%
589       \begin{minipage}[b][\vutinfth@signature@height]{%
590         \vutinfth@placedate@width
591       }%
592       \vutinfth@polylingual@Place,
593       \displaydate{\vutinfth@date@signing}\vspace*{\baselineskip}%
594     \end{minipage}%
595     \hfill
596   }{}%
597   \ifstrequal{#1}{n}{}{}%
598   \ifstrequal{#1}{h}{%
599     \hspace*{\vutinfth@placedate@width}%
600     \hfill
601   }{}%
602   \ifstreempty{#2}{%
603     \hspace*{\vutinfth@signature@width}%
604     \hfill
605   }{}%
606   \begin{minipage}[b][\vutinfth@signature@height]{%
607     \vutinfth@signature@width
608   }%
609   \centering
610   \rule{\vutinfth@signature@width}{0.5pt}\\
611   #2%
612   \end{minipage}%
613   \hfill
614 }%
615 \ifstreempty{#3}{}{%
616   \begin{minipage}[b][\vutinfth@signature@height]{%
617     \vutinfth@signature@width
618   }%
619   \centering
620   \rule{\vutinfth@signature@width}{0.5pt}\\
621   #3%
622   \end{minipage}%
623 }%
624 }%
625 }%

```

`\ReviewerBlock` Generates a block with the relevant signatures.

```

626 \newcommand{\ReviewerBlock}{%
627   \ifgraduate{%
628     \ifdoctor{%

```

```

629     {\vutinfth@normalsize
630       \vutinfth@polylingual@Reviewed\\
631       \SignatureFields[h]{%
632         \vutinfth@person@firstreviewer@name
633       }{%
634         \vutinfth@person@secondreviewer@name
635       }%
636     }%
637   }%
638   \ifphd{%
639     {\vutinfth@normalsize
640       \vutinfth@polylingual@Reviewers\\
641       \vutinfth@person@firstreviewer@name.
642       \vutinfth@data@firstreviewerdata.\\
643       \vutinfth@person@secondreviewer@name.
644       \vutinfth@data@secondreviewerdata.\\
645     }%
646   }%
647 }%
648 }%

```

`\SignatureBlock` Generates a block with the relevant signatures.

```

649 \newcommand{\SignatureBlock}{%
650   \ifundergraduate{%
651     {\vutinfth@normalsize
652       \SignatureFields[y]{%
653         \vutinfth@person@author@name
654       }{%
655         \vutinfth@person@advisor@name
656       }%
657     }%
658   }%
659   \ifgraduate{%
660     {\vutinfth@normalsize
661       \ifdoctor{%
662         \SignatureFields[y]{%
663           \vutinfth@person@author@name
664         }%
665       }%
666       \ifphd{%
667         \SignatureFields[y]{%
668           \vutinfth@person@author@name
669         }{%
670           \vutinfth@person@advisor@name
671         }%
672       }%
673     }%
674   }%
675 }%

```

`\AddTitlePage` Generates the language-dependant title page. Multiline title and subtitle are supported.

```
676 \newcommand{\AddTitlePage}{
677   \thispagestyle{vutinfth@pagestyle@titlepage}%
```

Set a new page geometry where the header separation length (`headsep`) places the header. The actual header height (`head`) has to be large enough to contain the header content otherwise the underlying `memoir` class issues a warning.

```
678   \newgeometry{%
679     left=2.4cm,right=2.4cm,bottom=2.5cm,top=2cm,
680     headsep=\vutinfth@header@placement,
681     head=2\vutinfth@logo@offset@height
682   }%
```

Save the current page layout lengths for later restoration.

```
683   \vutinfth@savelayout
684   \setlength{\parindent}{0pt}%
685   \setlength{\baselineskip}{13.6pt}%
686   \setlength{\parskip}{0pt plus 1pt}%
```

Set title page text to helvetica.

```
687   \begin{SFFont}{phv}%
688   \sffamily
689   {\centering
690     \vspace*{1.2cm}}\par
```

Title and subtitle are bottom aligned and grow upwards.

```
691     \begin{minipage}[t][5cm][b]{\textwidth}%
692       \centering
693       \vutinfth@HUGE{\bfseries\vutinfth@polylingual@Title}\\
694       \bigskip
695       \vutinfth@huge{\bfseries
696         \ifdef{\vutinfth@polylingual@Subtitle}{%
697           \vutinfth@polylingual@Subtitle}{%
698         }%
699       }%
700     \end{minipage}\par
701     \vutinfth@bigskip\vutinfth@bigskip
702     {\vutinfth@LARGE\vutinfth@polylingual@thesisname}\par
703     \vutinfth@bigskip
704     {\vutinfth@large\vutinfth@polylingual@submission}\par
705     \vutinfth@bigskip
706     \ifundergraduate{%
707       {\vutinfth@LARGE{\bfseries\vutinfth@polylingual@degreename}}\par
708       \vutinfth@bigskip
709       {\vutinfth@large\vutinfth@polylingual@in}\par
```

```

710      \vutinfth@bigskip
711      {\vutinfth@Large{\bfseries\vutinfth@polylingual@Curriculum}}\par
712    }%
713    \ifgraduate{%
714      {\vutinfth@LARGE{\bfseries\vutinfth@polylingual@degreename}}\par
715      \ifphd{%
716        \vutinfth@bigskip
717        {\vutinfth@large\vutinfth@polylingual@within}\par
718        \vutinfth@bigskip
719        {\vutinfth@LARGE{\bfseries\vutinfth@polylingual@School}}\par
720      }%
721    }%
722    \vutinfth@bigskip
723    {\vutinfth@large\vutinfth@polylingual@by}\par
724    \vutinfth@bigskip
725    {\vutinfth@Large{\bfseries\vutinfth@person@author@fullname}}\par
726    \smallskip
727    {\vutinfth@large\vutinfth@polylingual@Registrationnumber\
728     \vutinfth@data@regnumber}\par
729  }%
730  \vutinfth@bigskip\vutinfth@bigskip
731  \ifgraduate{\ifphd{\vspace*{-8mm}}}%
732  \begin{minipage}[b][1.6cm][c]{\textwidth}%
733    \vutinfth@normalsize%
734    \vutinfth@polylingual@faculty\par
735    \vutinfth@polylingual@university
736  \end{minipage}\par
737  \AdvisorBlock\par

```

Add stretchable glue between the advisor block and the signatures. This ensures that the signature part is always at the bottom of the page.

```

738    \vfill
739    \ReviewerBlock\par
740    \SignatureBlock\par
741    \vspace*{1cm}%
742  \end{SFFont}%
743  \pagestyle{empty}%
744  \cleardoublepage
745  \vutinfth@restorelayout
746  \restoregeometry
747 }%

```

5.3.3 Front Matter Material

`\AddStatementPage` Generates the statement page.

```

748 \newcommand{\AddStatementPage}{

```

Set the same page geometry as for the titlepages.

```

749 %^^A \newgeometry{%
750 %^^A left=2.4cm,right=2.4cm,bottom=2.5cm,top=2cm,
751 %^^A headsep=\vutinfth@header@placement,
752 %^^A head=2\vutinfth@logo@offset@height
753 %^^A }%

```

Save the current page layout lengths for later restoration.

```

754 \vutinfth@savelayout
755 \setlength{\parindent}{0pt}%
756 \setlength{\baselineskip}{13.6pt}%
757 \setlength{\parskip}{0pt plus 1pt}%
758 \begin{SFFont}{phv}%
759 \sffamily
760 \chapter*{\vutinfth@polylingual@StatementChapter}%
761 \vutinfth@person@author@fullname\\
762 \vutinfth@data@address\par
763 \vspace{1.2cm}%
764 {\normalfont\vutinfth@polylingual@Statement}\par
765 \vspace{1.2cm}%
766 \SignatureFields[y]{\vutinfth@person@author@name}{}%
767 \end{SFFont}%
768 \cleardoublepage
769 \vutinfth@restorelayout
770 %^^A \restoregeometry
771 }%

```

`\addtitlepage` Generates the titlepage in given language.

```

772 \newcommand{\addtitlepage}[1]{%
773 \selectlanguage{#1}%
774 \AddTitlePage
775 }%

```

`\addstatementpage` Generates the statement page.

```

776 \newcommand{\addstatementpage}{%
777 \selectlanguage{naustrian}%
778 \ifundergraduate{\AddStatementPage}%
779 \ifgraduate{%
780 \ifdoctor{\AddStatementPage}%
781 \ifphd{%
782 \selectlanguage{english}%
783 \AddStatementPage
784 }%
785 }%
786 }%

```

`acknowledgements` Generates the English acknowledgement section.

```

787 \newenvironment{acknowledgements}{%
788   \selectlanguage{english}%
789   \chapter{Acknowledgements}%
790 }{%
791   \cleardoublepage
792 }%

```

acknowledgements* Generates the English acknowledgement section without an entry in the table of contents.

```

793 \newenvironment{acknowledgements*}{%
794   \selectlanguage{english}%
795   \chapter*{Acknowledgements}%
796 }{%
797   \cleardoublepage
798 }%

```

danksagung Generates the German acknowledgement section.

```

799 \newenvironment{danksagung}{%
800   \selectlanguage{naustrian}%
801   \chapter{Danksagung}%
802 }{%
803   \cleardoublepage
804 }%

```

danksagung* Generates the German acknowledgement section without an entry in the table of contents.

```

805 \newenvironment{danksagung*}{%
806   \selectlanguage{naustrian}%
807   \chapter*{Danksagung}%
808 }{%
809   \cleardoublepage
810 }%

```

abstract Generates the English abstract.

```

811 \renewenvironment{abstract}{%
812   \selectlanguage{english}%
813   \chapter{Abstract}%
814 }{%
815   \cleardoublepage
816 }%

```

abstract* Generates the English abstract without an entry in the table of contents.

```

817 \newenvironment{abstract*}{%
818   \selectlanguage{english}%

```



```

819 \chapter*{Abstract}%
820 }{%
821 \cleardoublepage
822 }%

```

kurzfassung Generates the German abstract without an entry in the table of contents.

```

823 \newenvironment{kurzfassung}{%
824 \selectlanguage{naustrian}%
825 \chapter{Kurzfassung}%
826 }{%
827 \cleardoublepage
828 }%

```

kurzfassung* Generates the German abstract.

```

829 \newenvironment{kurzfassung*}{%
830 \selectlanguage{naustrian}%
831 \chapter*{Kurzfassung}%
832 }{%
833 \cleardoublepage
834 }%

```

5.3.4 Page Style

vutinfth@pagestyle@default Define the default page style of the thesis.

```

835 \makepagestyle{vutinfth@pagestyle@default}%
836 \makeevenfoot{vutinfth@pagestyle@default}{\thepage}{}%
837 \makeoddfoot{vutinfth@pagestyle@default}{\thepage}%

```

\frontmatter Apply the default page style to the thesis.

```

\mainmatter
\backmatter
838 \aliaspagestyle{chapter}{vutinfth@pagestyle@default}%
839 \aliaspagestyle{part}{vutinfth@pagestyle@default}%
840 \addto\frontmatter{\pagestyle{vutinfth@pagestyle@default}}%
841 \addto\mainmatter{\pagestyle{Ruled}}%
842 \addto\backmatter{\pagestyle{vutinfth@pagestyle@default}}%

```

6 Change History

v0.9		v1.3
General: Pre-release version	1	\AddStatementPage: Updated to support multiple languages.
v1.0		
General: Initial release version . . .	1	Issue #4 30
v1.1		
General: Added references to the GitLab environment	1	\AddTitlePage: Added check for subtitle existence before usage. Issue #1 29

Updated to support PhD School mentioning and fixed the associated vertical overflow. Issue #4	29	support multiple dissertation types. Issue #4	17
\AdvisorBlock : Updated to support second advisor. Issue #4	25	General: Added support for a dissertation at the Vienna Phd School of Informatics. Issue #4	1
\ReviewerBlock : Updated to support external reviewers. Issue #4	27	Persons : Updated to support second advisor. Issue #4	20
\SignatureBlock : Updated to support multiple dissertation types. Issue #4	28	PolyLinguals : Added to support multiple dissertation types. Issue #4	20
\addstatementpage : Updated to support english version. Issue #4	31	TextualData : Updated to support external reviewer data. Issue #4	20
\ifdoctor : Added to support multiple dissertation types. Issue #4	16	v1.4	
\ifphd : Added to support multiple dissertation types. Issue #4	16	\mainmatter : Added ‘Ruled’ pagestyle.	33
\setthesis : Altered to support multiple dissertation types. Issue #4	17	\vutinfth@def@person : Added comma to separate posttitle.	12
\vutinfth@thesis@doctortype : Added to support multiple dissertation types. Issue #4	16	General: Added comma to separate posttitle and changed mainmatter pagestyle to ‘Ruled’.	1
\vutinfth@thesis@doctortype@doctor : Added to support multiple dissertation types. Issue #4	16	v1.5	
\vutinfth@thesis@doctortype@phd : Added to support multiple dissertation types. Issue #4	16	General: Updated name of university to ‘TU Wien’.	1
\vutinfth@thesis@phd : Added to support multiple dissertation types. Issue #4	16	PolyLinguals : Updated name of university to ‘TU Wien’.	20
		\AdvisorBlock : Enabled second advisor for dissertations.	25
		General: Enabled second advisor for dissertations.	1
		PolyLinguals : Provided German term for second advisor.	20

Index

Symbols

\"	364, 367, 381, 389, 390, 391, 514
\@empty	134, 153
\@namedef	47, 48, 51, 54, 57, 71, 72, 73, 74, 76, 79, 83, 86, 88, 94, 96, 100, 102, 108, 111, 113, 115, 117, 119, 123, 129, 130, 167
\@namelet	136, 155
\@nameuse	54, 112, 114, 116, 118, 120, 132, 139, 148, 158, 159
\@namexdef	18, 140
\@setdegreename	218, 231, 240, 251, 262, 280
\@setgendereddegreename	218, 272, 284, 292, 304, 311, 318
\@setthesisname	218, 230, 236, 250, 261, 271, 279, 283, 291

\\ 514, 544, 547, 553, 563, 576, 610, 620, 630, 640, 642, 644, 693, 761

_ 727

A

abstract (environment) 7, 811
 abstract* (environment) 7, 817
 acknowledgements (environment) 7, 787
 acknowledgements* (environment) 7, 793
 \AddLanguage 8, 128, 337, 338
 \AddStatementPage 9, 748, 778, 780, 783
 \addstatementpage 7, 776
 \AddTitlePage 9, 676, 774
 \addtitlepage 6, 6, 772
 \addto 840, 841, 842
 \AdvisorBlock 9, 538, 737
 \aliaspagestyle 838, 839

B

\backmatter 838
 \baselineskip 478, 483, 593, 685, 756
 \begin 502, 512, 540, 542, 571, 589, 606, 616, 687, 691, 732, 758
 \begingroup 20, 34, 163
 \bfseries 693, 695, 707, 711, 714, 719, 725
 \bigskip 694

C

\centering 501, 511, 513, 609, 619, 689, 692
 \chapter 760, 789, 795, 801, 807, 813, 819, 825, 831
 \chapterstyle 6
 \ClassError 52, 109, 199, 203, 207, 211, 237, 241, 252
 \cleardoublepage 744, 768, 791, 797, 803, 809, 815, 821, 827, 833
 \CreateData 7, 56, 325, 326, 327, 328
 \CreatePerson 7, 122, 329, 330, 331, 332, 333, 334, 335, 336
 \CreatePolylingual 8, 162, 339, 342, 345, 349, 352, 354, 356, 359, 362, 365,
 368, 371, 374, 376, 379, 382, 396, 399, 402, 405, 408, 411, 414, 418, 422,
 425, 428, 431, 434, 438, 442, 445, 448, 451, 454, 457, 460, 463, 466
 \csname 18
 \CurrentOption 2

D

danksagung (environment) 7, 799
 danksagung* (environment) 7, 805
 \DeclareOption 1
 \displaydate 593

E

<code>\edef</code>	21, 22
<code>\else</code>	144
<code>\end</code>	508, 519, 567, 568, 580, 594, 612, 622, 700, 736, 742, 767
<code>\endcsname</code>	18
<code>\endgroup</code>	25, 37, 166
environments:	
<code>abstract</code>	7, <u>811</u>
<code>abstract*</code>	7, <u>817</u>
<code>acknowledgements</code>	7, <u>787</u>
<code>acknowledgements*</code>	7, <u>793</u>
<code>danksagung</code>	7, <u>799</u>
<code>danksagung*</code>	7, <u>805</u>
<code>kurzfassung</code>	7, <u>823</u>
<code>kurzfassung*</code>	7, <u>829</u>
<code>SFFont</code>	9, <u>33</u>
<code>\expandafter</code>	18, 23, 24

F

<code>\f@family</code>	36, 39
<code>\fi</code>	146
<code>\fontsize</code>	27, 28, 29, 30, 31, 32
<code>\footruleskip</code>	531
<code>\frontmatter</code>	<u>838</u>

G

<code>\global</code>	36
<code>\graphicspath</code>	17

H

<code>\hfill</code>	595, 600, 604, 613
<code>\hspace</code>	505, 599, 603

I

<code>\ifcempty</code>	141
<code>\ifcsstring</code>	65, 68
<code>\ifdef</code>	545, 549, 556, 575, 696
<code>\ifdefstrequal</code>	39
<code>\ifdefstring</code>	75, 78, 159, 227, 233, 245, 256, 270, 278, 282, 290, 303, 310, 317
<code>\ifdoctor</code>	<u>188</u> , 628, 661, 780
<code>\ifdraftdoc</code>	142
<code>\ifestrequal</code>	<u>19</u> , 175, 180, 189, 194
<code>\iffemale</code>	64, 224
<code>\ifgraduate</code>	<u>174</u> , 570, 627, 659, 713, 731, 779
<code>\ifmale</code>	64, 223
<code>\ifphd</code>	<u>188</u> , 638, 666, 715, 731, 781

<code>\ifstrempy</code>	81, 82, 85, 92, 93, 99, 602, 615
<code>\ifstrequal</code>	23, 588, 597, 598
<code>\ifundef</code>	133, 152, 550, 557, 560
<code>\ifundergraduate</code>	174, 539, 650, 706, 778

K

<code>kurzfassung</code> (environment)	7, 823
<code>kurzfassung*</code> (environment)	7, 829

L

<code>\language</code>	159
<code>\Languages</code>	337
<code>\let</code>	36
<code>\LoadClass</code>	5

M

<code>\mainmatter</code>	838
<code>\makeevenfoot</code>	532, 836
<code>\makeevenhead</code>	526
<code>\makefootrule</code>	530
<code>\makeheadposition</code>	524
<code>\makeoddfoot</code>	534, 837
<code>\makeoddhead</code>	528
<code>\makepagestyle</code>	521, 835
<code>\makerunningwidth</code>	522

N

<code>\newcommand</code>	18, 19, 27, 28, 29, 30, 31, 32, 43, 46, 50, 56, 62, 63, 64, 67, 70, 107, 122, 128, 134, 153, 162, 170, 172, 174, 179, 184, 186, 188, 193, 198, 202, 206, 210, 214, 215, 216, 217, 218, 220, 222, 226, 265, 266, 267, 268, 269, 299, 300, 301, 302, 459, 462, 465, 468, 472, 476, 481, 500, 510, 537, 538, 586, 626, 649, 676, 748, 772, 776
<code>\newdate</code>	44
<code>\newenvironment</code>	33, 787, 793, 799, 805, 817, 823, 829
<code>\newgeometry</code>	678, 749
<code>\newlength</code>	469, 473, 474, 475
<code>\newsetlength</code>	468, 486, 487, 488, 489, 490, 491, 492, 493, 494, 496, 498, 536, 583, 584, 585
<code>\normalfont</code>	764

P

<code>\pagestyle</code>	743, 840, 841, 842
<code>\par</code>	580, 690, 700, 702, 704, 707, 709, 711, 714, 717, 719, 723, 725, 728, 734, 736, 737, 739, 740, 762, 764
<code>\parindent</code>	477, 482, 684, 755
<code>\parskip</code>	479, 484, 686, 757
<code>\PassOptionsToClass</code>	2

\Persons	329
\PolyLinguals	339
\ProcessOptions	4

R

\raisebox	506
\relax	4 , 145
\renewcommand	38 , 41 , 138 , 157 , 219 , 221 , 228 , 234 , 246 , 248 , 257 , 259
\renewenvironment	811
\RequirePackage	7 , 8 , 9 , 10 , 11 , 12 , 13 , 14 , 15 , 16
\restoregeometry	746 , 770
\ReviewerBlock	9 , 626 , 739
\rule	472 , 610 , 620

S

\selectfont	27 , 28 , 29 , 30 , 31 , 32
\selectlanguage	773 , 777 , 782 , 788 , 794 , 800 , 806 , 812 , 818 , 824 , 830
\set	60 , 126
\setaddress	3
\setadvisor	4 , 5
\setauthor	4 , 5
\setcurriculum	3 , 6 , 465
\setdate	4 , 43
\setdoctordegree	5 , 252 , 253 , 302
\setfirstassistant	4
\setfirstreviewer	4
\setfirstreviewerdata	3
\setkeys	164
\setlength ...	470 , 477 , 478 , 479 , 482 , 483 , 484 , 684 , 685 , 686 , 755 , 756 , 757
\setmasterdegree	5 , 237 , 238 , 241 , 242 , 269
\setregnumber	3
\setsecondadvisor	4
\setsecondassistant	4
\setsecondreviewer	4
\setsecondreviewerdata	3
\setsubtitle	3 , 6 , 462
\setthesis	5 , 199 , 200 , 203 , 204 , 207 , 208 , 211 , 212 , 226
\setthirdassistant	4
\settitle	3 , 6 , 459
\sfdefault	35 , 38 , 39 , 41
\sffamily	513 , 688 , 759
SFFont (environment)	9 , 33
\SignatureBlock	8 , 649 , 740
\SignatureFields	8 , 586 , 631 , 652 , 662 , 667 , 766
\smallskip	726
\space	199 , 203 , 207 , 211 , 237 , 241 , 252 , 515 , 516 , 517

\ss	392
\string	60, 126, 199, 200, 203, 204, 207, 208, 211, 212, 237, 238, 241, 242, 252, 253

T

\Textual_Data	325
\textwidth	512, 522, 540, 571, 691, 732
\thepage	836, 837
\thispagestyle	677

V

\vfill	738
\vspace	537, 593, 690, 731, 741, 763, 765
\vutinfth@allocate@polylingual	133, 134, 137, 138, 165
\vutinfth@bar@height	488
\vutinfth@bar@pivot@x	489, 497
\vutinfth@bar@pivot@y	490, 495, 499
\vutinfth@bar@width	487, 496, 503, 523
\vutinfth@bigskip	537, 701, 703, 705, 708, 710, 716, 718, 722, 724, 730
\vutinfth@bigskipamount	536, 537
\vutinfth@data@address	762
\vutinfth@data@firstreviewerdata	642
\vutinfth@data@regnumber	728
\vutinfth@data@secondreviewerdata	644
\vutinfth@def@data	46, 58
\vutinfth@def@data@invalid	50, 60
\vutinfth@def@person	70, 124
\vutinfth@def@person@invalid	107, 126
\vutinfth@f@family@tmp	36, 39, 41
\vutinfth@footer@titlepage	510, 533, 535
\vutinfth@header@placement	486, 680, 751
\vutinfth@header@titlepage	500, 527, 529
\vutinfth@HUGE	27, 693
\vutinfth@huge	27, 695
\vutinfth@LARGE	27, 702, 707, 714, 719
\vutinfth@Large	27, 711, 725
\vutinfth@large	27, 704, 709, 717, 723, 727
\vutinfth@logo@height	491, 494
\vutinfth@logo@offset@height	494, 502, 681, 752
\vutinfth@logo@offset@x	496, 505
\vutinfth@logo@offset@y	498, 506
\vutinfth@logo@pivot@x	492, 497
\vutinfth@logo@pivot@y	493, 495, 499
\vutinfth@normalsize	27, 513, 541, 572, 587, 629, 639, 651, 660, 733
\vutinfth@pagestyle@default	835
\vutinfth@pagestyle@titlepage	521

\vutinfth@pagestyle@titlepagefootrunwidth	531
\vutinfth@person@advisor@fullname	544, 574
\vutinfth@person@advisor@name	655, 670
\vutinfth@person@author@fullname	725, 761
\vutinfth@person@author@name	653, 663, 668, 766
\vutinfth@person@female	62, 68, 78, 79
\vutinfth@person@firstassistant@def	545, 550, 557
\vutinfth@person@firstassistant@error	551, 558
\vutinfth@person@firstassistant@fullname	547
\vutinfth@person@firstreviewer@name	632, 641
\vutinfth@person@male	62, 65, 75, 76
\vutinfth@person@secondadvisor@def	575
\vutinfth@person@secondadvisor@fullname	578
\vutinfth@person@secondassistant@def	549, 560
\vutinfth@person@secondassistant@error	561
\vutinfth@person@secondassistant@fullname	553
\vutinfth@person@secondreviewer@name	634, 643
\vutinfth@person@thirdassistant@def	556
\vutinfth@person@thirdassistant@fullname	563
\vutinfth@placedate@width	583, 590, 599
\vutinfth@polylingual@Advisor	543, 573
\vutinfth@polylingual@Assistance	546
\vutinfth@polylingual@BACHELORTHESIS	230
\vutinfth@polylingual@Bdeg	231
\vutinfth@polylingual@by	723
\vutinfth@polylingual@Curriculum	711
\vutinfth@polylingual@DdegRerNatFemale	307
\vutinfth@polylingual@DdegRerNatMale	305
\vutinfth@polylingual@DdegRerSocOecFemale	321
\vutinfth@polylingual@DdegRerSocOecMale	319
\vutinfth@polylingual@DdegTechnFemale	314
\vutinfth@polylingual@DdegTechnMale	312
\vutinfth@polylingual@degreename	206, 221, 707, 714
\vutinfth@polylingual@DIPLOMATHESES	271
\vutinfth@polylingual@DOCTORTHESIS	250
\vutinfth@polylingual@faculty	734
\vutinfth@polylingual@in	709
\vutinfth@polylingual@MASTERTHESIS	279, 283, 291
\vutinfth@polylingual@MdegDiplFemale	275
\vutinfth@polylingual@MdegDiplMale	273
\vutinfth@polylingual@MdegMaster	280
\vutinfth@polylingual@MdegRerNatFemale	287
\vutinfth@polylingual@MdegRerNatMale	285
\vutinfth@polylingual@MdegRerSocOecFemale	295
\vutinfth@polylingual@MdegRerSocOecMale	293
\vutinfth@polylingual@Pdeg	262

\vutinfth@polylingual@PHDTHESIS	261
\vutinfth@polylingual@Place	592
\vutinfth@polylingual@Registrationnumber	727
\vutinfth@polylingual@Reviewed	630
\vutinfth@polylingual@Reviewers	640
\vutinfth@polylingual@School	719
\vutinfth@polylingual@Secondadvisor	577
\vutinfth@polylingual@Statement	764
\vutinfth@polylingual@StatementChapter	760
\vutinfth@polylingual@submission	704
\vutinfth@polylingual@Subtitle	696, 697
\vutinfth@polylingual@thesisname	210, 219, 702
\vutinfth@polylingual@Title	693
\vutinfth@polylingual@university	735
\vutinfth@polylingual@within	717
\vutinfth@restorelayout	476, 745, 769
\vutinfth@savelayout	476, 683, 754
\vutinfth@selectlanguage@polylingual	152, 153, 156, 157, 168
\vutinfth@signature@height	583, 589, 606, 616
\vutinfth@signature@width	583, 603, 607, 610, 617, 620
\vutinfth@squarebullet	468, 515, 516, 517
\vutinfth@tempa	21, 24
\vutinfth@tempb	22, 24
\vutinfth@thesis@bachelor	214, 227
\vutinfth@thesis@basetype	175, 180, 198, 228, 234, 246, 257
\vutinfth@thesis@basetype@graduate	170, 181, 247, 258
\vutinfth@thesis@basetype@undergraduate	170, 176, 229, 235
\vutinfth@thesis@dddeg@rernat	299, 303
\vutinfth@thesis@dddeg@rersocoec	299, 317
\vutinfth@thesis@dddeg@techn	299, 310
\vutinfth@thesis@degreename	198
\vutinfth@thesis@doctor	214, 245
\vutinfth@thesis@doctortype	189, 194, 198, 248, 259
\vutinfth@thesis@doctortype@doctor	184, 190, 249
\vutinfth@thesis@doctortype@phd	184, 195, 260
\vutinfth@thesis@master	214, 233
\vutinfth@thesis@mdeg@dipl	265, 270
\vutinfth@thesis@mdeg@master	265, 278
\vutinfth@thesis@mdeg@rernat	265, 282
\vutinfth@thesis@mdeg@rersocoec	265, 290
\vutinfth@thesis@phd	214, 256
\vutinfth@thesis@thesisname	198
\vutinfth@tmp@baselineskip	473, 478, 483
\vutinfth@tmp@parindent	473, 477, 482
\vutinfth@tmp@parskip	473, 479, 484

	X	
<code>\xdef</code>	18