

lec51

Dylan Tang

May 2026

1 Multi-class Classification

Recall:

- Given $(X, Y)_{i=1}^n$, classify new point $y_i \in \mathcal{L}$ given x_i , where $\mathcal{L}$ is the class of labels
- Since labels are discrete, evaluate with confusion matrix rather than R^2

Confusion Matrix

	Predicted a	Predicted b	Predicted c
Actual a	n_{aa}	n_{ab}	n_{ac}
Actual b	n_{ba}	n_{bb}	n_{bc}
Actual c	n_{ca}	n_{cb}	n_{cc}

- **Precision:**

$$\text{Precision}_{\ell \in \mathcal{L}} = \frac{\# \text{ of True Positives}}{\# \text{ of Predicted Positives}} = \frac{TP}{TP + FP}$$

- Ex. Precision for class c is $\frac{n_{cc}}{n_{ac} + n_{bc} + n_{cc}}$

- **Recall:**

$$\text{Recall}_{\ell \in \mathcal{L}} = \frac{\# \text{ of True Positives}}{\# \text{ of Actual Positives}} = \frac{TP}{TP + FN}$$

- Ex. Recall for class c is $\frac{n_{cc}}{n_{ca} + n_{cb} + n_{cc}}$

```
from sklearn.model_selection import train_test_split
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import precision_score
X_train, y_train, X_test, y_test = train_test_split(X, y)
model = LogisticRegression()
model.fit(X_train, Y_train)
y_pred = model.predict(X_test)
precision_score(y_test, y_pred)
```