

Bachelor-Thesis

Human-Machine Interface for Operating a Blimb

Spring Term 2012

Supervised by:

Konrad Rudin
Mora Javier Alonso
Paul Beardsley XXXXX

Authors:

Krebs Matthias
Ledergerber Anton

Declaration of Originality

I hereby declare that the written work I have submitted entitled

Human-Machine Interface for Operating a Blimb

is original work which I alone have authored and which is written in my own words.¹

Author(s)

Anton	Ledergerber
Matthias	Krebs

Supervising lecturer

Konrad	Rudin
Javier Alonso	Mora
Paul XXX	Beardsley XXX

With the signature I declare that I have been informed regarding normal academic citation rules and that I have read and understood the information on 'Citation etiquette' (http://www.ethz.ch/students/exams/plagiarism_s_en.pdf). The citation conventions usual to the discipline in question here have been respected.

The above written work may be tested electronically for plagiarism.

Place and date

Signature

¹Co-authored work: The signatures of all authors are required. Each signature attests to the originality of the entire piece of written work in its final form.

Inhaltsverzeichnis

Abstract	v
Acknowledgements	vii
Symbols	ix
1 Introduction	1
1.1 Context	1
1.2 Goals	1
1.3 System Overview	1
1.4 Similar Systems and their HMI	1
1.5 Structure of the Report	1
2 Einige wichtige Hinweise zum Arbeiten mit L^AT_EX	3
2.1 Gliederungen	3
2.2 Referenzen und Verweise	3
2.3 Aufzählungen	3
2.4 Erstellen einer Tabelle	4
2.5 Einbinden einer EPS-Graphik	5
2.6 Mathematische Formeln	5
2.7 Weitere nützliche Befehle	6
3 Finding a Hardware and Software Solution	7
3.1 Requirements	7
3.2 Existing Solutions	7
3.2.1 Hardware	7
3.2.2 Software	7
3.3 Realization	7
3.3.1 Compact and Convenient Solution	7
3.3.2 QGroundControl	7
3.3.3 Mavlink	7
4 The different Control Modes	9
4.1 Evaluation	9
4.2 Manual Control Modes	9
4.3 Automatic Control Modes	9
5 Trajectory Planning	11
5.1 Definition	11
5.1.1 Paths and Trajectories	11
5.1.2 Interpolation and Approximation	11
5.1.3 Parametrization	11
5.1.4 Experimental Design	11

5.2	Spline Theory	11
5.2.1	Splines	12
5.2.2	Piecewise Polynomial Interpolating Splines	12
5.2.3	B-Splines	12
5.3	Trajectory Generation	12
5.3.1	System Constraints	12
5.3.2	Time Parametrization	13
5.4	Controller Implementation	13
5.4.1	Trajectory Controller	13
5.4.2	Pure Pursuit Position Controller	13
5.4.3	Cross Track Error Controller	13
5.5	Discussion	13
6	Conclusion	15
	Bibliography	16

Abstract

Hier kommt der Abstact hin ...

Acknowledgements

Without the help of a few people this thesis would not have been possible. We received the necessary support from all sides throughout the project to realize the this HMI which we are proud of.

Prof. Dr. Roland Y. Siegwart

Dr. Paul Beardsley

PhD students Konrad Rudin and Javier Alonso Mora

Gerhard Röthlin

Lorenz Meier

Alexander Rudyk

Symbols

Symbols

ϕ, θ, ψ	roll, pitch and yaw angle
b	gyroscope bias
Ω_m	3-axis gyroscope measurement

Indices

x	x axis
y	y axis

Acronyms and Abbreviations

ETH	Eidgenössische Technische Hochschule
EKF	Extended Kalman Filter
IMU	Inertial Measurement Unit
UAV	Unmanned Aerial Vehicle
UKF	Unscented Kalman Filter

Kapitel 1

Introduction

1.1 Context

1.2 Goals

1.3 System Overview

1.4 Similar Systems and their HMI

1.5 Structure of the Report

Kapitel 2

Einige wichtige Hinweise zum Arbeiten mit L^AT_EX

Nachfolgend wird die Codierung einiger oft verwendeten Elemente kurz beschrieben. Das Einbinden von Bildern ist in L^AT_EX nicht ganz unproblematisch und hängt auch stark vom verwendeten Compiler ab. Typisches Format für Bilder in L^AT_EX ist EPS¹.

2.1 Gliederungen

Ein Text kann mit den Befehlen `\chapter{.}`, `\section{.}`, `\subsection{.}` und `\subsubsection{.}` gegliedert werden.

2.2 Referenzen und Verweise

Literaturreferenzen werden mit dem Befehl `\cite{.}` erzeugt. Ein Beispiel: [3]. Zur Erzeugung von Fussnoten wird der Befehl `\footnote{.}` verwendet. Auch hier ein Beispiel².

Querverweise im Text werden mit `\label{.}` verankert und mit `\ref{.}` erzeugt. Beispiel einer Referenz auf das zweite Kapitel: Kapitel 2.

2.3 Aufzählungen

Folgendes Beispiel einer Aufzählung ohne Numerierung,

- Punkt 1
- Punkt 2

wurde erzeugt mit:

```
\begin{itemize}
  \item Punkt 1
  \item Punkt 2
\end{itemize}
```

Folgendes Beispiel einer Aufzählung mit Numerierung,

1. Punkt 1

¹Encapsulated Postscript

²Bla bla.

2. Punkt 2

wurde erzeugt mit:

```
\begin{enumerate}
  \item Punkt 1
  \item Punkt 2
\end{enumerate}
```

Folgendes Beispiel einer Auflistung,

P1 Punkt 1

P2 Punkt 2

wurde erzeugt mit:

```
\begin{description}
  \item[P1] Punkt 1
  \item[P2] Punkt 2
\end{description}
```

2.4 Erstellen einer Tabelle

Ein Beispiel einer Tabelle:

Tabelle 2.1: Daten der Fahrzyklen ECE, EUDC, NEFZ.

Kennzahl	Einheit	ECE	EUDC	NEFZ
Dauer	s	780	400	1180
Distanz	km	4.052	6.955	11.007
Durchschnittsgeschwindigkeit	km/h	18.7	62.6	33.6
Leerlaufanteil	%	36	10	27

Die Tabelle wurde erzeugt mit:

```
\begin{table}[h]
\begin{center}
\caption{Daten der Fahrzyklen ECE, EUDC, NEFZ.}\vspace{1ex}
\label{tab:tabnefz}
\begin{tabular}{l|ccc}
\hline
Kennzahl & Einheit & ECE & EUDC & NEFZ \\
\hline
Dauer & s & 780 & 400 & 1180 \\
Distanz & km & 4.052 & 6.955 & 11.007 \\
Durchschnittsgeschwindigkeit & km/h & 18.7 & 62.6 & 33.6 \\
Leerlaufanteil & \% & 36 & 10 & 27 \\
\hline
\end{tabular}
\end{center}
\end{table}
```


2.5 Einbinden einer EPS-Graphik

Das Einbinden von Graphiken kann wie folgt bewerkstelligt werden:

```
\begin{figure}[h]
  \centering
  \includegraphics[width=0.75\textwidth]{pics/k_surf.eps}
  \caption{Ein Bild.}
  \label{pics:k_surf}
\end{figure}
```




Abbildung 2.1: Ein Bild.

oder bei zwei Bildern nebeneinander mit:

```
\begin{figure}[h]
  \begin{minipage}[t]{0.48\textwidth}
    \includegraphics[width = \textwidth]{pics/cycle_we.eps}
  \end{minipage}
  \hfill
  \begin{minipage}[t]{0.48\textwidth}
    \includegraphics[width = \textwidth]{pics/cycle_ml.eps}
  \end{minipage}
  \caption{Zwei Bilder nebeneinander.}
  \label{pics:cycle}
\end{figure}
```

Bemerkung: Ersetzt man den Positionierungsparameter `h` durch `H`, so wird das Gleiten der Abbildung verhindert.

2.6 Mathematische Formeln

Einfache mathematische Formeln werden mit der `equation`-Umgebung erzeugt:

$$p_{me0f}(T_e, \omega_e) = k_1(T_e) \cdot (k_2 + k_3 S^2 \omega_e^2) \cdot \Pi_{max} \cdot \sqrt{\frac{k_4}{B}}. \quad (2.1)$$

Der Code dazu lautet:




Abbildung 2.2: Zwei Bilder nebeneinander.

```
\begin{equation}
p_{me0f}(T_e,\omega_e) \ = \ k_1(T_e) \cdot (k_2+k_3 \ S^2
\omega_e^2) \cdot \Pi_{max} \cdot \sqrt{\frac{k_4}{B}} \ , \ .
\end{equation}
```

Mathematische Ausdrücke im Text werden mit `$formel$` erzeugt (zB: $a^2 + b^2 = c^2$).

2.7 Weitere nützliche Befehle

Hervorhebungen im Text sehen so aus: *hervorgehoben*. Erzeugt werden sie mit dem `\epmh{.}` Befehl.

Kapitel 3

Finding a Hardware and Software Solution

References to [6]

3.1 Requirements

Remote Control, Intuitive Control for 6DoF, Livestream, Waypoints

3.2 Existing Solutions

3.2.1 Hardware

RC, Joystick, QGoSphere, 3dMouse, Wii Controller, Smartphones, Tablets, TabletPC

3.2.2 Software

QGroundControl, OpenPilot, Qt-Libraries

3.3 Realization

3.3.1 Compact and Convenient Solution

About advantages of TabletPC, 3dMouse, RC

3.3.2 QGroundControl

Adaptions in QGroundControl, 3dMouse, Touchscreen, Splines and Trajectory Controller

Only how it looks like and how to use. 3dMouse and Touchscreen are not described further, splines, trajectories and trajectory controller are described in chapter 5

3.3.3 Mavlink

Summary of Protocol, adaptions and use for SKYE

Kapitel 4

The different Control Modes

4.1 Evaluation

About the need of different modes, the requirements of image capturing and overview of the realized modes

4.2 Manual Control Modes

Direct Control and Assisted Control

4.3 Automatic Control Modes

Half Automatic Control and Full Automatic Control

Kapitel 5

Trajectory Planning

For the two most advanced modes, i. e. the Half-Automatic and the Full-Automatic Mode, trajectories had to be generated. In this chapter the best trajectories for SKYE are elaborated.

5.1 Experimental Design

5.2 Definition of Trajectories

5.2.1 Paths and Trajectories

5.2.2 Interpolation and Approximation

If one wants to draw a line through a set of data points, there exists two ways to do this. On the one hand the line must pass all data points no matter how many bends it will have, on the other hand the line tries to best fit the data, i.e. a function of a certain order is adopted to best fit the data. E.g. this can be done with least-squares. If the pilot defines the trajectory with a set of waypoints, i.e. data points, he usually wants the (UAV already defined?!!!!) to pass through all of them. Therefore the waypoints must be interpolated and not approximated with a suitable curve.

(!!!Bsp Plot von interpolierenden und approximierenden funktionen!!!)

5.3 Spline Theory

A set of data points can be interpolated with one single curve or with a set of curves defined over a certain interval. For a references to [1], [2] and [?]

Continuity

Boundary Conditions

Polynomial Order

Parametrization

5.3.1 Piecewise Polynomial Interpolating Splines

Boundary Conditions

Polynomial Order

Parameterization

5.3.2 B-Splines

Boundary Conditions

Polynomial Order

Parametrization

5.4 Trajectory Generation

5.4.1 System Constraints

Maximum Velocities and Accelerations

In order to plan a feasible trajectory one has to know the capabilities of the system. Here just a basic derivation for the velocities and accelerations is given, for more details refer to (!!!!Bsc Thesis Joe, Bsc Thesis Andy)

The maximum feasible acceleration in any direction is calculated to be:

$$|a_{max}| = \frac{|F_{res,w}|}{m_{tot}} = 0.96m/s^2 \quad (5.1)$$

Whereas the $F_{res,w}$ is the force resulting from all four thrusters operated under full load in the worst direction and m_{tot} is the sum of the masses of the helium, the virtual mass and the mass of the system itself.

The maximum feasible velocity in any direction is calculated to be:

$$|v_{max}| = \sqrt{\frac{|F_{res,w}|}{\frac{1}{2}c_d\rho\pi r^2}} = 2.9m/s \quad (5.2)$$

which is nothing but $|F_{res,min}| = |F_{drag}|$.

For trajectories for position and orientation the maximal feasible angular acceleration is also important. It is calculated to be:

$$|\Psi_{max}| = \frac{|M_{res,w}|}{|\lambda_{max,J_B}|} = 2.06rad/s^2 \quad (5.3)$$

which is quite conservative because it is assumed that worst axis for turning is also the principle axis of the inertia tensor with the highest inertia.

Since the system is almost undamped for rotations, the rotational velocities will never be the limiting factor.

5.4.2 Time Parametrization

5.5 Controller Implementation

5.5.1 Trajectory Controller

see [3] and [4]

5.5.2 Pure Pursuit Position Controller

see also [3]

5.5.3 Cross Track Error Controller

see [5]

5.6 Discussion

Kapitel 6

Conclusion

Literaturverzeichnis

- [1] G. ENGELN-MÜLLGES, K. NIEDERDRENK, R. WODICKA: *Numerik- Algorithmen : Verfahren, Beispiele, Anwendungen*. Springer Verlag, 2011.
- [2] L. BIAGIOTTI, C. MELCHIORRI: *Trajectory Planning for Automatic Machines and Robots*. Springer Verlag, 2008.
- [3] J. M. SNIDER: *Automatic Steering Methods for Autonomous Automobile Path Tracking*. Research Report CMU-RI-TR-09-08, Robotics Institute Carnegie Mellon University Pittsburgh, Pennsylvania, 2009.
- [4] A. DE LUCA, G. ORIOLO, C. SAMSON: *Feedback Control of a Nonholonomic Car-Like Robot*. In *Robot Motion Planning and Control*, pages 171-249, 1998.
- [5] D. L. WILLIAMS: *Loitering Behaviors of Autonomous Underwater Vehicles*. MSc thesis, Naval Postgraduate School, Monterey, California, 2002.
- [6] T. KAMMERMANN: *Evaluation and implementation of a control device for a ballbot*. BSc thesis, ETH Zurich, 2010.
- [7] S. DÖSEGGGER: *Time-optimal trajectories for a Ballbot*. BSc thesis, ETH Zurich, 2010.
- [8] J. WEICHART: *Agile Blimp Modeling and Simulation Environment*. BSc thesis, ETH Zurich, 2012.
- [9] D. MEIER, L. MÜRI: *Agile Blimp Controller Design*. BSc thesis, ETH Zurich, 2012.
- [10] WON Y. YANG, [ET AL.]: *Applied Numerical Methods Using MATLAB*. Wiley-Interscience, Hoboken, 2005.
- [11] J. BLANCHETTE, M SUMMERFIELD: *C++ GUI Programming with Qt 4*. Prentice Hall, Upper Saddle River, N.J., 2010.
- [12] E. T. Y. LEE: *Choosing nodes in parametric curve interpolation, Computer-Aided Design*. pages 363-370, (<http://www.sciencedirect.com/science/article/pii/0010448589900031>), 1989