

THESIS' TITLE

eingereichte
DIPLOMARBEIT
von

cand. ing. Vorname Nachname

geb. am xx.xx.19xx
wohnhaft in:
Musterstrasse xx
8xxxx München
Tel.: 089 1234567

Lehrstuhl für
INFORMATIONSTECHNISCHE REGELUNG
Technische Universität München

Univ.-Prof. Dr.-Ing. Sandra Hirche

Betreuer:	Dipl.-Ing./Dr. Betreuer/in
Beginn:	xx.xx.201x
Zwischenbericht:	xx.xx.201x
Abgabe:	xx.xx.201x

In your final hardback copy, replace this page with the signed exercise sheet.

Abstract

A short (1–3 paragraphs) summary of the work. Should state the problem, major assumptions, basic idea of solution, results. Avoid non–standard terms and acronyms. The abstract must be able to be read completely on its own, detached from any other work (e.g., in collections of paper abstracts). Don't use references in an abstract.

Zusammenfassung

Hier die deutschsprachige Zusammenfassung

Contents

1	Working with this Template	5
1.1	Style and Expressions	5
1.1.1	Subsection	5
1.2	Compiling	6
1.3	Equations	6
1.4	Figures	6
1.5	Citations	7
2	Introduction	9
2.1	Problem Statement	10
2.2	Related Work	10
2.2.1	Control schemes for rigidly connected manipulators	11
2.2.2	Friction grasps in Cooperative Manipulation	12
2.2.3	A passivity based control structure	13
2.2.4	Determination of desired internal forces	14
3	Main Part	17
3.1	Design of your solution	17
3.2	Implementation	17
3.3	Experimental Results	18
3.4	Discussion	18
4	Conclusion	19
	List of Figures	21
	Bibliography	23

Chapter 1

Working with this Template

Make sure your thesis is well structured, that each major section does what it is supposed to do, and that the whole thing hangs together. The basic structure is often as given in this template (but other structures are possible). In particular, don't think you need to have exactly as many major sections or chapters as the list implies; sometimes it makes sense to merge things, sometimes it makes sense to move things (e.g., the literature review is in many papers deferred until after the results), sometimes it makes sense to split a logical part into several individual sections. Just use some common sense.

Hand in your thesis at minimum **one week** before the deadline for correction. You will receive feedback for the final version and very likely have to do minor or major revisions of your writing. Plan your writing schedule to allow for these adjustments, which can have quite some impact on your grade!

1.1 Style and Expressions

Before handing in your thesis, even for an intermediate review, please perform a spellcheck and correct grammar mistakes. The report is not meant to be a narrative text. Please stick to neutral and technical style and avoid subjective or biased expressions or adjectives/adverbs such as *obviously*, *always*, *very*, *especially well*, *actually*, *so-called etc.* Scientific writing is about precision and you should underpin your statements factually, not soften them with unnecessary qualifiers.

1.1.1 Subsection

Use chapters, sections and subsections to structure your document

Subsubsection

Subsubsections can be used to further structure information within a subsection. They don't show up in your list of contents.

Paragraphs are sometimes more useful than subsubsections to structure text without breaking the flow.

1.2 Compiling

Linux: do the following in a Shell:

```
latex myfile
dvips myfile
ps2pdf -sPAPERSIZE=a4 myfile.ps
```

Make sure to use the A4 option, when you print the pdf!

1.3 Equations

Equations are written like that x^2 . Or like that:

$$x^2 \tag{1.1}$$

You can use (1.1) to reference an equation in the text. Equations without reference number:

$$x^2$$

Please type all numbers in mathematics mode. Mathematical equations which are not part of the text should be centred. A parameter or variable must not be used at the beginning of a sentence. Type physical units as normal text, e.g. s, not s ! Formulas must not jut out over the text margin, so take care to stay within the margins and eventually break the equation into several lines. Explain the variables you use. For each newly introduced variable, at least a short description of it should follow the equation in the style of *... with x being the position of the cart and u the control input*. In columns, align equations with the arithmetic operator ($=, <, \dots$). Mathematical units must be consistently labeled with only one variable. Do not use a variable for more than one mathematical unit.

1.4 Figures

For pictures, it is convenient, if they are .eps.

Figure 1.1: Long Description: The subtitles of tables and illustrations should be self-explanatory.

Every illustration must be described and referenced in the text, cf. Fig. 1.1. There is no such thing as a decorative figure! If the figure is not mentioned in the text and therefore lacks an explanatory function, leave it. Lines in plots need to be clearly distinguishable, also in black-and-white print. The subtitles and axis labels must be clearly legible (i.e. big enough) and include a scaling. If the illustration is copied from another person's work, you need to mention the source with `\cite{}`.

1.5 Citations

For bibliography, edit `mybib.bib` and list all references in a special style, e.g. for a book:

```
@book{literaturselle1,
  author    = {S. Sastry},
  title     = {Nonlinear Systems - Analysis, Stability, and Control},
  publisher = {Springer},
  year      = 1999
}
```

Cite references in the text by.

In order to have your references shown in your PDF, compile by:

```
latex myfile
bibtex myfile
latex myfile
latex myfile
dvips myfile
ps2pdf -sPAPERSIZE=a4 myfile.ps
```

Whether to use numeric or alphabetic references isn't all that important (unless prescribed by a conference or journal), but alphabetic tends to be more readable. Independent of citation style, the following rules should be followed:

- Use the `LATEX` cite package. It doesn't give you additional commands, but it fixes a few quirks in `LATEX`. Among others it automatically sorts multiple citations, and it correctly spaces the angular brackets (if you use the `\cite` command without leading white space).
- Citing several papers at one point should be done with a single `\cite` command. For example, use `gives good results\cite{Bloe_99, Jay_87}`, resulting in gives good results [BJ99, Jay99].

Do not use `gives good results\cite{Bloe_99}\cite{Jay_87}` which produces the ugly gives good results [BJ99][Jay99]. Also, note that there is no space between the `\cite` command and the preceding word, `LATEX` (with the cite package) does the spacing correctly.

- Avoid citations of the kind: [BJ99] thinks that $x > y$ is valid, but [OLH00] argues that this is invalid in case of $z \geq 5$. This works a bit better if using alphanumeric citation labels. Better, though, use the author's names: Bloe and Joe [1] think that $x > y$ is valid, but O'Neill et al. [OLH00] argues that this is invalid in case of $z \geq 5$.
- BibTeX is a great tool, but you need to know how to use it. A regular trap is to forget that TeX knows more about typesetting than you do. So, for example, it changes the case of words in the title. If your title contains acronyms and proper names (most do), they tend to get down-cased. Any such words which should not have their case changed should be put into braces, e.g., `{The {Mungi} {OS} and its Use in Merry-Go-Round Seat Allocation}`.
- In citations don't abuse the category technical report. People tend to cite just about anything that hasn't been published in a journal or conferences as a TR. This is outright wrong. The concept of a TR is actually fairly well defined: A TR is published in some sort. This is generally as part of a formal TR series of some institution, in hardcopy or on the web or both. (They aren't always called "technical report", other common names are "research report", "technical memorandum", <institution> "report" etc.) The publication (i.e. availability outside) is essential, otherwise it's at best an internal report. A TR has a number (absolutely!), an institution (publisher), a date (month and year at least) and a publisher's address (besides all the other stuff bibentries have). If your document doesn't have these features, it's not a TR. It's probably better categorized as a working paper. Even then it has a date and an institution address.
- Citing web pages is often unavoidable (but also often a sign of laziness). When citing web pages be aware that they may only be short-lived. Consider whether the reference will be of any use to the reader at all if the link is broken. Or whether your whole document only has a use-by date a few months past writing.

Any cited document, whatever it may be, has a few **mandatory** features:

- Date. Absolutely.
- Author/organization/creator/person responsible for contents.
- Whatever information the reader needs to find that document. In most BibTeX entry types these are clearly identified as mandatory fields. Mandatory means that they aren't optional. Don't pretend they are. For a working paper these might be the contact details of the author.

Chapter 2

Introduction

Cooperative manipulation involves two or more robots collectively moving or manipulating a common object. Such a set-up overcomes many limitations seen by single robots. Tasks for cooperative manipulators are for instance, carrying of large or heavy objects, grasping of objects without special fixtures and even manipulation of flexible objects.

The major challenge is to simultaneously control the forces between the manipulators and the object, so to say the internal stress exerted on the object, and the forces between the object and the environment, i.e. the absolute motion of the object. Strategies that map force and velocity of the object to the manipulators have to be considered.

One important assumption is the nature of the connection between manipulator and object. It can be seen as rigid or more general as friction-based. With a rigid fixture the grasp is always stable, on the contrary friction grasps need to be actively stabilized. To comply with the friction constraints a contact normal force has to be set, dependent on the tangential components present during manipulation.

Towards a versatile usage of cooperative manipulation it is vital to let the human operator control the robotic system intuitively and naturally. A promising approach is gesture control. Gioioso et al. [GFS⁺14] demonstrated this for a formation of unmanned aerial vehicles. They are able to control opening and closing of the grasp. In a grasped state the objects's pose and the grasping forces can be changed, just by tracking gesture of a single human hand. Directly integrating the human into the control scheme makes use of the visual tracking capacities of the human and eases operation in unknown environments. Regardless of the operator being present on-site with the robots or not, hand tracking and analysis requires a certain time. This delay in the control loop can cause instability. The problem can be modelled as a transmission line with delay and treated with methods known from tele-operation. The human takes the role of a supervisor, representing a high-level part of the control scheme. He is responsible for planning, choosing a trajectory and if necessary setting of grasping forces. On a local low-level robots need to coordinate their motion compliant with the commanded trajectory and adjust their formation to realize

the desired internal forces. For non-rigid fixtures the local robot controller requires the position of the other manipulators. The local communication between the robots causes delay, which has to be treated with tele-operation techniques in order to ensure stability.

Haptic feedback??

2.1 Problem Statement

You can either state the problem you are trying to solve in the general introduction, providing the transition from the overall picture to your specific approach, or state it in a separate section. Even if you don't use the separate section, writing down in a few sentences why the problem you are trying to solve is actually hard and hasn't been solved before can give you a better idea of how to approach the topic. This can be also merged with the related work part.

Manipulating an unknown object in an unstructured environment is an interesting task for a human-guided cooperative manipulation set-up. Dropping the assumption of a rigid-connection between manipulator and object, the grasp has to be actively stabilized under varying circumstances. During dynamic manipulation a slipping of contact due to the inertia of the object has to be avoided using an automatic mechanism. On the other hand the operator must directly adjust grasp forces for heavy or fragile objects.

Position and velocity of the manipulated object are difficult to track in an everyday setting. Usually only end-effector position and velocity of the robots are available. Object position has to be estimated from the known data.

For grasping an object of unknown or even flexible shape, the determination of a fixed grasp map in advance is not useful. Size and shape of the grasp have to be determined by the operator during the grasp process. The controller has to be flexible to varying grasp geometries during the whole task execution.

Integrating the human into the control loop, energetic passivity of the closed loop system is a meaningful and intuitive way to ensure stability and a natural way of interaction. Energetic passivity limits the extractable mechanical energy from the closed loop system. This means that the potential damage is also limited. Energetic passivity of the robotic system ensures stability of the interconnection stability with any passive systems. Since humans and many relevant environments are passive the closed loop system will always be stable if the overall control scheme is designed energetically passive.

2.2 Related Work

Control strategies suitable for Cooperative Manipulation can be classified dependent on the nature of the manipulator-object connection: rigid-fixture and friction-grasps.

An import group within the former are the hybrid position/force control approaches. Control action is decomposed in a motion control loop, accounting for the tracking of the desired trajectory for the overall system and a force control loop to control the internal forces on the object. A pre-defined selection matrix determines for every workspace coordinate whether it is position or force controlled. Controlling the robot on joint level, the necessary torques can be computed using a PD plus gravity compensation control scheme. The desired joint positions and velocities are computed by inverse kinematics [WKD92]. Object level control architectures often use feedback linearisation of the non-linear manipulator dynamics to achieve a linear and decoupled control of motion and grasping force [Hsu93]. Force control is only meaningful if contact between manipulator and object. Motion control leads to unbounded forces if the motion direction is not consistent with the constraints, since force in this direction is not controlled. The transition between contact and no contact during grasping cannot be handled with these approaches. For these reasons in the following only the better suited impedance control schemes are considered. Impedance control, introduced by Hogan [Hog84], is a well known strategy to avoid unbounded forces when it comes to interaction of manipulators with objects/environment. It does not control one state variable (position, velocity, force) dynamically enforces a relation between forces and system state. Contact directions do not have to be pre-specified. The controller is stable independently of the contact state. A physical analogy the impedance control scheme is a spring-mass-damper system.

2.2.1 Control schemes for rigidly connected manipulators

A rigid fixture between manipulator and object means that both forces and moments are exchanged at the grasp points: all translational and rotational motion components can be transmitted through the contact points. The rigid connections are expressed by a number of kinematic constraints, which reduce the Degrees-of-Freedom (DoF) of the constrained system. The attempt to move in the constrained directions results in internal loading of the object. Therefore trajectories of the manipulators have to be generated to avoid internal stress on the object. Assuming a rigid connection normally no grasping force is needed to stabilize the grasp, i.e. internal forces are undesired because possibly harmful to the object. Nevertheless some papers propose possibilities to specify or control internal forces.

Among the first to use impedance control in cooperative manipulation were Schneider and Cannon [SC92]. They replaced the actual object by a virtual mass and connected it to the environment with a spring and a parallel damper. The resulting impedance equation is:

$$M_{o,d}(\ddot{x}_o^d - \ddot{x}_o) + D_o(\dot{x}_o^d - \dot{x}_o) + K_o(x_o^d, x_o) = h_{ext} \quad (2.1)$$

Here $M_{o,d}$ denotes the inertia of the virtual object, D_o is the damping along the spring, which is represented by $K_o(x_d, x)$. $x_o = (p_o^T, Q_o^T)^T$ is the stacked vector of position and orientation of the object. x^d denotes a desired quantity. The external wrench, exerted by the environment on the object, $h_{ext} = (f_{ext}^T, t_{ext}^T)^T$ consists of force and torque vectors. The dynamics of the virtual object is then given as:

$$M_{o,d}\ddot{x} = -h_{ext} + h_o^\Sigma = -h_{ext} + M_{o,d}\ddot{x}_d + D_o(\dot{x}_d - \dot{x}) + K_o(x_d, x) \quad (2.2)$$

The resulting impedance control output h_o^Σ is then mapped to the manipulators using a generalized inverse of the grasp matrix:

$$h^\Sigma = G^\dagger h_o^\Sigma \quad (2.3)$$

Performance of this strategy depends on choosing the virtual inertia close to the actual, i.e. good knowledge of the object is required. Furthermore gravity compensation would be necessary to model the full object dynamics. In general the equation of motion for a rigid object is:

$$M_o\ddot{x}_o + C_o\dot{x}_o + g_o = h_{ext} + h^\Sigma \quad (2.4)$$

Wherein M_o is the actual object inertia, C_o is the Matrix accounting for the Coriolis force and g_o is the gravity. For notational convenience the pose dependencies of the parameter matrices, e.g. $M_o(x_o)$, are omitted.

Bonitz and Hsia [?] propose to model each manipulator as an impedance relation. Thereby a relation between manipulator dynamics and internal forces on the object is enforced:

$$M_i(\ddot{x}_i^d - \ddot{x}_i) + D_i(\dot{x}_i^d - \dot{x}_i) + K_i(x_i^d, x_i) = h_{int} \quad (2.5)$$

$M_i, D_i, K_i(x_i^d, x_i)$ are the desired inertia, damping and stiffness representations of the i -th manipulator.

2.2.2 Friction grasps in Cooperative Manipulation

A common assumption in Cooperative Manipulation is a rigid-connection between object and manipulators. This is a bilateral constraint with 6 Degrees-of-freedom (DoF), allowing the manipulator to push and pull the object in 3D space as well as to transmit moments around all axis. This assumption is reasonable if the manipulator is equipped with appropriate devices. In analogy to a human this device would be fingers wrapping around an inhomogeneity on the object, to achieve a form-closure grasp. For an even object (e.g. ball) humans often use their hand palms to realize a friction grasp. Grasp stability is ensured by pressing the object. This approach can be represented with either the Point Contact with Friction (PCwF) or the soft contact model. Technical applications where cooperative manipulators should be able to do a friction grasp are numerous, e.g. when no appropriate grasping device is available (or shall be avoided) or the object structure is not graspable.

Research of friction grasps is mainly done with robotic hands [references here], internal forces are chosen sufficiently high to maintain a stable grasps. Undesired or unnecessary and possibly harmful internal forces, which occur during dynamic manipulation of the object, however are a minor concern. Discrete robots in cooperative manipulation are often powerful, enabling them to handle heavy objects. But on the other hand they are able to destroy the object if internal wrenches are not properly controlled. Allowing a human to directly control the formation (e.g. with gestures), three parameters are to be specified by the operator: position, orientation and grasping force. Tracking and processing human inputs causes a delay, which can be compared to a telemanipulation setting, although the operator may be on-site. A local controller is required to ensure a secure grasp while human interfacing can be higher level control.

2.2.3 A passivity based control structure

The controller is divided into two parts, the local one does the real-time interaction of the manipulators with the object. This part is passive, i.e. the robot along with its local controller has a certain amount of energy, the energy can not increase as long as no power is provided by the environment or the higher-level control part. Therefore the two parts will be called Intrinsically Passive Controller and Supervisor, this scheme was introduced by Stramigioli [??] as a general framework with application to robotic hands.

The Intrinsically Passive Controller (IPC)

The IPC has a physically meaningful behaviour, because it is described by a spatial interconnection of springs, inertias and dampers. Each manipulator is represented by an inertia and connected to the (virtual) object by a spatial spring. The object is modelled by a virtual inertia and its dimensions are represented by a sphere that does not necessarily coincide with the actual shape. The resulting virtual object is subjected to forces exerted by the manipulator springs and is connected to the environment with another spatial spring. This ensures compliant behaviour between object and environment and manipulators and environment. Furthermore object movement is damped with respect to the inertial frame. Dynamic behaviour of the virtual object is simulated in real-time, so no tracking of the object is necessary. The only values that have to be measured are the end-effector positions, the object speed required for the damping term is computed in the simulation. Dampers parallel to the manipulator-object springs are applicable if manipulator speed is measurable. By choosing the rest-length of the manipulator-object springs a internal force can be indirectly specified. This rest-length can be adjusted on-line without violating passivity, so the operator can adjust grasp forces if necessary (e.g. opening closing grasp). Another example for on-line adjustment of grasp forces is having them

determined dependent on dynamic requirements, e.g. higher internal forces during acceleration to satisfy the contact friction constraints at all time.

The Supervisor

The higher control part has the role of planning and scheduling. It controls the state of energy of the IPC and robot. Trajectory and formation of the manipulators are determined, e.g. moving the robots independently to open or close the grasp, directing the formation of robots to move the object. The grasping process can be controlled by changing the virtual object sphere size. Translation or rotation of the grasped object can be commanded by setting the desired virtual object pose. A human operator taking tasks of the Supervisor causes a delay which can be modelled as transmission line with delay between Supervisor and IPC. The control architecture is still valid in a teleoperation setting. Using scattering the passivity of the IPC can be preserved.

2.2.4 Determination of desired internal forces

Non-rigid grasps object and manipulators are connected with friction constraints. Contact force towards the object generates frictional force opposed to external forces tangential to the contact point. If the tangential forces exceed the frictional force the friction constraint is violated and contact slippage occurs. Squeezing or internal forces do not contribute to the motion of the constrained system. They need to be chosen sufficiently high to maintain a stable grasp under external forces acting on the object. On the other hand they must be bounded to not damage the object. These opposed requirements can be formulated as a cost function.

Buss et al. [BHM96] propose a cost function consisting of two factors: one is a barrier function tending to infinity for violating the friction constraint limit, the other is linear function rising with the exerted force, making high forces costly. The optimal desired internal force is the minimum of the cost function, thus the forces are chosen as small as possible, preserving a stable grasp.

Non-linear friction constraints are given for the *point contact friction* and the *soft contact friction* model:

The *point contact friction* constraint allows transmitting force in tangential and normal (only towards the object) direction. In addition the *soft contact* constraint transmits the torsional moment around the normal axes. Buss' main contribution is that friction constraints can be reformulated equivalent to positive definite matrices. These matrices are used to construct the cost function. This results in a convex optimization problem, thus an optimum is always a global optimum.

Bicchi et al. [BPA98] limit their contribution to the *point contact friction* model but expand the cost function. A maximum contact force is introduced, this is useful for rather losing contact than destroying the object. Furthermore a minimum force in normal direction is specified to ensure grasp stability even under uncertainties.

This two add up to with the friction constraint to a function, which has a negative scalar value if the set of constraints are respected. The sum of this functions for all contact points forms the cost function.

Han et al. [HTL00] reformulated Buss' positive definite matrix approach as a *linear matrix inequality*(LMI) problem. Being a common optimization task, efficient solvers (e.g. interior point algorithm) exist. Calculation time could be significantly reduced.

Chapter 3

Main Part

3.1 Design of your solution

Having explained the problem, and what others have done in similar situations, now explain your approach. Again, give a general overview of your design first, and then go into detail. The important part here is the concept of your work, not the actual implementation! Make sure that the document (particularly a thesis) is self-contained: It should be possible for a reader familiar with the general area to understand your design. Again, be forthright about the limitations of your design. Also, make sure you justify any shortcuts/limitations convincingly.

3.2 Implementation

In many (not all cases) there is a clear difference between the general approach (design) and its implementation in your particular circumstances. The design may be more general than what you can do given time and resources. Or you have developed a general design, and are now implementing a prototype on particular hardware. Give all required details. It should be possible to understand all this without referring to the source code.

This will, in general, include extracts of actual algorithms and hardware components used. Don't list pages of C code, an electronic copy of the source will accompany the submission and should be available to the marker, so there's no point in killing extra trees to put it into the report. Source code, if included at all, goes into the appendix and not the main document.

Make sure you describe your implementation in enough detail. Someone who has nothing else but your thesis report to go by should be able to repeat your work, and arrive at essentially the same implementation. Reproducibility is an important component of scientific work. Also, clearly state the limitations of your implementation, and justify them.

3.3 Experimental Results

A thesis almost always has an experimental part, typically some comparison to other approaches. Benchmarking takes time, for running the experiments, but also for thinking them up in the first place, and for analysing the results. Plan accordingly to spend enough time here!

Think about what makes sense to measure, what you want to learn from your measurements. Think about what is really the relevant contribution of your thesis, and how you can prove that you have achieved your goals. Think about what you can measure in order to get a good insight into the performance of various aspects of your design, how you can distinguish between systematic and accidental effects, how you can convince yourself that your results are right. If you get surprising results, don't just say "surprise, surprise, performance isn't as good as hoped". Find out why. Surprises without explanation indicate either that you are clueless about what's going on, or that you have made a mistake. Unconvincing results, therefore, tend to imply unconvincing marks.

Statistics: Measurements always have statistical (sampling) errors. Owing to the deterministic nature of simulations these are sometimes very small, as disturbing factors can be designed. However, the reader should be given an indication of how statistically significant the results are. This is done by providing at least a standard deviation in addition to averages. Whenever the results of several runs are averaged, a standard deviation can (and must) be supplied. After all, you average to reduce statistical errors.

The reproducibility argument applies here just as much as for the implementation. Give enough detail on what you measure, and how you measure it, so that someone who has your implementation (but not your test code) or has re-done your implementation independently, should be able to repeat your measurements and arrive at essentially the same results. In some cases, results seem outright wrong in a thesis. In those cases, not enough detail is provided to allow the supervisor/reader to pinpoint the likely source of the error. Often the cause is systematic errors resulting from an incorrect measurement technique. If it seems wrong, and the text doesn't convince the reader that it is not wrong, the reader will assume that it is wrong.

3.4 Discussion

Discuss and explain your results. Show how they support your thesis (or, if they don't, give a convincing explanation). It is important to separate objective facts clearly from their discussion (which is bound to contain subjective opinion). If the reader doesn't understand your results, reconsider if you have managed to extract the core information and explain it in a straightforward way.

Chapter 4

Conclusion

Don't leave it at the discussion: discuss what you/the reader can learn from the results. Draw some real conclusions. Separate discussion/interpretation of the results clearly from the conclusions you draw from them. (So-called "conclusion creep" tends to upset reviewers. It means surrendering your scientific objectivity.) Identify all shortcomings/limitations of your work, and discuss how they could be fixed ("future work"). It is not a sign of weakness of your work, if you clearly analyse and state the limitations. Informed readers will notice them anyway and draw their own conclusions, if not addressed properly.

Recap: don't stick to this structure at all cost. Also, remember that the thesis must be:

- honest, stating clearly all limitations;
- self-contained, don't write just for the locals, don't assume that the reader has read the same literature as you, don't let the reader work out the details for themselves.

This chapter is followed by the list of figures and the bibliography. If you are using acronyms, listing them (with the expanded full name) before the bibliography is also a good idea. The acronyms package helps with consistency and an automatic listing.

List of Figures

1.1	Abbreviated Description	6
-----	-----------------------------------	---

Bibliography

- [BHM96] M. Buss, H. Hashimoto, and J.B. Moore. Dextrous hand grasping force optimization. *Robotics and Automation, IEEE Transactions on*, 12(3):406–418, 1996.
- [BJ99] Adam Bloe and Fred Joe. Towards a unified solution of $x > y$. *Math and other geeky stuff*, 1(1):1–23, 1999.
- [BPA98] A. Bicchi, D. Prattichizzo, and G. Antognetti. Optimization of internal forces in force-closure grasp. *Proc. of the the 6th IEEE Mediterranean Conf. on Control and Systems*, 16(6), 1998.
- [GFS⁺14] G. Gioioso, A. Franchi, G. Salvietti, S. Scheggi, and D. Prattichizzo. The flying hand: A formation of uavs for cooperative aerial tele-manipulation. *Robotics and Automation (ICRA), 2014 IEEE International Conference on*, pages 4335–4341, May 2014.
- [Hog84] N. Hogan. Impedance control: An approach to manipulation. *American Control Conference*, pages 304–313, June 1984.
- [Hsu93] P. Hsu. Coordinated control of multiple manipulator systems. *Robotics and Automation, IEEE Transactions on*, 9(4):400–410, 1993.
- [HTL00] L. Han, J.C. Trinkle, and Z.X. Li. Grasp analysis as linear matrix inequality problems. *Robotics and Automation, IEEE Transactions on*, 16(6):663–674, 2000.
- [Jay99] D Jay. Applications of $x > y$ with respect to constraints in y and bounded x . *Journal of Solutions to Bounded Inputs*, 1(3):66–99, 1999.
- [OLH00] James O’Neill, Stan Laurel, and Oliver Hardy. On the correctness of $x > y$: Limits in the case of $z > 5$. *Math and other geeky stuff*, 5(3):56–87, 2000.
- [SC92] S.A. Schneider and R.H. Cannon. Object impedance control for cooperative manipulation: theory and experimental results. *Robotics and Automation, IEEE Transactions on*, 8(3):383–394, 1992.

- [WKD92] J. Wen and K. Kreutz-Delgado. Motion and force control of multiple robotic manipulators. *Automatica*, 28(4):729–743, 1992.

License

This work is licensed under the Creative Commons Attribution 3.0 Germany License. To view a copy of this license, visit <http://creativecommons.org> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California 94105, USA.