Control of a multi-robot cooperative team guided by a human operator

M. Angerer

Intermediate Presentation Master Thesis

Betreuer: S. Musić

Lehrstuhl für Informationstechnische Regelung

Technische Universität München

Why use human guided cooperative manipulation?



Human reasoning

- Foresight and adaptiveness to incidents
- Superior planning capabilities

Enhanced flexibility of multiple robots

- Transportation of large/heavy objects
- Assembly of multiple parts
- Coordinated use of tools

Problem setting

- A set of robots manipulating a common object
- A human guiding the formation by hand motion



Goal

- Consistent modelling of constrained systems
- Model-based control with human-in-the-loop

Related Work

Robot-team control

- Virtual object based impedance control [SC92]
- Internal and external impedance control [CV01,CCMV08]
- Intrinsically Passive Control [Str01,WOH08]
- Object dynamics' feed-forward [EH15]
- Formation control of a robot team [SMH15,WOH06]

Human in the loop

- Formation-based control [SMH15,SMP14]
- Bilateral tele-manipulation [LS05]
- Gesture-based Control [GFS+14]

- port-Hamiltonian systems allow for energy consistent modelling of complex physical systems
- *IPC* concept based on a physical model
- Closed loop stability for bounded energy supply

port-Hamiltonian systems

Idea

Network representation of interconnected non-linear physical systems

Hamiltonian H: total energy of the system
Port: a pair (f, e) of *flow* f and *effort* e variables

$$\dot{x} = J(x)\frac{\partial H}{\partial x}(x) + g(x)f$$
$$e = g^T(x)\frac{\partial H}{\partial x}(x)$$

state-space representation with *structure matrix* $J(x)$,
input matrix $g(x)$
Energy balance: power exchanged through a port $\frac{d}{dt}H = e^T f$

Interconnection and elements

Structure of a port-Hamiltonian system



Elements are geometrically interconnected by the *energy routing* structure $\mathcal{D}$

- Energy storing elements (inertia, spring)
- Energy dissipating elements (damper)
- Energy conservative elements (transformer, gyrator)

Energy supply through port (f_p, e_p) from *operator* or *environment*

System model

$$\begin{pmatrix} \dot{x}_M \\ \dot{x}_S \end{pmatrix} = \begin{pmatrix} J_M & -(\phi_M)^T \\ \phi_M & 0 \end{pmatrix} \begin{pmatrix} \frac{\partial H}{\partial x_M} \\ \frac{\partial H}{\partial x_S} \end{pmatrix} + \begin{pmatrix} 0 & 0 & 0 \\ \phi_h & \phi_{rl} & \phi_m \end{pmatrix} \begin{pmatrix} T_h \\ T_{rl} \\ T \end{pmatrix}$$

$$\begin{pmatrix} W_h \\ W_{rl} \\ W \end{pmatrix} = \begin{pmatrix} 0 & \phi_h^T \\ 0 & \phi_{rl}^T \\ 0 & \phi_m^T \end{pmatrix} \begin{pmatrix} \frac{\partial H}{\partial x_M} \\ \frac{\partial H}{\partial x_S} \end{pmatrix}$$

- x_M: inertia state vector
- x_S: spring state vector
- T_h: desired object twist
- T_{rl}: desired rest-length twist
- T: manipulator twist
- W_h, W_{rl}, W: wrenches



Intrinsically Passive Control

Control based on the model of an impedance controlled cooperative manipulation set-up



- Internal and external *impedance* relations
- Energy supplied by operator/environment

Stability

Model errors never influence passivity nor stability [Str01]

Comparison: position tracking



Comparison: velocity tracking



Human in the loop

- Desired object position is connected with a spring to the human
- Time-discrete reference changes possibly violate passivity
- Spring energy leap $\Delta\bar{P}(k) = H_S(t_k) - H_S(t_k^-)$
- Pre-filled energy tank to allow for initial twist



Overview & open issues

- port-Hamiltonian model of a cooperative manipulation set-up
- Appropriate dynamic performance of the model-based controller

Open issues

- Formulation of the HIL in the Hamiltonian framework
- Passive, stable closed loop behaviour
- Experimental evaluation

References I

F. Caccavale, P. Chiacchio, A. Marino, and L. Villani.
Six-DOF Impedance Control of Dual-Arm Cooperative Manipulators.
In: *Mechatronics, IEEE/ASME Transactions on* 13.5 (2008), pp. 576–586.

F. Caccvale and L. Villani. **An impedance control strategy for cooperative manipulation**.
In: *Advanced Intelligent Mechatronics, IEEE/ASME International Conference on* 1 (2001), pp. 343–348.

S. Erhart and S. Hirche.
Internal Force Analysis and Load Distribution for Cooperative Multi-Robot Manipulation.
In: *Robotics, IEEE Transactions on* 31.5 (2015), pp. 1238–1243.

G. Gioioso, A. Franchi, G. Salvietti, S. Scheggi, and D. Prattichizzo.
The flying hand: A formation of UAVs for cooperative aerial tele-manipulation.
In: *Robotics and Automation (ICRA), 2014 IEEE International Conference on* (2014), pp. 4335–4341.

Dongjun Lee and Ke Huang.
Passive-Set-Position-Modulation Framework for Interactive Robotic Systems.
In: *Robotics, IEEE Transactions on* 26.2 (2010), pp. 354–369.

Dongjun Lee and M.W. Spong. **Bilateral Teleoperation of Multiple Cooperative Robots over Delayed Communication Networks: Theory**.
In: *Robotics and Automation (ICRA), International Conference on* (2005), pp. 360–365.

Ltd. MHI. **"MEISTeR" Remote Control Robot Completes Demonstration Testing At Fukushima Daiichi Nuclear Power Station**. Press Information 1775, February 20, 2014; Online, accessed January 13, 2016. 2014. URL: `https://www.mhi-global.com/news/story/1402201775.html`.

S. Scheggi, F. Morbidi, and D. Prattichizzo.
Human-Robot Formation Control via Visual and Vibrotactile Haptic Feedback.
In: *Haptics, IEEE Transactions on* 7.4 (2014), pp. 499–511.

References II

S.A. Schneider and R.H. Cannon.
Object impedance control for cooperative manipulation: theory and experimental results.
In: *Robotics and Automation, IEEE Transactions on* 8.3 (1992), pp. 383–394.

D. Sieber, S. Music, and S. Hirche.
Multi-robot manipulation controlled by a human with haptic feedback.
In: *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)* (2015), pp. 2440–2446.

Stefano Stramigioli.
Modeling and IPC Control of Interactive Mechanical Systems: A Coordinate-Free Approach.
London, UK: Springer-Verlag London, 2001. ISBN: 1852333952.

T. Wimboeck, C. Ott, and G. Hirzinger. **Analysis and experimental evaluation of the Intrinsically Passive Controller (IPC) for multifingered hands**.
In: *Robotics and Automation, IEEE International Conference on* (2008), pp. 278–284.

T. Wimboeck, C. Ott, and G. Hirzinger.
Passivity-based Object-Level Impedance Control for a Multifingered Hand.
In: *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)* (2006), pp. 4621–4627.