

Control of a multi-robot cooperative team guided by a human operator

M. Angerer

Intermediate Presentation Master Thesis

Betreuer: S. Musić

Lehrstuhl für Informationstechnische Regelung

Technische Universität München

Why use cooperative manipulation with human guidance?



Figure : Coordinated handling of tools by a tele-operated robot [MHI 2014]

Human reasoning

- Foresight and adaptiveness to incidents
- Superior planning capabilities

Enhanced flexibility of multiple robots

- Transportation of large/heavy objects
- Assembly of multiple parts
- Coordinated use of tools

Problem Formulation

- Precise and stable control during free-motion/contact transition
- Enhance versatility by performing friction grasps
- (Intuitive) high-level human supervisory control
- Local control of formation, independent of the operator
- Assistance of the operator with suitable feedback

Goal

Enable a human to **intuitively** control a robot team executing **versatile** tasks

Related Work: Robot-team control

- Virtual object based impedance control [Schneider and Cannon 1992]
- Internal and external impedance control [Caccavale and Villani 2001; Caccavale et al. 2008]
 - Force/Torque sensors at the manipulators required
- Intrinsically Passive Control [Stramigioli 2001; Wimboeck, Ott, and Hirzinger 2008]
 - no object tracking, virtual object simulation
- Internal impedance control + object dynamics' feed-forward [Erhart and Hirche 2015]
- Formation control of a robot team [Sieber, Music, and Hirche 2015; Wimboeck, Ott, and Hirzinger 2006]
 - no object dynamics considered

Related Work: Human in the loop

- Bilateral tele-manipulation [Lee and Spong 2005]
 - Single master coupled to human, constrained system as slave
 - Local control of interaction dynamics
 - Force feedback
- Formation-based control [Sieber, Music, and Hirche 2015; Scheggi, Morbidi, and Prattichizzo 2014]
 - Single leader, multiple followers
 - Robots preserve formation autonomously
 - Tactile feedback
- Gesture-based Control [Gioioso et al. 2014]
 - Free-hand motion controls constrained system
 - Visual feedback

System modelling

How can we consistently model different forms of energy stored in a system?

Port-Hamiltonian systems

- Mechanical elements (spring, mass, damper)

$$\begin{pmatrix} \dot{x}_B \\ \dot{x}_S \end{pmatrix} = \begin{pmatrix} J_B & -Ad_{H_b^0}^T \phi_b^T \\ \phi_b Ad_{H_b^0} & 0 \end{pmatrix} \begin{pmatrix} \frac{\partial V}{\partial x_B} \\ \frac{\partial V}{\partial x_S} \end{pmatrix} + \begin{pmatrix} 0 & 0 & 0 \\ \phi_v & \phi_i & \phi_{rl} \end{pmatrix} \begin{pmatrix} T_v^0 \\ T_i^0 \\ T_{rl}^b \end{pmatrix}$$

$$\begin{pmatrix} W_v^0 \\ W_i^0 \\ W_{rl}^b \end{pmatrix} = \begin{pmatrix} 0 & \phi_v^T \\ 0 & \phi_i^T \\ 0 & \phi_{rl}^T \end{pmatrix} \begin{pmatrix} \frac{\partial V}{\partial x_B} \\ \frac{\partial V}{\partial x_S} \end{pmatrix}$$

- Conservative elements (transformer, gyrator)
- Interconnection through power ports

$$\mathcal{P} = \mathcal{V} \times \mathcal{V}^*$$

Energy consistent modelling and control

- *Virtual object* concept
 - Maps object forces to manipulators
 - Stores kinetic energy
 - Changes size to adjust formation
- Model represents energy content of the complete system
- Dampers dissipate energy: **passive system**
- Operator controls system by energy supply

Stability

Model errors never influence passivity nor stability [Stramigioli 2001]

Intrinsically Passive Control

- Geometric interconnection of springs, masses and dampers
- Internal and external *impedance* relations
- No manipulator inertia re-shaping
- Energy supplied by operator/environment
- Grasping with variable rest-length springs





Figure : Mass-spring-damper structure of the IPC [Stramigioli 2001]


Human supervisory control

- Command value: velocity \Leftrightarrow force :feedback value
- Suitable for bilateral tele-manipulation
- Energy intuition: humans can estimate possible impacts of interaction
- Spring rest-lengths: adjust to grasp/release objects

Comparison: position tracking



Comparison: velocity tracking



Comparison: internal forces (rotation)




Figure : Top: Object force feed-forward; Bottom: Virtual Object

Overview & open issues

- ...

Open issues

- Experimental evaluation
- Evaluation of different human-in-the-loop set-ups
- Suitable control design

References I



F. Caccavale, P. Chiacchio, A. Marino, and L. Villani.
Six-DOF Impedance Control of Dual-Arm Cooperative Manipulators.
In: *Mechatronics, IEEE/ASME Transactions on* 13.5 (2008), pp. 576–586.



F. Caccavale and L. Villani. **An impedance control strategy for cooperative manipulation.**
In: *Advanced Intelligent Mechatronics, IEEE/ASME International Conference on* 1 (2001), pp. 343–348.



S. Erhart and S. Hirche.
Internal Force Analysis and Load Distribution for Cooperative Multi-Robot Manipulation.
In: *Robotics, IEEE Transactions on* 31.5 (2015), pp. 1238–1243.



G. Gioioso, A. Franchi, G. Salvietti, S. Scheggi, and D. Prattichizzo.
The flying hand: A formation of UAVs for cooperative aerial tele-manipulation.
In: *Robotics and Automation (ICRA), 2014 IEEE International Conference on* (2014), pp. 4335–4341.



Dongjun Lee and M.W. Spong. **Bilateral Teleoperation of Multiple Cooperative Robots over Delayed Communication Networks: Theory.**
In: *Robotics and Automation (ICRA), International Conference on* (2005), pp. 360–365.



Ltd. MHI. **"MEISTeR" Remote Control Robot Completes Demonstration Testing At Fukushima Daiichi Nuclear Power Station.** Press Information 1775, February 20, 2014; Online, accessed January 13, 2016. 2014. URL: <https://www.mhi-global.com/news/story/1402201775.html>.



S. Scheggi, F. Morbidi, and D. Prattichizzo.
Human-Robot Formation Control via Visual and Vibrotactile Haptic Feedback.
In: *Haptics, IEEE Transactions on* 7.4 (2014), pp. 499–511.



S.A. Schneider and R.H. Cannon.
Object impedance control for cooperative manipulation: theory and experimental results.
In: *Robotics and Automation, IEEE Transactions on* 8.3 (1992), pp. 383–394.

References II



D. Sieber, S. Music, and S. Hirche.

Multi-robot manipulation controlled by a human with haptic feedback.

In: *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)* (2015), pp. 2440–2446.



Stefano Stramigioli.

Modeling and IPC Control of Interactive Mechanical Systems: A Coordinate-Free Approach.

London, UK: Springer-Verlag London, 2001. ISBN: 1852333952.



T. Wimboeck, C. Ott, and G. Hirzinger. **Analysis and experimental evaluation of the Intrinsically Passive Controller (IPC) for multifingered hands.**

In: *Robotics and Automation, IEEE International Conference on* (2008), pp. 278–284.



T. Wimboeck, C. Ott, and G. Hirzinger.

Passivity-based Object-Level Impedance Control for a Multifingered Hand.

In: *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)* (2006), pp. 4621–4627.