

Resilient Asymptotic Consensus in Robust Networks [[LeBlanc, 2013](#)]

Jedediah Fry, George Kontoudis

Midterm

AOE5984 Cyber-Physical Systems and Distributed Control
Spring 2017

Aerospace and Ocean Engineering Department, Virginia Tech

March 14, 2017

Outline

Introduction

Problem Formulation

Consensus Algorithm

Robust Network Topologies

Resilient Consensus Analysis

Simulations

Construction & Properties of Robust Digraphs

References

Introduction

Problem Formulation

Consensus Algorithm

Robust Network Topologies

Resilient Consensus Analysis

- ▶ W-MSR always satisfies safety condition for RAC
- ▶ $M[t]$, $m[t]$ maximum & minimum values of normal nodes $i \in N$

Lemma: Regardless of network topology, for each normal node $i \in N$ we get

$$x_i[t+1] \in [m(t), M(t)],$$

when using W-MSR algorithm w/ parameter F or f under F -local, F -total or f -fraction (Byzantine or malicious) models.

F-Total Malicious Model

- Characterize networks by necessary & sufficient conditions of W-MSR to succeed

Time-	Threat Models	Scope	Necessary	Sufficient
Invariant	Malicious	F-Total	$(F+1, F+1)$ -robust	$(F+1, F+1)$ -robust
Variant	Malicious	F-Total	-	$(2F+1)$ -robust

F-Local Malicious Model

- Employ F-Local when total number of adversaries is large in large-scale networks

Time-	Threat Models	Scope	Necessary	Sufficient
Invariant	Malicious	F-Local	$(F+1)$ -robust	$(2F+1)$ -robust
Variant	Malicious	F-Local	-	$(2F+1)$ -robust

- For every $F \in \mathbb{Z}_{>0}$ there exists a $2F$ -robust network that fails to reach consensus w/ W-MSR

f -Fraction Local Malicious Model

- Characterize networks by necessary & sufficient conditions of W-MSR to succeed

Time-	Threat Models	Scope	Necessary	Sufficient
Invariant	Malicious	f -Fraction Local	p' -fraction robust, $2f \leq p \leq 1$	p -fraction robust, $2f \leq p \leq 1$
Variant	Malicious	f -Fraction Local	-	p -fraction robust, $2f < p \leq 1$


Byzantine Threat Models

Time-	Threat Models	Scope	Necessary	Sufficient
Invariant	Byzantine	F-Total & F-Local	Normal Network (F+1)-robust	Normal Network (F+1)-robust
Invariant	Byzantine	f -Fraction Local	Normal Network f -robust	Normal Network p -robust, $p > f$
Variant	Byzantine	F-Total & F-Local	-	Normal Network (F+1)-robust
Variant	Byzantine	f -Fraction Local	-	Normal Network p -robust, $2f < p \leq 1$

- Normal network D_N , induced by normal nodes

Simulation Network Topology

- For a given $(2,2)$ -robust network we can sustain 1-Total malicious threat model




LCP algorithm

The Linear Consensus Protocol (LCP) is given by

$$x_i(t+1) = \sum_{j \in J_i(t)} w_{ij}(t) x_j^i(t)$$

- ▶ $\sum_{j=1}^n w_{ij}(t) = 1$
- ▶ $J_i(t) = V_i(t) \cup \{i\}$
- ▶ $x_1(t+1) = w_{1,1}x_1 + w_{1,2}x_2 + w_{1,11}x_{11} + w_{1,12}x_{12}$




W-MSR algorithm

The W-MSR algorithm is given by

$$x_i(t+1) = \sum_{j \in J_i(t) \setminus R_i(t)} w_{ij}(t) x_j^i(t)$$

- ▶ $R_i(t)$ denotes the reduced nodes
- ▶ Using $F=1$ because we have 1-Total model



Node removal W-MSR

The following update law applies w/ W-MSR algorithm

Node	Sort List	Step	Values	Removed
1	{1, 2, 11, 12}	0	{0, 0, 0, 0}	-
1	{1, 2, 11, 12}	1	{0, 0.25, 0.4, 0.2}	{11}
1	{1, 2, 11, 12}	6	{0.4453, 0.4322, 0.4649, 0.4553}	{2, 11}
10	{9, 10, 11, 13, 14}	0	{1, 1, 0, 1, 2}	{11, 14}
10	{9, 10, 11, 13, 14}	1	{1.167, 1, 0.4, 0.87, 0}	{9, 14}
10	{9, 10, 11, 13, 14}	30	{0.7, 0.6921, 0.68, 0.6935, 0.28}	{13, 14}

Construction of Robust Digraphs

Theorem: Let $D = (V, \mathcal{E})$ be an (r, s) -robust digraph, $S \in \mathbb{Z}_{>0}$. Then, $D' = (V \cup \{v_{new}\}, \mathcal{E} \cup \{\varepsilon_{new}\})$ is (r, s) -robust if


$$d_{v_{new}}^{in} \geq r + s - 1,$$

where v_{new} is the new vertex added to D , and ε_{new} is the directed edge set related to v_{new} ,

- ▶ Start w/ an (r, s) -robust digraph
- ▶ Add new nodes w/ incoming edges at least $r + s - 1$
- ▶ Arbitrary node selection, scale-free networks







Robust Digraph Example

- ▶ Start w/ a K_5 graph (complete-fully connected on 5 nodes)
- ▶ K_5 is the only $(3, 2)$ -robust 5 node digraph
- ▶ Add new nodes w/ incoming edges w/ at least $r + s - 1 = 3 + 2 - 1 = 4$
- ▶ End up w/ a $(3, 2)$ -robust 10 node digraph, also 4-robust



[LeBlanc, 2013]

Robust Digraph Illustration



Properties of Robust Networks (1/2)

Observation: $(r, 1)$ -robustness $\equiv r$ -robustness

Lemma: Every (r, s) -robust digraph $D = (V, \mathcal{E})$ is also (r', s') -robust when $0 \leq r' \leq r$, $1 \leq s' \leq s$.

Lemma: Suppose digraph $D = (V, \mathcal{E})$ is (r, s) -robust, spanning $D' = (V, \mathcal{E}')$, where $\mathcal{E}' = \mathcal{E} \cup \mathcal{E}''$ and $|\mathcal{E}''| \leq 0$. Then D' is (r, s) -robust.

Lemma: No digraph $D = (V, \mathcal{E})$ on n nodes is $(\lceil n/2 \rceil + 1)$ -robust. On the other hand, the complete digraph $K_n = (V, \mathcal{E}_{K_n})$ is the only $(\lceil n/2 \rceil, s)$ -robust for $1 \leq s \leq n$ and n odd.

Properties of Robust Networks (2/2)

Lemma: Given an (r, s) -robust digraph $D = (V, \mathcal{E})$ w/
 $0 \leq r \leq \lfloor n/2 \rfloor$ the minimum in-degree of D is at least

$$\delta^{in}(D) \geq \begin{cases} r + s - 1 & \text{if } s < r; \\ 2r - 2 & \text{if } s \geq r. \end{cases}$$

Lemma: Given an (r, s) -robust (p -fraction robust) digraph D , let D' be the digraph produced by removing up to k incoming edges from each node in D , where $0 \leq k \leq r$ ($0 \leq q < p \leq 1$). Then D' is $(r - k, s)$ -robust ($(p - q)$ -fraction robust).

Theorem: Suppose $D = (V, \mathcal{E})$ is an r -robust (or (r, r) -robust) digraph, w/ $0 \leq r \leq \lfloor n/2 \rfloor$ (or $3 \leq r \leq \lfloor n/2 \rfloor$). Then the underlying graph G_D is at least r -connected (or $\lfloor 3r/2 \rfloor - 1$ -connected).

References



H. LeBlanc, H. Zhang, X. Koutsoukos, S. Sundaram (2013)

Resilient asymptotic consensus in robust networks

IEEE Journal on Selected Areas in Communications, 31(4), 766-781, 2013.

Thank You!