QUAD-ROTOR FLIGHT PATH ENERGY OPTIMIZATION

By Edward Kemper

A Thesis

Submitted in Partial Fulfillment

of the requirements for the degree of

Masters of Science

in Electrical Engineering

Northern Arizona University

April 2014

Approved:

Dr. Niranjan Venkatraman, Ph.D.,Chair

Dr. Sheryl Howard, Ph.D.

Dr. Allison Kipple, Ph.D.

ABSTRACT

QUADROTOR FLIGHT PATH ENERGY OPTIMIZATION

by Edward Kemper

Quad-Rotor unmanned areal vehicles (UAVs) have been a popular area of research and development in the last decade, especially with the advent of affordable microcontrollers like the MSP 430 and the Raspberry Pi. Path-Energy Optimization is an area that is well developed for linear systems. In this thesis, this idea of path-energy optimization is extended to the nonlinear model of the Quad-rotor UAV. The classical optimization technique is adapted to the nonlinear model that is derived for the problem at hand, coming up with a set of partial differential equations and boundary value conditions to solve these equations. Then, different techniques to implement energy optimization algorithms are tested using simulations in Python. First, a purely nonlinear approach is used. This method is shown to be computationally intensive, with no practical solution available in a reasonable amount of time. Second, heuristic techniques to minimize the energy of the flight path are tested, using Ziegler-Nichols' proportional integral derivative (PID) controller tuning technique. Finally, a brute force lookup table based PID controller is used. Simulation results of the heuristic method show that both reliable control of the system and path-energy optimization are achieved in a reasonable amount of time.

ACKNOWLEDGEMENTS

There are a great many people who need to be recognized for their contribution to the success of my academic endeavors. Thank you to my parents for their continued financial and moral support. Thank you to Terry Halmo, Dr. Monty Mola, Dr. Wes Bliven, Dr. Robert Zoellner, and the rest of the Physics and Chemistry Faculty at Humboldt State for their work in mentoring and teaching. Thank you to Dr. Allison Kipple, Dr. Sheryl Howard, Dr. Paul Flikkema, Dr. Phillip Mlsna, and the rest of the Engineering Faculty at NAU. Thank you to Emily, my partner, for taking in stride the rich insanity of math and code that sometimes dominates my being. Finally thank you to Dr. Niranjan Venkatraman for his continuous, enthusiastic involvement in the development of this thesis.

Contents

List of Figures

For my Parents Jack and Carol...

Chapter 1

Introduction

The technology surrounding Unmanned Aerial Vehicles (UAVs), and in particular quad-rotor devices, has seen tremendous development in recent years. Likewise, the creative application of this technology has expanded into many contexts. Like many new technologies, the early development of UAVs was mostly in a military context. This is not the case any more. The private sector has taken a huge interest in this technology. There is a wide range of companies contributing to the development of UAV technology from open-source projects like DIY Drones [diy] to start-up firms backed by Google, such as Airware [air]. The Federal Aviation Administration in the USA has plans to produce concrete policy regarding the regulation of commercial applications of UAVs by 2015 [faa]. This will sow the seeds for the rapid growth of a multi-billion dollar industry. There are many applications for this technology which have the potential to save lives and collect scientific data that could inform state and federal legislation. Certainly, the range of potential applications will be further diversified as the technology sees more development.

Unmanned Ariel Vehicles are also called by various other names: remotely piloted vehicles (RPVs), remote controlled drones, robot planes, and pilot-less aircraft. Such vehicles are defined as powered, aerial vehicles that do not carry a human operator and can use aerodynamics forces to provide vehicle lift. They can fly autonomously or be piloted remotely, can be expendable or recoverable, and can carry a lethal or nonlethal payload [1].

1.1 Motivation

With many private organizations making use of UAVs for a variety of applications, one pervasive engineering problem that still exists in general is that of managing the energy usage. Quad-rotors specifically are plagued by very high energy demand. There are two different kinds of UAVs: fixed wing, which have the ability to soar or glide, and multi-rotor systems, which are entirely thrust-driven. It is the natural instability of multi-rotor UAVs which make them extremely maneuverable, but this comes at the cost of high energy expenditure. This provides the motivation for this thesis - to develop an optimal control technique that optimizes the path-energy of a quad-copter UAV.

1.2 Prior Work

There have been work published on the energy optimization and trajectory planning of fixed wing UAVs. Given the ability to soar and utilize thermal gradients in the atmosphere, it is suggested that fixed wing UAVs have the potential to stay aloft almost permanently [2], [3], and [4]. This makes fixed wing UAVs ideal for applications like aerial surveys or surveillance missions. These aircrafts have

the major disadvantage that they are dependent upon some kind of launching mechanism, or a runway, for takeoff and landing.

In contrast, rotary wing UAVs have a higher degree of mechanical complexity. These UAVs can take off and land vertically and have the capacity to hover. This makes rotary wing UAVs, such as the quad-copter, more suitable for short range search and rescue missions, facility inspections, and single-target tracking. Since fixed wing and multi-rotor UAVs are fundamentally different in their physical operation, procedures for managing their respective energy usage are also necessarily unique.

In academic contexts, many advances in UAV and specifically quad-rotor research have provided the seeds for growth for this industry. The problem of basic stability and position control is solved in [5], [6], and [7].

The background material for understanding the dynamical model of the quad-rotor as given by the Euler-Lagrange formulation is explained in [8] and [9]. These references provide detailed derivations and discussions of the Euler-Lagrange equations of motion as well as related topics like Hamiltonian mechanics and the calculus of variations. Also, [9] provides an in-depth review of the historical context surrounding the development of classical mechanics. The derivation of the quad-rotor dynamical model as well as attitude and position control via PD or PID controllers is discussed in [5], [6], and [7]. These papers provide derivations of both the Euler-Lagrange and Newtonian formulations for the quad-rotor.

Optimal control was born in 1697, when Johann Bernoulli published his solution to the Brachystochrone problem in [10] . With the work of Bernoulli, Newton, Leibniz, l'Hopital, and Tschirnhaus, the field of optimal control was clearly defined. This was followed by the works of Euler, Lagrange, and Legendre which

led to the fundamental optimization equations, Euler's equation [11], the Euler-Lagrange formulation, and Legendre's necessary condition for a minimum. W. R. Hamilton then came up with an equivalent to the Euler-Lagrange equation that could be used in deriving control equations. This was known as the control Hamiltonian form of the Euler-Lagrange equations. The next development was from Weierstass, who came up with the fundamental path optimization problem in optimal control theory in the late 19th century. This was followed by the fundamental minimization principle by Pontryagin that allows for solving most optimization problems [12]. Several books on optimal control ([13] , [14], [15], [16]) were referenced for the derivations used in this thesis. In order to test the nonlinear optimization, numerical algorithms for the shooting method ([17], [18], [19]) and the finite difference method ([18], [19]) were used.

The Proportional-Integral-Derivative (PID) controller is a control loop feedback mechanism widely used to drive a system to a desired set point. The mechanism uses an error value as the input to the controller. PID controllers are common in industrial applications [20]. In the absence of the knowledge of an underlying process, the PID is considered the best method of control. It must be noted that PID controllers do not necessarily result in optimal control of the system. However, it is possible to achieve a desired system response by adjusting the mathematical parameters of the control expressions. This process is called "tuning". The tuning must satisfy many criteria within the limitations of PID control and the system itself. There are various tuning techniques [21]. For instance, there are the Ziegler-Nichols, manual tuning, and software tuning methods which can be applied to other control problems [22], [23].

1.3 Organization of the Thesis

The objective of this thesis is to develop a path-energy optimization technique that can operate on a near real-time schedule. Two different methods are discussed. We compare a classical optimal control technique with a simpler heuristic approach involving PID controller tuning. The organization of the chapters is as follows.

In Chapter 2, we present a detailed problem statement where the goal of the research project is defined. Chapter 3 uses the Euler-Lagrange equations of motion to derive a nonlinear dynamical model for the quad-rotor UAV. This mathematical model is the basis of the development of the control and energy optimization algorithms. In chapter 4, we define the various optimality conditions. Then we and formulate a generalized, classical optimal control scheme. Then we solve the boundary value problem generated by two methods and discuss their pros and cons. In Chapter 5, the classical optimal control scheme developed in the previous chapter is applied to the quad-rotor UAV. The resulting boundary value problem and its solution method is discussed. Chapter 6 deals with the PID/PD control technique. The control expressions are derived, and the method is tested. Results from these tests are discussed. Chapter 7 outlines a heuristic approach to the path-energy optimization problem and presents the simulation results of the control algorithm developed. Chapter 8 summarizes the results and proposes avenues for continued research.

Chapter 2

Problem Statement

We wish to find a set of control expressions for a quad-rotor UAV which minimizes the energy expended in flying between two known points in three-dimensional space. In order to maintain focus on a tractable problem, some mathematical assumptions are made about the scenario. First, we assume that the flight path that will be optimized is free of obstacles. Second, we assume only modeled environmental variables. We use a mathematical model of the system derived from a Euler-Lagrange formulation as in [6] and [7].

In the classical optimal control approach, as in [13] and [14], the control of the system and the optimization are represented in a single mathematical formulation. Solving the optimal control problem is achieved by solving a boundary value problem. For a highly nonlinear system such as a quad-rotor, this becomes extremely involved. The classical optimal control approach is shown to be too computationally intensive for a real-time implementation because the result is a substantial two point boundary value problem. Solving the theoretical optimal control problem would likely produce accurate results, but the solution could potentially take

weeks of computation to attain. Also, the convergence of the solution is shown to be intermittent.

For the heuristic approach, full control of the UAV is attained by using PD attitude controllers in conjunction with PID controllers for position. This provides a platform for simulating the UAV as it flies from a known initial position to a desired set point location. The optimization procedure evaluates the results of these simulations for optimality as a function of the PID gains used in the position control expressions.

It is pertinent to define what is meant by near real-time in our somewhat sterile mathematical context. We assume that the set of initial and final locations of the quad-rotor are defined by a user on a human time scale. Imagine a graphical user interface in which the desired location of the UAV is programmed. The quad-rotor then physically traverses the optimal path without more than a second or two of computation before the flight begins. For an autonomous UAV, the on-board computational resources define an upper limit to the computational complexity of the control algorithm. Our aim is to design an energy optimized control scheme which meets these constraints.

Chapter 3

Quad-Rotor Dynamic Model

In this chapter, a mathematical model of the quad-rotor is derived, and the assumptions that go into this derivation are explained in detail. This model will be used as the basis for the optimization techniques outlined in subsequent chapters.

3.1 Description of a Quad-Rotor

A generic model of a quad-rotor is physically composed of a simple frame supporting four brushless motors. Thrust is provided by propellers attached to these motors. The speeds of the rotors are governed by a control algorithm which is implemented on some form of on board processor.

The stabilization and control of a quad-rotor is accomplished by varying the speeds of the motors. The thrust in the vertical direction is controlled by varying all four motor speeds uniformly. In the quad-rotor frame of reference, the direction of the thrusts from the motors is fixed. This means that in order to produce lateral

motion, the UAV must tilt such that a component of the total thrust vector points in the desired direction of motion.

In Figure **??** the basic mechanical structure and the relationships between the spatial coordinates are shown. The linear and angular coordinates are defined as follows.



FIGURE 3.1: Quad-Rotor Coordinate System

ψ is the yaw angle around the z-axis

θ is the pitch angle around the y-axis

ϕ is the roll angle around the x-axis

The pitch and roll angular positions are controlled by driving motors on opposite sides of the frame at different speeds. This produces torque about the center of mass of the quad-rotor. Given non-zero pitch, roll, and total thrust, the UAV experiences horizontal linear acceleration. The yaw angular position is controlled by driving pairs of opposite motors at the different speeds. This produces a torque about the yaw axis but not about the pitch or roll axes. Also, the two opposite pairs of motors must spin in opposite directions so that when hovering, the net torque about the yaw axis is zero. The details of this description are represented mathematically in the next section.

3.2 Coordinate System Definitions

In order to implement a control algorithm, we must understand the mathematical relationships between the control input and the resulting dynamics of the system. Using the Euler-Lagrange formulation from classical mechanics, we can obtain a nonlinear, deterministic dynamical model. General derivation of the Euler Lagrange differential equations of motion can be found in [8] and [9].

The spatial variables can be grouped into linear and angular components, with ξ representing the linear components and η representing the angular components:

$$\boldsymbol{\xi} = \begin{bmatrix} x \\ y \\ z \end{bmatrix}, \boldsymbol{\eta} = \begin{bmatrix} \phi \\ \theta \\ \psi \end{bmatrix}, \boldsymbol{q} = \begin{bmatrix} \xi \\ \eta \end{bmatrix} \tag{3.1}$$

3.3 Motor Speeds, Thrust and Torque

The rotor angular velocities are related to the forces they produce by $f_i = k\omega_i^2$ where k is the constant of proportionality and i is the motor index. The torques due to the rotation of the rotors about their respective axes of rotation are given by $\tau_i = b\omega_i^2 + I_M\dot{\omega}_i$. The variable τ_i is the torque from the ith motor and the parameter b is a drag coefficient. Note the effect of $\dot{\omega}_i$ is considered to be negligible because the rotational inertia of the rotor itself is negligible.

In the quad-rotor frame of reference, the motors produce the following torques on the system:

$$\boldsymbol{\tau}_B = \begin{bmatrix} \tau_\phi \\ \tau_\theta \\ \tau_\psi \end{bmatrix} = \begin{bmatrix} lk(-\omega_2^2 + \omega_4^2) \\ lk(-\omega_1^2 + \omega_3^2) \\ \sum_{i=1}^{4} b\omega^2 \end{bmatrix} \tag{3.2}$$

In the above expression the parameters l and k refer to the length of the quad-rotor arm and an aerodynamic thrust coefficient respectively. The combined thrust of the rotors in the direction of the quad-rotor frame z axis is

$$\boldsymbol{T}_B = [0, 0, T]^T \tag{3.3}$$

where,

$$T = \sum_{i=1}^{4} f_i \tag{3.4}$$

.

3.4 Euler-Lagrange Equations of Motion

The mass of the quad-rotor is m. Each of the moments of inertia i_{xx} and i_{yy} are assumed to be composed of a rod of length l which accounts for half of the mass of the quad-rotor. Assume the mass is evenly distributed along the two perpendicular rods. Let $\beta = \frac{1}{12}ml^2$. The inertia matrix for the quad-rotor is then:

$$I = \begin{pmatrix} \frac{1}{12}\left(\frac{m}{2}\right)l^2 & 0 & 0 \\ 0 & \frac{1}{12}\left(\frac{m}{2}\right)l^2 & 0 \\ 0 & 0 & \frac{1}{12}ml^2 \end{pmatrix} = \begin{pmatrix} \frac{\beta}{2} & 0 & 0 \\ 0 & \frac{\beta}{2} & 0 \\ 0 & 0 & \beta \end{pmatrix} \tag{3.5}$$

In this section, we will use Newton's notation for time derivatives. For instance, $\dot{\eta} = \frac{\partial \eta}{\partial t}$. In the inertial frame, the kinetic ((translational and rotational)and potential energy of the system are given by

$$KE_{\text{trans}} = \frac{1}{2}m\dot{\xi}^T\dot{\xi} \tag{3.6}$$

$$KE_{\text{rot}} = \frac{1}{2}\dot{\eta}^T J\dot{\eta} \tag{3.7}$$

$$U = mgz. \tag{3.8}$$

The Lagrangian is formed as the difference between kinetic and potential energy:

$$L = \frac{1}{2}m\dot{\xi}^T\dot{\xi} + \frac{1}{2}\dot{\eta}^T J\dot{\eta} \ - mgz. \tag{3.9}$$

The Jacobian J is given by

$$J = W_\eta^T I W_\eta, \tag{3.10}$$

where

$$W_\eta = \begin{bmatrix} 1 & 0 & -sin(\theta) \\ 0 & cos(\phi) & cos(\theta)sin(\phi) \\ 0 & -sin(\phi) & cos(\theta)cos(\phi) \end{bmatrix} \tag{3.11}$$

The matrix W_η is the matrix transformation which relates the angular velocities from the quad-rotor frame of reference to the inertial frame. Substituting equation 3.11 into equation 3.10 then provides:

$$J = \begin{pmatrix} \frac{\beta}{2} & 0 & -\frac{\beta}{2}s(\theta) \\ 0 & \frac{\beta}{2}c(\phi)^2 + \beta s(\phi)^2 & \frac{-\beta}{2}c(\phi)\ s(\phi)\ c(\theta) \\ -\beta s(\theta) & \frac{-\beta}{2}c(\phi)\ s(\phi)\ c(\theta) & \frac{\beta}{2}s(\theta)^2 + \frac{\beta}{2}s(\phi)^2c(\theta)^2 + \beta c(\phi)^2c(\theta)^2 \end{pmatrix} \tag{3.12}$$

The dynamics of the system are represented by the Euler - Lagrange differential equations of motion, as follows:

$$\frac{d}{dt}\left(\frac{\delta L}{\delta \dot{q}}\right) - \frac{\delta L}{\delta q} = F \tag{3.13}$$

where $q = \{x, y, z, \psi, \theta, \phi\} = \{\xi, \eta\}$.

f is the generalized force vector representing the linear external force acting on the system. τ is the vector of torques acting on the system due to the rotors.

$$\begin{pmatrix} f \\ \tau \end{pmatrix} = \frac{d}{\mathrm{dt}} \left(\frac{\delta L}{\delta \dot{q}} \right) - \frac{\delta L}{\delta q} \tag{3.14}$$

General derivations of the Euler-Lagrange equations of motion can be found in [8] and [9].

The coordinates $q_i = \{x, y, z, \psi, \theta, \phi\}$ are in reference to a ground-based inertial coordinate system. The system states and control inputs must be mapped from the quad-rotor frame of reference to the inertial frame in order to express the dynamics of the system. The matrix R below represents an arbitrary rotation transformation from the body frame to the inertial frame:

$$\boldsymbol{R} = \begin{bmatrix} c(\psi)c(\theta) & c(\psi)s(\theta)s(\phi) - s(\psi)c(\phi) & c(\psi)s(\theta)c(\phi) + s(\psi)s(\phi) \\ s(\psi)c(\theta) & s(\psi)s(\theta)s(\phi) + c(\psi)c(\phi) & s(\psi)s(\theta)c(\phi) - c(\psi)s(\phi) \\ -s(\theta) & c(\theta)s(\phi) & c(\theta)c(\phi) \end{bmatrix} \tag{3.15}$$

For simplicity, cos is denoted by 'c' and sin is denoted by 's' in the above expression.

The linear components of the generalized forces produce the following equations.

$$f = RT_B = m\ddot{\xi} - G \tag{3.16}$$

$$m\begin{pmatrix}\ddot{x}\\ \ddot{y}\\ \ddot{z}\end{pmatrix}-\begin{pmatrix}0\\ 0\\ -mg\end{pmatrix}=u\begin{pmatrix}\cos\psi\sin\theta\cos\phi+\sin\psi\sin\phi\\ \sin\psi\sin\theta\cos\phi-\cos\psi\sin\phi\\ \cos\theta\cos\phi\end{pmatrix} \tag{3.17}$$

The angular components are expressed as

$$\tau=\tau_b=\frac{d}{dt}\left(\frac{\partial L}{\partial\dot{\eta}}\right)-\frac{\partial L}{\partial\eta} \tag{3.18}$$

$$\tau_b=\frac{d}{dt}(J\dot{\eta})-\frac{1}{2}\frac{\partial}{\partial\eta}(\dot{\eta}^T J\dot{\eta}) \tag{3.19}$$

$$\tau_b=J\ddot{\eta}+\frac{d}{dt}(J)\dot{\eta}-\frac{1}{2}\frac{\partial}{\partial\eta}(\dot{\eta}^T J\dot{\eta}) \tag{3.20}$$

$$\tau_b=J\ddot{\eta}+\mathfrak{C}(\eta,\dot{\eta})\dot{\eta} \tag{3.21}$$

$$\ddot{\eta}=J^{-1}\big(\tau_b-\mathfrak{C}(\eta,\dot{\eta})\dot{\eta}\big) \tag{3.22}$$

In the above equations, $\mathfrak{C}(\eta,\dot{\eta})$ is called the Coriolis Matrix. The Coriolis term is a mathematical result of the rotational motion of one coordinate system with respect to another. Since we are considering arbitrary three dimensional motion, there are three orthogonal axes of rotation and the resulting matrix is quite complicated. According to the expression for the angular acceleration (Equation (3.22)), the physical units of the Coriolis term must be torque to maintain algebraic continuity.

The Coriolis matrix provides a method to relate the rotational coordinates to the translational coordinates [24], [25]. For our problem, it is defined as follows.

$$\mathfrak{C}(\eta,\dot{\eta}) = \begin{pmatrix} \mathfrak{C}_{(11)} & \mathfrak{C}_{(12)} & \mathfrak{C}_{(13)} \\ \mathfrak{C}_{(21)} & \mathfrak{C}_{(22)} & \mathfrak{C}_{(23)} \\ \mathfrak{C}_{(31)} & \mathfrak{C}_{(32)} & \mathfrak{C}_{(33)} \end{pmatrix} \tag{3.23}$$

$$\mathfrak{C}_{(11)} = 0$$

$$\mathfrak{C}_{(12)} = (I_{yy} - I_{zz})(\dot{\theta}C_\phi S_\phi + \dot{\psi}C_\theta S_\phi^2) + (I_{zz} - I_{yy})\dot{\psi}C_\phi^2 C_\theta - I_{xx}\dot{\psi}C_\theta$$

$$\mathfrak{C}_{(13)} = (I_{zz} - I_{yy})\dot{\psi}C_\phi S_\phi C_\theta^2$$

$$\mathfrak{C}_{(21)} = (I_{zz} - I_{yy})(\dot{\theta}C_\phi S_\phi + \dot{\psi}S_\phi C_\theta) + (I_{yy} - I_{zz})\dot{\psi}C_\phi^2 C_\theta + I_{xx}\dot{\psi}C_\theta$$

$$\mathfrak{C}_{(22)} = (I_{zz} - I_{yy})\dot{\phi}C_\phi S_\phi$$

$$\mathfrak{C}_{(23)} = -I_{xx}\dot{\psi}S_\theta C_\theta + I_{yy}\dot{\psi}S_\phi^2 S_\theta C_\theta + I_{zz}\dot{\psi}C_\phi^2 S_\theta C_\theta$$

$$\mathfrak{C}_{(31)} = (I_{yy} - I_{zz})\dot{\psi}C_\theta^2 S_\phi C_\phi - I_{xx}\dot{\theta}C_\theta$$

$$\mathfrak{C}_{(32)} = (I_{zz} - I_{yy})(\dot{\theta}C_\phi S_\phi S_\theta + \dot{\phi}S_\phi^2 C_\theta) + (I_{yy} - I_{zz})\dot{\phi}C_\phi^2 C_\theta + I_{xx}\dot{\psi}S_\theta C_\theta - I_{yy}\dot{\psi}S_\phi^2 S_\theta C_\theta - I_{zz}\dot{\psi}C_\phi^2 S_\theta C_\theta$$

$$\mathfrak{C}_{(33)} = (I_{yy} - I_{zz})\dot{\phi}C_\phi S_\phi C_\theta^2 - I_{yy}\dot{\theta}S_\phi^2 C_\theta S_\theta - I_{zz}\dot{\theta}C_\phi^2 C_\theta S_\theta + I_{xx}\dot{\theta}C_\theta S_\theta$$

It is important to keep in mind that the Coriolis term does not represent a real force or torque acting on the system. It is only an artifact which is needed to account for the relative rotation of one coordinate frame with respect to another.

3.5 A Complete Model

A complete mathematical representation of the quad-rotor is as follows:

$$\begin{pmatrix} \ddot{x} \\ \ddot{y} \\ \ddot{z} \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ g \end{pmatrix} + \frac{T}{m} \begin{pmatrix} C_\psi S_\theta C_\phi + S_\psi S_\phi \\ S_\psi S_\theta C_\phi - C_\psi S_\phi \\ C_\theta C_\phi \end{pmatrix} \tag{3.24}$$

$$\begin{pmatrix} \ddot{\phi} \\ \ddot{\theta} \\ \ddot{\psi} \end{pmatrix} = J^{-1} \left[\begin{pmatrix} ls(-\omega_2^2 + \omega_4^2) \\ ls(-\omega_1^2 + \omega_3^2) \\ \sum_{i=1}^{4} b\omega_i^2 \end{pmatrix} - \mathfrak{C} \begin{pmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\psi} \end{pmatrix} \right] \tag{3.25}$$

Even in this form there are many important aspects of quad-rotor flight dynamics and environmental variables which are omitted. The general problem of designing a system that is able to understand and adapt to varying goals and circumstances is a large one.

Despite the apparent shortcomings of this model, it is very useful as a core component to this thesis. Although the assumed mathematical environment is somewhat of a departure from reality, it allows for a firm theoretical basis which validates the development of the control system and optimization scheme.

Chapter 4

Classical Optimal Control Formulation

In this chapter, we will define a two point boundary value problem and explore the classical optimal control formulation. The solution to this boundary value problem gives the control inputs to the system which produce optimal behavior. The set of mathematical conditions which define the boundary value problem are termed 'optimality conditions'. The content of this chapter is left generalized. It can be applied to any second order dynamic system. In chapter 5, the optimality conditions are applied to the dynamical model of the quad-rotor which was derived in Chapter 3.

Note the names 'Lagrangian' and 'Hamiltonian' are used here in an optimal control context. The multiple use of these names in reference to specific types of expressions is an artifact of the pervasive work of Lagrange and Hamilton. Both optimal control theory and Hamiltonian / Lagrangian mechanics are rooted in the calculus of variations. The dynamic model of the quad-rotor and the optimal

control formulation described below are both results from a form of functional optimization. We rely on a contextual and conceptual separation in our understanding. Specifically, the 'Lagrangian', which is formed as the difference of the expressions for kinetic and potential energies, is unique to the context of classical mechanics. Likewise, the 'Lagrangian' in the optimal control context is a term in the integrand of our objective function which represents a vector of performance metrics. The 'Hamiltonian' from classical mechanics is formed as the sum of kinetic and potential energies. This is different than the Hamiltonian used here in the optimal control context.

4.1 Derivation of the Objective Function

In section 2.3 of Bryson and Ho [14], the conditions for the optimal control of a continuous time system are derived. There, it is presumed that the system is presented as a set of first order differential equations. For a quad-rotor, it is more convenient to leave the system equations as a set of second order differential equations. The motivation for this is as follows. With the finite difference method for solving two point boundary value problems, there are a set of simultaneous algebraic equations that are defined for each point in time for which a solution is desired. If we were to express the system of differential equations that govern the dynamics of a quad-rotor in a first order form, the number of algebraic equations defined by the finite difference method would be effectively doubled. Here, we derive the analogous conditions for optimality for a second order system.

4.1.1 Lagrangian

The real power of the optimal control formulation is in the use of the Lagrangian function (also called the performance index) $L(q(t), u(t), t)$ and the co-state $\lambda(t)$. The objective function in our context is an extension of classical constrained optimization to systems which evolve in time. In our case, the Lagrangian is the function which we wish to minimize, the system model (as derived in chapter 3) F plays the role of the constraint relationship, and the function $\lambda(t)$ plays the same role here as a lagrange muliplier in the context of static optimization. Since our optimization procedure accounts for the time variation of the performance index and the system equations, $\lambda(t)$ is likewise a function of time. The variable $\lambda(t)$ is allowed to vary in time along with the state of the system and is therefore given the name "co-state". In other words it allows for an expression of the criteria for optimallity at every instance in time.

The Lagrangian for our problem is defined as

$$L[q(t), u(t), t] = u^T I u, \tag{4.1}$$

where u is the control input vector and I is the 4×4 identity.

4.1.2 Objective Function

The dynamic equations of motion are appended to the performance index as follows. By definition:

$$F = \ddot{q} \tag{4.2}$$

$$0 = F - \ddot{q} \tag{4.3}$$

Note that F is the vector function representation of the quad-rotor system equations. The components' physical units are linear and angular acceleration, not force. The variable q is a vector of generalized spatial coordinates. F is generally a function of the generalized coordinates, the input to the system $u(t)$, and time. The full objective function can be written as

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \int_{t_0}^{t_f} \left[L(q(t), u(t), t) + \lambda^T \big(F(q(t), u(t), t) - \ddot{q}\big)\right] dt. \tag{4.4}$$

The function $\Psi(q(t_f), t_f)$ represents the effect that the final state has on the objective function. In general, $\Psi(q(t_f), t_f)$ is a vector quantity and is scaled by the vector ν.

For the optimal control formulation, the Hamiltonian is defined as a measure of optimallity as a function of time. In the next section we'll see that the full objective function invloves a time-integration of the Hamiltonian. It is written as:

$$H = L(q(t), u(t), t) + \lambda^T \big(F(q(t), u(t), t) - \ddot{q}\big). \tag{4.5}$$

The Hamiltonian allows for a concise expression of the Lagrangian, the co-state function λ and the constraint equations.

The objective function is simplified as:

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \int_{t_0}^{t_f} H(q(t), u(t), t) - \lambda^T \ddot{q} dt \tag{4.6}$$

The second term in the integrand is integrated by parts.

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \int_{t_0}^{t_f} H(q(t), u(t), t)\ dt - \int_{t_0}^{t_f} \lambda^T \ddot{q}\ dt \tag{4.7}$$

In general: $\int u\ dv = (uv)|_{t_0}^{t_f} - \int v\ du$. Using this, the second term is expanded.

$$\int_{t_0}^{t_f} \lambda^T \ddot{q}\ dt = (\lambda^T \dot{q})|_{t_0}^{t_f} - \int_{t_0}^{t_f} \dot{\lambda}^T \dot{q}\ dt \tag{4.8}$$

The result is:

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \int_{t_0}^{t_f} H(q(t), u(t), t)\ dt - (\lambda^T \dot{q})|_{t_0}^{t_f} + \int_{t_0}^{t_f} \dot{\lambda}^T \dot{q}\ dt \tag{4.9}$$

.

The last term is integrated by parts again.

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) - (\lambda^T \dot{q})|_{t_0}^{t_f} + (\dot{\lambda}^T q)|_{t_0}^{t_f} + \int_{t_0}^{t_f} H(q(t), u(t), t) - \ddot{\lambda}^T q\ dt \tag{4.10}$$

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \left[\dot{\lambda}^T q - \lambda^T \dot{q}\right]_{t_0}^{t_f} + \int_{t_0}^{t_f} \left(H(q(t), u(t), t) - \ddot{\lambda}^T q\right)\, dt \tag{4.11}$$

This result is the objective function which we wish to minimize.

4.2 Derivation of the Optimality Conditions

To find the mathematical conditions necessary for a minimum in $\mathcal{J}$, the first variation is computed and set equal to 0. In this context, the variation of a function is essentially the same as the total derivative. Further reading on this is found in [8] and [9].

The first variation in $\mathcal{J}$ is given by

$$\delta\mathcal{J} = \frac{\partial \mathcal{J}}{\partial q}\delta q + \frac{\partial \mathcal{J}}{\partial \dot{q}}\delta \dot{q} + \frac{\partial \mathcal{J}}{\partial u}\delta u. \tag{4.12}$$

$$\begin{aligned}\delta\mathcal{J} = {} & \nu^T \frac{\partial \Psi}{\partial q}\delta q|_{t_f} + \nu^T \frac{\partial \Psi}{\partial \dot{q}}\delta \dot{q}|_{t_f} + \left[\dot{\lambda}^T \delta q - \lambda^T \delta \dot{q}\right]_{t_0}^{t_f} \\ & + \int_{t_0}^{t_f} \left[\frac{\partial H}{\partial q}\delta q + \frac{\partial H}{\partial \dot{q}}\delta \dot{q} + \frac{\partial H}{\partial u}\delta u - \ddot{\lambda}^T \delta q\right]\, dt\end{aligned} \tag{4.13}$$

$$\begin{aligned}\delta\mathcal{J} = {} & (\nu^T \frac{\partial \Psi}{\partial q} + \dot{\lambda}^T)\delta q|_{t_f} + (\nu^T \frac{\partial \Psi}{\partial \dot{q}} - \lambda^T)\delta \dot{q}|_{t_f} + [\lambda^T \delta \dot{q} - \dot{\lambda}^T \delta q]_{t_0} \\ & + \int_{t_0}^{t_f} \left[\left(\frac{\partial H}{\partial q} - \ddot{\lambda}^T\right)\delta q + \frac{\partial H}{\partial \dot{q}}\delta \dot{q} + \frac{\partial h}{\partial u}\delta u\right]\, dt.\end{aligned} \tag{4.14}$$

The optimality conditions are found by setting $\delta\mathcal{J} = 0$ and asserting that each of the added terms must therefore go to 0. The results are summarized as follows.

The Co-State equations are

$$\frac{\partial H}{\partial q} = \ddot{\lambda} \tag{4.15}$$

$$\ddot{\lambda} = \left(\frac{\partial L}{\partial q}\right)^T + \left(\frac{\partial F}{\partial q}\right)^T \lambda. \tag{4.16}$$

The Stationarity Conditions are

$$\frac{\partial H}{\partial u} = 0 \tag{4.17}$$

$$\frac{\partial L}{\partial u} + \left(\frac{\partial F}{\partial u}\right)^T \lambda = 0 \tag{4.18}$$

Secondary algebraic Co state condition

$$\frac{\partial H}{\partial \dot{q}} = 0 \tag{4.19}$$

$$\left(\frac{\partial F}{\partial \dot{q}}\right)^T \lambda = 0 \tag{4.20}$$

Terminal Boundary conditions:

$$\nu^T \frac{\partial \Psi}{\partial q}|_{t_f} + \dot{\lambda}(t_f)^T = 0 \tag{4.21}$$

$$\nu^T \frac{\partial \Psi}{\partial \dot{q}}|_{t_f} - \lambda(t_f)^T = 0 \tag{4.22}$$

Initial Co state conditions

$$(\lambda^T \delta\dot{q} - \dot{\lambda}^T \delta q)|_{t_0} = 0 \tag{4.23}$$

$$\lambda(t_0) = 0 \tag{4.24}$$

$$\dot{\lambda}(t_0) = 0 \tag{4.25}$$

Together, the state equations, co-state equations, stationarity equations, secondary algebraic constraints, and boundary conditions form a complete two-point boundary value problem.

4.3 Solving the Boundary Value Problem

Boundary value problems are very common in many science and engineering fields. They can become quite complicated and require significant computation to reach a solution. Two general ways to solve two-point boundary value problems are described next. These are the shooting method and the finite difference method [19],[26]. Both have limitations.

4.3.1 Shooting Method

The shooting method is a relatively straightforward combination of a time marching quadrature method (Runga-Kutta or the like) to solve a set of differential equations and an error minimization technique. The shooting method works by iteratively solving the set of differential equations as an initial value problem and then measuring the error in the final state of the system compared to the desired final state. The shooting method is subject to the stability of the differential equations in question. If the time marching algorithm does not converge, the method will not work. Unfortunately, the boundary value problem for the quad-rotor that is formulated in the next chapter falls into this category. The quad-rotor system model and the coupled optimality conditions are simply too unstable to be solved with the shooting method.

- Advantages : straightforward iterative quadrature method and error minimization,
- Disadvantages : does not always converge

4.3.2 Finite Difference Method

The finite difference method poses another possibility [26]. It involves creating a system of algebraic equations to be solved at each instance in time where the solution is desired. For a simulation like ours, this means at least hundreds if not thousands of time steps. The derivatives in the differential equations are expressed as finite differences involving variables at adjacent time steps. The values of each state and co-state variable are defined as unknowns at each time step. This creates a system of equations involving several thousand unknowns that need to be solved

for. For a linear system this is not so bad because the problem is reduced to the inversion of a sparse matrix. For this, there are efficient numerical algorithms that can be used. Since the quad-rotor boundary value problem is nonlinear, it must be solved with a gradient descent technique or something similar.

- Advantages : turns the BVP into a system of algebraic equations, easy to solve for linear systems,
- Disadvantages : hard to solve for nonlinear systems, does not always converge

In the next chapter we derive the set of differential equations which form the boundary value problem defined by our goal of optimizing the energy usage of a quad-rotor.

Chapter 5

Quad-rotor Boundary Value Problem

In this chapter we use the expressions for the dynamic model of the quad-rotor (equations 3.24 and 3.25) and the optimal control formulation (equations 4.15 through 4.25) to derive the optimality conditions for our specific problem.

Recall from chapter 4 that each of the optimality conditions is a mathematical result of setting the first variation of the objective function equal to zero. To maintain algebraic continuity, each additive term must then be zero. Using this logic, each of the optimality conditions is obtained. Given the general form of the optimality conditions, we can introduce the quad-rotor dynamic model. The resulting expressions can be simplified to arrive at specific equations which form our quad-rotor boundary value problem. The optimal flight path and the optimal control input as a function of time form the solution to this boundary value problem.

5.1 Co-State Equations

The co-state equations are expressed as follows where F is our set of system equations and L is the Lagrangian defined in our performance index. Since the Lagrangian does not depend on the state, the co-state differential equation simplifies. Recall that the Lagrangian for our optimization is $L[q(t), u(t), t] = u^T I u$

.

$$\ddot{\lambda} = -\left(\frac{\partial F}{\partial q}\right)^T \lambda - \left(\frac{\partial L}{\partial q}\right)^T \tag{5.1}$$

$$\ddot{\lambda} = -\left(\frac{\partial F}{\partial q}\right)^T \lambda \tag{5.2}$$

The state transition matrix, $\left(\frac{\partial F}{\partial q}\right)$ is tremendous, but there are some simplifications to be made as some of the partial derivatives are zero.

$$\frac{\partial F}{\partial q} = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial x} & \frac{\partial F_{(1)}}{\partial y} & \frac{\partial F_{(1)}}{\partial z} & \frac{\partial F_{(1)}}{\partial \phi} & \frac{\partial F_{(1)}}{\partial \theta} & \frac{\partial F_{(1)}}{\partial \psi} \\ \frac{\partial F_{(2)}}{\partial x} & \frac{\partial F_{(2)}}{\partial y} & \frac{\partial F_{(2)}}{\partial z} & \frac{\partial F_{(2)}}{\partial \phi} & \frac{\partial F_{(2)}}{\partial \theta} & \frac{\partial F_{(2)}}{\partial \psi} \\ \cdot & & & & & \\ \cdot & & & & & \\ \cdot & & & & & \\ \frac{\partial F_{(6)}}{\partial x} & \frac{\partial F_{(6)}}{\partial y} & \frac{\partial F_{(6)}}{\partial z} & \frac{\partial F_{(6)}}{\partial \phi} & \frac{\partial F_{(6)}}{\partial \theta} & \frac{\partial F_{(6)}}{\partial \psi} \end{pmatrix} \tag{5.3}$$

$$\frac{\partial F}{\partial q} = \begin{pmatrix} 0 & 0 & 0 & \frac{\partial F_{(1)}}{\partial \phi} & \frac{\partial F_{(1)}}{\partial \theta} & \frac{\partial F_{(1)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(2)}}{\partial \phi} & \frac{\partial F_{(2)}}{\partial \theta} & \frac{\partial F_{(2)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(3)}}{\partial \phi} & \frac{\partial F_{(3)}}{\partial \theta} & 0 \\ 0 & 0 & 0 & \frac{\partial F_{(4)}}{\partial \phi} & \frac{\partial F_{(4)}}{\partial \theta} & \frac{\partial F_{(4)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(5)}}{\partial \phi} & \frac{\partial F_{(5)}}{\partial \theta} & \frac{\partial F_{(5)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(6)}}{\partial \phi} & \frac{\partial F_{(6)}}{\partial \theta} & \frac{\partial F_{(6)}}{\partial \psi} \end{pmatrix} \tag{5.4}$$

Each of the elements must be computed numerically. An analytical representation of all the partial derivatives in $\left(\frac{\partial F}{\partial q}\right)$ is possible but the task of computing them all would be too time consuming. For our simulations, a simple backward finite difference is much more appropriate:

$$\frac{\partial F_i}{\partial q_j} \approx \frac{F_i(q_j + \alpha) - F_i(q_j)}{\alpha} \tag{5.5}$$

In the above equation, i the index for the state equations, j is the index for the state variables and α is the discrete step size.

The simplified result is

$$\ddot{\lambda} = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial \phi} & \frac{\partial F_{(1)}}{\partial \theta} & \frac{\partial F_{(1)}}{\partial \psi} \\ \frac{\partial F_{(2)}}{\partial \phi} & \frac{\partial F_{(2)}}{\partial \theta} & \frac{\partial F_{(2)}}{\partial \psi} \\ \frac{\partial F_{(3)}}{\partial \phi} & \frac{\partial F_{(3)}}{\partial \theta} & 0 \\ \frac{\partial F_{(4)}}{\partial \phi} & \frac{\partial F_{(4)}}{\partial \theta} & \frac{\partial F_{(4)}}{\partial \psi} \\ \frac{\partial F_{(5)}}{\partial \phi} & \frac{\partial F_{(5)}}{\partial \theta} & \frac{\partial F_{(5)}}{\partial \psi} \\ \frac{\partial F_{(6)}}{\partial \phi} & \frac{\partial F_{(6)}}{\partial \theta} & \frac{\partial F_{(6)}}{\partial \psi} \end{pmatrix} \begin{pmatrix} \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \tag{5.6}$$

.

5.2 Secondary Algebraic Co-State Equations

The secondary algebraic co-state equations are a result of setting the variation of J equal to zero. They are unique to the derivation in Chapter 4, which involves a second order rather than first order representation of the system equations.

$$\frac{\partial H}{\partial \dot{q}} = 0 \tag{5.7}$$

$$0 = \left(\frac{\partial F}{\partial \dot{q}}\right)^T \lambda + \left(\frac{\partial L}{\partial \dot{q}}\right)^T \tag{5.8}$$

$$0 = \left(\frac{\partial F}{\partial \dot{q}}\right)^T \lambda \tag{5.9}$$

$$0 = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial \dot{x}} & \frac{\partial F_{(1)}}{\partial \dot{y}} & \frac{\partial F_{(1)}}{\partial \dot{z}} & \frac{\partial F_{(1)}}{\partial \dot{\phi}} & \frac{\partial F_{(1)}}{\partial \dot{\theta}} & \frac{\partial F_{(1)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(2)}}{\partial \dot{x}} & \frac{\partial F_{(2)}}{\partial \dot{y}} & \frac{\partial F_{(2)}}{\partial \dot{z}} & \frac{\partial F_{(2)}}{\partial \dot{\phi}} & \frac{\partial F_{(2)}}{\partial \dot{\theta}} & \frac{\partial F_{(2)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(3)}}{\partial \dot{x}} & \frac{\partial F_{(3)}}{\partial \dot{y}} & \frac{\partial F_{(3)}}{\partial \dot{z}} & \frac{\partial F_{(3)}}{\partial \dot{\phi}} & \frac{\partial F_{(3)}}{\partial \dot{\theta}} & \frac{\partial F_{(3)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(4)}}{\partial \dot{x}} & \frac{\partial F_{(4)}}{\partial \dot{y}} & \frac{\partial F_{(4)}}{\partial \dot{z}} & \frac{\partial F_{(4)}}{\partial \dot{\phi}} & \frac{\partial F_{(4)}}{\partial \dot{\theta}} & \frac{\partial F_{(4)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(5)}}{\partial \dot{x}} & \frac{\partial F_{(5)}}{\partial \dot{y}} & \frac{\partial F_{(5)}}{\partial \dot{z}} & \frac{\partial F_{(5)}}{\partial \dot{\phi}} & \frac{\partial F_{(5)}}{\partial \dot{\theta}} & \frac{\partial F_{(5)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(6)}}{\partial \dot{x}} & \frac{\partial F_{(6)}}{\partial \dot{y}} & \frac{\partial F_{(6)}}{\partial \dot{z}} & \frac{\partial F_{(6)}}{\partial \dot{\phi}} & \frac{\partial F_{(6)}}{\partial \dot{\theta}} & \frac{\partial F_{(6)}}{\partial \dot{\psi}} \end{pmatrix}^T \begin{pmatrix} \lambda_1 \\ \lambda_2 \\ \lambda_3 \\ \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \tag{5.10}$$

Again this matrix can simplify considerably because the state equations don't depend on all of the state variable time derivatives.

$$0 = \begin{pmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & \frac{\partial F_{(4)}}{\partial \dot{\phi}} & \frac{\partial F_{(4)}}{\partial \dot{\theta}} & \frac{\partial F_{(4)}}{\partial \dot{\psi}} \\ 0 & 0 & 0 & \frac{\partial F_{(5)}}{\partial \dot{\phi}} & \frac{\partial F_{(5)}}{\partial \dot{\theta}} & \frac{\partial F_{(5)}}{\partial \dot{\psi}} \\ 0 & 0 & 0 & \frac{\partial F_{(6)}}{\partial \dot{\phi}} & \frac{\partial F_{(6)}}{\partial \dot{\theta}} & \frac{\partial F_{(6)}}{\partial \dot{\psi}} \end{pmatrix}^T \begin{pmatrix} \lambda_1 \\ \lambda_2 \\ \lambda_3 \\ \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \tag{5.11}$$

$$0 = \begin{pmatrix} \frac{\partial F_{(4)}}{\partial \dot{\phi}} & \frac{\partial F_{(4)}}{\partial \dot{\theta}} & \frac{\partial F_{(4)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(5)}}{\partial \dot{\phi}} & \frac{\partial F_{(5)}}{\partial \dot{\theta}} & \frac{\partial F_{(5)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(6)}}{\partial \dot{\phi}} & \frac{\partial F_{(6)}}{\partial \dot{\theta}} & \frac{\partial F_{(6)}}{\partial \dot{\psi}} \end{pmatrix}^T \begin{pmatrix} \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \tag{5.12}$$

As with the other optimality conditions, the partial derivatives in this matrix must be computed numerically as follows:

$$\frac{\partial F_i}{\partial \dot{q}_j} \approx \frac{F_i(\dot{q}_j + \alpha) - F_i(\dot{q}_j)}{\alpha} \tag{5.13}$$

5.3 Stationarity Conditions

The stationarity conditions express the relationship between the derivatives of the system equation with respect to the input u, the co-state variable $\lambda(t)$, and the derivative of the Lagrangian with respect to the input.

$$\left(\frac{\partial H}{\partial u}\right)^T = \left(\frac{\partial F}{\partial u}\right)^T \lambda + \left(\frac{\partial L}{\partial u}\right)^T = 0 \tag{5.14}$$

$$\frac{\partial F}{\partial q} = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial u_1} & \frac{\partial F_{(1)}}{\partial u_2} & \frac{\partial F_{(1)}}{\partial u_3} & \frac{\partial F_{(1)}}{\partial u_4} \\ \\ \frac{\partial F_{(2)}}{\partial u_1} & \frac{\partial F_{(2)}}{\partial u_2} & \frac{\partial F_{(2)}}{\partial u_3} & \frac{\partial F_{(2)}}{\partial u_4} \\ \\ \frac{\partial F_{(3)}}{\partial u_1} & \frac{\partial F_{(3)}}{\partial u_2} & \frac{\partial F_{(3)}}{\partial u_3} & \frac{\partial F_{(3)}}{\partial u_4} \\ \\ \cdot & & & \\ \cdot & & & \\ \cdot & & & \\ \frac{\partial F_{(6)}}{\partial u_1} & \frac{\partial F_{(6)}}{\partial u_2} & \frac{\partial F_{(6)}}{\partial u_3} & \frac{\partial F_{(6)}}{\partial u_4} \\ \\ \end{pmatrix} \tag{5.15}$$

$$\frac{\partial L}{\partial u} = 2(u_1, u_2, u_3, u_4) \tag{5.16}$$

$$0 = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial u_1} & \frac{\partial F_{(2)}}{\partial u_1} & \frac{\partial F_{(3)}}{\partial u_1} & \frac{\partial F_{(4)}}{\partial u_1} & \frac{\partial F_{(5)}}{\partial u_1} & \frac{\partial F_{(6)}}{\partial u_1} \\ \frac{\partial F_{(1)}}{\partial u_2} & \frac{\partial F_{(2)}}{\partial u_2} & \frac{\partial F_{(3)}}{\partial u_2} & \frac{\partial F_{(4)}}{\partial u_2} & \frac{\partial F_{(5)}}{\partial u_2} & \frac{\partial F_{(6)}}{\partial u_2} \\ \frac{\partial F_{(1)}}{\partial u_3} & \frac{\partial F_{(2)}}{\partial u_3} & \frac{\partial F_{(3)}}{\partial u_3} & \frac{\partial F_{(4)}}{\partial u_3} & \frac{\partial F_{(5)}}{\partial u_3} & \frac{\partial F_{(6)}}{\partial u_3} \\ \frac{\partial F_{(1)}}{\partial u_4} & \frac{\partial F_{(2)}}{\partial u_4} & \frac{\partial F_{(3)}}{\partial u_4} & \frac{\partial F_{(4)}}{\partial u_4} & \frac{\partial F_{(5)}}{\partial u_4} & \frac{\partial F_{(6)}}{\partial u_4} \end{pmatrix} \begin{pmatrix} \lambda_1 \\ \lambda_2 \\ \lambda_3 \\ \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} + 2 \begin{pmatrix} u_1 \\ u_2 \\ u_3 \\ u_4 \end{pmatrix} \tag{5.17}$$

Again, the partials are computed with a finite difference.

$$\frac{\partial F_i}{\partial u_j} \approx \frac{F_i(u_j + \alpha) - F_i(u_j)}{\alpha} \tag{5.18}$$

5.4 Discretization

In a real implementation the measurements and subsequent state estimates, which are the input to the control algorithm, are made available at discrete time intervals. In order to code a simulation and evaluate the behavior of this system of equations, it is more convenient if these equations are represented in a discrete-time form. First order derivatives are approximated as a first backward finite difference. By using backward finite differences, the causality of the expressions is preserved.

$$\dot{x} \approx \frac{x[k] - x[k-1]}{h} \tag{5.19}$$

The second-order time derivatives are approximated as second-order backward finite differences.

$$\ddot{x} \approx \frac{x[k] - 2x[k-1] + x[k-2]}{h^2} \tag{5.20}$$

The continuous system equations are given as follows.

$$\begin{pmatrix} \ddot{x} \\ \ddot{y} \\ \ddot{z} \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ g \end{pmatrix} + \frac{T}{m} \begin{pmatrix} C_\psi S_\theta C_\phi + S_\psi S_\phi \\ S_\psi S_\theta C_\phi - C_\psi S_\phi \\ C_\theta C_\phi \end{pmatrix} \tag{5.21}$$

$$\begin{pmatrix} \ddot{\phi} \\ \ddot{\theta} \\ \ddot{\psi} \end{pmatrix} = J^{-1} \left[\begin{pmatrix} ls(-\omega_2^2 + \omega_4^2) \\ ls(-\omega_1^2 + \omega_3^2) \\ \sum_{i=1}^{4} b\omega_i^2 \end{pmatrix} - \mathfrak{C} \begin{pmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\psi} \end{pmatrix} \right] \tag{5.22}$$

The discrete-time system equations are

$$\begin{pmatrix} \frac{x[k]-2x[k-1]+x[k-2]}{h^2} \\ \frac{y[k]-2y[k-1]+y[k-2]}{h^2} \\ \frac{z[k]-2z[k-1]+z[k-2]}{h^2} \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ g \end{pmatrix} + \frac{T[k]}{m} \begin{pmatrix} C_{\psi[k]} S_{\theta[k]} C_{\phi[k]} + S_{\psi[k]} S_{\phi[k]} \\ S_{\psi[k]} S_{\theta[k]} C_{\phi[k]} - C_{\psi[k]} S_{\phi[k]} \\ C_{\theta[k]} C_{\phi[k]} \end{pmatrix} \tag{5.23}$$

$$\begin{pmatrix} \frac{\phi[k]-2\phi[k-1]+\phi[k-2]}{h^2} \\ \\ \frac{\theta[k]-2\theta[k-1]+\theta[k-2]}{h^2} \\ \\ \frac{\psi[k]-2\psi[k-1]+\psi[k-2]}{h^2} \\ \\ \end{pmatrix} = J^{-1}[k] \left[\begin{pmatrix} ls(-\omega_2[k]^2 + \omega_4[k]^2) \\ \\ ls(-\omega_1[k]^2 + \omega_3[k]^2) \\ \\ \sum_{i=1}^{4} b\omega_i[k]^2 \\ \\ \end{pmatrix} - \mathfrak{C}[k] \begin{pmatrix} \frac{\phi[k]-\phi[k-1]}{h} \\ \\ \frac{\theta[k]-\theta[k-1]}{h} \\ \\ \frac{\psi[k]-\psi[k-1]}{h} \\ \\ \end{pmatrix} \right] \tag{5.24}$$

.

The reason for computing all the partial derivatives numerically is now apparent. To compute the partial derivatives analytically, one would have to deal with the products between the rows of the Coriolis matrix (Equation 3.23) and the columns of the inverse of the Jacobian matrix (Equation 3.12). This sort of computation is the very reason computers were invented in the first place.

5.5 A Finite Difference Solution to the Quad-Rotor Boundary Value Problem

The finite difference method for solving boundary value problems was introduced at the end of Chapter 4. This method reduces our optimal control problem to solving a system of nonlinear algebraic equations. This is a reduction in theoretical complexity but a dramatic increase in computational complexity.

The script 'finiteDiffSolution.py' (Appendix F) implements the finite difference method in an attempt to solve the quad-rotor boundary value problem. Recall

that the computational problem is posed as solving a system of nonlinear algebraic equations. This system of equations is composed of the state equations, the co-state equations, the stationarity conditions, the secondary algebraic conditions, and the boundary conditions. Each of these expressions is possibly a function of the state variables, the co-state variables and the control input. Solving this system becomes a significant task since the state, co-state, and control variables become the unknowns for each instance in time for which a solution to the boundary value problem is desired! In order to sufficiently represent the dynamics of the quad-rotor, on the order of thousands of time steps are necessary. To solve this nonlinear system, a straightforward steepest descent technique was used:

- Steepest Descent Algorithm:

    1. An objective function is formed out of the sum of the squared residuals of each equation in the system.
    2. The gradient is computed as the list of partial derivatives of the objective function with respect to every unknown (every variable defined at each time instance). These partials are approximated as finite differences.
    3. The vector of unknowns is 'moved' in the direction of the negative of the gradient.
    4. The new value of the objective function as well as the gradient are evaluated with the new vector of unknowns.
    5. The state of the minimization process is checked against appropriate convergence criteria.

Conceptually, this algorithm is relatively straightforward but it poses a significant computational challenge. With ten defined time steps, the algorithm ran for several

hours before terminating. Additionally, with only ten time steps defined, the dynamics of the system over a period of several seconds of flight are not well represented. In a physical implementation, the motor speeds need to be updated at a rate on the order of 50 Hz at a minimum. Given these constraints, there would be no realistic way to implement the algorithm in this form on an embedded system, which was loosely included as one of our research objectives.

Instead, in the next chapter we turn to different methods of control and optimization. Control of the system will be achieved with PID expressions. The optimization problem will be approached by appropriately manipulating the gains of the PID control laws in order to change the system behavior.

Chapter 6

PID/PD Control

Among the many methods available for mathematical control of the quad-rotor, a well-tuned PID controller offers both relative robustness and a simple mathematical representation. In this chapter we derive and test the PID control scheme for attitude and 3D position control of a quad-rotor.

6.1 Deriving the Control Expressions

The control of the quad-rotor requires three independent PID controllers for the x, y, and z directions. In addition, the attitude stability of the aircraft is accomplished by three independent PD controllers for each of the Euler angles (ϕ, θ, ψ) . It is assumed for the purpose of simulation that the input to the control expressions includes accurate knowledge of the system state. In other words, it is assumed that the process noise and the measurement noise are zero. Given the natural complexity of the system, inclusion of stochastic processes into the model is left

for further work. As in [6] and [7], the control algorithm proceeds as follows (Algorithm 6.1).

- Algorithm 6.1

    1. The position control expressions give the 'commanded' linear accelerations that are required to drive the system to the desired state.
    2. Given the commanded linear accelerations, the necessary total thrust, pitch, and roll are determined.
    3. The commanded torques about the three axes of the quad-rotor are given by PD controllers using the commanded yaw, pitch, and roll as angular set points.
    4. Given the commanded total thrust and the commanded torques, the motor speeds can be determined.
    5. Once the motor speeds are known, the system model can be used to obtain the updated state of the system.
    6. Go to step 1.

Our goal in the following derivation is to arrive at expressions for the motor speeds that are required to drive the system to the desired state. The discrete-time PID control expressions are formulated using these vectors.

$$P_c = \begin{pmatrix} x_c \\ y_c \\ z_c \end{pmatrix} = \textit{desired (commanded) set point location}$$

$$P = \begin{pmatrix} x \\ y \\ z \end{pmatrix} = \textit{actual position at time step } k$$

The vector of commanded accelerations is given by $\ddot{P}_c$:

$$\ddot{P}_c = K_p(P_c - P) + K_i \sum_k (P_c - P) + K_d(\dot{P}_c - \dot{P}), \tag{6.1}$$

where

$$K_p = \begin{bmatrix} k_{px} \\ k_{py} \\ k_{pz} \end{bmatrix}, K_i = \begin{bmatrix} k_{ix} \\ k_{iy} \\ k_{iz} \end{bmatrix}, K_d = \begin{bmatrix} k_{dx} \\ k_{dy} \\ k_{dz} \end{bmatrix}. \tag{6.2}$$

Recall equation 3.16:

$$f = RT_B = m\ddot{\xi} - G. \tag{6.3}$$

This can be rearranged to give:

$$\ddot{P}_c = -ge_{inz} + \left(\frac{1}{m}\right)(Te_{qrz})\,R. \tag{6.4}$$

$$e_{inz} = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix} \quad \text{(in the inertial reference frame)}$$

$$e_{qrz} = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix} \quad \text{(in the quad-rotor reference frame)}$$

The angles ϕ and θ, and the total thrust T can be determined algebraically, assuming we know $\ddot{P}_c$ and ψ.

$$R^T\left(\ddot{P}_c + ge_{inz}\right) = \left(\frac{1}{m}\right)(Te_{qrz}) \tag{6.5}$$

$$\begin{pmatrix} c(\psi)c(\theta) & s(\psi)c(\theta) & -s(\theta) \\ c(\psi)s(\theta)s(\phi) - s(\psi)c(\phi) & s(\psi)s(\theta)s(\phi) + c(\psi)c(\phi) & c(\theta)s(\phi) \\ c(\psi)s(\theta)c(\phi) + s(\psi)s(\phi) & s(\psi)s(\theta)c(\phi) - c(\psi)s(\phi) & c(\theta)c(\phi) \end{pmatrix} \begin{pmatrix} a_x \\ a_y \\ a_z + g \end{pmatrix} = \frac{1}{m}\begin{pmatrix} 0 \\ 0 \\ T \end{pmatrix} \tag{6.6}$$

The matrix equation above is then written as three independent scalar expressions.

$$a_x c(\psi)c(\theta) + a_y s(\psi)c(\theta) - s(\theta)(a_z + g) = 0 \tag{6.7}$$

$$\begin{aligned} & a_x(c(\psi)s(\theta)s(\phi) - s(\psi)c(\phi)) \\ & + a_y(s(\psi)s(\theta)s(\phi) + c(\psi)c(\phi)) \\ & + (a_z + g)c(\theta)s(\phi) = 0 \end{aligned} \tag{6.8}$$

$$\begin{aligned} &a_x(c(\psi)s(\theta)c(\phi) + s(\psi)s(\phi)) \\ &+ a_y(s(\psi)s(\theta)c(\phi) - c(\psi)s(\phi)) \\ &+ (a_z + g)c(\theta)c(\phi) = \left(\frac{T}{m}\right) \end{aligned} \tag{6.9}$$

Next, we divide Equation (6.7) by $c(\theta)$ and solve for θ.

$$a_x c(\psi) + a_y s(\psi) + (a_z + g)(-\tan(\theta)) = 0 \tag{6.10}$$

$$\theta_c = \arctan\left(\frac{a_x c(\psi) + a_y s(\psi)}{a_z + g}\right) \tag{6.11}$$

Next: Equation (6.8) x $s(\phi)$ - Equation (6.9) x $c(\phi)$. The result is

$$\phi = \arcsin\left(\frac{a_x s(\psi) - a_y c(\psi)}{T/m}\right). \tag{6.12}$$

Square both sides of (6.5) and note that $R^T = R^{-1}$.

$$a_x^2 + a_y^2 + (a_z + g)^2 = \left(\frac{T}{m}\right)^2 \tag{6.13}$$

$$\left(\frac{T}{m}\right) = \sqrt{a_x^2 + a_y^2 + (a_z + g)^2} \tag{6.14}$$

This result is then substituted back in Equation (6.12) to give

$$\phi_c = \arcsin\left(\frac{a_x s(\psi) - a_y c(\psi)}{\sqrt{a_x^2 + a_y^2 + (a_z + g)^2}}\right) \tag{6.15}$$

Using θ_c and ϕ_c as set points, we can write the PD angular control laws. The subscript 'c' stands for 'commanded'.

$$\tau_{\phi c} = [k_{p\phi}(\phi_c - \phi) + k_{d\phi}(\dot{\phi}_c - \dot{\phi})]I_x \tag{6.16}$$

$$\tau_{\theta c} = [k_{p\theta}(\theta_c - \theta) + k_{d\theta}(\dot{\theta}_c - \dot{\theta})]I_y \tag{6.17}$$

$$\tau_{\psi c} = [k_{p\psi}(\psi_c - \psi) + k_{d\psi}(\dot{\psi}_c - \dot{\psi})]I_z \tag{6.18}$$

Given the commanded torques and the commanded total thrust, the commanded motor speeds can be obtained from the expressions (3.2) and (3.4) from section 3.3:

$$\omega_{1c} = \sqrt{\frac{T_c}{4k} - \frac{\tau_{\theta c}}{2kL} - \frac{\tau_{\psi c}}{4b}} \tag{6.19}$$

$$\omega_{2c} = \sqrt{\frac{T_c}{4k} - \frac{\tau_{\phi c}}{2kL} + \frac{\tau_{\psi c}}{4b}} \tag{6.20}$$

$$\omega_{3c} = \sqrt{\frac{T_c}{4k} + \frac{\tau_{\theta c}}{2kL} - \frac{\tau_{\psi c}}{4b}} \tag{6.21}$$

$$\omega_{4c} = \sqrt{\frac{T_c}{4k} + \frac{\tau_{\phi c}}{2kL} + \frac{\tau_{\psi c}}{4b}} \tag{6.22}$$

With the above results, we can summarize the control loop. The PID control expressions prescribe linear accelerations in each direction (x, y, z) which will drive the system toward the desired position. The linear accelerations and knowledge of ψ are used to calculate the angles ϕ and θ, and the total thrust T. Given the angles and their time derivatives, the prescribed torques about the quad-rotor center of mass are given by PD control laws. Given the torques and the total thrust, the vector of motor speeds can be calculated.

In a physical implementation, after the motor speeds are updated, the state of the system would be estimated from whatever sensor data is available. The environmental context would dictate which type of sensor hardware would be appropriate. In a simulation context, we use the dynamical system model from Chapter 3 to evaluate the resulting motion of the system. In a sense, this process is just the inverse of the control loop. For further work, a random process could be included here to model sensor noise. This would give a nice simulation platform for evaluating the performance of a Kalman filter for estimating the state of the quad-rotor.

6.2 Testing the Control Scheme

With experimentally tuned control expressions, arbitrarily shaped, sub-optimal paths can be formed by updating the desired location periodically. Figures **??** through **??** show the utility of the control scheme. It is important to note that in our simulations, the desired velocity at each of the ordered set points is zero. In words, the control algorithm is saying to the quad-rotor: 'Go to the desired

location and hover until the set point is updated'. To design a path that includes set points with a non-zero desired velocity vector would require modification of the algorithm.

The values of the constants that were used in the simulation are shown in Table 6.2. Figure 6.3 shows the quad-rotor traversing along the edges of a 4 meter cube. This shows that in the simulation context, we have the ability to precisely locate the quad-rotor in space. The mathematical reality here is that the state of the system is exactly known within the algorithm. For a real implementation, the system model is replaced by the actual system. In this case the validity of the control algorithm is a function of the uncertainty of the state at each instance in time. This can be quantified by the state estimation process by which physical sensor measurements are combined.

Figure **??** shows that there is an upper limit to the difference in initial and final vector positions. A single PID tuning is only usable up to a certain magnitude of desired displacement. Mathematically, the controller is still stable but the overshoot of the desired position grows proportionately to the desired position itself. For arbitrarily shaped, long distance flights, the path would have to be composed of incremental pieces which are small enough so that a performance metric for the overshoot for each segment was satisfied.

The time domain plots (Figures **??**, 6.4, and **??**) offer information about the stability of the system and the controller. Small oscillations in the linear and angular positions and velocities can be seen in Figure **??**. These oscillations are an artifact of the coupling between the angular and linear control laws. Intuitively, this makes sense because the control of the linear position requires that the angular state of the quad-rotor be destabilized. In general it is the natural instability of this system which allows it to be so maneuverable. Also the mathematical complexity

of the system makes for a difficult optimization problem. In the next chapter we use the PID tuning as a basis for optimizing the system according to specific performance criteria.



FIGURE 6.1: A typical run - the 3D path



FIGURE 6.2: A typical run - time domain

Simulation Parameters	Units	Description
$g = -9.81$	$\frac{m}{s^2}$	acceleration due to gravity
$m = 1$	kg	mass
$L = 1$	m	length of quad-rotor arm
$b = 10^{-6}$	$\frac{Nms^2}{Rad^2}$	aerodynamic torque coefficient
$k = 2.45 * 10^{-6}$	$\frac{Ns^2}{Rad^2}$	aerodynamic thrust coefficient
$Ixx = 5.0 * 10^{-3}$	$\frac{Nms^2}{Rad}$	moments of inertia
$Iyy = 5.0 * 10^{-3}$	$\frac{Nms^2}{Rad}$	
$Izz = 10.0 * 10^{-3}$	$\frac{Nms^2}{Rad}$	

TABLE 6.1: Simulation Parameters



FIGURE 6.3: Tracing some of the edges of a 4m cube - the 3D path



FIGURE 6.4: Tracing some of the edges of a 4m cube - time domain plots



FIGURE 6.5: Testing the control with larger set points - the 3D path



FIGURE 6.6: Testing the control with larger set points - time domain plots

Chapter 7

PID Gain Optimization

In order to arrive at a solution to the quad-rotor energy optimization problem that is closer to running in real-time, a heuristic approach has been adopted. Recall that our general aim is to effectively control the vector position of the quad-rotor and additionally use the least energy in doing so. The relative simplicity of a PID controller makes it a good choice instead of the full nonlinear classical optimal control formulation. Also, if the PID control expressions are tuned well and that tuning is not changed, the control algorithm performs well.

The motivation for our heuristic method is to find the PID controller tuning which uses the least energy to drive the UAV to the desired state. The PID tuning defines the dynamics of the controller. Using the quad-rotor model derived in Chapter 3, the performance of the controller and the dynamics of the system can be evaluated as a function of the tuning. Mathematically, this can be represented as follows.

The aim of the optimization is to find: $arg\ min\big[\sum_{k,i}\omega_i[k] \mid K_p, K_i, K_d\big]$, where $\omega_i[k]$ is the ith rotor speed at the kth time step. The variables K_p , K_i and K_d are the vectors of proportional, integral, and derivative gains defined as:

$$K_p = \begin{bmatrix} k_{px} \\ k_{py} \\ k_{pz} \end{bmatrix}, K_i = \begin{bmatrix} k_{ix} \\ k_{iy} \\ k_{iz} \end{bmatrix}, K_d = \begin{bmatrix} k_{dx} \\ k_{dy} \\ k_{dz} \end{bmatrix}$$

In our simulations, the time integral of all four motor speeds is proportional to the total energy used. Calculation of the actual energy used by the UAV in traversing a flight path would require a model for the motor. This is seen as unnecessary for our purposes since the time integral of the motor speeds and the total energy used will have the same effective minimum. Since the control input is calculated as part of the control algorithm anyway, it is used as a performance metric.

In any realistic application of UAV technology, the energy budget is only one important aspect of the control problem. Other important criteria for evaluating the performance of a controller are over-shoot of the desired location, the time of flight, and mathematical resonances or marginal instabilities. These factors must be considered in the design of the system. However, in the initial results described below, the time integral of the motor speeds is used as a single performance metric. The reason for this is to simplify the relationship between the performance metric and the PID gains. This is described in the next section.

7.1 Initial Simulation Results

In the context of the optimization process described in the previous section, there is evidence for the lack of robustness of the PID control. This can be shown by analyzing the relationship between the measured total thrust and the PID gains. Ideally, a gradient descent method would be used to minimize the thrust as a

function of the control gains. The basic flow of the algorithm that we would really like to implement is as follows.

1. Choose a set of proportional and derivative gains for each vector direction (x, y, and z);
2. Perform a simulation that controls the quad-rotor from an initial vector position to a desired vector position;
3. Calculate the sum of the four motor speeds over the duration of the simulation;
4. Appropriately change the PID gains such that the sum of the motor speeds decreases;
5. Go to step 1. Repeat until the sum of the motor speeds is found to be a minimum.

In reality, it has been found that the relationship between the measured total thrust and PID gains is not well-behaved. After many days of trying to debug a gradient descent algorithm, and observing inconsistent behavior, it was decided that a brute force method might be the only possibility. A deeper understanding of the objective function was needed. The brute force method simply requires that we simulate the system and determine the value of the performance criteria for each possible set of PID gain vectors within a given range.

In order to limit the number of simulations required to really represent the dynamics of the system, the set point $(0, 0, 1)$ was chosen. By choosing this set point, the motion of the quad-rotor is intentionally limited to the z-direction which limits the number of possible gain vectors for this test. This makes the tuning of the

x and y direction controllers irrelevant. To further limit the number of simulations required, the Ziegler-Nichols PID tuning method was used. This method is discussed in [27]. There are also excellent resources online to explain tuning [znw].

The Ziegler-Nichols method specifies simple algebraic relationships between the proportional, integral, and derivative gains. This allows each of the PID gains to be expressed as a function of a single gain variable, k_u , which is allowed to range from 1 to 100.

The results of these simulations are shown in Figure **??**.



FIGURE 7.1: The relationship between Ku and the measured total thrust.

The relationship between Ku and the total measured thrust depicted in Figure **??** is rather disappointing to say the least. The values of zero total thrust are the

result of simulations that failed to converge to the set point. Without an objective function that is at least marginally well behaved we have no hope to employ a gradient descent minimization technique. The relationship shown in Figure **??** is indeed a product of a deterministic system but displays little to no continuity.

Another detail which cannot be ignored is that the total thrust alone is not sufficient as a performance criteria. Additionally, for appropriate control of the UAV, the overshoot and oscillations which show up in improperly tuned PID controllers must be accounted for. Specifically, as the proportional gain is increased to drive the system to the desired location more quickly, the total thrust for the simulation will decrease but eventually the overshoot and oscillations grow to unacceptable levels. In the opposite fashion, if the differential gain is increased, the overshoot and oscillations will be suppressed but the time required to reach the set point will increase along with the total thrust. The competitive nature of these three (necessary) performance criteria further complicate the relationship between the PID gain vectors and the objective function making a gradient descent minimization technique even less viable.

7.2 Brute Force Simulation Results

Given that a standard mathematical optimization technique is out of the question, what options are left? A nonlinear control law could be implemented and would perhaps make the optimization possible, but this is uncertain and not possible in the current time frame.

The decision was made to try many possible gain vectors and have an appropriate objective function to characterize each of the simulations. Given that the brute

force algorithm is easy to write (and massively parallel-izable), around 6000 simulations were performed over a period of several hours. The computation was delegated to six independent instantiations of a python script, each one taking on a subset of the possible gain vectors and a separate CPU.

A separate script was used to parse through all the results of the simulations which were stored in many time-stamped files. Of the roughly 6000 simulations, about 1000 of them converged. For these, the set point was reached and the stopping criteria for the simulation were satisfied. Of the 1000 or so good runs, about 80 simulations satisfied the maximum overshoot and oscillation criteria. Only the gain vectors which produced less than ten percent overshoot were accepted. Likewise, only simulations which crossed the desired set point in each direction fewer than four times were deemed acceptable. The remaining 80 simulations were sorted lowest to highest by total measured thrust. The optimal run that was found is detailed in Table 7.2. In Figures 7.2 and 7.3 the dynamics of the system with optimal PID tuning are shown.

Figures 7.2 and 7.3 show the simulation of the quad-rotor flight from the initial point $(0, 0, 1)$ to the desired point $(1, 1, 2)$ using the optimal PID tuning. There are actually two distinct legs to the simulation. The reason for this comes from the fact that there are two types of initial conditions which have fundamental differences. There is a hovering state which we use as initial conditions for the simulations in the optimization procedure. There is another mathematical state which occurs at the very beginning of the simulation. The mathematical initialization of the quad-rotor state is at the origin $(0, 0, 0)$ with zero velocity and acceleration but it is not exactly hovering. This subtle distinction comes from the fact that the force of gravity is not canceled out by the thrust initially. The controller has had no time to act to stabilize the system. The physical scenario that this condition

Parameter	Value
kpx	15
kpy	15
kpz	40
kix	0.8
kiy	0.8
kiz	15
kdx	10
kdy	10
kdz	50
ending iteration	987
discrete time step	0.01 (s)
flight time	9.87 (s)
cpu runtime	11.41 (s)
return value	1 (great success)
initial position	[0, 0, 1] (m)
set point	[1, 1, 2] (m)
total thrust	4969.8 (Newton seconds)
x crossings	3
x overshoot	0.0249 (m)
y crossings	1
y overshoot	0.0185 (m)
z crossings	1
z overshoot	0.0992 (m)

TABLE 7.1: Numerical descriptors of the optimal run



FIGURE 7.2: The Optimal Run - 3D path

would correspond to is if a person held the quad-rotor at the initial position in free space (perhaps designated as the origin) and then at $t = 0$, simply let go. Another way to state this is that the simulations do not account for the normal force which would be imparted to the quad-rotor if it were simply taking off from the ground. To account for this would perhaps require augmentation of the dynamical model of the quad-rotor.

Our aim was to start and end in a hovering state for the optimization. This is why our simulations start with a 'take-off sequence' where the quad-rotor leaves from the origin and goes to the position $(0, 0, 1)$. After this, the system is stabilized in a hovering state. From there, arbitrary paths can be incrementally constructed by simply redefining the desired location.



FIGURE 7.3: The Optimal Run - time domain

Despite the mathematical difficulties that were experienced with the various optimization techniques that were explored, this final result is useful. Until a reasonable mathematical optimization technique is found, the optimality of the solution described above is a function of how much time one is willing to run the brute force algorithm.

Chapter 8

Summary and Future Work

8.1 Summary

In this final chapter we review the main points of the paper and propose directions for further work. Our first significant result was the dynamic model of the quadrotor. The Euler-Lagrange formulation was used to derive the dynamic model. The resulting set of nonlinear differential equations formed the basis for both the control and optimization methods which were subsequently derived.

Our first approach to the path-energy optimization problem which incorporated the dynamic model was classical optimal control. Using this formulation, we derived a set of differential and algebraic equations which form a complex boundary value problem. Our initial aim was to develop a method for achieving a path-energy optimization which would perform on a near-real-time-schedule. The computational resources needed to solve the optimal control boundary value problem on this real-time schedule invalidate it as a possible solution.

The next method of optimization which was explored was a heuristic method. Control of the UAV was attained by way of a set of PID and PD controllers. Since the performance of the quad-rotor is defined by the controller tuning, the system can be optimized as a function of this tuning. Relevant criteria for evaluating the performance of the system are the total thrust integrated over the duration of the simulation, oscillations that the system experiences, overshoot of the desired location, and the total time of flight. It was determined experimentally that the relationship between these performance metrics and the controller tuning was not well-behaved mathematically. Without a clean mathematical representation of our objective function, the viability of an efficient optimization method is questioned.

Next, a brute force method was used to determine the optimal controller tuning. With limited time, the true optimality of the solution is not certain. Even with limited resources we were able to determine a controller tuning which is good enough to perform simulated fights in a relatively efficient manner.

8.2 Further Work

The problem of path-energy optimization as solved in this thesis can be worked on in the future to produce more robust results. Two possible mathematical modifications that could possibly allow for an efficient optimization algorithm are as follows. They both have design trade-offs.

- *Model Linearization* One approach would beto use a linearized model. The goal there would be to simplify the relationship between the controller tuning and the relevant performance metrics by simplifying the mathematical

representation of the dynamic model. The danger in using a linear approximation is creating an over-simplified model that is divergent from reality to an extent that makes it unusable.

- *Nonlinear Control*If instead of a linear PID controller, a nonlinear control method was used, the stability of the system could be increased. This would perhaps allow for a well behaved and more well defined relationship between the parameters of the controller and the measurable dynamics of the system. The obvious caveat here is the increase in complexity of the controller. The only real way to know if one of these options would allow for an efficient optimization procedure would be to try them all and characterize them in the context of the goal of the flight.

- *UAV Swarm Optimization* Another area of research interest that would benefit from an energy optimization procedure is the control of swarms of UAVs. The distributed control of UAVs is a field which offers a wide range of engineering challenges such as collision avoidance, optimization of networked communication, and optimization of workload delegation toward a common goal. The contextual details of the cooperative aim of the swarm would inform the optimization of the system.

- *Sensor Fusion and State Estimation* Yet another area of possible further research is in the sensor fusion and state estimation problem. For a physical implementation, knowledge of the state of the system is a critical component. Given that there are a very large variety of physical sensors that could contribute to this knowledge, this is an interesting problem. An aspect of this problem that adds richness to this situation is the fact that each type of sensor will have a different rate at which physical information is available. This rate is determined by the physical nature of the quantity being measured.

A good example is the integration of GPS measurements and accelerometer measurements. Values from these sensors are available perhaps at rates of 1 Hz and 100 Hz respectively. The sensor data would be integrated with a Kalman filter to develop situational awareness which allows for effective control of the system.

In general the control and optimization of UAVs is a rich and evolving field of research with many unsolved problems. There will be many commercial applications of this technology appearing in coming years which will be informed by future research.

Appendix A

agentModule.py

breakatwhitespace

```
1
'''
3 here is an outline of the program flow:

5     1) initialize lists for state variables and appropriate derivatives
         as well as constants.
7     2) calculate total thrust T and the torques using the state variables from
         the [k]th time step
9     3) using T[k] and tao_[k] calculate new motor speed vector for time [k]
      4) using T[k] and tao_[k] calculate new state variables at time [k+1]
11    5) repeat
'''
13

from numpy import cos as c, sin as s , sqrt, array, dot, arctan2, arcsin, sign , around
15 from numpy.linalg import inv
from wind import *
17 import sys
import math
19

################################################################################
21

class agent:
23

    def __init__(self, x_0,   y_0,   z_0,
25                 initial_setpoint_x,  initial_setpoint_y, initial_setpoint_z,
                   agent_priority = 10 ):
27



29


31          #------------------------------ physical constants
            self.g = -9.81    #[m/s^2]
```

```
33          self.m = 1       #[kg]
            self.L = 1     #[m]
35          self.b = 10**-6
            self.k = self.m*abs(self.g)/(4*(1000**2))
37          #print 'self.k = ',self.k
            #raw_input()
39          #--------------------------------moments of inertia
            self.Ixx = 5.0*10**-3
41          self.Iyy = 5.0*10**-3
            self.Izz = 10.0*10**-3
43
            #--------------------------------directional drag coefficients
45          self.Ax = 0.25
            self.Ay = 0.25
47          self.Az = 0.25

49          self.hover_at_setpoint = True

51          # a list of distances to each other agent sorted nearest to farthest
            self.distance_vectors = []
53
            self.agent_priority = agent_priority
55
            # state vector and  derivative time series' list initializations
57          self.x = [x_0]
            self.y = [y_0]
59          self.z = [z_0]

61          self.xdot = [0]
            self.ydot = [0]
63          self.zdot = [0]

65          self.xddot = [0]
            self.yddot = [0]
67          self.zddot = [0]

69          self.phi   = [0]
            self.theta = [0]
71          self.psi   = [0]

73          self.phidot   = [0]
            self.thetadot = [0]
75          self.psidot   = [0]

77          self.phiddot   = [0]
            self.thetaddot = [0]
79          self.psiddot   = [0]

81          self.tao_qr_frame = []
            self.etadot = []
83          self.etaddot =[]


85
            #------------------------------------------------------------CONTROLLER GAINS
87
```

```
        self.kpx = 0.          # PID proportional gain values
89      self.kpy = 0.
        self.kpz = 0.
91
        self.kdx = 0.           # PID derivative gain values
93      self.kdy = 0.
        self.kdz = 0.
95
        self.kddx = 0.
97      self.kddy = 0.
        self.kddz = 0.
99
        self.kix = 0.         # PID integral gain values
101     self.kiy = 0.
        self.kiz = 0.
103
        self.kpphi   = 4  # gains for the angular pid control laws
105     self.kptheta = 4
        self.kppsi   = 4
107
        self.kiphi   = 0.
109     self.kitheta = 0.
        self.kipsi   = 0.
111
        self.kdphi   = 5
113     self.kdtheta = 5
        self.kdpsi   = 5
115
        self.xdd_des = 0
117     self.ydd_des = 0
        self.zdd_des = 0
119
        self.x_integral_error = [0]
121     self.y_integral_error = [0]
        self.z_integral_error = [0]
123
        # angular set points
125     self.phi_des = 0
        self.theta_des = 0
127     self.psi_des = 0

129     self.psidot_des = 0


131



133     self.phi_comm = [0,0]
        self.theta_comm = [0,0]
135     self.T_comm = [0,0]

137     self.tao_phi_comm = [0,0]
        self.tao_theta_comm = [0,0]
139     self.tao_psi_comm = [0,0]


141
        # force, torque, and motor speed list initializations
```

```
143
144         self.T = [9.81]
145         self.tao_phi   = [0]
146         self.tao_theta = [0]
147         self.tao_psi   = [0]
148
149         self.w1 = [1000]
150         self.w2 = [1000]
151         self.w3 = [1000]
152         self.w4 = [1000]
153
154         self.etaddot = []
155         #-----------------------------------
156
157         self.max_iterations = 10000
158         self.h = 0.01
159         self.ending_iteration = 0
160
161         #-------------------------------------------------------------------wind!!
162         self.wind_duration = self.max_iterations
163         self.max_gust = 0.1
164
165         # generate the wind for the entire simulation beforehand
166         self.wind_data = wind_vector_time_series(self.max_gust,self.wind_duration)
167
168         self.wind_x = self.wind_data[0]
169         self.wind_y = self.wind_data[1]
170         self.wind_z = self.wind_data[2]
171
172
173         #-----------------------------------------------------------------------
174
175         #TODO: NEED TO SORT OUT THE MIN AND MAX THRUST PARAMETERS AND CORRELATE
176         #      THIS PHYSICAL LIMITATION WITH THE MAX VALUES FOR THE PROPORTIONAL
177         #      GAIN TERMS IN EACH CONTROL LAW.
178
179         #self.max_total_thrust = 50.0  # [newtons]
180         #self.min_total_thrust = 1.0
181
182         self.x_des = initial_setpoint_x
183         self.y_des = initial_setpoint_y
184         self.z_des = initial_setpoint_z
185
186         self.xdot_des = 0
187         self.ydot_des = 0
188         self.zdot_des = 0
189
190         self.initial_setpoint_x = initial_setpoint_x
191         self.initial_setpoint_y = initial_setpoint_y
192         self.initial_setpoint_z = initial_setpoint_z
193
194         #-----------------------------------------------------------------------
195
196
197         self.w1_arg = [0,0]
```

```
        self.w2_arg = [0,0]
        self.w3_arg = [0,0]
        self.w4_arg = [0,0]


        self.xacc_comm = [0]
        self.yacc_comm = [0]
        self.zacc_comm = [19.62]




    ##################################################  END   " __INIT__() "



    # the Jacobian for transforming from body frame to inertial frame

    def J(self):

        ixx = self.Ixx
        iyy = self.Iyy
        izz = self.Izz

        th = self.theta[-1]
        ph = self.phi[-1]


        j11 = ixx

        j12 = 0

        j13 = -ixx * s(th)

        j21 = 0

        j22 = iyy*(c(ph)**2) + izz * s(ph)**2

        j23 = (iyy-izz)*c(ph)*s(ph)*c(th)

        j31 = -ixx*s(th)

        j32 = (iyy-izz)*c(ph)*s(ph)*c(th)

        j33 = ixx*(s(th)**2) + iyy*(s(th)**2)*(c(th)**2) + izz*(c(ph)**2)*(c(th)**2)

        return array([
                    [j11, j12, j13],
                    [j21, j22, j23],
                    [j31, j32, j33]
                ])
```

```
253
255
    #-------------------Coriolis matrix
257
    def coriolis_matrix(self):
259
        ph = self.phi[-1]
261     th = self.theta[-1]
263     phd = self.phidot[-1]
        thd = self.thetadot[-1]
265     psd = self.psidot[-1]
267     ixx = self.Ixx
        iyy = self.Iyy
269     izz = self.Izz
271     c11 = 0
273     # break up the large elements in to bite size chunks and then add each term ...
275     c12_term1 = (iyy-izz) * ( thd*c(ph)*s(ph) + psd*c(th)*s(ph)**2 )
277     c12_term2and3 = (izz-iyy)*psd*(c(ph)**2)*c(th) - ixx*psd*c(th)
279     c12 = c12_term1  + c12_term2and3
281
283     c13 = (izz-iyy) * psd * c(ph) * s(ph) * c(th)**2
285
287     c21_term1 = (izz-iyy) * ( thd*c(ph)*s(ph) + psd*s(ph)*c(th) )
289     c21_term2and3 = (iyy-izz) * psd * (c(ph)**2) * c(th) + ixx * psd * c(th)
291     c21 = c21_term1 + c21_term2and3
293
295     c22 = (izz-iyy)*phd*c(ph)*s(ph)
297     c23 = -ixx*psd*s(th)*c(th) + iyy*psd*(s(ph)**2)*s(th)*c(th)
299     c31 = (iyy-izz)*phd*(c(th)**2)*s(ph)*c(ph) - ixx*thd*c(th)
301
303     c32_term1     = (izz-iyy)*( thd*c(ph)*s(ph)*s(th) + phd*(s(ph)**2)*c(th) )
305     c32_term2and3 = (iyy-izz)*phd*(c(ph)**2)*c(th) + ixx*psd*s(th)*c(th)
307     c32_term4 = - iyy*psd*(s(ph)**2)*s(th)*c(th)
```

```
309         c32_term5 = - izz*psd*(c(ph)**2)*s(th)*c(th)

311         c32 = c32_term1 + c32_term2and3 + c32_term4 + c32_term5

313

315         c33_term1 = (iyy-izz) * phd *c(ph)*s(ph)*(c(th)**2)

317         c33_term2 = - iyy * thd*(s(ph)**2) * c(th)*s(th)

319         c33_term3and4 = - izz*thd*(c(ph)**2)*c(th)*s(th) + ixx*thd*c(th)*s(th)

321         c33 = c33_term1 + c33_term2 + c33_term3and4

323

            return array([
325                     [c11,c12,c13],
                        [c21,c22,c23],
327                     [c31,c32,c33]
                         ])
329

331     #---------------------------------------------------------------------

333

        def control_block(self):
335

337         # calculate the integral of the error in position for each direction

339         self.x_integral_error.append( self.x_integral_error[-1] + (self.x_des - self.x[-1])*self.h )
            self.y_integral_error.append( self.y_integral_error[-1] + (self.y_des - self.y[-1])*self.h )
341         self.z_integral_error.append( self.z_integral_error[-1] + (self.z_des - self.z[-1])*self.h )

343

            # computte the comm linear accelerations needed to move the system from present location to the
         desired location
345

            self.xacc_comm.append( self.kdx * (self.xdot_des - self.xdot[-1])
347                                 + self.kpx * ( self.x_des - self.x[-1] )
                                    + self.kddx * (self.xdd_des - self.xddot[-1] )
349                                 + self.kix * self.x_integral_error[-1]  )

351

            self.yacc_comm.append( self.kdy * (self.ydot_des - self.ydot[-1])
353                                     + self.kpy * ( self.y_des - self.y[-1] )
                                        + self.kddy * (self.ydd_des - self.yddot[-1] )
355                                     + self.kiy * self.y_integral_error[-1]  )

357

            self.zacc_comm.append( self.kdz * (self.zdot_des - self.zdot[-1])
359                                     + self.kpz * ( self.z_des - self.z[-1] )
                                        + self.kddz * (self.zdd_des - self.zddot[-1] )
361                                     + self.kiz * self.z_integral_error[-1] )
```

```
363
        # need to limit the max linear acceleration that is perscribed by the control law
365
        # as a meaningful place to start, just use the value '10m/s/s' , compare to g = -9.8 ...
367
        max_latt_acc = 5
369
        max_z_acc = 30
371
        if abs(self.xacc_comm[-1]) > max_latt_acc: self.xacc_comm[-1] = max_latt_acc * sign(self.xacc_comm
    [-1])
373     if abs(self.yacc_comm[-1]) > max_latt_acc: self.yacc_comm[-1] = max_latt_acc * sign(self.yacc_comm
    [-1])
        if abs(self.zacc_comm[-1]) > max_z_acc: self.zacc_comm[-1] = max_z_acc * sign(self.zacc_comm[-1])
375
        min_z_acc = 12
377
        if self.zacc_comm[-1] < min_z_acc: self.zacc_comm[-1] = min_z_acc
379
        # using the comm linear accellerations, calc  theta_c, phi_c and T_c
381
        theta_numerator = (self.xacc_comm[-1] * c(self.psi[-1]) + self.yacc_comm[-1] * s(self.psi[-1]) )
383
        theta_denominator = float( self.zacc_comm[-1] + self.g )
385
        if theta_denominator <= 0:
387
            theta_denominator = 0.1           # don't divide by zero !!!
389
        self.theta_comm.append(arctan2( theta_numerator ,  theta_denominator ))
391
        self.phi_comm.append(arcsin( (self.xacc_comm[-1] * s(self.psi[-1]) - self.yacc_comm[-1] * c(self.psi
    [-1]) ) / float(sqrt( self.xacc_comm[-1]**2 +
393
             self.yacc_comm[-1]**2 +
            (self.zacc_comm[-1] + self.g)**2  )) ))
395
        self.T_comm.append(self.m * ( self.xacc_comm[-1] * ( s(self.theta[-1])*c(self.psi[-1])*c(self.phi
    [-1]) + s(self.psi[-1])*s(self.phi[-1]) ) +
397                                  self.yacc_comm[-1] * (  s(self.theta[-1])*s(self.psi[-1])*c(self.phi
    [-1]) - c(self.psi[-1])*s(self.phi[-1]) ) +
                                    (self.zacc_comm[-1] + self.g) * ( c(self.theta[-1])*c(self.phi[-1])  )
399                                ))
401     if self.T_comm[-1] < 1.0:
            self.T_comm = self.T_comm[:-1]
403         self.T_comm.append(1.0)
405
        # we will need the derivatives of the comanded angles for the torque control laws.
407     self.phidot_comm = (self.phi_comm[-1] - self.phi_comm[-2])/self.h
409     self.thetadot_comm = (self.theta_comm[-1] - self.theta_comm[-2])/self.h
```

```
411
        # solve for torques based on theta_c, phi_c and T_c , also psi_des , and previous values of theta,
    phi, and psi
413

415     tao_phi_comm_temp = ( self.kpphi*(self.phi_comm[-1] - self.phi[-1]) + self.kdphi*(self.phidot_comm -
    self.phidot[-1]) )*self.Ixx

417     tao_theta_comm_temp = ( self.kptheta*(self.theta_comm[-1] - self.theta[-1]) + self.kdtheta*(self.
    thetadot_comm - self.thetadot[-1]) )*self.Iyy

419     tao_psi_comm_temp = ( self.kppsi*(self.psi_des - self.psi[-1]) + self.kdpsi*( self.psidot_des - self.
    psidot[-1] ) )*self.Izz

421     self.tao_phi_comm.append(tao_phi_comm_temp )
        self.tao_theta_comm.append(tao_theta_comm_temp )
423     self.tao_psi_comm.append(tao_psi_comm_temp )

425     #--------------------------------solve for motor speeds, eq 24

427     self.w1_arg.append( (self.T_comm[-1] / (4.0*self.k)) - ( self.tao_theta_comm[-1] / (2.0*self.k*self.L
    ) )  - ( self.tao_psi_comm[-1] / (4.0*self.b) ) )
        self.w2_arg.append( (self.T_comm[-1] / (4.0*self.k)) - ( self.tao_phi_comm[-1]   / (2.0*self.k*self.L
    ) )  + ( self.tao_psi_comm[-1] / (4.0*self.b) ) )
429     self.w3_arg.append( (self.T_comm[-1] / (4.0*self.k)) + ( self.tao_theta_comm[-1] / (2.0*self.k*self.L
    ) )  - ( self.tao_psi_comm[-1] / (4.0*self.b) ) )
        self.w4_arg.append( (self.T_comm[-1] / (4.0*self.k)) + ( self.tao_phi_comm[-1]   / (2.0*self.k*self.L
    ) )  + ( self.tao_psi_comm[-1] / (4.0*self.b) ) )
431

        self.w1.append( sqrt( self.w1_arg[-1] )  )
433     self.w2.append( sqrt( self.w2_arg[-1] )  )
        self.w3.append( sqrt( self.w3_arg[-1] )  )
435     self.w4.append( sqrt( self.w4_arg[-1] )  )

437     # IMPORTANT!!! THIS ENDS THE 'CONTROLLER BLOCK' IN A REAL IMPLEMENTATION, WE WOULD NOW TAKE
    MEASUREMENTS AND ESTIMATE THE STATE and then start over...

439 def system_model_block(self):

441     # BELOW ARE THE EQUATIONS THAT MODEL THE SYSTEM,
        # FOR THE PURPOSE OF SIMULATION, GIVEN THE MOTOR SPEEDS WE CAN CALCULATE THE STATES OF THE SYSTEM
443

        self.tao_qr_frame.append( array([
445                             self.L*self.k*( -self.w2[-1]**2 + self.w4[-1]**2 ) ,
                                self.L*self.k*( -self.w1[-1]**2 + self.w3[-1]**2 ) ,
447                             self.b* ( -self.w1[-1]**2 + self.w2[-1]**2 - self.w3[-1]**2 + self.w4[-1]**2
    )
                           ]) )
449

        self.tao_phi.append(self.tao_qr_frame[-1][0])
451     self.tao_theta.append(self.tao_qr_frame[-1][1])
        self.tao_psi.append(self.tao_qr_frame[-1][2])
453

        self.T.append(self.k*( self.w1[-1]**2 + self.w2[-1]**2 + self.w3[-1]**2 + self.w4[-1]**2 ) )
```

```
455
        # use the previous known angles and the known thrust to calculate the new resulting linear
    accelerations
457     # remember this would be measured ...
        # for the purpose of modeling the measurement error and testing a kalman filter, inject noise here...
459     # perhaps every 1000ms substitute an artificial gps measurement (and associated uncertianty) for the
    double integrated imu value

461     self.xddot.append(  (self.T[-1]/self.m)*( c(self.psi[-1])*s(self.theta[-1])*c(self.phi[-1])
                          + s(self.psi[-1])*s(self.phi[-1]) )
463                       - self.Ax * self.xdot[-1] / self.m  )

465     self.yddot.append(  (self.T[-1]/self.m)*( s(self.psi[-1])*s(self.theta[-1])*c(self.phi[-1])
                          - c(self.psi[-1])*s(self.phi[-1]) )
467                       - self.Ay * self.ydot[-1] / self.m  )

469     self.zddot.append(  self.g + (self.T[-1]/self.m)*( c(self.theta[-1])*c(self.phi[-1]) ) - self.Az *
    self.zdot[-1] / self.m  )

471     # calculate the new angular accelerations based on the known values
        self.etadot.append( array( [self.phidot[-1], self.thetadot[-1], self.psidot[-1] ] ) )
473
        self.etaddot.append( dot(inv( self.J() ), self.tao_qr_frame[-1]  -  dot(self.coriolis_matrix() , self
    .etadot[-1]) ) )
475
        # parse the etaddot vector of the new accelerations into the appropriate time series'
477     self.phiddot.append(self.etaddot[-1][0])

479     self.thetaddot.append(self.etaddot[-1][1])

481     self.psiddot.append(self.etaddot[-1][2])

483     #----------------------------- integrate new acceleration values to obtain velocity values

485     self.xdot.append(  self.xdot[-1] + self.xddot[-1] * self.h  )
        self.ydot.append(  self.ydot[-1] + self.yddot[-1] * self.h  )
487     self.zdot.append(  self.zdot[-1] + self.zddot[-1] * self.h  )

489     self.phidot.append(    self.phidot[-1]   + self.phiddot[-1] * self.h  )
        self.thetadot.append(  self.thetadot[-1] + self.thetaddot[-1] * self.h  )
491     self.psidot.append(    self.psidot[-1]   + self.psiddot[-1] * self.h  )

493     #----------------------------- integrate new velocity values to obtain position / angle values

495     self.x.append(  self.x[-1] + self.xdot[-1] * self.h  )
        self.y.append(  self.y[-1] + self.ydot[-1] * self.h  )
497     self.z.append(  self.z[-1] + self.zdot[-1] * self.h  )

499     self.phi.append(  self.phi[-1] + self.phidot[-1] * self.h  )
        self.theta.append(  self.theta[-1] + self.thetadot[-1] * self.h  )
501     self.psi.append( self.psi[-1] + self.psidot[-1] * self.h  )

503

505 ##########################################################################
```

```
507
    def plot_results(self,show_plot = True, save_plot = False, fig1_file_path = None,fig2_file_path = None):
509
        timeSeries = [self.h*i for i in range(len(self.x))]
511
        from mpl_toolkits.mplot3d import Axes3D
513     import matplotlib.pyplot as plt
        from pylab import title
515     import matplotlib.gridspec as gridspec


517
        fig0 = plt.figure()
519


521     ax = fig0.add_subplot(111, projection='3d')

523     ax.scatter(
                    self.x[0:len(self.x):5],
525                 self.y[0:len(self.y):5],
                    self.z[0:len(self.z):5])
527
        ax.set_xlabel('X (m)')
529     ax.set_ylabel('Y (m)')
        ax.set_zlabel('Z (m)')
531


533     fig1 = plt.figure()
        gs1 = gridspec.GridSpec(3, 2)
535
        #-------------------------------------------------------linear displacements
537     xx = fig1.add_subplot(gs1[0,0])
        plt.plot(timeSeries, self.x,'r',
539              timeSeries, self.y,'g',
                 timeSeries, self.z,'b')
541     title('x,y,z',fontsize=10)
        plt.xlabel('time (s)',fontsize=10)
543     plt.ylabel('dist. (m)',fontsize=10)

545     #-----------------------------------------------------------------angles
        thth = fig1.add_subplot(gs1[1,0])
547     plt.plot(timeSeries, self.phi,'r',
                 timeSeries, self.theta,'g',
549              timeSeries, self.psi,'b')
        title('Phi = roll, Theta = pitch, Psi = yaw',fontsize=10)
551     plt.xlabel('time (s)',fontsize=10)
        plt.ylabel('(rad)',fontsize=10)
553     #-------------------------------------------------------------motor speeds


555
        spd = fig1.add_subplot(gs1[2,0])
557     plt.plot([self.h*i for i in range(len(self.w1))], self.w1,'r',
                 [self.h*i for i in range(len(self.w2))], self.w2,'g',
559              [self.h*i for i in range(len(self.w3))], self.w3,'b',
                 [self.h*i for i in range(len(self.w4))], self.w4,'k')
```

```
561         title('motor speeds',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
563         plt.ylabel('(rad/sec)',fontsize=10)
            #------------------------------------------------------------------torque
565         spd = fig1.add_subplot(gs1[0,1])
            plt.plot([self.h*i for i in range(len(self.tao_phi))], self.tao_phi,'r',
567                  [self.h*i for i in range(len(self.tao_theta))], self.tao_theta,'g',
                     [self.h*i for i in range(len(self.tao_psi))], self.tao_psi,'b')
569         title('torques ',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
571         plt.ylabel('(Nm)',fontsize=10)
            #------------------------------------------------------------------thrust
573         spd = fig1.add_subplot(gs1[1,1])
            plt.plot([self.h*i for i in range(len(self.T))], self.T,'r',)
575         title('Total Thrust',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
577         plt.ylabel('(N)',fontsize=10)

579

            #------------------------------------------------------------------commanded total thrust
581         t_comm = fig1.add_subplot(gs1[2,1])
            plt.plot([self.h*i for i in range(len(self.T_comm))], self.T_comm,'r')
583         title('T_comm',fontsize=10)

585

587         '''
            #----------------------------------------------------------wind velocities
589         wind_plot = fig1.add_subplot( gs1[ 8:10 ,0:3 ] )

591         plt.plot([self.h*i for i in range(len(self.wind_x))], self.wind_x,'-r',
                     [self.h*i for i in range(len(self.wind_y))], self.wind_y,'-g',
593                  [self.h*i for i in range(len(self.wind_z))], self.wind_z,'-b'  )

595         title('wind velocities, rgb = xyz', fontsize=10)
            '''
597         fig1.tight_layout()

599         ###############################################

601

603         fig2 = plt.figure()
            gs2 = gridspec.GridSpec(4, 2)
605
            #------------------------------------------------------------------linear velocities
607         lin_vel = fig2.add_subplot(gs2[0,0])
            plt.plot(timeSeries, self.xdot,'r',
609                  timeSeries, self.ydot,'g',
                     timeSeries, self.zdot,'b')
611         title('xdot, ydot, self.zdot',fontsize=10)

613         #------------------------------------------------------------------linear accelerations
            lin_acc = fig2.add_subplot(gs2[1,0])
615         plt.plot(timeSeries, self.xddot,'r',
```

```
                timeSeries, self.yddot,'g',
                timeSeries, self.zddot,'b')
        title('xddot, yddot, self.zddot',fontsize=10)


        #-------------------------------------------------------------------angular velocities
        ang_vel = fig2.add_subplot(gs2[2,0])
        plt.plot(timeSeries, self.phidot,'r',
                timeSeries, self.thetadot,'g',
                timeSeries, self.psidot,'b')
        title('phidot, thetadot, self.psidot',fontsize=10)


        #-------------------------------------------------------------------commanded torques
        t_comm  = fig2.add_subplot(gs2[3,0])
        plt.plot([self.h*i for i in range(len(self.tao_phi_comm))], self.tao_phi_comm,'r',
                [self.h*i for i in range(len(self.tao_theta_comm))], self.tao_theta_comm,'g',
                [self.h*i for i in range(len(self.tao_psi_comm))], self.tao_psi_comm,'b',
                )
        title('tao_phi_comm,tao_theta_comm,tao_psi_comm',fontsize=10)


        #-------------------------------------------------------------------angular velocities
        ang_acc = fig2.add_subplot(gs2[0,1])
        plt.plot(timeSeries, self.phiddot,'r',
                timeSeries, self.thetaddot,'g',
                timeSeries, self.psiddot,'b')
        title('phiddot, thetaddot, self.psiddot',fontsize=10)


        #-------------------------------------------------------------------integral errors
        integral_errors = fig2.add_subplot(gs2[1,1])
        plt.plot(timeSeries, self.x_integral_error,'r',
                timeSeries, self.y_integral_error,'g',
                timeSeries, self.z_integral_error,'b')
        title('x_integral_error, y_integral_error, z_integral_error',fontsize=10)


        #-------------------------------------------------------------------w_args
        integral_errors = fig2.add_subplot(gs2[2,1])
        plt.plot([self.h*i for i in range(len(self.w1_arg))], self.w1_arg,'r',
                [self.h*i for i in range(len(self.w2_arg))], self.w2_arg,'g',
                [self.h*i for i in range(len(self.w3_arg))], self.w3_arg,'b',
                [self.h*i for i in range(len(self.w4_arg))], self.w4_arg,'k'
               )
        title('w1_arg, w2_arg, w3_arg, w4_arg ',fontsize=10)

        #-------------------------------------------------------------------commanded phi and theta
        integral_errors = fig2.add_subplot(gs2[3,1])
        plt.plot([self.h*i for i in range(len(self.theta_comm))], self.theta_comm,'r',
                [self.h*i for i in range(len(self.phi_comm))], self.phi_comm,'g'
               )
        title('theta_com ,phi_com  ',fontsize=10)
```

```
671
673         fig2.tight_layout()
675         if save_plot == True:
677             fig1.savefig(fig1_file_path)
                fig2.savefig(fig2_file_path)
679
681
            if show_plot == True:
683
                plt.show()
685
#-------------------------------------------------------------------------------
687
    def print_dump(self,n=5):
689
            print '\n\nself.xacc_comm[-n:] = ',around(self.xacc_comm[-n:], decimals=5)
691         print '\n\nself.yacc_comm[-n:] = ',around(self.yacc_comm[-n:], decimals=5)
            print '\n\nself.zacc_comm[-n:] = ',around(self.zacc_comm[-n:], decimals=5)
693
            print '\n\ntheta_com[-n:] = ',around(self.theta_comm[-n:], decimals=5)
695
            print '\n\nphi_com[-n:] = ',around(self.phi_comm[-n:], decimals=5)
697
            print '\n\nT_comm[-n:] = ',around(self.T_comm[-n:], decimals=5)
699
            print '\n\nself.tao_phi_comm = ',around(self.tao_phi_comm[-n:], decimals=5)
701         print '\n\nself.tao_theta_comm = ',around(self.tao_theta_comm[-n:], decimals=5)
            print '\n\nself.tao_psi_comm = ',around(self.tao_psi_comm[-n:], decimals=5)
703
            print '\n\nw1_arg[-n:] = ',around(self.w1_arg[-n:], decimals=0)
705         print '\n\nw2_arg[-n:] = ',around(self.w2_arg[-n:], decimals=0)
            print '\n\nw3_arg[-n:] = ',around(self.w3_arg[-n:], decimals=0)
707         print '\n\nw4_arg[-n:] = ',around(self.w4_arg[-n:], decimals=0)

709         print '\n\nw1[-n:] = ',around(self.w1[-n:] , decimals=1)
            print '\n\nw2[-n:] = ',around(self.w2[-n:], decimals=1)
711         print '\n\nw3[-n:] = ',around(self.w3[-n:] , decimals=1)
            print '\n\nw4[-n:] = ',around(self.w4[-n:], decimals=1)
713
            print '\n\nself.tao_qr_frame[-n:] = ',around(self.tao_qr_frame[-n:], decimals=5)
715
            print '\n\nself.T[-n:] = ',around(self.T[-n:], decimals=5)
717
            print '\n\nself.phi[-n:] = ',around(self.phi[-n:], decimals=5)
719         print '\n\nself.theta[-n:] = ',around(self.theta[-n:], decimals=5)
            print '\n\nself.psi[-n:] = ',around(self.psi[-n:], decimals=5)
721
            print '\n\nself.phidot[-n:] = ',around(self.phidot[-n:], decimals=5)
723         print '\n\nself.thetadot[-n:] = ',around(self.thetadot[-n:], decimals=5)
            print '\n\nself.psidot[-n:] = ',around(self.psidot[-n:], decimals=5)
725
```

```
        print '\n\nself.phiddot[-n:] = ',around(self.phiddot[-n:], decimals=5)
        print '\n\nself.thetaddot[-n:] = ',around(self.thetaddot[-n:], decimals=5)
        print '\n\nself.psiddot[-n:] = ',around(self.psiddot[-n:], decimals=5)

        print '\n\nself.x[-n:] = ',around(self.x[-n:], decimals=5)
        print '\n\nself.y[-n:] = ',around(self.y[-n:], decimals=5)
        print '\n\nself.z[-n:] = ',around(self.z[-n:], decimals=5)

        print '\n\nself.xdot[-n:] = ',around(self.xdot[-n:], decimals=5)
        print '\n\nself.ydot[-n:] = ',around(self.ydot[-n:], decimals=5)
        print '\n\nself.zdot[-n:] = ',around(self.zdot[-n:], decimals=5)

        print '\n\nself.xddot[-n:] = ',around(self.xddot[-n:], decimals=5)
        print '\n\nself.yddot[-n:] = ',around(self.yddot[-n:], decimals=5)
        print '\n\nself.zddot[-n:] = ',around(self.zddot[-n:], decimals=5)

        print '\n\nself.x_integral_error[-n:] = ',around(self.x_integral_error[-n:], decimals=5)
        print '\n\nself.y_integral_error[-n:] = ',around(self.y_integral_error[-n:], decimals=5)
        print '\n\nself.z_integral_error[-n:] = ',around(self.z_integral_error[-n:], decimals=5)

        print '\n\n'
#------------------------------------------------------------------------------

if __name__ == "__main__":

    a = agent(x_0 = 0,
              y_0 = 0,
              z_0 = 0,
              initial_setpoint_x = 1,
              initial_setpoint_y = 1,
              initial_setpoint_z = 1,
              agent_priority = 1)



    #the following gains worked well for a setpoint of (1,1,1)

    a.kpx = 40     # ----------------------PID proportional gain values
    a.kpy = 40
    a.kpz = 40

    a.kdx = 20         #----------------- -----PID derivative gain values
    a.kdy = 20
    a.kdz = 10

    a.kix = .2
    a.kiy = .2
    a.kiz = 40

    a.kpphi   = 4  # gains for the angular pid control laws
    a.kptheta = 4
    a.kppsi   = 4

    a.kdphi   = 10
    a.kdtheta = 10
```

```
781     a.kdpsi   = 5
783
785
787
    for i in range(a.max_iterations):
789
791         a.ending_iteration = i  # preemptively...
793         a.system_model_block()
795         a.control_block()
797         x_ave = sum(a.x[-100:])/100.0
            y_ave = sum(a.y[-100:])/100.0
799         z_ave = sum(a.z[-100:])/100.0
801         xerr = a.x_des - x_ave
            yerr = a.y_des - y_ave
803         zerr = a.z_des - z_ave
805
            #if i%50 == 0:
807         print 'x_ave = ',x_ave
            print 'y_ave = ',y_ave
809         print 'z_ave = ',z_ave
811         print 'i = ',i
            print 'xerr, yerr, zerr = ',xerr,',',yerr,',',zerr
813         print 'sqrt( xerr**2 + yerr**2 + zerr**2 ) = ',sqrt( xerr**2 + yerr**2 + zerr**2 )
            #a.print_dump(3)
815
817
819         # Stopping Criteria: if the agent is within a 5 cm error sphere for 200 time steps ( .2 sec )
821         if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) < 10**-2) and (i>50):
823             print 'set point reached!!'
825             print 'i = ', i
827             break
829         if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) > 200) and (i>50):
831             print 'you are lost!!'
833             print 'i = ', i
835             break
```

```
837         k_th_variable_list = [
                                  a.xacc_comm[-1],
839                               a.yacc_comm[-1],
                                  a.zacc_comm[-1],
841                               a.theta_comm[-1],
                                  a.phi_comm[-1],
843                               a.T_comm[-1],
                                  a.tao_phi_comm[-1],
845                               a.tao_theta_comm[-1],
                                  a.tao_psi_comm[-1],
847                               a.w1_arg[-1],
                                  a.w2_arg[-1],
849                               a.w3_arg[-1],
                                  a.w4_arg[-1],
851                               a.w1[-1],
                                  a.w2[-1],
853                               a.w3[-1],
                                  a.w4[-1],
855                               a.tao_qr_frame[-1][0],
                                  a.tao_qr_frame[-1][1],
857                               a.tao_qr_frame[-1][2],
                                  a.T[-1],
859                               a.phi[-1],
                                  a.theta[-1],
861                               a.psi[-1],
                                  a.phidot[-1],
863                               a.thetadot[-1],
                                  a.psidot[-1],
865                               a.phiddot[-1],
                                  a.thetaddot[-1],
867                               a.psiddot[-1],
                                  a.x[-1],
869                               a.y[-1],
                                  a.z[-1],
871                               a.xdot[-1],
                                  a.ydot[-1],
873                               a.zdot[-1],
                                  a.xddot[-1],
875                               a.yddot[-1],
                                  a.zddot[-1],
877                               a.x_integral_error[-1],
                                  a.y_integral_error[-1],
879                               a.z_integral_error[-1],
                                  ]
881
        for k in k_th_variable_list:
883
            if math.isnan(k):
885
                a.print_dump(1)
887
                break
889
```

```
891         if a.phi[-1] > 5: break
            if a.theta[-1] > 5: break
893         if a.psi[-1] > 5: break

895         if math.isnan(xerr):

897             break

899     print '##############################################\n\n'

901     a.print_dump(10)

903     fig1_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig1_agent_module.png'
        fig2_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig2_agent_module.png'
905
        a.plot_results()#False, True, fig1_file_path, fig2_file_path)
```

/home/ek/Dropbox/THESIS/python_scripts/agent_module.py

Appendix B

waypointNavigation.py

breakatwhitespace

```
from agent_module import *

def go(agent):

    for i in range(agent.max_iterations):

        a.system_model_block()

        a.control_block()

        retval = stopping_criteria(agent)

        if (retval == 0) or (retval == 1):

            print 'i = ', i

            break

#-------------------------------------------------------------------------------

def stopping_criteria(agent):

    x_ave = sum(agent.x[-100:])/100.0
    y_ave = sum(agent.y[-100:])/100.0
    z_ave = sum(agent.z[-100:])/100.0

    xerr = agent.x_des - x_ave
    yerr = agent.y_des - y_ave
    zerr = agent.z_des - z_ave

    #if i%50 == 0:
```

```
        #print 'x_ave = ',x_ave
        #print 'y_ave = ',y_ave
        #print 'z_ave = ',z_ave

    print 'xerr, yerr, zerr = ',xerr,',',yerr,',',zerr
    print 'sqrt( xerr**2 + yerr**2 + zerr**2 ) = ',sqrt( xerr**2 + yerr**2 + zerr**2 )

    if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) < 10**-2) and (len(agent.x) >50):

        print 'set point reached!!'

        #print 'i = ', i

        return 1

    if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) > 200) and (i>50):

        print 'you are lost!!'


        return 0

    k_th_variable_list = [
                            a.xacc_comm[-1],a.yacc_comm[-1],a.zacc_comm[-1],
                            a.theta_comm[-1],a.phi_comm[-1],a.T_comm[-1],
                            a.tao_phi_comm[-1],a.tao_theta_comm[-1],a.tao_psi_comm[-1],
                            a.w1_arg[-1],a.w2_arg[-1],a.w3_arg[-1],a.w4_arg[-1],
                            a.w1[-1],a.w2[-1],a.w3[-1],a.w4[-1],
                            a.tao_qr_frame[-1][0],a.tao_qr_frame[-1][1],a.tao_qr_frame[-1][2],
                            a.T[-1],
                            a.phi[-1],a.theta[-1],a.psi[-1],
                            a.phidot[-1],a.thetadot[-1],a.psidot[-1],
                            a.phiddot[-1],a.thetaddot[-1],a.psiddot[-1],
                            a.x[-1],a.y[-1],a.z[-1],
                            a.xdot[-1],a.ydot[-1],a.zdot[-1],
                            a.xddot[-1],a.yddot[-1],a.zddot[-1],
                            a.x_integral_error[-1],a.y_integral_error[-1],a.z_integral_error[-1],
                            ]

    for k in k_th_variable_list:

        if math.isnan(k):

            a.print_dump(1)

            return 0


    if a.phi[-1] > 5: return 0

    if a.theta[-1] > 5: return 0

    if a.psi[-1] > 5: return 0

    if math.isnan(xerr): return 0
```

```
88
##############################################################################
90
if __name__ == '__main__':
92
    a = agent(x_0 = 0,
94              y_0 = 0,
                z_0 = 0,
96              initial_setpoint_x = 1,
                initial_setpoint_y = 1,
98              initial_setpoint_z = 1,
                agent_priority = 1)
100
    #the following gains worked well for a setpoint of (1,1,1)
102
    a.kpx = 15     # ----------------------PID proportional gain values
104 a.kpy = 15
    a.kpz = 50
106
    a.kdx = 10         #----------------- -----PID derivative gain values
108 a.kdy = 10
    a.kdz = 50
110
    a.kix = 0.8
112 a.kiy = 0.8
    a.kiz = 15
114
    a.kpphi   = 4  # gains for the angular pid control laws
116 a.kptheta = 4
    a.kppsi   = 4
118
    a.kdphi   = 6
120 a.kdtheta = 6
    a.kdpsi   = 6
122 '''
    u'a0.ending_iteration': 257,                          the  optimal run
124 u'a0.kdx': 10,
    u'a0.kdy': 10,
126 u'a0.kdz': 50,
    u'a0.kix': 0.8,
128 u'a0.kiy': 0.8,
    u'a0.kiz': 20,
130 u'a0.kpx': 15,
    u'a0.kpy': 15,
132 u'a0.kpz': 40,
    u'ith_runtime': 11.414505958557129,
134 u'return_val2': 1,
    u'setpoint': [1, 1, 2],
136 u'total_thrust': 4969.888344602483,
    u'x_crossings': 3,
138 u'x_over_shoot': 0.024969492375947366,
    u'y_crossings': 1,
140 u'y_over_shoot': 0.01858534082026475,
    u'z_crossings': 1,
142 u'z_over_shoot': 0.09928387955818296}
```

```
144
146
    '''
148
    a.max_iterations = 1000
150
    position_setpoint_list =  [[0,0,1],[1,1,2]]  #[[1,1,1],[5,5,5],[20,20,20],[100,100,100]]
     #[[1,1,1],[5,1,1],[5,5,1],[5,5,5],[1,5,5],[1,1,5],[1,1,1]] #
152
    for ss in range(len(position_setpoint_list)):
154
        a.x_des = position_setpoint_list[ss][0]
156     a.y_des = position_setpoint_list[ss][1]
        a.z_des = position_setpoint_list[ss][2]
158
        go(a)
160
162 print '################################################\n\n'
164 a.print_dump(10)
166 fig1_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig1_agent_module.png'
    fig2_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig2_agent_module.png'
168
    a.plot_results()
```

/home/ek/Dropbox/THESIS/python_scripts/waypoint_navigation.py

Appendix C

bruteForceFunctions.py

breakatwhitespace

```
1
from agent_module import *
3
from numpy import mean
5
import json
7 #------------------------------------------------------------------------------
#------------------------------------------------------------------------------
9
def run(agent,plots = False):
11
    for i in range(agent.max_iterations):
13
        agent.ending_iteration = i
15
        agent.system_model_block()
17
        agent.control_block()
19

21      x_ave = sum(agent.x[-100:])/100.0
        y_ave = sum(agent.y[-100:])/100.0
23      z_ave = sum(agent.z[-100:])/100.0

25      xerr = agent.x_des - x_ave
        yerr = agent.y_des - y_ave
27      zerr = agent.z_des - z_ave

29      # Stopping Criteria: if the agent is within a n cm error sphere for 200 time steps ( .2 sec )

31      if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) <10**-2) and (i>50):
```

```
33              print 'i = ', i

35              print 'set point reached'

37              return 1

39          if ( abs(zerr) > 200) and (i>50):

41              print 'i = ', i

43              print 'you are lost'

45              return 'err'

47          k_th_variable_list = [  agent.xacc_comm[-1],agent.yacc_comm[-1],agent.zacc_comm[-1],
                                    agent.theta_comm[-1],agent.phi_comm[-1],agent.T_comm[-1],
49                                  agent.tao_phi_comm[-1],agent.tao_theta_comm[-1],agent.tao_psi_comm[-1],
                                    agent.w1_arg[-1],agent.w2_arg[-1],agent.w3_arg[-1],agent.w4_arg[-1],
51                                  agent.w1[-1],agent.w2[-1],agent.w3[-1],agent.w4[-1],
                                    agent.tao_qr_frame[-1][0],agent.tao_qr_frame[-1][1],agent.tao_qr_frame
    [-1][2],
53                                  agent.T[-1],
                                    agent.phi[-1],agent.theta[-1],agent.psi[-1],
55                                  agent.phidot[-1],agent.thetadot[-1],agent.psidot[-1],
                                    agent.phiddot[-1],agent.thetaddot[-1],agent.psiddot[-1],
57                                  agent.x[-1],agent.y[-1],agent.z[-1],
                                    agent.xdot[-1],agent.ydot[-1],agent.zdot[-1],
59                                  agent.xddot[-1],agent.yddot[-1],agent.zddot[-1],
                                    agent.x_integral_error[-1],agent.y_integral_error[-1],agent.z_integral_error
    [-1],
61                                  ]

63          for k in k_th_variable_list:

65              if math.isnan(k):

67                  agent.print_dump(1)

69                  return 'err'

71              if agent.phi[-1] > 5: break
                if agent.theta[-1] > 5: break
73              if agent.psi[-1] > 5: break

75              if math.isnan(xerr):
                    print 'math.isnan(xerr) = True'
77
                    return 'err'
79
#-------------------------------------------------------------------------
81  #-------------------------------------------------------------------------

83  def take_off():

85      agent0 = agent(x_0 = 0,
```

```
            y_0 = 0,
            z_0 = 0,
            initial_setpoint_x = 0,
            initial_setpoint_y = 0,
            initial_setpoint_z = 1,
            agent_priority = 1)

    agent0.max_iterations = 800

    #the following gains worked well for a setpoint of (1,1,1)

    agent0.kpx = 40     # ----------------------PID proportional gain values
    agent0.kpy = 40
    agent0.kpz = 40

    agent0.kdx = 25         #----------------- -----PID derivative gain values
    agent0.kdy = 25
    agent0.kdz = 40

    agent0.kix = .2
    agent0.kiy = .2
    agent0.kiz = 40

    run(agent0)

    return agent0   # return the agent instance hovering at (0,0,1)

#-------------------------------------------------------------------------------
#-------------------------------------------------------------------------------
def test_gain_vector(a0, set_point, gain_dictionary):

    a0.x_des = set_point[0]
    a0.y_des = set_point[1]
    a0.z_des = set_point[2]

    a0.max_iterations = 1000

    a0.kpx = gain_dictionary['kpxy']
    a0.kix = gain_dictionary['kixy']
    a0.kdx = gain_dictionary['kdxy']

    a0.kpy = gain_dictionary['kpxy']
    a0.kiy = gain_dictionary['kixy']
    a0.kdy = gain_dictionary['kdxy']

    a0.kpz = gain_dictionary['kpz']
    a0.kiz = gain_dictionary['kiz']
    a0.kdz = gain_dictionary['kdz']

    return_val2 = run(a0)
    '''
    #-----------------------------------------------------
    variable_dictionary = {
                'a0.xacc_comm' : a0.xacc_comm,'a0.yacc_comm' : a0.yacc_comm,'a0.zacc_comm' : a0.zacc_comm,
                'a0.theta_comm' : a0.theta_comm,'a0.phi_comm' : a0.phi_comm,'a0.T_comm' : a0.T_comm,
```

```
141             'a0.tao_phi_comm' : a0.tao_phi_comm,'a0.tao_theta_comm' : a0.tao_theta_comm,'a0.tao_psi_comm'
    : a0.tao_psi_comm,
                'a0.w1_arg' : a0.w1_arg,'a0.w2_arg' : a0.w2_arg,'a0.w3_arg' : a0.w3_arg,'a0.w4_arg' : a0.
    w4_arg,
143             'a0.w1' : a0.w1,'a0.w2' : a0.w2,'a0.w3' : a0.w3,'a0.w4' : a0.w4,
                'a0.tao_qr_frame[0]' : a0.tao_qr_frame[0].tolist(),'a0.tao_qr_frame[1]' : a0.tao_qr_frame[1].
    tolist(),'a0.tao_qr_frame[2]' : a0.tao_qr_frame[2].tolist(),
145             'a0.T' : a0.T,
                'a0.phi' : a0.phi,'a0.theta' : a0.theta,'a0.psi' : a0.psi,
147             'a0.phidot' : a0.phidot,'a0.thetadot' : a0.thetadot,'a0.psidot' : a0.psidot,
                'a0.phiddot' : a0.phiddot,'a0.thetaddot' : a0.thetaddot,'a0.psiddot' : a0.psiddot,
149             'a0.x' : a0.x,'a0.y' : a0.y,'a0.z' : a0.z,
                'a0.xdot' : a0.xdot,'a0.ydot' : a0.ydot,'a0.zdot' : a0.zdot,
151             'a0.xddot' : a0.xddot,'a0.yddot' : a0.yddot,'a0.zddot' : a0.zddot,
                'a0.x_integral_error' : a0.x_integral_error,
153             'a0.y_integral_error' : a0.y_integral_error,
                'a0.z_integral_error' : a0.z_integral_error,
155             }
    #-----------------------------------------------------
157 '''
    if return_val2 != 1:
159


161     test_run_dictionary = {'setpoint':set_point,
                           'a0.kpx' : a0.kpx,
163                        'a0.kix' : a0.kix,
                           'a0.kdx' : a0.kdx,
165                        'a0.kpy' : a0.kpy,
                           'a0.kiy' : a0.kiy,
167                        'a0.kdy' : a0.kdy,
                           'a0.kpz' : a0.kpz,
169                        'a0.kiz' : a0.kiz,
                           'a0.kdz' : a0.kdz,
171                        'return_val2' : return_val2,
                           'a0.ending_iteration' : a0.ending_iteration
173                        }#'variable_dictionary':variable_dictionary
                           #}
175
        return test_run_dictionary
177


179
    elif return_val2 ==1:
181


183     #need to calculate the number of times the state crosses the setpoint value:

185     x_crossings = 0
        y_crossings = 0
187     z_crossings = 0

189     for i in range(len(a0.x)-1):

191         if sign( a0.x[i] - a0.x_des ) != sign( a0.x[i+1] - a0.x_des ) :
```

```
                x_crossings += 1


            if sign( a0.y[i] - a0.y_des ) != sign( a0.y[i+1] - a0.y_des ) :

                y_crossings += 1


            if sign( a0.z[i] - a0.z_des ) != sign( a0.z[i+1] - a0.z_des ) :

                z_crossings += 1




        #-----------------------------------------------------


        if (max(a0.x) - a0.x_des) > 0: x_over_shoot = max(a0.x) - a0.x_des

        if (max(a0.y) - a0.y_des) > 0: y_over_shoot = max(a0.y) - a0.y_des

        if (max(a0.z) - a0.z_des) > 0: z_over_shoot = max(a0.z) - a0.z_des


       #-----------------------------------------------------



        test_run_dictionary = {'setpoint':set_point,
                               'a0.kpx' : a0.kpx,
                               'a0.kix' : a0.kix,
                               'a0.kdx' : a0.kdx,
                               'a0.kpy' : a0.kpy,
                               'a0.kiy' : a0.kiy,
                               'a0.kdy' : a0.kdy,
                               'a0.kpz' : a0.kpz,
                               'a0.kiz' : a0.kiz,
                               'a0.kdz' : a0.kdz,
                               'return_val2' : return_val2,
                               'a0.ending_iteration' : a0.ending_iteration,
                               'total_thrust' : sum(a0.T),
                               'x_over_shoot':x_over_shoot,
                               'y_over_shoot':y_over_shoot,
                               'z_over_shoot':z_over_shoot,
                               'x_crossings':x_crossings,
                               'y_crossings':y_crossings,
                               'z_crossings':z_crossings
                               }

        return test_run_dictionary

#-------------------------------------------------------------------------
'''
{   u'a0.ending_iteration': 266,
```

```
    u'a0.kdx': 5,
    u'a0.kdy': 5,
    u'a0.kdz': 20,
    u'a0.kix': 0.8,
    u'a0.kiy': 0.8,
    u'a0.kiz': 15,
    u'a0.kpx': 5,
    u'a0.kpy': 5,
    u'a0.kpz': 30,
    u'ith_runtime': 7.14291787147522,
    u'return_val2': 1,
    u'setpoint': [1, 1, 2],
    u'total_thrust': 4973.812742102159,
    u'x_crossings': 1,
    u'x_over_shoot': 0.06537601013649552,
    u'y_crossings': 1,
    u'y_over_shoot': 0.0706587304875288,
    u'z_crossings': 1,
    u'z_over_shoot': 0.03570385076740079}

'''
#------------------------------------------------------------------------------

if __name__ == '__main__':

    gain_dictionary = {
                    'kpxy' : 5,
                    'kpz'  : 30,
                    'kdxy' : 5,
                    'kdz'  : 20,
                    'kixy' : 0.8,
                    'kiz'  : 15}

    agent = take_off() # ----> returns the agent instance hovering at (0,0,1)

    set_point = [1,1,2]

    test_run_dictionary = test_gain_vector(agent, set_point, gain_dictionary)

    print 'test_run_dictionary = ',test_run_dictionary

    agent.plot_results()
```

/home/ek/Dropbox/THESIS/python_scripts/brute_force_functions.py

Appendix D

runSimsBruteForce.py

breakatwhitespace

```
'''
THis is a last resort , brute force approch to finding the gain vector that
produces the lowest objective function value for a set point of (1,1,2)

each run will start with the state variable and input lists produced by the take_off
function . for speed this data will be read from a json file which is produced beforehand

for each run the ku gain variable will be incremented by 5 and the objective function measured
'''
import sys
from numpy import arange
from brute_force_functions import *
from datetime import datetime
import json
import time
'''
gain_dictionary = {
                    'kpxy' : 10,
                    'kpz'  : 40,
                    'kdxy' : 10,
                    'kdz'  : 40,
                    'kixy' : 0.5,
                    'kiz'  : 25}
'''

global_start_time = time.time()


kpxy_range = arange(5,30,5)

kpz_range = arange(20,70,10)

```

```
kdxy_range = arange(5,30,5)

kdz_range = arange(20,70,10)

kixy_range = arange(0.2,1.0,0.2)

kiz_range = arange(15,45,5)

print 'kpxy_range = ',kpxy_range

print 'kpz_range = ',kpz_range

print 'kdxy_range = ',kdxy_range

print 'kdz_range = ',kdz_range

print 'kixy_range = ',kixy_range

print 'kiz_range = ',kiz_range

number_of_sims = len(kpxy_range)*len(kpz_range)*len(kdxy_range)*len(kdz_range)*len(kixy_range)*len(kiz_range)

print 'number_of_sims = ',number_of_sims


index = int(sys.argv[1])

runtimes = []
run_dictionaries = []

for kpxy in [kpxy_range[index]]:
    for kpz in kpz_range:
        for kdxy in kdxy_range:
            for kdz in kdz_range:
                for kixy in kixy_range:

                    date_and_time = datetime.now().strftime('%Y-%m-%d__%H.%M.%S')

                    filepath = '/home/ek/Dropbox/THESIS/python_scripts/brute_force_output_data/
     bruteforce_output_index'+str(index)+'_' + date_and_time+ '.json'

                    with open(filepath, 'wb') as fp:
                        json.dump(run_dictionaries, fp)
                        fp.close()


                    run_dictionaries = []

                    for kiz in kiz_range:

                        gain_dictionary = {
                                        'kpxy' : kpxy,
                                        'kpz'  : kpz,
                                        'kdxy' : kdxy,
                                        'kdz'  : kdz,
```

```
                                        'kixy' : kixy,
                                        'kiz'  : kiz}

                        print '\ngain_dictionary = ',gain_dictionary

                        ith_starttime = time.time()

                        agent = take_off() # ----> returns the agent instance hovering at (0,0,1)

                        set_point = [1,1,2]

                        test_run_dictionary = test_gain_vector(agent, set_point, gain_dictionary)

                        test_run_dictionary['ith_runtime'] = time.time() - ith_starttime

                        print 'test_run_dictionary = ',test_run_dictionary

                        run_dictionaries.append( test_run_dictionary )

                        #-------------------------------------------------------


total_run_time = time.time() - global_start_time



date_and_time = datetime.now().strftime('%Y-%m-%d__%H.%M.%S')

filepath = '/home/ek/Dropbox/THESIS/python_scripts/brute_force_output_data/bruteforce_output_index'+str(index
    )+'_' + date_and_time+ '.json'

with open(filepath, 'wb') as fp:
    json.dump(run_dictionaries, fp)
    fp.close()


'''
for r in run_dictionaries:

    for kee in r.keys():

        if kee != 'variable_dictionary':

            print kee,r[kee]
'''
```

/home/ek/Dropbox/THESIS/python_scripts/run_sims_brute_force.py

Appendix E

parseResults.py

breakatwhitespace

```
import os
import json
import itertools
from operator import itemgetter
import pprint
pp = pprint.PrettyPrinter(indent=4)

'''
def obj_fun(d):

    of = d['total_thrust']

    return of
'''



# need to go through all the output files and make a list of all the sims that still need to be run:

output_dir = '/home/ek/Dropbox/THESIS/python_scripts/brute_force_output_data/'

output_file_names = [fn for fn in os.listdir(output_dir)]

output_file_paths = [output_dir + ofn for ofn in output_file_names]


data = []

for ofp in output_file_paths:
```

```
34      with open(ofp, 'rb') as fp:
            output_data = json.load(fp)
36
            data = data + output_data
38


40  good_runs = []

42  for d in data:

44      if d['return_val2'] == 1:

46          good_runs.append(d)

48
    min_overshoot_runs = []
50
    for g in good_runs:
52
        if ( g['x_over_shoot'] < 0.1 ) and ( g['y_over_shoot'] < 0.1 ) and ( g['z_over_shoot'] < 0.1 ):
54
            min_overshoot_runs.append(g)
56


58  min_oscillation_runs = []

60  for r in min_overshoot_runs:

62      if (r['x_crossings'] < 4) and (r['y_crossings'] < 4) and (r['z_crossings'] < 4) :

64          min_oscillation_runs.append(r)

66



68  thrust_sorted_good_runs = sorted(min_oscillation_runs, key=itemgetter('total_thrust'))

70  for t in thrust_sorted_good_runs[:20]:
        print '\n'
72      pp.pprint(t)

74



76

    # according to the available data, here is the best run...
78  '''
    {   u'a0.ending_iteration': 266,
80      u'a0.kdx': 5,
        u'a0.kdy': 5,
82      u'a0.kdz': 20,
        u'a0.kix': 0.8,
84      u'a0.kiy': 0.8,
        u'a0.kiz': 15,
86      u'a0.kpx': 5,
        u'a0.kpy': 5,
```

```
88      u'a0.kpz': 30,
        u'ith_runtime': 7.14291787147522,
90      u'return_val2': 1,
        u'setpoint': [1, 1, 2],
92      u'total_thrust': 4973.812742102159,
        u'x_crossings': 1,
94      u'x_over_shoot': 0.06537601013649552,
        u'y_crossings': 1,
96      u'y_over_shoot': 0.0706587304875288,
        u'z_crossings': 1,
98      u'z_over_shoot': 0.03570385076740079}


100


102
'''
```

/home/ek/Dropbox/THESIS/python_scripts/parse_results.py

Appendix F

finiteDiffSolution.py

breakatwhitespace

```
from os import system

from numpy import cos as c , sin as s , array as a , concatenate , arange , sqrt, reshape, log

from numpy import dot
from numpy.linalg import inv
from numpy.linalg import norm
from numpy import transpose
global ixx
global iyy
global izz

ixx = 5.0*10**-3
iyy = 5.0*10**-3
izz = 10.0*10**-3

global g
global s
global l
global b
global m
global h
global d

g = -9.8
alpha = 0.001
l = 0.25   # m
b = 0.001
m = 1.

h = 0.1
```

```
d = 0.0001 # the value for adding to the input variables of f to express the finite differences

#-----------------------------------------------------------the jacobian for transforming from body frame to inertial frame

def J(ph,th):

    jac = a([
    [ixx        , 0                              , -ixx * s(th)                                              ],
    [0          , iyy*(c(ph)**2) + izz * s(ph)**2  , (iyy-izz)*c(ph)*s(ph)*c(th)                             ],
    [-ixx*s(th) , (iyy-izz)*c(ph)*s(ph)*c(th)      , ixx*(s(th)**2) + iyy*(s(th)**2)*(c(th)**2) + izz*(c(ph)**2)*(c(th)**2)]
    ])

    #print '\n\njac = \n',jac


    return jac








# -----------------------------------------------------------------------------------------------------------------------


def coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1 , partial_with_respect_to ):

    # the argument 'partial_with_respect_to' specifies the angular quantity for which the derivative is bein computed

    # note that   'partial_with_respect_to'  MUST be a string

    # if the standard coriolis matrix is needed, the argument: 'partial_with_respect_to' should be set to None

    if partial_with_respect_to == 'phd':    phd =  ( ( ph_k - ph_k_minus_1 ) / h ) + d

    else: phd = ( ph_k - ph_k_minus_1 ) / h



    if partial_with_respect_to == 'thd':   thd =  ( ( th_k - th_k_minus_1 ) / h ) + d

    else: thd =  ( th_k - th_k_minus_1 ) / h

```

```
79
    if partial_with_respect_to == 'psd':    psd = ( ( ps_k - ps_k_minus_1 ) / h  ) + d
81
    else: psd =  ( ps_k - ps_k_minus_1 ) / h
83


85
    # here are the elements in the matrix
87
    c11 = 0
89
    c12 = (iyy-izz) * ( thd*c(ph_k)*s(ph_k) + psd*c(th_k)*s(ph_k)**2 )  + (izz-iyy)*psd*(c(ph_k)**2)*c(th_k)
     - ixx*psd*c(th_k)
91
    c13 = (izz-iyy) * psd * c(ph_k) * s(ph_k) * c(th_k)**2
93
    c21 = (izz-iyy) * ( thd*c(ph_k)*s(ph_k) + psd*s(ph_k)*c(th_k) ) + (iyy-izz) * psd * (c(ph_k)**2) * c(th_k
     ) + ixx * psd * c(th_k)
95
    c22 = (izz-iyy)*phd*c(ph_k)*s(ph_k)
97
    c23 = -ixx*psd*s(th_k)*c(th_k) + iyy*psd*(s(ph_k)**2)*s(th_k)*c(th_k)
99
    c31 = (iyy-izz)*phd*(c(th_k)**2)*s(ph_k)*c(ph_k) - ixx*thd*c(th_k)
101
    c32 = (izz-iyy)*( thd*c(ph_k)*s(ph_k)*s(th_k) + phd*(s(ph_k)**2)*c(th_k) ) + (iyy-izz)*phd*(c(ph_k)**2)*c
     (th_k) + ixx*psd*s(th_k)*c(th_k) - iyy*psd*(s(ph_k)**2)*s(th_k)*c(th_k) - izz*psd*(c(ph_k)**2)*s(th_k)*
     c(th_k)
103
    c33 = (iyy-izz) * phd *c(ph_k)*s(ph_k)*(c(th_k)**2) - iyy * thd*(s(ph_k)**2) * c(th_k)*s(th_k) - izz*thd
     *(c(ph_k)**2)*c(th_k)*s(th_k) + ixx*thd*c(th_k)*s(th_k)
105


107
    cm = a([[c11,c12,c13],
              [c21,c22,c23],
109           [c31,c32,c33]])


111


113
    #print '\n\ncm = \n',cm
115


117
    return cm
119


121


123


125


#
     ------------------------------------------------------------------------------------------------------------
```

```
127
# the function f will be used as the state equations as well as for the many partial derivatives
129
def f(x , x_k_minus_1 , x_k_minus_2 ,
131       y , y_k_minus_1 , y_k_minus_2 ,
          z , z_k_minus_1 , z_k_minus_2 ,
133       ph_k , ph_k_minus_1 , ph_k_minus_2,
          th_k , th_k_minus_1 , th_k_minus_2,
135       ps_k , ps_k_minus_1 , ps_k_minus_2,
          u1_k , u2_k , u3_k , u4_k ):
137
    T = alpha * (u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2)
139     #print '\nT = ',T

141
    xdd = (1/h**2) * ( x - 2*x_k_minus_1 - x_k_minus_2 )
143
    x_residual = T/m * ( c(ps_k) * s(th_k) * c(ph_k) + s(ps_k) * s(ph_k) )  #  F1
145

147     ydd =  (1/h**2) * ( x - 2*y_k_minus_1 - y_k_minus_2 )

149     y_residual = T/m * ( s(ps_k) * s(th_k) * c(ph_k) + c(ps_k) * s(ph_k) )  #  F2

151
    zdd =  (1/h**2) * ( x - 2*z_k_minus_1 - z_k_minus_2 )
153
    z_residual = T/m * c(th_k) * c(ph_k) + g  #  F3
155

157     # the angular equations are better kept as vectors and matrices

159
    input_func_vector = a([
161                           l * alpha * ( -u2_k**2 + u4_k**2 ) ,
                              l * alpha * ( -u1_k**2 + u3_k**2 ) ,
163                           b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
                          ])
165     #print '\ninput_func_vector = ',input_func_vector

167     coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, None )
    #print '\ncoriolis_k = ',coriolis_k
169

171     ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h , (th_k - th_k_minus_1)/h , ( ps_k - ps_k_minus_1)/h ] )
    #print '\nang_vel_vector = ',ang_vel_vector
173

175
    # this is the large bracketed factor which is multiplied into the inverse of the jacobian
177
    temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )
179     #print '\ntemp_factor = ',temp_factor

181
```

```
183     etadd = ( 1/h**2 ) * a([
                               ph_k - 2* ph_k_minus_1 - ph_k_minus_2,
185                            th_k - 2* th_k_minus_1 - th_k_minus_2,
                               ps_k - 2* ps_k_minus_1 - ps_k_minus_2,
187                           ])

189     angular_residual = dot( inv( J(ph_k,th_k) ) , temp_factor ) - etadd
        #print '\netadd = ',etadd
191

193     state_equations_residual = a( [ x_residual , y_residual , z_residual ,angular_residual[0] ,
         angular_residual[1] , angular_residual[2] ] )

195     #print '\n\nstate_equations_residual = \n',state_equations_residual

197


199     return state_equations_residual

201



203
#
      ------------------------------------------------------------------------------------------------------------------------


205
# The costate
207

def costate(x_k , x_k_minus_1 , x_k_minus_2 ,
209             y_k , y_k_minus_1 , y_k_minus_2 ,
                z_k , z_k_minus_1 , z_k_minus_2 ,
211             ph_k , ph_k_minus_1 , ph_k_minus_2,
                th_k , th_k_minus_1 , th_k_minus_2,
213             ps_k , ps_k_minus_1 , ps_k_minus_2,
                u1_k , u2_k , u3_k , u4_k,
215             la1_k , la1_k_minus_1 , la1_k_minus_2,
                la2_k , la2_k_minus_1 , la2_k_minus_2,
217             la3_k , la3_k_minus_1 , la3_k_minus_2,
                la4_k , la4_k_minus_1 , la4_k_minus_2,
219             la5_k , la5_k_minus_1 , la5_k_minus_2,
                la6_k , la6_k_minus_1 , la6_k_minus_2
221             ):

223     # this is the list of state equations differenciated with respect to phi:

225     ff =  f(x , x_k_minus_1 , x_k_minus_2 ,
          y , y_k_minus_1 , y_k_minus_2 ,
227       z , z_k_minus_1 , z_k_minus_2 ,
          ph_k , ph_k_minus_1 , ph_k_minus_2,
229       th_k , th_k_minus_1 , th_k_minus_2,
          ps_k , ps_k_minus_1 , ps_k_minus_2,
231       u1_k , u2_k , u3_k , u4_k )

233
```

```
    f_at_phi_plus_d =  f(x , x_k_minus_1 , x_k_minus_2 ,
235   y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
237   ph_k + d, ph_k_minus_1 , ph_k_minus_2,
      th_k    , th_k_minus_1 , th_k_minus_2,
239   ps_k    , ps_k_minus_1 , ps_k_minus_2,
      u1_k , u2_k , u3_k , u4_k )
241
    del_f_d_phi = ( f_at_phi_plus_d - ff )/d
243



245

    f_at_theta_plus_d =  f(x , x_k_minus_1 , x_k_minus_2 ,
247   y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
249   ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k + d, th_k_minus_1 , th_k_minus_2,
251   ps_k    , ps_k_minus_1 , ps_k_minus_2,
      u1_k    , u2_k , u3_k , u4_k )
253
    del_f_d_theta = ( f_at_theta_plus_d - ff )/d
255



257

    f_at_psi_plus_d =  f(x , x_k_minus_1 , x_k_minus_2 ,
259   y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
261   ph_k    , ph_k_minus_1 , ph_k_minus_2,
      th_k    , th_k_minus_1 , th_k_minus_2,
263   ps_k + d, ps_k_minus_1 , ps_k_minus_2,
      u1_k , u2_k , u3_k , u4_k )
265
    del_f_d_psi = ( f_at_psi_plus_d - ff )/d
267


269
    state_transition_matrix = a( [  del_f_d_phi ,
271                                 del_f_d_theta,
                                    del_f_d_psi     ] )
273
    #print '\n\nstate_transition_matrix = ',state_transition_matrix
275


277 lam = a( [ la1_k , la2_k , la3_k , la4_k , la5_k , la6_k ] )

279 la_k_double_dot = (1/h)*a([
                              la1_k - 2* la1_k_minus_1 - la1_k_minus_2  ,
281                           la2_k - 2* la2_k_minus_1 - la2_k_minus_2  ,
                              la3_k - 2* la3_k_minus_1 - la3_k_minus_2  ,
283                           la4_k - 2* la4_k_minus_1 - la4_k_minus_2  ,
                              la5_k - 2* la5_k_minus_1 - la5_k_minus_2  ,
285                           la6_k - 2* la6_k_minus_1 - la6_k_minus_2
                             ])
287
```

```
289     costate_residual_vector  =  dot( state_transition_matrix , lam ) - la_k_double_dot[3:]
        #print '\n\ncostate_residual_vector = \n',costate_residual_vector
291     return costate_residual_vector

293

295 #   ------------------------------------------------------------------------------------------------------------------------


297 # we must compute the partials of the angular state equations ( etadd ) with respect to the angular
        velocities ( phi_dot, theta_dot, psi_dot )

299

301 # this function just evaluates the angular state equations replacing "(ph_k - ph_k_minus_1)/h "   with  "( (
        ph_k - ph_k_minus_1)/h ) + d"

303 def etadd_with_phi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
        u3_k , u4_k ):

305     input_func_vector = a([
                              l * alpha * ( -u2_k**2 + u4_k**2 ) ,
307                           l * alpha * ( -u1_k**2 + u3_k**2 ) ,
                              b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
309                         ])

311     coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, 'phd' )

313     ang_vel_vector = a( [ ( (ph_k - ph_k_minus_1)/h ) + d , (th_k - th_k_minus_1)/h , ( ps_k - ps_k_minus_1)/
         h ] )

315     temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )

317     etadd_phi_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
        #print '\n\netadd_phi_plus_d = \n',etadd_phi_plus_d
319     return a( etadd_phi_plus_d )

321

323 def etadd_with_theta_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
        u3_k , u4_k ):

325     input_func_vector = a([
                              l * alpha * ( -u2_k**2 + u4_k**2 ) ,
327                           l * alpha * ( -u1_k**2 + u3_k**2 ) ,
                              b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
329                         ])

331     coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, 'thd' )

333     ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h, ( (th_k - th_k_minus_1)/h ) + d  , ( ps_k - ps_k_minus_1)/
         h ] )

335     temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )
```

```
337     etadd_theta_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
        #print '\n\netadd_theta_plus_d = \n',etadd_theta_plus_d
339     return a( etadd_theta_plus_d )


341


343 def etadd_with_psi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
        u3_k , u4_k ):

345     input_func_vector = a([
                              l * alpha * ( -u2_k**2 + u4_k**2 ) ,
347                           l * alpha * ( -u1_k**2 + u3_k**2 ) ,
                              b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
349                         ])

351     coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, 'psd' )

353     ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h, (th_k - th_k_minus_1)/h , ( ( ps_k - ps_k_minus_1)/h ) + d
          ] )

355     temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )

357     etadd_psi_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
        #print '\n\netadd_psi_plus_d = \n',etadd_psi_plus_d
359     return a( etadd_psi_plus_d )


361


363
    # this is just the plain ole angular state equation vector
365
    def etadd( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k , u3_k , u4_k ):
367
        input_func_vector = a([
369                           l * alpha * ( -u2_k**2 + u4_k**2 ) ,
                              l * alpha * ( -u1_k**2 + u3_k**2 ) ,
371                           b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
                            ])
373
        coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, None )
375
        ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h, (th_k - th_k_minus_1)/h , ( ps_k - ps_k_minus_1)/h ] )
377
        temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )
379
        etadd_theta_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
381     #print '\n\netadd_theta_plus_d = \n',etadd_theta_plus_d
        return a( etadd_theta_plus_d )
383


385
    #
          ------------------------------------------------------------------------------------------------------------
          print '\n\n = \n',
```

```
387
# The algebraic costate equations
389
def algebraic_costate_equations(
391             ph_k , ph_k_minus_1, th_k , th_k_minus_1 , ps_k , ps_k_minus_1,
                u1_k , u2_k , u3_k , u4_k,
393             la4_k ,
                la5_k ,
395             la6_k
                ):
397
    # the pnumeonic for the following three assignments is ppd -> phi plus d
399     ppd = etadd_with_phi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k ,
         u2_k , u3_k , u4_k )

401     tpd = etadd_with_theta_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k ,
         u2_k , u3_k , u4_k )

403     ppd = etadd_with_psi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k ,
         u2_k , u3_k , u4_k )


405
    eta_douple_dot = etadd( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
         u3_k , u4_k )
407

409     del_f_d_phi_dot = (ppd-eta_douple_dot)/d

411     del_f_d_theta_dot = (tpd-eta_douple_dot)/d

413     del_f_d_psi_dot = (ppd-eta_douple_dot)/d


415
    algebraic_transition_matrix = a( [  del_f_d_phi_dot , del_f_d_theta_dot , del_f_d_psi_dot  ]  )#.reshape
         ([3,3])
417
    #print '\n\nalgebraic_transition_matrix = ',algebraic_transition_matrix
419


421     la4_through_6 = a( [ la4_k , la5_k , la6_k ] )
    #print '\n\nla4_through_6 = ',la4_through_6
423
    algebraic_costate_equations_residual_vector  =  dot( algebraic_transition_matrix , la4_through_6 )
425     #print '\n\nalgebraic_costate_equations_residual_vector = \n',algebraic_costate_equations_residual_vector
    return algebraic_costate_equations_residual_vector
427


429 #-------------------------------------------------------------------------------------------# stationarity
         conditions:


431


433 def stationarity_conditions(x_k , x_k_minus_1 , x_k_minus_2 ,
                y_k , y_k_minus_1 , y_k_minus_2 ,
435             z_k , z_k_minus_1 , z_k_minus_2 ,
```

```
            ph_k , ph_k_minus_1 , ph_k_minus_2,
            th_k , th_k_minus_1 , th_k_minus_2,
            ps_k , ps_k_minus_1 , ps_k_minus_2,
            u1_k , u2_k , u3_k , u4_k,
            la1_k , la2_k ,la3_k , la4_k , la5_k , la6_k ):


    ff = f(x , x_k_minus_1 , x_k_minus_2 ,
      y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
      ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k , th_k_minus_1 , th_k_minus_2,
      ps_k , ps_k_minus_1 , ps_k_minus_2,
      u1_k , u2_k , u3_k , u4_k )


    ff_u1_k_plus_d = f(x , x_k_minus_1 , x_k_minus_2 ,
      y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
      ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k , th_k_minus_1 , th_k_minus_2,
      ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k + d, u2_k     , u3_k     ,  u4_k )

    ff_u2_k_plus_d = f(x , x_k_minus_1 , x_k_minus_2 ,
      y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
      ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k , th_k_minus_1 , th_k_minus_2,
      ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k    , u2_k + d , u3_k     , u4_k )

    ff_u3_k_plus_d = f(x , x_k_minus_1 , x_k_minus_2 ,
      y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
      ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k , th_k_minus_1 , th_k_minus_2,
      ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k    , u2_k     , u3_k + d , u4_k )

    ff_u4_k_plus_d = f(x , x_k_minus_1 , x_k_minus_2 ,
      y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
      ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k , th_k_minus_1 , th_k_minus_2,
      ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k    , u2_k     , u3_k     , u4_k +d )


    # note this is the TRANSPOSE of the matrix of partials of f WRT u

    dfdq1 = (ff_u1_k_plus_d - ff)/d
    dfdq2 = (ff_u2_k_plus_d - ff)/d
    dfdq3 = (ff_u3_k_plus_d - ff)/d
    dfdq4 = (ff_u4_k_plus_d - ff)/d

    lambda_k =  [ la1_k , la2_k ,la3_k , la4_k , la5_k , la6_k ]

    individ_rows = a([ dot( dfdq1 ,lambda_k ),
```

```
491                     dot( dfdq2 ,lambda_k ),
                        dot( dfdq3 ,lambda_k ),
493                     dot( dfdq4 ,lambda_k )
                    ])
495


497
    stationarity_conditions_residual_vector =  individ_rows + 2* a( [ u1_k , u2_k , u3_k , u4_k ] )
499 #print '\n\nstationarity_conditions_residual_vector = \n',stationarity_conditions_residual_vector
    return stationarity_conditions_residual_vector
501


503


505

#-------------------------------------------------------------------------------------------# the objective
     function at the kth timestep
507


509 def G_at_k(x_k, x_k_minus_1 , x_k_minus_2 ,
      y_k , y_k_minus_1 , y_k_minus_2 ,
511   z_k , z_k_minus_1 , z_k_minus_2 ,
      ph_k , ph_k_minus_1 , ph_k_minus_2,
513   th_k , th_k_minus_1 , th_k_minus_2,
      ps_k , ps_k_minus_1 , ps_k_minus_2,
515   u1_k , u2_k , u3_k , u4_k,
      la1_k , la1_k_minus_1 , la1_k_minus_2,
517   la2_k , la2_k_minus_1 , la2_k_minus_2,
      la3_k , la3_k_minus_1 , la3_k_minus_2,
519   la4_k , la4_k_minus_1 , la4_k_minus_2,
      la5_k , la5_k_minus_1 , la5_k_minus_2,
521   la6_k , la6_k_minus_1 , la6_k_minus_2
    ):
523
    state_vector_residual = f(x_k , x_k_minus_1 , x_k_minus_2 ,
525   y_k , y_k_minus_1 , y_k_minus_2 ,
      z_k , z_k_minus_1 , z_k_minus_2 ,
527   ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k , th_k_minus_1 , th_k_minus_2,
529   ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k , u2_k , u3_k , u4_k )
    #print '\n\nstate_vector_residual = \n',state_vector_residual
531


533 costate_residual  = costate(x_k , x_k_minus_1 , x_k_minus_2 ,
            y_k , y_k_minus_1 , y_k_minus_2 ,
535         z_k , z_k_minus_1 , z_k_minus_2 ,
            ph_k , ph_k_minus_1 , ph_k_minus_2,
537         th_k , th_k_minus_1 , th_k_minus_2,
            ps_k , ps_k_minus_1 , ps_k_minus_2,
539         u1_k , u2_k , u3_k , u4_k,
            la1_k , la1_k_minus_1 , la1_k_minus_2,
541         la2_k , la2_k_minus_1 , la2_k_minus_2,
            la3_k , la3_k_minus_1 , la3_k_minus_2,
543         la4_k , la4_k_minus_1 , la4_k_minus_2,
            la5_k , la5_k_minus_1 , la5_k_minus_2,
```

```
            la6_k , la6_k_minus_1 , la6_k_minus_2
            )
    #print '\n\ncostate_residual = \n',costate_residual


    algebraic_costate_equations_residual_vector = algebraic_costate_equations(
                ph_k , ph_k_minus_1, th_k , th_k_minus_1 , ps_k , ps_k_minus_1,
                u1_k , u2_k , u3_k , u4_k,
                la4_k ,
                la5_k ,
                la6_k
                )
    #print '\n\nalgebraic_costate_equations_residual_vector = \n',algebraic_costate_equations_residual_vector


    stationarity_conditions_residual_vector = stationarity_conditions(x_k , x_k_minus_1 , x_k_minus_2 ,
            y_k , y_k_minus_1 , y_k_minus_2 ,
            z_k , z_k_minus_1 , z_k_minus_2 ,
            ph_k , ph_k_minus_1 , ph_k_minus_2,
            th_k , th_k_minus_1 , th_k_minus_2,
            ps_k , ps_k_minus_1 , ps_k_minus_2,
            u1_k , u2_k , u3_k , u4_k,
            la1_k , la2_k ,la3_k , la4_k , la5_k , la6_k )

    #print '\n\nstationarity_conditions_residual_vector = \n',stationarity_conditions_residual_vector


    temp_array =  a( concatenate([
                                state_vector_residual,
                                costate_residual,
                                algebraic_costate_equations_residual_vector,
                                stationarity_conditions_residual_vector])
                            )

    kth_residual = sum( temp_array )
    #print '\n\nkth_residual = \n',kth_residual

    return kth_residual


#-------------------------------------------------------------------------------
     full_objective_function
```

```
599 # the full objective function sums up all the contributions from each time step
601
    def full_objective_function(N,
603                             x,y,z,
                                ph,th,ps,
605                             u1,u2,u3,u4,
                                la1,la2,la3,la4,la5,la6):
607
        glist = []
609
        for k in arange(2,N):
611
            g_k = G_at_k(
613                 x[k] , x[k-1], x[k-2],
                    y[k] , y[k-1], y[k-2],
615                 z[k] , z[k-1], z[k-2],
                    ph[k] , ph[k-1], ph[k-2],
617                 th[k] , th[k-1], th[k-2],
                    ps[k] , ps[k-1], ps[k-2],
619                 u1[k] , u2[k] , u3[k] , u4[k],
                    la1[k] , la1[k-1] , la1[k-2],
621                 la2[k] , la2[k-1] , la2[k-2],
                    la3[k] , la3[k-1] , la3[k-2],
623                 la4[k] , la4[k-1] , la4[k-2],
                    la5[k] , la5[k-1] , la5[k-2],
625                 la6[k] , la6[k-1] , la6[k-2]
                    )
627
            glist.append(g_k)
629
        objective_function_residual =  sum(glist)
631
        #print '\n\nobjective_function_residual = \n',objective_function_residual
633
        return objective_function_residual
635
637
639 #------------------------------------------------------------------------------------- gradient
641
643 def gradient(N,
                 x,y,z,
645              ph,th,ps,
                 u1,u2,u3,u4,
647              la1,la2,la3,la4,la5,la6
                ):
649
        grad = []
651
        input_vars_1d = concatenate([
653                                 x[2:-1],   y[2:-1],  z[2:-1],
```

```
                                ph[2:-1], th[2:-1], ps[2:-1],
655                             u1[2:-1], u2[2:-1], u3[2:-1], u4[2:-1],
                                la1[2:-1],la2[2:-1],la3[2:-1],la4[2:-1],la5[2:-1],la6[2:-1]
657                             ])

659     obj_func_res = full_objective_function(N,
                        x,y,z,
661                     ph,th,ps,
                        u1,u2,u3,u4,
663                     la1,la2,la3,la4,la5,la6)

665     delta = 0.0001

667     for i in range(len(input_vars_1d)):

669         aug_input = []
            #print 'aug_input  = ',aug_input
671
            for j in range(len(input_vars_1d)):
673             if j == i:
                    aug_input.append(a(input_vars_1d[j] + delta) )
675
                else: aug_input.append(input_vars_1d[j])
677
            aug_input_parsed = reshape(aug_input, ( 16 , N ))
679
            #print 'aug_input_parsed = ',aug_input_parsed
681
            x_aug = aug_input_parsed[0]
683         y_aug = aug_input_parsed[1]
            z_aug = aug_input_parsed[2]
685         ph_aug = aug_input_parsed[3]
            th_aug = aug_input_parsed[4]
687         ps_aug = aug_input_parsed[5]
            u1_aug = aug_input_parsed[6]
689         u2_aug = aug_input_parsed[7]
            u3_aug = aug_input_parsed[8]
691         u4_aug = aug_input_parsed[9]
            la1_aug = aug_input_parsed[10]
693         la2_aug = aug_input_parsed[11]
            la3_aug = aug_input_parsed[12]
695         la4_aug = aug_input_parsed[13]
            la5_aug = aug_input_parsed[14]
697         la6_aug = aug_input_parsed[15]

699


701         aug_obj_func_res = full_objective_function(N,
                                x_aug,y_aug,z_aug,
703                             ph_aug,th_aug,ps_aug,
                                u1_aug,u2_aug,u3_aug,u4_aug,
705                             la1_aug,la2_aug,la3_aug,la4_aug,la5_aug,la6_aug)


707
            dg = ( aug_obj_func_res - obj_func_res )/delta
```

```
709
        #print '\n\ndg = ',dg
711
        grad.append(dg)    # grad returns as a one d list...
713
    return a(grad)
715

717 ##########################################################################################################

719 if __name__ == '__main__':

721     from time import time

723     t1 = time()

725     N = 10 # the number of timesteps

727     # initialize the lists that will contain the solutions for each variable

729     init = a( [ 1 for i in range(N) ] )  # note this list does not include the boundary values

731     xterm = a([10])
        yterm = a([10])
733     zterm = a([10])

735     x = concatenate([ a([0,0]) , 5 * init , xterm ])
        y = concatenate([ a([0,0]) , 5 * init , yterm ])
737     z = concatenate([ a([0,0]) , 5 * init , zterm ])

739     ph = concatenate([ a([0,0]) , 0.1 * init , a([0])])
        th = concatenate([ a([0,0]) , 0.1 * init , a([0])])
741     ps = concatenate([ a([0,0]) , 0.1 * init , a([0])])

743
    # the terminal conditions for the control imputs are defined by the fact that we want the quadrotor to
     end in a hovering state
745
    # this means that the total thrust must equal g, and that all the imputs (motor speeds) must be the same
747 '''
    g = T
749
    g = alpha * (u1**2 + u2**2 + u3**2 + u4**2)
751
    g = alpha*4*u**2
753
    uterm = sqrt(g)/(4*alpha)
755 '''
    uhover = sqrt(abs(g))/(4*alpha)
757 #print 'uterm = ',uterm

759

    u1 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])
761 u2 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])
    u3 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])
```

```
763     u4 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])
765
        la1 = concatenate( [ a([0,0]) ,  init , a([0]) ] )
767
        la2 = concatenate( [ a([0,0]) ,  init , a([0]) ] )
769
        la3 = concatenate( [ a([0,0]) ,  init , a([0]) ] )
771
        la4 = concatenate( [ a([0,0]) ,  init , a([0]) ] )
773
        la5 = concatenate( [ a([0,0]) ,  init , a([0]) ] )
775
        la6 = concatenate( [ a([0,0]) ,  init , a([0]) ] )
777
        '''
779     for i in [x,y,z,ph,th,ps,u1,u2,u3,u4,la1,la2,la3,la4,la5,la6]:
            print len(i)
781     '''
783
        #-------------------------------------------------------------------------
785
787     initial_objective_function_residual = full_objective_function(N,
                                    x,y,z,
789                                 ph,th,ps,
                                    u1,u2,u3,u4,
791                                 la1,la2,la3,la4,la5,la6)
793     #print '\n\nobjective_function_residual= \n',objective_function_residual
795
797     obj_func_res_list = [initial_objective_function_residual]
        grad_norm_list = []
799
801     max_iterations = 10
        tol = 1
803
        for iteration_number in range(max_iterations):
805
            grad = gradient(N,
807                         x,y,z,
                            ph,th,ps,
809                         u1,u2,u3,u4,
                            la1,la2,la3,la4,la5,la6
811                        )
813
            grad_norm = norm( a( grad ))
815
            print '-----------------------------------------iteration_number = ',iteration_number
817         print '\n\ngrad = \n',grad
```

```
819
        grad_norm_list.append( grad_norm )
821
        normalized_gradient = grad/grad_norm
823
        step_size = 0.5
825     '''
        if iteration_number > 10:
827         step_size = 0.01
        elif iteration_number > 40:
829         step_size = 0.001
        elif iteration_number > 60:
831         step_size = 0.0001
        '''
833
        # step in the direction opposite of the gradient
835     step =  a(   ( step_size ) * normalized_gradient  )

837     print '\n\nstep = ',step

839
        input_vars_1d = concatenate([
841                               x[2:-1],   y[2:-1],  z[2:-1],
                                  ph[2:-1], th[2:-1], ps[2:-1],
843                               u1[2:-1], u2[2:-1], u3[2:-1], u4[2:-1],
                                  la1[2:-1],la2[2:-1],la3[2:-1],la4[2:-1],la5[2:-1],la6[2:-1]
845                               ])

847

849
        new_partial_input_vector =  reshape( input_vars_1d - step , ( 16 , N ) )         # this does not
    contain the boundary conditions hence the 'partial'
851

853

855
        x   = concatenate([ a([0,0]) , new_partial_input_vector[0] , xterm      ])
857     y   = concatenate([ a([0,0]) , new_partial_input_vector[1] , yterm      ])
        z   = concatenate([ a([0,0]) , new_partial_input_vector[2] , zterm      ])
859     ph  = concatenate([ a([0,0]) , new_partial_input_vector[3] , a([0])     ])
        th  = concatenate([ a([0,0]) , new_partial_input_vector[4] , a([0])     ])
861     ps  = concatenate([ a([0,0]) , new_partial_input_vector[5] , a([0])     ])
        u1  = concatenate([ a([uhover,uhover]) , new_partial_input_vector[6] , a([uhover]) ])
863     u2  = concatenate([ a([uhover,uhover]) , new_partial_input_vector[7] , a([uhover]) ])
        u3  = concatenate([ a([uhover,uhover]) , new_partial_input_vector[8] , a([uhover]) ])
865     u4  = concatenate([ a([uhover,uhover]) , new_partial_input_vector[9] , a([uhover]) ])
        la1 = concatenate([ a([0,0]) , new_partial_input_vector[10], a([0])     ])
867     la2 = concatenate([ a([0,0]) , new_partial_input_vector[11], a([0])     ])
        la3 = concatenate([ a([0,0]) , new_partial_input_vector[12], a([0])     ])
869     la4 = concatenate([ a([0,0]) , new_partial_input_vector[13], a([0])     ])
        la5 = concatenate([ a([0,0]) , new_partial_input_vector[14], a([0])     ])
871     la6 = concatenate([ a([0,0]) , new_partial_input_vector[15], a([0])     ])
```

```
873
        print '\n\nx = \n',x
875     print '\n\nphi = \n',ph
        print '\n\nu1 = \n',u1
877     print '\n\nla1 = \n',la1

879     objective_function_residual = full_objective_function(N,
                                x,y,z,
881                             ph,th,ps,
                                u1,u2,u3,u4,
883                             la1,la2,la3,la4,la5,la6)

885     print '\n\nobjective_function_residual = ',objective_function_residual

887     obj_func_res_list.append(objective_function_residual)

889
    # ----------------------------------------------------TEST FOR CONVERGENCE
891


893
        if objective_function_residual > obj_func_res_list[0]:
895
            print '\n\n ERROR : the new value of the objective function has exceeded the initial value'
897         print '\n objective_function_residual = ',objective_function_residual
            print '\n obj_func_res_list[0] = ',obj_func_res_list[0]
899         break
            #step_size = step_size*0.5
901


903
        elif grad_norm < tol:
905
            print 'norm_del_G < tolerance.........the process has converged!!!!'
907         break

909


911     #wait = raw_input('\n\n\npress space to continue...')

913
    t2 = time()
915
    delta_t = t2-t1
917
    print '-------------------------------------------------'
919
    print '\n\n\ndelta_t = ',delta_t
921
    ################################################################################
923


925
```

```
927
929     '''
931     delta = 0.0001
933         for i in range(len(input_vars_1d)):
935             aug_input = []
                #print 'aug_input  = ',aug_input
937
                for j in range(len(input_vars_1d)):
939                 if j == i:
                        aug_input.append(a(input_vars_1d[j] + delta) )
941
                    else: aug_input.append(input_vars_1d[j])
943
                aug_input_parsed = reshape(aug_input, ( 16 , N ))
945
                #print 'aug_input_parsed = ',aug_input_parsed
947
                x_aug = aug_input_parsed[0]
949             y_aug = aug_input_parsed[1]
                z_aug = aug_input_parsed[2]
951             ph_aug = aug_input_parsed[3]
                th_aug = aug_input_parsed[4]
953             ps_aug = aug_input_parsed[5]
                u1_aug = aug_input_parsed[6]
955             u2_aug = aug_input_parsed[7]
                u3_aug = aug_input_parsed[8]
957             u4_aug = aug_input_parsed[9]
                la1_aug = aug_input_parsed[10]
959             la2_aug = aug_input_parsed[11]
                la3_aug = aug_input_parsed[12]
961             la4_aug = aug_input_parsed[13]
                la5_aug = aug_input_parsed[14]
963             la6_aug = aug_input_parsed[15]
965
967             aug_obj_func_res = full_objective_function(N,
                                    x_aug,y_aug,z_aug,
969                                 ph_aug,th_aug,ps_aug,
                                    u1_aug,u2_aug,u3_aug,u4_aug,
971                                 la1_aug,la2_aug,la3_aug,la4_aug,la5_aug,la6_aug)
973
                dg = ( aug_obj_func_res - obj_func_res )/delta
975
                #print '\n\ndg = ',dg
977
                grad.append(dg)    # grad returns as a one d list...
979
981
```

```
983     '''
```

/home/ek/Dropbox/THESIS/quadrotor_optimal_control/finiteDiffSolution.py

Bibliography

[diy] URL http://diydrones.com/.

[air] URL http://www.airware.com/.

[faa] URL http://www.faa.gov/about/initiatives/uas/.

[1] Elizabeth Bone and Christopher C Bolkcom. *Unmanned aerial vehicles: background and issues*. Nova Science Pub Incorporated, 2004.

[2] Jack W Langelaan. Long distance/duration trajectory optimization for small uavs. In *AIAA Guidance, Navigation and Control Conference and Exhibit*, 2007.

[3] Andrew T Klesh and Pierre T Kabamba. Solar-powered aircraft: Energy-optimal path planning and perpetual endurance. *Journal of guidance, control, and dynamics*, 32(4):1320–1329, 2009.

[4] Nicholas RJ Lawrance and Salah Sukkarieh. A guidance and control strategy for dynamic soaring with a gliding uav. In *Robotics and Automation, 2009. ICRA'09. IEEE International Conference on*, pages 3632–3637. IEEE, 2009.

[5] Bora Erginer and Erdinc Altug. Modeling and pd control of a quadrotor vtol vehicle. pages 894–899, 2007.

[6] Samir Bouabdallah, Andre Noth, and Roland Siegwart. Pid vs lq control techniques applied to an indoor micro quadrotor. 3:2451–2456, 2004. URL http://citeseerx.ist.psu.edu/viewdoc/download?rep=rep1&type=pdf&doi=10.1.1.149.6169.

[7] Teppo Luukkonen. Modelling and control of quadcopter. *Aalto University*, August 2011.

[8] Jerry B Marion and Stephen T Thornton. *Classical dynamics of particles and systems*. Saunders College Pub., 1995.

[9] Cornelius Lanczos. *The variational principles of mechanics*, volume 4. Courier Dover Publications, 1970.

[10] J. Bernoulli. *Bending of light rays in transparent non-uniform media and the Solution to the problem of determing the Brachistochrone curve*. 1697.

[11] L.Euler. *Methodus Inveniendi Lineas Curvas Maximi Minimive Proprietate Gaudentes sive Solutio Problematis Isoperimetrici Latissimo Sensu Accepti (The Method of Finding Plane Curves that Show Some Property of Maximum or Minimum*. 1744.

[12] L.S. Pontryagin V.G. Boltyanskii, R.V. Gamkrelidze. *Towards a theory of optimal processes, (Russian)*. Reports Acad. Sci. USSR, vol.110(1), 1956.

[13] Frank L Lewis, Draguna Vrabie, and Vassilis L Syrmos. *Optimal control*. Wiley. com, 2012.

[14] A. E. Bryson and Y. C. Ho. *Applied Optimal Control*. Blaisdell, New York, 1969.

[15] Arturo Locatelli. *Optimal control: An introduction*. Springer, 2001.

[16] Michael Athans and Peter L Falb. *Optimal control: an introduction to the theory and its applications*. Courier Dover Publications, 2006.

[17] L Richard and J Burden. Douglas faires, numerical analysis, 1988.

[18] Singiresu S Rao and SS Rao. *Engineering optimization: theory and practice*. John Wiley & Sons, 2009.

[19] Herbert Bishop Keller. *Numerical methods for two-point boundary-value problems*. Dover Publications New York, NY, 1992.

[20] Aidan O'Dwyer. Reducing energy costs by optimizing controller tuning. In *Conference papers*, page 66, 2006.

[21] B Wayne Bequette. *Process control: modeling, design, and simulation*. Prentice Hall Professional, 2003.

[22] Chong G.C.Y. Ang, K.H. and Y. Li. Pid control system analysis, design, and technology. 2005.

[23] Stuart Bennett. A history of control engineering, 1800-1930. 1986.

[24] G.G. Coriolis. Mémoire sur les équations du mouvement relatif des systèmes de corps. 1835.

[25] David Hestenes. *New Foundations for Classical Mechanics*. The Netherlands: Kluwer Academic Publishers. p. 312. ISBN 90-277-2526-8., 1990.

[26] Singiresu S Rao. *Applied numerical methods for engineers and scientists*. Prentice Hall Professional Technical Reference, 2001.

[27] JG Ziegler and NB Nichols. Optimum settings for automatic controllers. *trans. ASME*, 64(11), 1942.

[znw] URL http://en.wikipedia.org/wiki/Ziegler-Nichols_method.