QUAD-ROTOR FLIGHT PATH ENERGY OPTIMIZATION

By Edward Kemper

A Thesis

Submitted in Partial Fulfillment

of the requirements for the degree of

Masters of Science

in Electrical Engineering

Northern Arizona University

April 2014

Approved:

Dr. Niranjan Venkatraman, Ph.D.,Chair

Dr. Sheryl Howard, Ph.D.

Dr. Allison Kipple, Ph.D.

ABSTRACT

QUADROTOR FLIGHT PATH ENERGY OPTIMIZATION

by Edward KEMPER

Quad-Rotor unmanned areal vehicles (UAVs) have been a popular area of research and development in the last decade, especially with the advent of affordable microcontrollers like the MSP 430 and the Raspberry Pi. Path-Energy Optimization is an area that is well developed for linear systems. In this thesis, this idea of path-energy optimization is extended to the nonlinear model of the Quad-rotor UAV. The classical optimization technique is adapted to the nonlinear model that is derived for the problem at hand, coming up with a set of partial differential equations and boundary value conditions to solve these equations. Then, different techniques to implement energy optimization algorithms are tested using simulations in Python. First, a purely nonlinear approach is used. This method is shown to be computationally intensive, with no practical solution available in a reasonable amount of time. Second, heuristic techniques to minimize the energy of the flight path are tested, using Ziegler-Nichols' proportional integral derivative (PID) controller tuning technique. Finally, a brute force lookup table based PID controller is used. Simulation results of the heuristic method show that both reliable control of the system and path-energy optimization are achieved in a reasonable amount of time.

ACKNOWLEDGEMENTS

Contents

List of Figures

For my Parents Jack and Carol. . .

Chapter 1

Introduction

The technology surrounding Unmanned Aerial Vehicles (UAVs), and in particular quad-rotor devices, has seen tremendous development in recent years. Likewise, the creative application of this technology has expanded into many contexts. Like many new technologies, the early development of UAVs was mostly in a military context. This is not the case any more. The private sector has taken a huge interest in this technology. There is a wide range of companies contributing to the development of UAV technology from open-source projects like DIY Drones [1] to start-up firms backed by Google, such as Airware [2]. The Federal Aviation Administration in the USA has plans to produce concrete policy regarding the regulation of commercial applications of UAVs by 2015 [3]. This will sow the seeds for the rapid growth of a multi-billion dollar industry. There are many applications for this technology which have the potential to save lives and collect scientific data that could inform state and federal legislation. Certainly, the range of potential applications will be further diversified as the technology sees more development.

Unmanned Ariel Vehicles are also called by various other names: remotely piloted vehicles (RPVs), remote controlled drones, robot planes, and pilot-less aircraft. Such vehicles are defined as powered, aerial vehicles that do not carry a human operator and can use aerodynamics forces to provide vehicle lift. They can fly autonomously or be piloted remotely, can be expendable or recoverable, and can carry a lethal or nonlethal payload [4].

1.1   Motivation

With many private organizations making use of UAVs for a variety of applications, one pervasive engineering problem that still exists in general is that of managing the energy usage. Quad-rotors specifically are plagued by very high energy demand. There are two different kinds of UAVs: fixed wing, which have the ability to soar or glide, and multi-rotor systems, which are entirely thrust-driven. It is the natural instability of multi-rotor UAVs which make them extremely maneuverable, but this comes at the cost of high energy expenditure. This provides the motivation for this thesis - to develop an optimal control technique that optimizes the path-energy of a quad-copter UAV.

1.2   Prior Work

There have been work published on the energy optimization and trajectory planning of fixed wing UAVs. Given the ability to soar and utilize thermal gradients in the atmosphere, it is suggested that fixed wing UAVs have the potential to stay aloft almost permanently [5], [6], and [7]. This makes fixed wing UAVs ideal for applications like aerial surveys or surveillance missions. These aircrafts have

the major disadvantage that they are dependent upon some kind of launching mechanism, or a runway, for takeoff and landing.

In contrast, rotary wing UAVs have a higher degree of mechanical complexity. These UAVs can take off and land vertically and have the capacity to hover. This makes rotary wing UAVs, such as the quad-copter, more suitable for short range search and rescue missions, facility inspections, and single-target tracking. Since fixed wing and multi-rotor UAVs are fundamentally different in their physical operation, procedures for managing their respective energy usage are also necessarily unique.

In academic contexts, many advances in UAV and specifically quad-rotor research have provided the seeds for growth for this industry. The problem of basic stability and position control is solved in [8], [9], and [10].

The background material for understanding the dynamical model of the quad-rotor as given by the Euler-Lagrange formulation is explained in [11] and [12]. These references provide detailed derivations and discussions of the Euler-Lagrange equations of motion as well as related topics like Hamiltonian mechanics and the calculus of variations. Also, [12] provides an in-depth review of the historical context surrounding the development of classical mechanics. The derivation of the quad-rotor dynamical model as well as attitude and position control via PD or PID controllers is discussed in [8], [9], and [10]. These papers provide derivations of both the Euler-Lagrange and Newtonian formulations for the quad-rotor.

Optimal control was born in 1697, when Johann Bernoulli published his solution to the Brachystochrone problem in [13] . With the work of Bernoulli, Newton, Leibniz, l'Hopital, and Tschirnhaus, the field of optimal control was clearly defined. This was followed by the works of Euler, Lagrange, and Legendre which

3

led to the fundamental optimization equations, Euler's equation [14], the Euler-Lagrange formulation, and Legendre's necessary condition for a minimum. W. R. Hamilton then came up with an equivalent to the Euler-Lagrange equation that could be used in deriving control equations. This was known as the control Hamiltonian form of the Euler-Lagrange equations. The next development was from Weierstass, who came up with the fundamental path optimization problem in optimal control theory in the late 19th century. This was followed by the fundamental minimization principle by Pontryagin that allows for solving most optimization problems [15]. Several books on optimal control ([16] , [17], [18], [19]) were referenced for the derivations used in this thesis. In order to test the nonlinear optimization, numerical algorithms for the shooting method ([20], [21], [22]) and the finite difference method ([21], [22]) were used.

The Proportional-Integral-Derivative (PID) controller is a control loop feedback mechanism widely used to drive a system to a desired set point. The mechanism uses an error value as the input to the controller. PID controllers are common in industrial applications [23]. In the absence of the knowledge of an underlying process, the PID is considered the best method of control. It must be noted that PID controllers do not necessarily result in optimal control of the system. However, it is possible to achieve a desired system response by adjusting the mathematical parameters of the control expressions. This process is called "tuning". The tuning must satisfy many criteria within the limitations of PID control and the system itself. There are various tuning techniques [24]. For instance, there are the Ziegler-Nichols, manual tuning, and software tuning methods which can be applied to other control problems [25], [26].

1.3 Organization of the Thesis

The objective of this thesis is to develop a path-energy optimization technique that can operate on a near real-time schedule. Two different methods are discussed. We compare a classical optimal control technique with a simpler heuristic approach involving PID controller tuning. The organization of the chapters is as follows.

In Chapter 2, we present a detailed problem statement where the goal of the research project is defined. Chapter 3 uses the Euler-Lagrange equations of motion to derive a nonlinear dynamical model for the quad-rotor UAV. This mathematical model is the basis of the development of the control and energy optimization algorithms. In chapter 4, we define the various optimality conditions. Then we and formulate a generalized, classical optimal control scheme. Then we solve the boundary value problem generated by two methods and discuss their pros and cons. In Chapter 5, the classical optimal control scheme developed in the previous chapter is applied to the quad-rotor UAV. The resulting boundary value problem and its solution method is discussed. Chapter 6 deals with the PID/PD control technique. The control expressions are derived, and the method is tested. Results from these tests are discussed. Chapter 7 outlines a heuristic approach to the path-energy optimization problem and presents the simulation results of the control algorithm developed. Chapter 8 summarizes the results and proposes avenues for continued research.

Chapter 2

Problem Statement

We wish to find a set of control expressions for a quad-rotor UAV which minimizes the energy expended in flying between two known points in three-dimensional space. In order to maintain focus on a tractable problem, some mathematical assumptions are made about the scenario. First, we assume that the flight path that will be optimized is free of obstacles. Second, we assume only modeled environmental variables. We use a mathematical model of the system derived from a Euler-Lagrange formulation as in [9] and [10].

In the classical optimal control approach, as in [16] and [17], the control of the system and the optimization are represented in a single mathematical formulation. Solving the optimal control problem is achieved by solving a boundary value problem. For a highly nonlinear system such as a quad-rotor, this becomes extremely involved. The classical optimal control approach is shown to be too computationally intensive for a real-time implementation because the result is a substantial two point boundary value problem. Solving the theoretical optimal control problem would likely produce accurate results, but the solution could potentially take

weeks of computation to attain. Also, the convergence of the solution is shown to be intermittent.

For the heuristic approach, full control of the UAV is attained by using PD attitude controllers in conjunction with PID controllers for position. This provides a platform for simulating the UAV as it flies from a known initial position to a desired set point location. The optimization procedure evaluates the results of these simulations for optimality as a function of the PID gains used in the position control expressions.

It is pertinent to define what is meant by near real-time in our somewhat sterile mathematical context. We assume that the set of initial and final locations of the quad-rotor are defined by a user on a human time scale. Imagine a graphical user interface in which the desired location of the UAV is programmed. The quad-rotor then physically traverses the optimal path without more than a second or two of computation before the flight begins. For an autonomous UAV, the on-board computational resources define an upper limit to the computational complexity of the control algorithm. Our aim is to design an energy optimized control scheme which meets these constraints.

Chapter 3

Quad-Rotor Dynamic Model

In this chapter, a mathematical model of the quad-rotor is derived, and the assumptions that go into this derivation are explained in detail. This model will be used as the basis for the optimization techniques outlined in subsequent chapters.

3.1 Description of a Quad-Rotor

A generic model of a quad-rotor is physically composed of a simple frame supporting four brushless motors. Thrust is provided by propellers attached to these motors. The speeds of the rotors are governed by a control algorithm which is implemented on some form of on-board processor.

The stabilization and control of a quad-rotor is accomplished by varying the speeds of the motors. The thrust in the vertical direction is controlled by varying all four motor speeds uniformly. In the quad-rotor frame of reference, the direction of the thrusts from the motors is fixed. This means that in order to produce lateral

motion, the UAV must tilt such that a component of the total thrust vector points in the desired direction of motion.

In Figure 3.1 the basic mechanical structure and the relationships between the spatial coordinates are shown. The linear and angular coordinates are defined as follows. ψ is the yaw angle around the z-axis, θ is the pitch angle around the y-axis and ϕ is the roll angle around the x-axis.


FIGURE 3.1: Angular and linear coordinate systems in the quad rotor dynamical model

The pitch and roll angular positions are controlled by driving motors on opposite sides of the frame at different speeds. This produces torque about the center of mass of the quad-rotor. Given non-zero pitch, roll, and total thrust, the UAV

experiences horizontal linear acceleration. The yaw angular position is controlled by driving pairs of opposite motors at the different speeds. This produces a torque about the yaw axis but not about the pitch or roll axes. Also, the two opposite pairs of motors must spin in opposite directions so that when hovering, the net torque about the yaw axis is zero. The details of this description are represented mathematically in the next section.

3.2 Coordinate System Definitions

In order to implement a control algorithm, we must understand the mathematical relationships between the control input and the resulting dynamics of the system. Using the Euler-Lagrange formulation from classical mechanics, we can obtain a nonlinear, deterministic dynamical model. General derivation of the Euler Lagrange differential equations of motion can be found in [11] and [12].

The spatial variables can be grouped into linear and angular components, with ξ representing the linear components and η representing the angular components:

$$\boldsymbol{\xi} = \begin{bmatrix} x \\ y \\ z \end{bmatrix}, \boldsymbol{\eta} = \begin{bmatrix} \phi \\ \theta \\ \psi \end{bmatrix}, \boldsymbol{q} = \begin{bmatrix} \xi \\ \eta \end{bmatrix} \tag{3.1}$$

3.3 Motor Speeds, Thrust and Torque

The rotor angular velocities are related to the forces they produce by $f_i = k\omega_i^2$ where k is the constant of proportionality and i is the motor index. The torques due to the rotation of the rotors about their respective axes of rotation are given by

$\tau_i = b\omega_i^2 + I_M\dot{\omega}_i$. The variable τ_i is the torque from the ith motor and the parameter b is a drag coefficient. Note the effect of $\dot{\omega}_i$ is considered to be negligible because the rotational inertia of the rotor itself is negligible.

In the quad-rotor frame of reference, the motors produce the following torques on the system:

$$\boldsymbol{\tau}_B = \begin{bmatrix} \tau_\phi \\ \tau_\theta \\ \tau_\psi \end{bmatrix} = \begin{bmatrix} lk(-\omega_2^2 + \omega_4^2) \\ lk(-\omega_1^2 + \omega_3^2) \\ \sum\limits_{i=1}^{4} b\omega^2 \end{bmatrix} \tag{3.2}$$

In the above expression the parameters l and k refer to the length of the quad-rotor arm and an aerodynamic thrust coefficient respectively. The combined thrust of the rotors in the direction of the quad-rotor frame z axis is

$$\boldsymbol{\mathcal{T}}_B = [0, 0, \mathcal{T}]^T \tag{3.3}$$

where,

$$\mathcal{T} = \sum_{i=1}^{4} f_i \tag{3.4}$$

.

3.4   Euler-Lagrange Equations of Motion

The mass of the quad-rotor is m. Each of the moments of inertia i_{xx} and i_{yy} are assumed to be composed of a rod of length l which accounts for half of the mass

of the quad-rotor. Assume the mass is evenly distributed along the two perpen-dicular rods. Let $\beta = \frac{1}{12}ml^2$. The inertia matrix for the quad-rotor is then:

$$I = \begin{pmatrix} \frac{1}{12}\left(\frac{m}{2}\right)l^2 & 0 & 0 \\ 0 & \frac{1}{12}\left(\frac{m}{2}\right)l^2 & 0 \\ 0 & 0 & \frac{1}{12}ml^2 \end{pmatrix} = \begin{pmatrix} \frac{\beta}{2} & 0 & 0 \\ 0 & \frac{\beta}{2} & 0 \\ 0 & 0 & \beta \end{pmatrix} \tag{3.5}$$

In this section, we will use Newton's notation for time derivatives. For instance, $\dot{\eta} = \frac{\partial \eta}{\partial t}$. In the inertial frame, the kinetic ((translational and rotational)and potential energy of the system are given by

$$KE_{\text{trans}} = \frac{1}{2}m\dot{\xi}^T\dot{\xi} \tag{3.6}$$

$$KE_{\text{rot}} = \frac{1}{2}\dot{\eta}^T J\dot{\eta} \tag{3.7}$$

$$U = mgz. \tag{3.8}$$

The Lagrangian is formed as the difference between kinetic and potential energy:

$$L = \frac{1}{2}m\dot{\xi}^T\dot{\xi} + \frac{1}{2}\dot{\eta}^T J\dot{\eta} - mgz. \tag{3.9}$$

The Jacobian J is given by
$$J = W_\eta^T I W_\eta, \tag{3.10}$$

where
$$W_\eta = \begin{bmatrix} 1 & 0 & -sin(\theta) \\ 0 & cos(\phi) & cos(\theta)sin(\phi) \\ 0 & -sin(\phi) & cos(\theta)cos(\phi) \end{bmatrix} \tag{3.11}$$

The matrix W_η is the matrix transformation which relates the angular velocities from the quad-rotor frame of reference to the inertial frame. Substituting equation 3.11 into equation 3.10 then provides:

$$J = \begin{pmatrix} \frac{\beta}{2} & 0 & -\frac{\beta}{2}s(\theta) \\ 0 & \frac{\beta}{2}c(\phi)^2 + \beta s(\phi)^2 & \frac{-\beta}{2}c(\phi)\ s(\phi)\ c(\theta) \\ -\beta s(\theta) & \frac{-\beta}{2}c(\phi)\ s(\phi)\ c(\theta) & \frac{\beta}{2}s(\theta)^2 + \frac{\beta}{2}s(\phi)^2c(\theta)^2 + \beta c(\phi)^2c(\theta)^2 \end{pmatrix} \quad (3.12)$$

The dynamics of the system are represented by the Euler - Lagrange differential equations of motion, as follows:

$$\frac{d}{dt}\left(\frac{\delta L}{\delta \dot{q}}\right) - \frac{\delta L}{\delta q} = F \quad (3.13)$$

where $q = \{x, y, z, \psi, \theta, \phi\} = \{\xi, \eta\}$.

f is the generalized force vector representing the linear external force acting on the system. τ is the vector of torques acting on the system due to the rotors.

$$\begin{pmatrix} f \\ \tau \end{pmatrix} = \frac{d}{dt}\left(\frac{\delta L}{\delta \dot{q}}\right) - \frac{\delta L}{\delta q} \quad (3.14)$$

General derivations of the Euler-Lagrange equations of motion can be found in [11] and [12].

The coordinates $q_i = \{x, y, z, \psi, \theta, \phi\}$ are in reference to a ground-based inertial coordinate system. The system states and control inputs must be mapped from the quad-rotor frame of reference to the inertial frame in order to express the dynamics of the system. The matrix R below represents an arbitrary rotation

13

transformation from the body frame to the inertial frame:

$$\boldsymbol{R} = \begin{bmatrix} c(\psi)c(\theta) & c(\psi)s(\theta)s(\phi) - s(\psi)c(\phi) & c(\psi)s(\theta)c(\phi) + s(\psi)s(\phi) \\ s(\psi)c(\theta) & s(\psi)s(\theta)s(\phi) + c(\psi)c(\phi) & s(\psi)s(\theta)c(\phi) - c(\psi)s(\phi) \\ -s(\theta) & c(\theta)s(\phi) & c(\theta)c(\phi) \end{bmatrix} \quad (3.15)$$

For simplicity, cos is denoted by 'c' and sin is denoted by 's' in the above expression.

The linear components of the generalized forces produce the following equations.

$$f = RT_B = m\ddot{\xi} - G \quad (3.16)$$

$$m \begin{pmatrix} \ddot{x} \\ \ddot{y} \\ \ddot{z} \end{pmatrix} - \begin{pmatrix} 0 \\ 0 \\ -mg \end{pmatrix} = u \begin{pmatrix} \cos\psi\sin\theta\cos\phi + \sin\psi\sin\phi \\ \sin\psi\sin\theta\cos\phi - \cos\psi\sin\phi \\ \cos\theta\cos\phi \end{pmatrix} \quad (3.17)$$

The angular components are expressed as

$$\tau = \tau_b = \frac{d}{dt}\left(\frac{\partial L}{\partial \dot{\eta}}\right) - \frac{\partial L}{\partial \eta} \quad (3.18)$$

$$\tau_b = \frac{d}{dt}(J\dot{\eta}) - \frac{1}{2}\frac{\partial}{\partial \eta}(\dot{\eta}^T J\dot{\eta}) \quad (3.19)$$

$$\tau_b = J\ddot{\eta} + \frac{d}{dt}(J)\dot{\eta} - \frac{1}{2}\frac{\partial}{\partial \eta}(\dot{\eta}^T J\dot{\eta}) \quad (3.20)$$

$$\tau_b = J\ddot{\eta} + \mathfrak{C}(\eta, \dot{\eta})\dot{\eta} \quad (3.21)$$

$$\ddot{\eta} = J^{-1}\big(\tau_b - \mathfrak{C}(\eta, \dot{\eta})\dot{\eta}\big) \quad (3.22)$$

In the above equations, $\mathfrak{C}(\eta, \dot{\eta})$ is called the Coriolis Matrix. The Coriolis term is a mathematical result of the rotational motion of one coordinate system with respect to another. Since we are considering arbitrary three dimensional motion, there are three orthogonal axes of rotation and the resulting matrix is quite complicated. According to the expression for the angular acceleration (Equation (3.22)), the physical units of the Coriolis term must be torque to maintain algebraic continuity. The Coriolis matrix provides a method to relate the rotational coordinates to the translational coordinates [27], [28]. For our problem, it is defined as follows.

$$\mathfrak{C}(\eta, \dot{\eta}) = \begin{pmatrix} \mathfrak{C}_{(11)} & \mathfrak{C}_{(12)} & \mathfrak{C}_{(13)} \\ \mathfrak{C}_{(21)} & \mathfrak{C}_{(22)} & \mathfrak{C}_{(23)} \\ \mathfrak{C}_{(31)} & \mathfrak{C}_{(32)} & \mathfrak{C}_{(33)} \end{pmatrix} \tag{3.23}$$

$\mathfrak{C}_{(11)} = 0$

$\mathfrak{C}_{(12)} = (I_{yy} - I_{zz})(\dot{\theta}C_\phi S_\phi + \dot{\psi}C_\theta S_\phi^2) + (I_{zz} - I_{yy})\dot{\psi}C_\phi^2 C_\theta - I_{xx}\dot{\psi}C_\theta$

$\mathfrak{C}_{(13)} = (I_{zz} - I_{yy})\dot{\psi}C_\phi S_\phi C_\theta^2$

$\mathfrak{C}_{(21)} = (I_{zz} - I_{yy})(\dot{\theta}C_\phi S_\phi + \dot{\psi}S_\phi C_\theta) + (I_{yy} - I_{zz})\dot{\psi}C_\phi^2 C_\theta + I_{xx}\dot{\psi}C_\theta$

$\mathfrak{C}_{(22)} = (I_{zz} - I_{yy})\dot{\phi}C_\phi S_\phi$

$\mathfrak{C}_{(23)} = -I_{xx}\dot{\psi}S_\theta C_\theta + I_{yy}\dot{\psi}S_\phi^2 S_\theta C_\theta + I_{zz}\dot{\psi}C_\phi^2 S_\theta C_\theta$

$\mathfrak{C}_{(31)} = (I_{yy} - I_{zz})\dot{\psi}C_\theta^2 S_\phi C_\phi - I_{xx}\dot{\theta}C_\theta$

$\mathfrak{C}_{(32)} = (I_{zz} - I_{yy})(\dot{\theta}C_\phi S_\phi S_\theta + \dot{\phi}S_\phi^2 C_\theta) + (I_{yy} - I_{zz})\dot{\phi}C_\phi^2 C_\theta + I_{xx}\dot{\psi}S_\theta C_\theta - I_{yy}\dot{\psi}S_\phi^2 S_\theta C_\theta - I_{zz}\dot{\psi}C_\phi^2 S_\theta C_\theta$

$\mathfrak{C}_{(33)} = (I_{yy} - I_{zz})\dot{\phi}C_\phi S_\phi C_\theta^2 - I_{yy}\dot{\theta}S_\phi^2 C_\theta S_\theta - I_{zz}\dot{\theta}C_\phi^2 C_\theta S_\theta + I_{xx}\dot{\theta}C_\theta S_\theta$

It is important to keep in mind that the Coriolis term does not represent a real force or torque acting on the system. It is only an artifact which is needed to account for the relative rotation of one coordinate frame with respect to another.

3.5   A Complete Model

A complete mathematical representation of the quad-rotor is as follows:

$$
\begin{pmatrix} \ddot{x} \\ \ddot{y} \\ \ddot{z} \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ g \end{pmatrix} + \frac{\mathcal{T}}{m} \begin{pmatrix} C_\psi S_\theta C_\phi + S_\psi S_\phi \\ S_\psi S_\theta C_\phi - C_\psi S_\phi \\ C_\theta C_\phi \end{pmatrix} \tag{3.24}
$$

$$
\begin{pmatrix} \ddot{\phi} \\ \ddot{\theta} \\ \ddot{\psi} \end{pmatrix} = J^{-1} \left[\begin{pmatrix} ls(-\omega_2^2 + \omega_4^2) \\ ls(-\omega_1^2 + \omega_3^2) \\ \sum_{i=1}^{4} b\omega_i^2 \end{pmatrix} - \mathfrak{C} \begin{pmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\psi} \end{pmatrix} \right] \tag{3.25}
$$

Even in this form there are many important aspects of quad-rotor flight dynamics and environmental variables which are omitted. The general problem of designing a system that is able to understand and adapt to varying goals and circumstances is a large one.

Despite the apparent shortcomings of this model, it is very useful as a core component to this thesis. Appendix A shows the python implementation of the system model. Although the assumed mathematical environment is somewhat of a departure from reality, it allows for a firm theoretical basis which validates the development of the control system and optimization scheme.

Chapter 4

Classical Optimal Control Formulation

In this chapter, we will define a two point boundary value problem and explore the classical optimal control formulation. The solution to this boundary value problem gives the control inputs to the system which produce optimal behavior. The set of mathematical conditions which define the boundary value problem are termed 'optimality conditions'. The content of this chapter is left generalized. It can be applied to any second order dynamic system. In chapter 5, the optimality conditions are applied to the dynamical model of the quad-rotor which was derived in Chapter 3.

Note the names 'Lagrangian' and 'Hamiltonian' are used here in an optimal control context. The multiple use of these names in reference to specific types of expressions is an artifact of the pervasive work of Lagrange and Hamilton. Both optimal control theory and Hamiltonian / Lagrangian mechanics are rooted in the calculus of variations. The dynamic model of the quad-rotor and the optimal

control formulation described below are both results from a form of functional optimization. We rely on a contextual and conceptual separation in our understanding. Specifically, the 'Lagrangian', which is formed as the difference of the expressions for kinetic and potential energies, is unique to the context of classical mechanics. Likewise, the 'Lagrangian' in the optimal control context is a term in the integrand of our objective function which represents a vector of performance metrics. The 'Hamiltonian' from classical mechanics is formed as the sum of kinetic and potential energies. This is different than the Hamiltonian used here in the optimal control context.

4.1   Derivation of the Objective Function

In section 2.3 of Bryson and Ho [17], the conditions for the optimal control of a continuous time system are derived. There, it is presumed that the system is presented as a set of first order differential equations. For a quad-rotor, it is more convenient to leave the system equations as a set of second order differential equations. The motivation for this is as follows. With the finite difference method for solving two point boundary value problems, there are a set of simultaneous algebraic equations that are defined for each point in time for which a solution is desired. If we were to express the system of differential equations that govern the dynamics of a quad-rotor in a first order form, the number of algebraic equations defined by the finite difference method would be effectively doubled. Here, we derive the analogous conditions for optimality for a second order system.

4.1.1 Lagrangian

The real power of the optimal control formulation is in the use of the Lagrangian function (also called the performance index) $L(q(t), u(t), t)$ and the co-state $\lambda(t)$. The objective function in our context is an extension of classical constrained optimization to systems which evolve in time. In our case, the Lagrangian is the function which we wish to minimize, the system model (as derived in chapter 3) F plays the role of the constraint relationship, and the function $\lambda(t)$ plays the same role here as a lagrange muliplier in the context of static optimization. Since our optimization procedure accounts for the time variation of the performance index and the system equations, $\lambda(t)$ is likewise a function of time. The variable $\lambda(t)$ is allowed to vary in time along with the state of the system and is therefore given the name "co-state". In other words it allows for an expression of the criteria for optimallity at every instance in time.

The Lagrangian for our problem is defined as

$$L[q(t), u(t), t] = u^T I u, \tag{4.1}$$

where u is the control input vector and I is the 4×4 identity.

4.1.2 Objective Function

The dynamic equations of motion are appended to the performance index as follows. By definition:

$$F = \ddot{q} \tag{4.2}$$

$$0 = F - \ddot{q} \tag{4.3}$$

Note that F is the vector function representation of the quad-rotor system equations. The components' physical units are linear and angular acceleration, not force. The variable q is a vector of generalized spatial coordinates. F is generally a function of the generalized coordinates, the input to the system $u(t)$, and time. The full objective function can be written as

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \int_{t_0}^{t_f} \left[L(q(t), u(t), t) + \lambda^T \left(F(q(t), u(t), t) - \ddot{q} \right) \right] dt. \quad (4.4)$$

The function $\Psi(q(t_f), t_f)$ represents the effect that the final state has on the objective function. In general, $\Psi(q(t_f), t_f)$ is a vector quantity and is scaled by the vector ν.

For the optimal control formulation, the Hamiltonian is defined as a measure of optimallity as a function of time. In the next section we'll see that the full objective function invloves a time-integration of the Hamiltonian. It is written as:

$$H = L(q(t), u(t), t) + \lambda^T \left(F(q(t), u(t), t) - \ddot{q} \right). \quad (4.5)$$

The Hamiltonian allows for a concise expression of the Lagrangian, the co-state function λ and the constraint equations.

The objective function is simplified as:

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \int_{t_0}^{t_f} H(q(t), u(t), t) - \lambda^T \ddot{q} dt \quad (4.6)$$

The second term in the integrand is integrated by parts.

$$\mathcal{J} = \nu\Psi(q(t_f), t_f) + \int_{t_0}^{t_f} H(q(t), u(t), t) \ dt - \int_{t_0}^{t_f} \lambda^T \ddot{q} \ dt \quad (4.7)$$

In general: $\int u \, dv = (uv)|_{t_0}^{t_f} - \int v \, du$. Using this, the second term is expanded.

$$\int_{t_0}^{t_f} \lambda^T \ddot{q} \, dt = (\lambda^T \dot{q})|_{t_0}^{t_f} - \int_{t_0}^{t_f} \dot{\lambda}^T \dot{q} \, dt \tag{4.8}$$

The result is:

$$\mathcal{J} = \nu \Psi(q(t_f), t_f) + \int_{t_0}^{t_f} H(q(t), u(t), t) \, dt - (\lambda^T \dot{q})|_{t_0}^{t_f} + \int_{t_0}^{t_f} \dot{\lambda}^T \dot{q} \, dt \tag{4.9}$$

The last term is integrated by parts again.

$$\mathcal{J} = \nu \Psi(q(t_f), t_f) - (\lambda^T \dot{q})|_{t_0}^{t_f} + (\dot{\lambda}^T q)|_{t_0}^{t_f} + \int_{t_0}^{t_f} H(q(t), u(t), t) - \ddot{\lambda}^T q \, dt \tag{4.10}$$

$$\mathcal{J} = \nu \Psi(q(t_f), t_f) + \left[\dot{\lambda}^T q - \lambda^T \dot{q}\right]_{t_0}^{t_f} + \int_{t_0}^{t_f} \left(H(q(t), u(t), t) - \ddot{\lambda}^T q\right) \, dt \tag{4.11}$$

This result is the objective function which we wish to minimize.

4.2 Derivation of the Optimality Conditions

To find the mathematical conditions necessary for a minimum in $\mathcal{J}$, the first variation is computed and set equal to 0. In this context, the variation of a function is essentially the same as the total derivative. Further reading on this is found in [11] and [12].

The first variation in $\mathcal{J}$ is given by

$$\delta \mathcal{J} = \frac{\partial \mathcal{J}}{\partial q} \delta q + \frac{\partial \mathcal{J}}{\partial \dot{q}} \delta \dot{q} + \frac{\partial \mathcal{J}}{\partial u} \delta u. \tag{4.12}$$

$$\delta \mathcal{J} = \nu^T \frac{\partial \Psi}{\partial q} \delta q|_{t_f} + \nu^T \frac{\partial \Psi}{\partial \dot{q}} \delta \dot{q}|_{t_f} + \left[\dot{\lambda}^T \delta q - \lambda^T \delta \dot{q} \right]_{t_0}^{t_f}$$
$$+ \int_{t_0}^{t_f} \left[\frac{\partial H}{\partial q} \delta q + \frac{\partial H}{\partial \dot{q}} \delta \dot{q} + \frac{\partial H}{\partial u} \delta u - \ddot{\lambda}^T \delta q \right] dt \tag{4.13}$$

$$\delta \mathcal{J} = (\nu^T \frac{\partial \Psi}{\partial q} + \dot{\lambda}^T) \delta q|_{t_f} + (\nu^T \frac{\partial \Psi}{\partial \dot{q}} - \lambda^T) \delta \dot{q}|_{t_f} + [\lambda^T \delta \dot{q} - \dot{\lambda}^T \delta q]_{t_0}$$
$$+ \int_{t_0}^{t_f} \left[\left(\frac{\partial H}{\partial q} - \ddot{\lambda}^T \right) \delta q + \frac{\partial H}{\partial \dot{q}} \delta \dot{q} + \frac{\partial h}{\partial u} \delta u \right] dt. \tag{4.14}$$

The optimality conditions are found by setting $\delta \mathcal{J} = 0$ and asserting that each of the added terms must therefore go to 0. The results are summarized as follows.

The Co-State equations are

$$\frac{\partial H}{\partial q} = \ddot{\lambda} \tag{4.15}$$

$$\ddot{\lambda} = \left(\frac{\partial L}{\partial q} \right)^T + \left(\frac{\partial F}{\partial q} \right)^T \lambda. \tag{4.16}$$

The Stationarity Conditions are

$$\frac{\partial H}{\partial u} = 0 \tag{4.17}$$

$$\frac{\partial L}{\partial u} + \left(\frac{\partial F}{\partial u} \right)^T \lambda = 0 \tag{4.18}$$

Secondary algebraic Co state condition

$$\frac{\partial H}{\partial \dot{q}} = 0 \tag{4.19}$$

$$\left(\frac{\partial F}{\partial \dot{q}} \right)^T \lambda = 0 \tag{4.20}$$

22

Terminal Boundary conditions:

$$\nu^T \frac{\partial \Psi}{\partial q}\big|_{t_f} + \dot{\lambda}(t_f)^T = 0 \tag{4.21}$$

$$\nu^T \frac{\partial \Psi}{\partial \dot{q}}\big|_{t_f} - \lambda(t_f)^T = 0 \tag{4.22}$$

Initial Co state conditions

$$(\lambda^T \delta \dot{q} - \dot{\lambda}^T \delta q)\big|_{t_0} = 0 \tag{4.23}$$

$$\lambda(t_0) = 0 \tag{4.24}$$

$$\dot{\lambda}(t_0) = 0 \tag{4.25}$$

Together, the state equations, co-state equations, stationarity equations, secondary algebraic constraints, and boundary conditions form a complete two-point boundary value problem.

4.3 Solving the Boundary Value Problem

Boundary value problems are very common in many science and engineering fields. They can become quite complicated and require significant computation to reach a solution. Two general ways to solve two-point boundary value problems are described next. These are the shooting method and the finite difference method [22],[29]. Both have limitations.

4.3.1 Shooting Method

The shooting method is a relatively straightforward combination of a time marching quadrature method (Runga-Kutta or the like) to solve a set of differential equations and an error minimization technique. The shooting method works by iteratively solving the set of differential equations as an initial value problem and then measuring the error in the final state of the system compared to the desired final state. The shooting method is subject to the stability of the differential equations in question. If the time marching algorithm does not converge, the method will not work. Unfortunately, the boundary value problem for the quad-rotor that is formulated in the next chapter falls into this category. The quad-rotor system model and the coupled optimality conditions are simply too unstable to be solved with the shooting method.

- Advantages : straightforward iterative quadrature method and error minimization,

- Disadvantages : does not always converge

4.3.2 Finite Difference Method

The finite difference method poses another possibility [29]. It involves creating a system of algebraic equations to be solved at each instance in time where the solution is desired. For a simulation like ours, this means at least hundreds if not thousands of time steps. The derivatives in the differential equations are expressed as finite differences involving variables at adjacent time steps. The values of each state and co-state variable are defined as unknowns at each time step. This creates a system of equations involving several thousand unknowns that need to be solved

for. For a linear system this is not so bad because the problem is reduced to the inversion of a sparse matrix. For this, there are efficient numerical algorithms that can be used. Since the quad-rotor boundary value problem is nonlinear, it must be solved with a gradient descent technique or something similar.

- Advantages : turns the BVP into a system of algebraic equations, easy to solve for linear systems,

- Disadvantages : hard to solve for nonlinear systems, does not always converge

In the next chapter we derive the set of differential equations which form the boundary value problem defined by our goal of optimizing the energy usage of a quad-rotor.

Chapter 5

Quad-rotor Boundary Value Problem

In this chapter we use the expressions for the dynamic model of the quad-rotor (equations 3.24 and 3.25) and the optimal control formulation (equations 4.15 through 4.25) to derive the optimality conditions for our specific problem.

Recall from chapter 4 that each of the optimality conditions is a mathematical result of setting the first variation of the objective function equal to zero. To maintain algebraic continuity, each additive term must then be zero. Using this logic, each of the optimality conditions is obtained. Given the general form of the optimality conditions, we can introduce the quad-rotor dynamic model. The resulting expressions can be simplified to arrive at specific equations which form our quad-rotor boundary value problem. The optimal flight path and the optimal control input as a function of time form the solution to this boundary value problem.

5.1 Co-State Equations

The co-state equations are expressed as follows where F is our set of system equations and L is the Lagrangian defined in our performance index. Since the Lagrangian does not depend on the state, the co-state differential equation simplifies. Recall that the Lagrangian for our optimization is $L[q(t), u(t), t] = u^T I u$.

$$\ddot{\lambda} = -\left(\frac{\partial F}{\partial q}\right)^T \lambda - \left(\frac{\partial L}{\partial q}\right)^T \tag{5.1}$$

$$\ddot{\lambda} = -\left(\frac{\partial F}{\partial q}\right)^T \lambda \tag{5.2}$$

The state transition matrix, $\left(\frac{\partial F}{\partial q}\right)$ is tremendous, but there are some simplifications to be made as some of the partial derivatives are zero.

$$\frac{\partial F}{\partial q} = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial x} & \frac{\partial F_{(1)}}{\partial y} & \frac{\partial F_{(1)}}{\partial z} & \frac{\partial F_{(1)}}{\partial \phi} & \frac{\partial F_{(1)}}{\partial \theta} & \frac{\partial F_{(1)}}{\partial \psi} \\ \frac{\partial F_{(2)}}{\partial x} & \frac{\partial F_{(2)}}{\partial y} & \frac{\partial F_{(2)}}{\partial z} & \frac{\partial F_{(2)}}{\partial \phi} & \frac{\partial F_{(2)}}{\partial \theta} & \frac{\partial F_{(2)}}{\partial \psi} \\ . & & & & & \\ . & & & & & \\ . & & & & & \\ \frac{\partial F_{(6)}}{\partial x} & \frac{\partial F_{(6)}}{\partial y} & \frac{\partial F_{(6)}}{\partial z} & \frac{\partial F_{(6)}}{\partial \phi} & \frac{\partial F_{(6)}}{\partial \theta} & \frac{\partial F_{(6)}}{\partial \psi} \end{pmatrix} \tag{5.3}$$

$$\frac{\partial F}{\partial q} = \begin{pmatrix} 0 & 0 & 0 & \frac{\partial F_{(1)}}{\partial \phi} & \frac{\partial F_{(1)}}{\partial \theta} & \frac{\partial F_{(1)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(2)}}{\partial \phi} & \frac{\partial F_{(2)}}{\partial \theta} & \frac{\partial F_{(2)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(3)}}{\partial \phi} & \frac{\partial F_{(3)}}{\partial \theta} & 0 \\ 0 & 0 & 0 & \frac{\partial F_{(4)}}{\partial \phi} & \frac{\partial F_{(4)}}{\partial \theta} & \frac{\partial F_{(4)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(5)}}{\partial \phi} & \frac{\partial F_{(5)}}{\partial \theta} & \frac{\partial F_{(5)}}{\partial \psi} \\ 0 & 0 & 0 & \frac{\partial F_{(6)}}{\partial \phi} & \frac{\partial F_{(6)}}{\partial \theta} & \frac{\partial F_{(6)}}{\partial \psi} \end{pmatrix} \tag{5.4}$$

Each of the elements must be computed numerically. An analytical representation of all the partial derivatives in $\left(\frac{\partial F}{\partial q}\right)$ is possible but the task of computing them all would be too time consuming. For our simulations, a simple backward finite difference is much more appropriate:

$$\frac{\partial F_i}{\partial q_j} \approx \frac{F_i(q_j + \alpha) - F_i(q_j)}{\alpha} \qquad (5.5)$$

In the above equation, i the index for the state equations, j is the index for the state variables and α is the discrete step size. The simplified result is:

$$\ddot{\lambda} = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial \phi} & \frac{\partial F_{(1)}}{\partial \theta} & \frac{\partial F_{(1)}}{\partial \psi} \\ \frac{\partial F_{(2)}}{\partial \phi} & \frac{\partial F_{(2)}}{\partial \theta} & \frac{\partial F_{(2)}}{\partial \psi} \\ \frac{\partial F_{(3)}}{\partial \phi} & \frac{\partial F_{(3)}}{\partial \theta} & 0 \\ \frac{\partial F_{(4)}}{\partial \phi} & \frac{\partial F_{(4)}}{\partial \theta} & \frac{\partial F_{(4)}}{\partial \psi} \\ \frac{\partial F_{(5)}}{\partial \phi} & \frac{\partial F_{(5)}}{\partial \theta} & \frac{\partial F_{(5)}}{\partial \psi} \\ \frac{\partial F_{(6)}}{\partial \phi} & \frac{\partial F_{(6)}}{\partial \theta} & \frac{\partial F_{(6)}}{\partial \psi} \end{pmatrix} \begin{pmatrix} \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \qquad (5.6)$$

.

5.2 Secondary Algebraic Co-State Equations

The secondary algebraic co-state equations are a result of setting the variation of the objective function $\mathcal{J}$ equal to zero. They are unique to the derivation in Chapter 4, which involves a second-order rather than first-order representation of the system equations. Recall that H is the Hamiltonian, q is the state vector, λ is the co-state vector, L is the performance index (also called the Lagrangian),

and F is the dynamic model derived in Chapter 3.

$$\frac{\partial H}{\partial \dot{q}} = 0 \tag{5.7}$$

$$0 = \left(\frac{\partial F}{\partial \dot{q}}\right)^T \lambda + \left(\frac{\partial L}{\partial \dot{q}}\right)^T \tag{5.8}$$

$$0 = \left(\frac{\partial F}{\partial \dot{q}}\right)^T \lambda \tag{5.9}$$

$$0 = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial \dot{x}} & \frac{\partial F_{(1)}}{\partial \dot{y}} & \frac{\partial F_{(1)}}{\partial \dot{z}} & \frac{\partial F_{(1)}}{\partial \dot{\phi}} & \frac{\partial F_{(1)}}{\partial \dot{\theta}} & \frac{\partial F_{(1)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(2)}}{\partial \dot{x}} & \frac{\partial F_{(2)}}{\partial \dot{y}} & \frac{\partial F_{(2)}}{\partial \dot{z}} & \frac{\partial F_{(2)}}{\partial \dot{\phi}} & \frac{\partial F_{(2)}}{\partial \dot{\theta}} & \frac{\partial F_{(2)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(3)}}{\partial \dot{x}} & \frac{\partial F_{(3)}}{\partial \dot{y}} & \frac{\partial F_{(3)}}{\partial \dot{z}} & \frac{\partial F_{(3)}}{\partial \dot{\phi}} & \frac{\partial F_{(3)}}{\partial \dot{\theta}} & \frac{\partial F_{(3)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(4)}}{\partial \dot{x}} & \frac{\partial F_{(4)}}{\partial \dot{y}} & \frac{\partial F_{(4)}}{\partial \dot{z}} & \frac{\partial F_{(4)}}{\partial \dot{\phi}} & \frac{\partial F_{(4)}}{\partial \dot{\theta}} & \frac{\partial F_{(4)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(5)}}{\partial \dot{x}} & \frac{\partial F_{(5)}}{\partial \dot{y}} & \frac{\partial F_{(5)}}{\partial \dot{z}} & \frac{\partial F_{(5)}}{\partial \dot{\phi}} & \frac{\partial F_{(5)}}{\partial \dot{\theta}} & \frac{\partial F_{(5)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(6)}}{\partial \dot{x}} & \frac{\partial F_{(6)}}{\partial \dot{y}} & \frac{\partial F_{(6)}}{\partial \dot{z}} & \frac{\partial F_{(6)}}{\partial \dot{\phi}} & \frac{\partial F_{(6)}}{\partial \dot{\theta}} & \frac{\partial F_{(6)}}{\partial \dot{\psi}} \end{pmatrix}^T \begin{pmatrix} \lambda_1 \\ \lambda_2 \\ \lambda_3 \\ \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \tag{5.10}$$

Again this matrix can simplify considerably because the state equations don't depend on all of the state variable time derivatives.

$$0 = \begin{pmatrix} 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & \frac{\partial F_{(4)}}{\partial \dot{\phi}} & \frac{\partial F_{(4)}}{\partial \dot{\theta}} & \frac{\partial F_{(4)}}{\partial \dot{\psi}} \\ 0 & 0 & 0 & \frac{\partial F_{(5)}}{\partial \dot{\phi}} & \frac{\partial F_{(5)}}{\partial \dot{\theta}} & \frac{\partial F_{(5)}}{\partial \dot{\psi}} \\ 0 & 0 & 0 & \frac{\partial F_{(6)}}{\partial \dot{\phi}} & \frac{\partial F_{(6)}}{\partial \dot{\theta}} & \frac{\partial F_{(6)}}{\partial \dot{\psi}} \end{pmatrix}^T \begin{pmatrix} \lambda_1 \\ \lambda_2 \\ \lambda_3 \\ \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \tag{5.11}$$

$$0 = \begin{pmatrix} \frac{\partial F_{(4)}}{\partial \dot{\phi}} & \frac{\partial F_{(4)}}{\partial \dot{\theta}} & \frac{\partial F_{(4)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(5)}}{\partial \dot{\phi}} & \frac{\partial F_{(5)}}{\partial \dot{\theta}} & \frac{\partial F_{(5)}}{\partial \dot{\psi}} \\ \frac{\partial F_{(6)}}{\partial \dot{\phi}} & \frac{\partial F_{(6)}}{\partial \dot{\theta}} & \frac{\partial F_{(6)}}{\partial \dot{\psi}} \end{pmatrix}^T \begin{pmatrix} \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} \tag{5.12}$$

As with the other optimality conditions, the partial derivatives in this matrix must be computed numerically as follows:

$$\frac{\partial F_i}{\partial \dot{q}_j} \approx \frac{F_i(\dot{q}_j + \alpha) - F_i(\dot{q}_j)}{\alpha} \tag{5.13}$$

5.3   Stationarity Conditions

The stationarity conditions express the relationship between the derivatives of the system equation with respect to the input u, the co-state variable $\lambda(t)$, and the derivative of the Lagrangian with respect to the input.

$$\left(\frac{\partial H}{\partial u}\right)^T = \left(\frac{\partial F}{\partial u}\right)^T \lambda + \left(\frac{\partial L}{\partial u}\right)^T = 0 \tag{5.14}$$

$$\frac{\partial F}{\partial q} = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial u_1} & \frac{\partial F_{(1)}}{\partial u_2} & \frac{\partial F_{(1)}}{\partial u_3} & \frac{\partial F_{(1)}}{\partial u_4} \\ \frac{\partial F_{(2)}}{\partial u_1} & \frac{\partial F_{(2)}}{\partial u_2} & \frac{\partial F_{(2)}}{\partial u_3} & \frac{\partial F_{(2)}}{\partial u_4} \\ \frac{\partial F_{(3)}}{\partial u_1} & \frac{\partial F_{(3)}}{\partial u_2} & \frac{\partial F_{(3)}}{\partial u_3} & \frac{\partial F_{(3)}}{\partial u_4} \\ . & & & \\ . & & & \\ . & & & \\ \frac{\partial F_{(6)}}{\partial u_1} & \frac{\partial F_{(6)}}{\partial u_2} & \frac{\partial F_{(6)}}{\partial u_3} & \frac{\partial F_{(6)}}{\partial u_4} \end{pmatrix} \tag{5.15}$$

$$\frac{\partial L}{\partial u} = 2(u_1, u_2, u_3, u_4) \tag{5.16}$$

$$0 = \begin{pmatrix} \frac{\partial F_{(1)}}{\partial u_1} & \frac{\partial F_{(2)}}{\partial u_1} & \frac{\partial F_{(3)}}{\partial u_1} & \frac{\partial F_{(4)}}{\partial u_1} & \frac{\partial F_{(5)}}{\partial u_1} & \frac{\partial F_{(6)}}{\partial u_1} \\ \frac{\partial F_{(1)}}{\partial u_2} & \frac{\partial F_{(2)}}{\partial u_2} & \frac{\partial F_{(3)}}{\partial u_2} & \frac{\partial F_{(4)}}{\partial u_2} & \frac{\partial F_{(5)}}{\partial u_2} & \frac{\partial F_{(6)}}{\partial u_2} \\ \frac{\partial F_{(1)}}{\partial u_3} & \frac{\partial F_{(2)}}{\partial u_3} & \frac{\partial F_{(3)}}{\partial u_3} & \frac{\partial F_{(4)}}{\partial u_3} & \frac{\partial F_{(5)}}{\partial u_3} & \frac{\partial F_{(6)}}{\partial u_3} \\ \frac{\partial F_{(1)}}{\partial u_4} & \frac{\partial F_{(2)}}{\partial u_4} & \frac{\partial F_{(3)}}{\partial u_4} & \frac{\partial F_{(4)}}{\partial u_4} & \frac{\partial F_{(5)}}{\partial u_4} & \frac{\partial F_{(6)}}{\partial u_4} \end{pmatrix} \begin{pmatrix} \lambda_1 \\ \lambda_2 \\ \lambda_3 \\ \lambda_4 \\ \lambda_5 \\ \lambda_6 \end{pmatrix} + 2 \begin{pmatrix} u_1 \\ u_2 \\ u_3 \\ u_4 \end{pmatrix} \quad (5.17)$$

Again, the partials are computed with a finite difference.

$$\frac{\partial F_i}{\partial u_j} \approx \frac{F_i(u_j + \alpha) - F_i(u_j)}{\alpha} \quad (5.18)$$

5.4   Discretization

In a real implementation the measurements and subsequent state estimates, which are the input to the control algorithm, are made available at discrete time intervals. In order to code a simulation and evaluate the behavior of this system of equations, it is more convenient if these equations are represented in a discrete-time form. First order derivatives are approximated as a first backward finite difference. By using backward finite differences, the causality of the expressions is preserved.

$$\dot{x} \approx \frac{x[k] - x[k-1]}{h} \quad (5.19)$$

The second-order time derivatives are approximated as second-order backward finite differences.

$$\ddot{x} \approx \frac{x[k] - 2x[k-1] + x[k-2]}{h^2} \quad (5.20)$$

31

The continuous system equations are given as follows.

$$
\begin{pmatrix} \ddot{x} \\ \ddot{y} \\ \ddot{z} \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ g \end{pmatrix} + \frac{\mathcal{T}}{m} \begin{pmatrix} C_\psi S_\theta C_\phi + S_\psi S_\phi \\ S_\psi S_\theta C_\phi - C_\psi S_\phi \\ C_\theta C_\phi \end{pmatrix} \tag{5.21}
$$

$$
\begin{pmatrix} \ddot{\phi} \\ \ddot{\theta} \\ \ddot{\psi} \end{pmatrix} = J^{-1} \left[\begin{pmatrix} ls(-\omega_2^2 + \omega_4^2) \\ ls(-\omega_1^2 + \omega_3^2) \\ \sum_{i=1}^{4} b\omega_i^2 \end{pmatrix} - \mathfrak{C} \begin{pmatrix} \dot{\phi} \\ \dot{\theta} \\ \dot{\psi} \end{pmatrix} \right] \tag{5.22}
$$

The discrete-time system equations are

$$
\begin{pmatrix} \frac{x[k]-2x[k-1]+x[k-2]}{h^2} \\ \frac{y[k]-2y[k-1]+y[k-2]}{h^2} \\ \frac{z[k]-2z[k-1]+z[k-2]}{h^2} \end{pmatrix} = \begin{pmatrix} 0 \\ 0 \\ g \end{pmatrix} + \frac{\mathcal{T}[k]}{m} \begin{pmatrix} C_{\psi[k]} S_{\theta[k]} C_{\phi[k]} + S_{\psi[k]} S_{\phi[k]} \\ S_{\psi[k]} S_{\theta[k]} C_{\phi[k]} - C_{\psi[k]} S_{\phi[k]} \\ C_{\theta[k]} C_{\phi[k]} \end{pmatrix} \tag{5.23}
$$

$$
\begin{pmatrix} \frac{\phi[k]-2\phi[k-1]+\phi[k-2]}{h^2} \\ \frac{\theta[k]-2\theta[k-1]+\theta[k-2]}{h^2} \\ \frac{\psi[k]-2\psi[k-1]+\psi[k-2]}{h^2} \end{pmatrix} = J^{-1}[k] \left[\begin{pmatrix} ls(-\omega_2[k]^2 + \omega_4[k]^2) \\ ls(-\omega_1[k]^2 + \omega_3[k]^2) \\ \sum_{i=1}^{4} b\omega_i[k]^2 \end{pmatrix} - \mathfrak{C}[k] \begin{pmatrix} \frac{\phi[k]-\phi[k-1]}{h} \\ \frac{\theta[k]-\theta[k-1]}{h} \\ \frac{\psi[k]-\psi[k-1]}{h} \end{pmatrix} \right]
$$
$$
\tag{5.24}
$$

The reason for computing all the partial derivatives numerically is now apparent.

To compute the partial derivatives analytically, one would have to deal with the products between the rows of the Coriolis matrix (Equation 3.23) and the columns of the inverse of the Jacobian matrix (Equation 3.12). This sort of computation is the very reason computers were invented in the first place.

5.5   A Finite Difference Solution to the Quad-Rotor Boundary Value Problem

The finite difference method for solving boundary value problems was introduced at the end of Chapter 4. This method reduces our optimal control problem to solving a system of nonlinear algebraic equations. This is a reduction in theoretical complexity but a dramatic increase in computational complexity.

The script 'finiteDiffSolution.py' (Appendix F) implements the finite difference method in an attempt to solve the quad-rotor boundary value problem. Recall that the computational problem is posed as solving a system of nonlinear algebraic equations. This system of equations is composed of the state equations, the co-state equations, the stationarity conditions, the secondary algebraic conditions, and the boundary conditions. Each of these expressions is possibly a function of the state variables, the co-state variables and the control input. Solving this system becomes a significant task since the state, co-state, and control variables become the unknowns for each instance in time for which a solution to the boundary value problem is desired! In order to sufficiently represent the dynamics of the quad-rotor, on the order of thousands of time steps are necessary. To solve this nonlinear system, a straightforward steepest descent technique was used.

Algorithm 5.1 : Steepest Descent Algorithm

1. An objective function is formed out of the sum of the squared residuals of each equation in the system.

2. The gradient is computed as the list of partial derivatives of the objective function with respect to every unknown (every variable defined at each time instance). These partials are approximated as finite differences.

3. The vector of unknowns is 'moved' in the direction of the negative of the gradient.

4. The new value of the objective function as well as the gradient are evaluated with the new vector of unknowns.

5. The state of the minimization process is checked against appropriate convergence criteria.

Conceptually, this algorithm is relatively straightforward but it poses a significant computational challenge. With ten defined time steps, the algorithm ran for several hours before terminating. Additionally, with only ten time steps defined, the dynamics of the system over a period of several seconds of flight are not well represented. In a physical implementation, the motor speeds need to be updated at a rate on the order of 50 Hz at a minimum. Given these constraints, there would be no realistic way to implement the algorithm in this form on an embedded system, which was loosely included as one of our research objectives. The Python Implementation of the finite difference method is shown Appendix F.

Instead, in the next chapter we turn to different methods of control and optimization. Control of the system will be achieved with PID expressions. The optimization problem will be approached by appropriately manipulating the gains of the PID control laws in order to change the system behavior.

34

Chapter 6

PID/PD Control

Among the many methods available for mathematical control of the quad-rotor, a well-tuned PID controller offers both relative robustness and a simple mathematical representation. In this chapter we derive and test the PID control scheme for attitude and 3D position control of a quad-rotor.

6.1   Deriving the Control Expressions

The control of the quad-rotor requires three independent PID controllers for the x, y, and z directions. In addition, the attitude stability of the aircraft is accomplished by three independent PD controllers for each of the Euler angles (ϕ, θ, ψ) . It is assumed for the purpose of simulation that the input to the control expressions includes accurate knowledge of the system state. In other words, it is assumed that the process noise and the measurement noise are zero. Given the natural complexity of the system, inclusion of stochastic processes into the model is left for further work. As in [9] and [10], the control algorithm proceeds as follows.

Algorithm 6.1 : PID Control Algorithm

1. The position control expressions give the 'commanded' linear accelerations that are required to drive the system to the desired state.

2. Given the commanded linear accelerations, the necessary total thrust, pitch, and roll are determined.

3. The commanded torques about the three axes of the quad-rotor are given by PD controllers using the commanded yaw, pitch, and roll as angular set points.

4. Given the commanded total thrust and the commanded torques, the motor speeds can be determined.

5. Once the motor speeds are known, the system model can be used to obtain the updated state of the system.

6. Go to step 1.

Our goal in the following derivation is to arrive at expressions for the motor speeds that are required to drive the system to the desired state. The discrete-time PID control expressions are formulated using these vectors.

$$P_c = \begin{pmatrix} x_c \\ y_c \\ z_c \end{pmatrix} = desired \ (commanded) \ set \ point \ location$$

$$P = \begin{pmatrix} x \\ y \\ z \end{pmatrix} = actual \ position \ at \ time \ step \ k$$

The vector of commanded accelerations is given by $\ddot{P}_c$:

$$\ddot{P}_c = K_p(P_c - P) + K_i \sum_k (P_c - P) + K_d(\dot{P}_c - \dot{P}), \tag{6.1}$$

where

$$K_p = \begin{bmatrix} k_{px} \\ k_{py} \\ k_{pz} \end{bmatrix}, K_i = \begin{bmatrix} k_{ix} \\ k_{iy} \\ k_{iz} \end{bmatrix}, K_d = \begin{bmatrix} k_{dx} \\ k_{dy} \\ k_{dz} \end{bmatrix}. \tag{6.2}$$

Recall equation 3.16:

$$f = RT_B = m\ddot{\xi} - G. \tag{6.3}$$

This can be rearranged to give:

$$\ddot{P}_c = -ge_{inz} + \left(\frac{1}{m}\right)(Te_{qrz})R. \tag{6.4}$$

where, $\qquad e_{inz} = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix}$ (in the inertial reference frame)

$$e_{qrz} = \begin{pmatrix} 0 \\ 0 \\ 1 \end{pmatrix} \text{ (in the quad-rotor reference frame)}$$

The angles ϕ and θ, and the total thrust T can be determined algebraically, assuming we know $\ddot{P}_c$ and ψ.

$$R^T \left(\ddot{P}_c + g e_{inz} \right) = \left(\frac{1}{m} \right) (T e_{qrz}) \tag{6.5}$$

$$\begin{pmatrix} C_\psi C_\theta & S_\psi C_\theta & -S_\theta \\ C_\psi S_\theta S_\phi - S_\psi C_\phi & S_\psi S_\theta S_\phi + C_\psi C_\phi & C_\theta S_\phi \\ C_\psi S_\theta C_\phi + S_\psi S_\phi & S_\psi S_\theta C_\phi - C_\psi S_\phi & C_\theta C_\phi \end{pmatrix} \begin{pmatrix} a_x \\ a_y \\ a_z + g \end{pmatrix} = \frac{1}{m} \begin{pmatrix} 0 \\ 0 \\ T \end{pmatrix} \tag{6.6}$$

The matrix equation above is then written as three independent scalar expressions.

$$a_x C_\psi C_\theta + a_y S_\psi C_\theta - S_\theta (a_z + g) = 0 \tag{6.7}$$

$$a_x (C_\psi S_\theta S_\phi - S_\psi C_\phi) + a_y (S_\psi S_\theta S_\phi + C_\psi C_\phi) + (a_z + g) C_\theta S_\phi = 0 \tag{6.8}$$

$$a_x (C_\psi S_\theta C_\phi + S_\psi S_\phi) + a_y (S_\psi S_\theta C_\phi - C_\psi S_\phi) + (a_z + g) C_\theta C_\phi = \left(\frac{T}{m} \right) \tag{6.9}$$

Next, we divide Equation (6.7) by C_θ and solve for θ as θ_c.

$$a_x C_\psi + a_y S_\psi + (a_z + g)(-\tan(\theta)) = 0 \tag{6.10}$$

$$\theta_c = \arctan \left(\frac{a_x C_\psi + a_y S_\psi}{a_z + g} \right) \tag{6.11}$$

Next, Equation (6.8) $\times S_\phi$ = Equation (6.9) $\times C_\phi$. The result is

$$\phi = \arcsin \left(\frac{a_x S_\psi - a_y C_\psi}{T/m} \right). \tag{6.12}$$

Square both sides of (6.5) and note that $R^T = R^{-1}$.

$$a_x^2 + a_y^2 + (a_z + g)^2 = \left(\frac{T}{m} \right)^2 \tag{6.13}$$

$$\left(\frac{T}{m}\right) = \sqrt{a_x^2 + a_y^2 + (a_z + g)^2} \tag{6.14}$$

This result is then substituted back in Equation (6.12) to give ϕ_c.

$$\phi_c = \arcsin\left(\frac{a_x S_\psi - a_y C_\psi}{\sqrt{a_x^2 + a_y^2 + (a_z + g)^2}}\right) \tag{6.15}$$

Using θ_c and ϕ_c as set points, we can write the PD angular control laws. The subscript 'c' stands for 'commanded'.

$$\tau_{\phi c} = [k_{p\phi}(\phi_c - \phi) + k_{d\phi}(\dot{\phi}_c - \dot{\phi})]I_x \tag{6.16}$$

$$\tau_{\theta c} = [k_{p\theta}(\theta_c - \theta) + k_{d\theta}(\dot{\theta}_c - \dot{\theta})]I_y \tag{6.17}$$

$$\tau_{\psi c} = [k_{p\psi}(\psi_c - \psi) + k_{d\psi}(\dot{\psi}_c - \dot{\psi})]I_z \tag{6.18}$$

Given the commanded torques and the commanded total thrust, the commanded motor speeds can be obtained from the expressions (3.2) and (3.4) from section 3.3:

$$\omega_{1c} = \sqrt{\frac{T_c}{4k} - \frac{\tau_{\theta c}}{2kL} - \frac{\tau_{\psi c}}{4b}} \tag{6.19}$$

$$\omega_{2c} = \sqrt{\frac{T_c}{4k} - \frac{\tau_{\phi c}}{2kL} + \frac{\tau_{\psi c}}{4b}} \tag{6.20}$$

$$\omega_{3c} = \sqrt{\frac{T_c}{4k} + \frac{\tau_{\theta c}}{2kL} - \frac{\tau_{\psi c}}{4b}} \tag{6.21}$$

$$\omega_{4c} = \sqrt{\frac{T_c}{4k} + \frac{\tau_{\phi c}}{2kL} + \frac{\tau_{\psi c}}{4b}} \tag{6.22}$$

With the above results, we can summarize the control loop. The PID control expressions prescribe linear accelerations in each direction (x, y, z) which will drive

the system toward the desired position. The linear accelerations and knowledge of ψ are used to calculate the angles ϕ and θ, and the total thrust T. Given the angles and their time derivatives, the prescribed torques about the quad-rotor center of mass are given by PD control laws. Given the torques and the total thrust, the vector of motor speeds can be calculated. The implementation of the PID control block is listed in Appendix A.

In a physical implementation, after the motor speeds are updated, the state of the system would be estimated from whatever sensor data is available. The environmental context would dictate which type of sensor hardware would be appropriate. In a simulation context, we use the dynamical system model from Chapter 3 to evaluate the resulting motion of the system. In a sense, this process is just the inverse of the control loop. For further work, a random process could be included here to model sensor noise. This would give a nice simulation platform for evaluating the performance of a Kalman filter for estimating the state of the quad-rotor.

6.2 Testing the Control Scheme

With experimentally tuned control expressions, arbitrarily shaped, sub-optimal paths can be formed by updating the desired location periodically. The code which implements this functionality is listed in Appendix B. Figures 6.1 through 6.6 show the utility of the control scheme. It is important to note that in our simulations, the desired velocity at each of the ordered set points is zero. In words, the control algorithm is saying to the quad-rotor: 'Go to the desired location and hover until the set point is updated'. To design a path that includes set points with a non-zero desired velocity vector would require modification of the algorithm. The values of the constants that were used in the simulation are shown in Table 6.2.

FIGURE 6.1: 3-D path of the quad-rotor for a flight simulation between the points (0,0,0) and (1,1,1). The PID control expressions were tuned experimentally.

FIGURE 6.2: Time domain graphs corresponding the 3-D path. The linear and angular state variables are shown to stabilize at the desired positions.

41

Simulation

Parameters	Units	Description
$g = -9.81$	$\frac{m}{s^2}$	acceleration due to gravity
$m = 1$	kg	mass
$L = 1$	m	length of quad-rotor arm
$b = 10^{-6}$	$\frac{Nms^2}{Rad^2}$	aerodynamic torque coefficient
$k = 2.45 * 10^{-6}$	$\frac{Ns^2}{Rad^2}$	aerodynamic thrust coefficient
$Ixx = 5.0 * 10^{-3}$	$\frac{Nms^2}{Rad}$	moments of inertia
$Iyy = 5.0 * 10^{-3}$	$\frac{Nms^2}{Rad}$	
$Izz = 10.0 * 10^{-3}$	$\frac{Nms^2}{Rad}$	

TABLE 6.1: Simulation parameters of the quad-rotor model

Figure 6.3 shows the quad-rotor traversing along the edges of a 4 meter cube. This shows that in the simulation context, we have the ability to precisely locate the quad-rotor in space. The mathematical reality here is that the state of the system is exactly known within the algorithm. For a real implementation, the system model is replaced by the actual system. In this case the validity of the control algorithm is a function of the uncertainty of the state at each instance in time. This can be quantified by the state estimation process by which physical sensor measurements are combined. Figure 6.6 shows that there is an upper limit to the difference in initial and final vector positions. A single PID tuning is only usable up to a certain magnitude of desired displacement. Mathematically, the controller is still stable but the over-shoot of the desired position grows proportionately to the desired position itself. For arbitrarily shaped, long distance flights, the path would have to be composed of incremental pieces which are small enough so that a performance metric for the overshoot for each segment was satisfied. The time

FIGURE 6.3: 3D path of the quad-rotor for an arbitrary path, tracing the edges of a cube.

FIGURE 6.4: Dynamics of the rotor during the arbitrary path. The angular positions are shown to change and effect the desired change in linear position.

domain plots (Figures 6.2, 6.4, and 6.6) offer information about the stability of the system and the controller. Small oscillations in the linear and angular positions and velocities can be seen in Figure 6.2. These oscillations are an artifact of the coupling between the angular and linear control laws. Intuitively, this makes sense because the control of the linear position requires that the angular state of the quad-rotor be destabilized. In general it is the natural instability of this system

43

which allows it to be so maneuverable. Also the mathematical complexity of the system makes for a difficult optimization problem. In the next chapter we use the PID tuning as a basis for optimizing the system according to specific performance criteria.

FIGURE 6.5: 3D path of the quad-rotor for a large set point.

FIGURE 6.6: Dynamics of the quad-rotor for a large set point. The overshoot grows proportionally to the set point itself.

44

Chapter 7

PID Gain Optimization

In order to arrive at a solution to the quad-rotor energy optimization problem that is closer to running in real-time, a heuristic approach has been adopted. Recall that our general aim is to effectively control the vector position of the quad-rotor and additionally use the least energy in doing so. The relative simplicity of a PID controller makes it a good choice instead of the full nonlinear classical optimal control formulation. Also, if the PID control expressions are tuned well and that tuning is not changed, the control algorithm performs well.

The motivation for our heuristic method is to find the PID controller tuning which uses the least energy to drive the UAV to the desired state. The PID tuning defines the dynamics of the controller. Using the quad-rotor model derived in Chapter 3, the performance of the controller and the dynamics of the system can be evaluated as a function of the tuning. Mathematically, this can be represented as follows.

The aim of the optimization is to find:

$$\operatorname*{arg\,min}_{K_p, K_i, K_d} \sum_{k,i} \omega_i[k], \tag{7.1}$$

where $\omega_i[k]$ is the *ith* rotor speed at the *kth* time step. The variables K_p, K_i and K_d are the vectors of proportional, integral, and derivative gains defined as:

$$K_p = \begin{bmatrix} k_{px} \\ k_{py} \\ k_{pz} \end{bmatrix}, K_i = \begin{bmatrix} k_{ix} \\ k_{iy} \\ k_{iz} \end{bmatrix}, K_d = \begin{bmatrix} k_{dx} \\ k_{dy} \\ k_{dz} \end{bmatrix}$$

In our simulations, the time integral of all four motor speeds is proportional to the total energy used. Calculation of the actual energy used by the UAV in traversing a flight path would require a model for the motor. This is seen as unnecessary for our purposes since the time integral of the motor speeds and the total energy used will have the same effective minimum. Since the control input is calculated as part of the control algorithm anyway, it is used as a performance metric.

In any realistic application of UAV technology, the energy budget is only one important aspect of the control problem. Other important criteria for evaluating the performance of a controller are over-shoot of the desired location, the time of flight, and mathematical resonances or marginal instabilities. These factors must be considered in the design of the system. However, in the initial results described below, the time integral of the motor speeds is used as a single performance metric. The reason for this is to simplify the relationship between the performance metric and the PID gains. This is described in the next section.

7.1   Initial Simulation Results

In the context of the optimization process described in the previous section, there is evidence for the lack of robustness of the PID control. This can be shown by analyzing the relationship between the measured total thrust and the PID gains.

Ideally, a gradient descent method would be used to minimize the thrust as a function of the control gains. The basic flow of the algorithm that we would really like to implement is as follows.

Algorithm 7.1: PID Gain Optimization

1. Choose a set of proportional and derivative gains for each vector direction (x, y, and z);

2. Perform a simulation that controls the quad-rotor from an initial vector position to a desired vector position;

3. Calculate the sum of the four motor speeds over the duration of the simulation;

4. Appropriately change the PID gains such that the sum of the motor speeds decreases;

5. Go to step 1. Repeat until the sum of the motor speeds is found to be a minimum.

In reality, it has been found that the relationship between the measured total thrust and PID gains is not well-behaved. After many days of trying to debug a gradient descent algorithm, and observing inconsistent behavior, it was decided that a brute force method might be the only possibility. A deeper understanding of the objective function was needed. The brute force method simply requires that we simulate the system and determine the value of the performance criteria for each possible set of PID gain vectors within a given range.

In order to limit the number of simulations required to really represent the dynamics of the system, the set point $(0, 0, 1)$ was chosen. By choosing this set point, the

motion of the quad-rotor is intentionally limited to the z-direction which limits the number of possible gain vectors for this test. This makes the tuning of the x and y direction controllers irrelevant. To further limit the number of simulations required, the Ziegler-Nichols PID tuning method was used. This method is discussed in [30]. There are also excellent resources online to explain tuning [31].

The Ziegler-Nichols method specifies simple algebraic relationships between the proportional, integral, and derivative gains. This allows each of the PID gains to be expressed as a function of a single gain variable, k_u , which is allowed to range from 1 to 100.

The results of these simulations are shown in Figure 7.1.

FIGURE 7.1: The relationship between Ku and the measured total thrust.

The relationship between Ku and the total measured thrust depicted in Figure 7.1 is rather disappointing to say the least. The values of zero total thrust are the result of simulations that failed to converge to the set point. Without an objective function that is at least marginally well behaved we have no hope to employ a gradient descent minimization technique. The relationship shown in Figure 7.1 is indeed a product of a deterministic system but displays little to no continuity.

Another detail which cannot be ignored is that the total thrust alone is not sufficient as a performance criteria. Additionally, for appropriate control of the UAV, the overshoot and oscillations which show up in improperly tuned PID controllers must be accounted for. Specifically, as the proportional gain is increased to drive the system to the desired location more quickly, the total thrust for the simulation will decrease but eventually the overshoot and oscillations grow to unacceptable levels. In the opposite fashion, if the differential gain is increased, the overshoot and oscillations will be suppressed but the time required to reach the set point will increase along with the total thrust. The competitive nature of these three (necessary) performance criteria further complicate the relationship between the PID gain vectors and the objective function making a gradient descent minimization technique even less viable.

7.2 Brute Force Simulation Results

Given that a standard mathematical optimization technique is out of the question, what options are left? A nonlinear control law could be implemented and would perhaps make the optimization possible, but this is uncertain and not possible in the current time frame.

The decision was made to try many possible gain vectors and have an appropriate objective function to characterize each of the simulations. Given that the brute force algorithm is easy to write (and massively parallel-izable), around 6000 simulations were performed over a period of several hours. The computation was delegated to six independent instantiations of a python script, each one taking on a subset of the possible gain vectors and a separate CPU. The code used in the brute force implementation is listed in Appendix C, D and E.

A separate script was used to parse through all the results of the simulations which were stored in many time-stamped files. Of the roughly 6000 simulations, about 1000 of them converged. For these, the set point was reached and the stopping criteria for the simulation were satisfied. Of the 1000 or so good runs, about 80 simulations satisfied the maximum overshoot and oscillation criteria. Only the gain vectors which produced less than ten percent overshoot were accepted. Likewise, only simulations which crossed the desired set point in each direction fewer than four times were deemed acceptable. The remaining 80 simulations were sorted lowest to highest by total measured thrust.

The optimal run that was found is detailed in Table 7.2. In addition to the PID gain vectors that produced the optimal system behavior, the measured performance metrics are also shown. The total thrust, set-point over shoot, and marginal instability of the system are quantified. The marginal instability is characterized by how many times the quad-rotor crossed the set-point value. Table 7.2 summarizes the statistics of the brute force simulation results. We can readily see that the optimal run is the run requiring the minimum thrust, and hence the minimum energy of all convergent runs. Figures 7.2 and 7.3 show the dynamics of the system with the optimal PID tuning.

Parameter	Value
kpx	15
kpy	15
kpz	40
kix	0.8
kiy	0.8
kiz	15
kdx	10
kdy	10
kdz	50
ending iteration	987
discrete time step	0.01 (s)
flight time	9.87 (s)
cpu runtime	11.41 (s)
return value	1 (great success)
initial position	[0, 0, 1] (m)
set point	[1, 1, 2] (m)
total thrust	4607 (Newton seconds)
x crossings	3
x overshoot	0.0249 (m)
y crossings	1
y overshoot	0.0185 (m)
z crossings	1
z overshoot	0.0992 (m)

TABLE 7.1: Numerical descriptors of the optimal run

Parameter	Value
number of convergent runs	1001
minimum thrust	4607(Newton seconds)
average total thrust	8075(Newton seconds)
number of runs with satisfactory oscillations	86
number of runs with satisfactory overshoot	91
average x crossings	3
average y crossings	3
average z crossings	1
average x overshoot	0.088(m)
average y overshoot	0.112(m)
average z overshoot	0.309(m)

TABLE 7.2: Brute force statistics

Figures 7.2 and 7.3 show the simulation of the quad-rotor flight from the initial point $(0, 0, 1)$ to the desired point $(1, 1, 2)$ using the optimal PID tuning. There are actually two distinct legs to the simulation. The reason for this comes from the fact that there are two types of initial conditions which have fundamental differences. There is a hovering state which we use as initial conditions for the simulations in the optimization procedure. There is another mathematical state which occurs at the very beginning of the simulation. The mathematical initialization of the quad-rotor state is at the origin $(0, 0, 0)$ with zero velocity and acceleration but it is not exactly hovering. This subtle distinction comes from the fact that the force of gravity is not canceled out by the thrust initially. The controller has had no time to act to stabilize the system. The physical scenario that this condition would correspond to is if a person held the quad-rotor at the initial position in free

FIGURE 7.2: 3D path simulation of the Quadcopter using the optimal run
parameters specified

space (perhaps designated as the origin) and then at $t = 0$, simply let go. Another
way to state this is that the simulations do not account for the normal force which
would be imparted to the quad-rotor if it were simply taking off from the ground.
To account for this would perhaps require augmentation of the dynamical model
of the quad-rotor.

Our aim was to start and end in a hovering state for the optimization. This is why
our simulations start with a 'take-off sequence' where the quad-rotor leaves from
the origin and goes to the position $(0, 0, 1)$. After this, the system is stabilized in
a hovering state. From there, arbitrary paths can be incrementally constructed by
simply redefining the desired location.

FIGURE 7.3: Quadcopter dynamics using the optimal run parameters

Despite the mathematical difficulties that were experienced with the various optimization techniques that were explored, this final result is useful. Until a reasonable mathematical optimization technique is found, the optimality of the solution described above is a function of how much time one is willing to run the brute force algorithm.

Chapter 8

Summary and Future Work

8.1 Summary

In this final chapter we review the main points of the paper and propose directions
for further work. Our first significant result was the dynamic model of the quad-
rotor. The Euler-Lagrange formulation was used to derive the dynamic model.
The resulting set of nonlinear differential equations formed the basis for both the
control and optimization methods which were subsequently derived.

Our first approach to the path-energy optimization problem which incorporated
the dynamic model was classical optimal control. Using this formulation, we de-
rived a set of differential and algebraic equations which form a complex boundary
value problem. Our initial aim was to develop a method for achieving a path-
energy optimization which would perform on a near-real-time-schedule. The com-
putational resources needed to solve the optimal control boundary value problem
on this real-time schedule invalidate it as a possible solution.

The next method of optimization which was explored was a heuristic method. Control of the UAV was attained by way of a set of PID and PD controllers. Since the performance of the quad-rotor is defined by the controller tuning, the system can be optimized as a function of this tuning. Relevant criteria for evaluating the performance of the system are the total thrust integrated over the duration of the simulation, oscillations that the system experiences, overshoot of the desired location, and the total time of flight. It was determined experimentally that the relationship between these performance metrics and the controller tuning was not well-behaved mathematically. Without a clean mathematical representation of our objective function, the viability of an efficient optimization method is questioned.

Next, a brute force method was used to determine the optimal controller tuning. Using this method, a controller tuning which is sufficient to perform simulated fights in a relatively efficient manner was determined.

8.2   Further Work

The problem of path-energy optimization as solved in this thesis can be worked on in the future to produce more robust results. Two possible mathematical modifications that could possibly allow for an efficient optimization algorithm are as follows. They both have design trade-offs.

1. *Model Linearization* One approach would beto use a linearized model. The goal there would be to simplify the relationship between the controller tuning and the relevant performance metrics by simplifying the mathematical

representation of the dynamic model. The danger in using a linear approximation is creating an over-simplified model that is divergent from reality to an extent that makes it unusable.

2. *Nonlinear Control* If instead of a linear PID controller, a nonlinear control method was used, the stability of the system could be increased. This would perhaps allow for a well behaved and more well defined relationship between the parameters of the controller and the measurable dynamics of the system. The obvious caveat here is the increase in complexity of the controller. The only real way to know if one of these options would allow for an efficient optimization procedure would be to try them all and characterize them in the context of the goal of the flight.

3. *UAV Swarm Optimization* Another area of research interest that would benefit from an energy optimization procedure is the control of swarms of UAVs. The distributed control of UAVs is a field which offers a wide range of engineering challenges such as collision avoidance, optimization of networked communication, and optimization of workload delegation toward a common goal. The contextual details of the cooperative aim of the swarm would inform the optimization of the system.

4. *Sensor Fusion and State Estimation* Yet another area of possible further research is in the sensor fusion and state estimation problem. For a physical implementation, knowledge of the state of the system is a critical component. Given that there are a very large variety of physical sensors that could contribute to this knowledge, this is an interesting problem. An aspect of this problem that adds richness to this situation is the fact that each type of sensor will have a different rate at which physical information is available. This rate is determined by the physical nature of the quantity being measured.

A good example is the integration of GPS measurements and accelerometer measurements. Values from these sensors are available perhaps at rates of 1 Hz and 100 Hz respectively. The sensor data would be integrated with a Kalman filter to develop situational awareness which allows for effective control of the system.

In general the control and optimization of UAVs is a rich and evolving field of research with many unsolved problems. There will be many commercial applications of this technology appearing in coming years which will be informed by future research.

Appendix A

Dynamic system model and PID control - agentModule.py

```
breakatwhitespace
1
   '''
3  here is an outline of the program flow:

5      1) initialize lists for state variables and appropriate derivatives
          as well as constants.
7      2) calculate total thrust T and the torques using the state variables from
          the [k]th time step
9      3) using T[k] and tao_[k] calculate new motor speed vector for time [k]
       4) using T[k] and tao_[k] calculate new state variables at time [k+1]
11     5) repeat
   '''

13
   from numpy import cos as c, sin as s , sqrt, array, dot, arctan2, arcsin, sign , around
15 from numpy.linalg import inv
   from wind import *
17 import sys
   import math

19
   #############################################################################

21
   class agent:

23
       def __init__(self, x_0,   y_0,   z_0,
25                   initial_setpoint_x,  initial_setpoint_y, initial_setpoint_z,
                     agent_priority = 10 ):
27
```

```python
29

31          #------------------------------- physical constants
            self.g = -9.81    #[m/s^2]
33          self.m = 1        #[kg]
            self.L = 1     #[m]
35          self.b = 10**-6
            self.k = self.m*abs(self.g)/(4*(1000**2))
37          #print 'self.k = ',self.k
            #raw_input()
39          #-------------------------------moments of inertia
            self.Ixx = 5.0*10**-3
41          self.Iyy = 5.0*10**-3
            self.Izz = 10.0*10**-3

43
            #-------------------------------directional drag coefficients
45          self.Ax = 0.25
            self.Ay = 0.25
47          self.Az = 0.25


49          self.hover_at_setpoint = True


51          # a list of distances to each other agent sorted nearest to farthest
            self.distance_vectors = []

53
            self.agent_priority = agent_priority

55
            # state vector and  derivative time series' list initializations
57          self.x = [x_0]
            self.y = [y_0]
59          self.z = [z_0]

61          self.xdot = [0]
            self.ydot = [0]
63          self.zdot = [0]

65          self.xddot = [0]
            self.yddot = [0]
67          self.zddot = [0]

69          self.phi   = [0]
            self.theta = [0]
71          self.psi   = [0]

73          self.phidot   = [0]
            self.thetadot = [0]
75          self.psidot   = [0]

77          self.phiddot   = [0]
            self.thetaddot = [0]
79          self.psiddot   = [0]

81          self.tao_qr_frame = []
            self.etadot = []
```

```python
        self.etaddot =[]


        #-------------------------------------------------------------CONTROLLER GAINS

        self.kpx = 0.          # PID proportional gain values
        self.kpy = 0.
        self.kpz = 0.

        self.kdx = 0.           # PID derivative gain values
        self.kdy = 0.
        self.kdz = 0.

        self.kddx = 0.
        self.kddy = 0.
        self.kddz = 0.

        self.kix = 0.          # PID integral gain values
        self.kiy = 0.
        self.kiz = 0.

        self.kpphi   = 4  # gains for the angular pid control laws
        self.kptheta = 4
        self.kppsi   = 4

        self.kiphi   = 0.
        self.kitheta = 0.
        self.kipsi   = 0.

        self.kdphi   = 5
        self.kdtheta = 5
        self.kdpsi   = 5

        self.xdd_des = 0
        self.ydd_des = 0
        self.zdd_des = 0

        self.x_integral_error = [0]
        self.y_integral_error = [0]
        self.z_integral_error = [0]

        # angular set points
        self.phi_des = 0
        self.theta_des = 0
        self.psi_des = 0

        self.psidot_des = 0



        self.phi_comm = [0,0]
        self.theta_comm = [0,0]
        self.T_comm = [0,0]


        self.tao_phi_comm = [0,0]
```

61

```python
            self.tao_theta_comm = [0,0]
139         self.tao_psi_comm = [0,0]


            # force, torque, and motor speed list initializations

            self.T = [9.81]
145         self.tao_phi   = [0]
            self.tao_theta = [0]
147         self.tao_psi   = [0]


149         self.w1 = [1000]
            self.w2 = [1000]
151         self.w3 = [1000]
            self.w4 = [1000]
153
            self.etaddot = []
155         #--------------------------------

157         self.max_iterations = 10000
            self.h = 0.01
159         self.ending_iteration = 0


161         #--------------------------------------------------------------------wind!!
            self.wind_duration = self.max_iterations
163         self.max_gust = 0.1


165         # generate the wind for the entire simulation beforehand
            self.wind_data = wind_vector_time_series(self.max_gust,self.wind_duration)
167
            self.wind_x = self.wind_data[0]
169         self.wind_y = self.wind_data[1]
            self.wind_z = self.wind_data[2]

171

173         #-----------------------------------------------------------------------

175         #TODO: NEED TO SORT OUT THE MIN AND MAX THRUST PARAMETERS AND CORRELATE
            #      THIS PHYSICAL LIMITATION WITH THE MAX VALUES FOR THE PROPORTIONAL
177         #      GAIN TERMS IN EACH CONTROL LAW.

179         #self.max_total_thrust = 50.0  # [newtons]
            #self.min_total_thrust = 1.0
181
            self.x_des = initial_setpoint_x
183         self.y_des = initial_setpoint_y
            self.z_des = initial_setpoint_z
185
            self.xdot_des = 0
187         self.ydot_des = 0
            self.zdot_des = 0
189
            self.initial_setpoint_x = initial_setpoint_x
191         self.initial_setpoint_y = initial_setpoint_y
            self.initial_setpoint_z = initial_setpoint_z
```

```python
        #----------------------------------------------------------------------

        self.w1_arg = [0,0]
        self.w2_arg = [0,0]
        self.w3_arg = [0,0]
        self.w4_arg = [0,0]


        self.xacc_comm = [0]
        self.yacc_comm = [0]
        self.zacc_comm = [19.62]




    ####################################################  END   " __INIT__() "




    # the Jacobian for transforming from body frame to inertial frame

    def J(self):

        ixx = self.Ixx
        iyy = self.Iyy
        izz = self.Izz

        th = self.theta[-1]
        ph = self.phi[-1]


        j11 = ixx

        j12 = 0

        j13 = -ixx * s(th)

        j21 = 0

        j22 = iyy*(c(ph)**2) + izz * s(ph)**2

        j23 = (iyy-izz)*c(ph)*s(ph)*c(th)

        j31 = -ixx*s(th)

        j32 = (iyy-izz)*c(ph)*s(ph)*c(th)

        j33 = ixx*(s(th)**2) + iyy*(s(th)**2)*(c(th)**2) + izz*(c(ph)**2)*(c(th)**2)

        return array([
                    [j11, j12, j13],
```

```
                              [j21, j22, j23],
                              [j31, j32, j33]
                         ])



        #-------------------Coriolis matrix

        def coriolis_matrix(self):

            ph = self.phi[-1]
            th = self.theta[-1]

            phd = self.phidot[-1]
            thd = self.thetadot[-1]
            psd = self.psidot[-1]

            ixx = self.Ixx
            iyy = self.Iyy
            izz = self.Izz

            c11 = 0

            # break up the large elements in to bite size chunks and then add each term ...

            c12_term1 = (iyy-izz) * ( thd*c(ph)*s(ph) + psd*c(th)*s(ph)**2 )

            c12_term2and3 = (izz-iyy)*psd*(c(ph)**2)*c(th) - ixx*psd*c(th)

            c12 = c12_term1  + c12_term2and3



            c13 = (izz-iyy) * psd * c(ph) * s(ph) * c(th)**2



            c21_term1 = (izz-iyy) * ( thd*c(ph)*s(ph) + psd*s(ph)*c(th) )

            c21_term2and3 = (iyy-izz) * psd * (c(ph)**2) * c(th) + ixx * psd * c(th)

            c21 = c21_term1 + c21_term2and3



            c22 = (izz-iyy)*phd*c(ph)*s(ph)

            c23 = -ixx*psd*s(th)*c(th) + iyy*psd*(s(ph)**2)*s(th)*c(th)

            c31 = (iyy-izz)*phd*(c(th)**2)*s(ph)*c(ph) - ixx*thd*c(th)

```

64

```python
        c32_term1     = (izz-iyy)*( thd*c(ph)*s(ph)*s(th) + phd*(s(ph)**2)*c(th) )

        c32_term2and3 = (iyy-izz)*phd*(c(ph)**2)*c(th) + ixx*psd*s(th)*c(th)

        c32_term4 = - iyy*psd*(s(ph)**2)*s(th)*c(th)

        c32_term5 = - izz*psd*(c(ph)**2)*s(th)*c(th)

        c32 = c32_term1 + c32_term2and3 + c32_term4 + c32_term5


        c33_term1 = (iyy-izz) * phd *c(ph)*s(ph)*(c(th)**2)

        c33_term2 = - iyy * thd*(s(ph)**2) * c(th)*s(th)

        c33_term3and4 = - izz*thd*(c(ph)**2)*c(th)*s(th) + ixx*thd*c(th)*s(th)

        c33 = c33_term1 + c33_term2 + c33_term3and4


        return array([
                        [c11,c12,c13],
                        [c21,c22,c23],
                        [c31,c32,c33]
                         ])


    #------------------------------------------------------------------------


    def control_block(self):


        # calculate the integral of the error in position for each direction

        self.x_integral_error.append( self.x_integral_error[-1] + (self.x_des - self.x[-1])*self.h )
        self.y_integral_error.append( self.y_integral_error[-1] + (self.y_des - self.y[-1])*self.h )
        self.z_integral_error.append( self.z_integral_error[-1] + (self.z_des - self.z[-1])*self.h )


        # computte the comm linear accelerations needed to move the system from present location to the
      desired location

        self.xacc_comm.append( self.kdx * (self.xdot_des - self.xdot[-1])
                            + self.kpx * ( self.x_des - self.x[-1] )
                            + self.kddx * (self.xdd_des - self.xddot[-1] )
                            + self.kix * self.x_integral_error[-1]  )


        self.yacc_comm.append( self.kdy * (self.ydot_des - self.ydot[-1])
                                + self.kpy * ( self.y_des - self.y[-1] )
                                + self.kddy * (self.ydd_des - self.yddot[-1] )
                                + self.kiy * self.y_integral_error[-1]  )
```

```python
            self.zacc_comm.append( self.kdz * (self.zdot_des - self.zdot[-1])
                                    + self.kpz * ( self.z_des - self.z[-1] )
                                    + self.kddz * (self.zdd_des - self.zddot[-1] )
                                    + self.kiz * self.z_integral_error[-1] )


        # need to limit the max linear acceleration that is perscribed by the control law

        # as a meaningful place to start, just use the value '10m/s/s' , compare to g = -9.8 ...

        max_latt_acc = 5

        max_z_acc = 30

        if abs(self.xacc_comm[-1]) > max_latt_acc: self.xacc_comm[-1] = max_latt_acc * sign(self.xacc_comm
[-1])
        if abs(self.yacc_comm[-1]) > max_latt_acc: self.yacc_comm[-1] = max_latt_acc * sign(self.yacc_comm
[-1])
        if abs(self.zacc_comm[-1]) > max_z_acc: self.zacc_comm[-1] = max_z_acc * sign(self.zacc_comm[-1])

        min_z_acc = 12

        if self.zacc_comm[-1] < min_z_acc: self.zacc_comm[-1] = min_z_acc

        # using the comm linear accellerations, calc  theta_c, phi_c and T_c

        theta_numerator = (self.xacc_comm[-1] * c(self.psi[-1]) + self.yacc_comm[-1] * s(self.psi[-1]) )

        theta_denominator = float( self.zacc_comm[-1] + self.g )

        if theta_denominator <= 0:

            theta_denominator = 0.1            # don't divide by zero !!!

        self.theta_comm.append(arctan2( theta_numerator ,  theta_denominator ))

        self.phi_comm.append(arcsin( (self.xacc_comm[-1] * s(self.psi[-1]) - self.yacc_comm[-1] * c(self.psi
[-1]) ) / float(sqrt( self.xacc_comm[-1]**2 +

             self.yacc_comm[-1]**2 +

            (self.zacc_comm[-1] + self.g)**2  )) ))

        self.T_comm.append(self.m * ( self.xacc_comm[-1] * ( s(self.theta[-1])*c(self.psi[-1])*c(self.phi
[-1]) + s(self.psi[-1])*s(self.phi[-1]) ) +
                                      self.yacc_comm[-1] * (  s(self.theta[-1])*s(self.psi[-1])*c(self.phi
[-1]) - c(self.psi[-1])*s(self.phi[-1]) ) +
                                      (self.zacc_comm[-1] + self.g) * ( c(self.theta[-1])*c(self.phi[-1])  )
                                      ))

        if self.T_comm[-1] < 1.0:
            self.T_comm = self.T_comm[:-1]
            self.T_comm.append(1.0)
```

```python
        # we will need the derivatives of the comanded angles for the torque control laws.
        self.phidot_comm = (self.phi_comm[-1] - self.phi_comm[-2])/self.h

        self.thetadot_comm = (self.theta_comm[-1] - self.theta_comm[-2])/self.h


        # solve for torques based on theta_c, phi_c and T_c , also psi_des , and previous values of theta,
        phi , and psi


        tao_phi_comm_temp = ( self.kpphi*(self.phi_comm[-1] - self.phi[-1]) + self.kdphi*(self.phidot_comm -
        self.phidot[-1]) )*self.Ixx

        tao_theta_comm_temp = ( self.kptheta*(self.theta_comm[-1] - self.theta[-1]) + self.kdtheta*(self.
        thetadot_comm - self.thetadot[-1]) )*self.Iyy

        tao_psi_comm_temp = ( self.kppsi*(self.psi_des - self.psi[-1]) + self.kdpsi*( self.psidot_des - self.
        psidot[-1] ) )*self.Izz

        self.tao_phi_comm.append(tao_phi_comm_temp )
        self.tao_theta_comm.append(tao_theta_comm_temp )
        self.tao_psi_comm.append(tao_psi_comm_temp )

        #--------------------------------solve for motor speeds , eq 24

        self.w1_arg.append( (self.T_comm[-1] / (4.0*self.k)) - ( self.tao_theta_comm[-1] / (2.0*self.k*self.L
        ) ) - ( self.tao_psi_comm[-1] / (4.0*self.b) ) )
        self.w2_arg.append( (self.T_comm[-1] / (4.0*self.k)) - ( self.tao_phi_comm[-1]   / (2.0*self.k*self.L
        ) ) + ( self.tao_psi_comm[-1] / (4.0*self.b) ) )
        self.w3_arg.append( (self.T_comm[-1] / (4.0*self.k)) + ( self.tao_theta_comm[-1] / (2.0*self.k*self.L
        ) ) - ( self.tao_psi_comm[-1] / (4.0*self.b) ) )
        self.w4_arg.append( (self.T_comm[-1] / (4.0*self.k)) + ( self.tao_phi_comm[-1]   / (2.0*self.k*self.L
        ) ) + ( self.tao_psi_comm[-1] / (4.0*self.b) ) )

        self.w1.append( sqrt( self.w1_arg[-1] )  )
        self.w2.append( sqrt( self.w2_arg[-1] )  )
        self.w3.append( sqrt( self.w3_arg[-1] )  )
        self.w4.append( sqrt( self.w4_arg[-1] )  )

        # IMPORTANT!!! THIS ENDS THE 'CONTROLLER BLOCK' IN A REAL IMPLEMENTATION , WE WOULD NOW TAKE
        MEASUREMENTS AND ESTIMATE THE STATE and then start over...

    def system_model_block(self):

        # BELOW ARE THE EQUATIONS THAT MODEL THE SYSTEM,
        # FOR THE PURPOSE OF SIMULATION , GIVEN THE MOTOR SPEEDS WE CAN CALCULATE THE STATES OF THE SYSTEM

        self.tao_qr_frame.append( array([
                            self.L*self.k*( -self.w2[-1]**2 + self.w4[-1]**2 ) ,
                            self.L*self.k*( -self.w1[-1]**2 + self.w3[-1]**2 ) ,
                            self.b* ( -self.w1[-1]**2 + self.w2[-1]**2 - self.w3[-1]**2 + self.w4[-1]**2
        )
                            ]) )
```

```
            self.tao_phi.append(self.tao_qr_frame[-1][0])
451         self.tao_theta.append(self.tao_qr_frame[-1][1])
            self.tao_psi.append(self.tao_qr_frame[-1][2])
453
            self.T.append(self.k*( self.w1[-1]**2 + self.w2[-1]**2 + self.w3[-1]**2 + self.w4[-1]**2 ) )
455
            # use the previous known angles and the known thrust to calculate the new resulting linear
        accelerations
457         # remember this would be measured ...
            # for the purpose of modeling the measurement error and testing a kalman filter, inject noise here...
459         # perhaps every 1000ms substitute an artificial gps measurement (and associated uncertianty) for the
        double integrated imu value
461         self.xddot.append(  (self.T[-1]/self.m)*( c(self.psi[-1])*s(self.theta[-1])*c(self.phi[-1])
                                + s(self.psi[-1])*s(self.phi[-1]) )
463                             - self.Ax * self.xdot[-1] / self.m  )
465         self.yddot.append(  (self.T[-1]/self.m)*( s(self.psi[-1])*s(self.theta[-1])*c(self.phi[-1])
                                - c(self.psi[-1])*s(self.phi[-1]) )
467                             - self.Ay * self.ydot[-1] / self.m  )
469         self.zddot.append(  self.g + (self.T[-1]/self.m)*( c(self.theta[-1])*c(self.phi[-1]) ) - self.Az *
        self.zdot[-1] / self.m  )
471         # calculate the new angular accelerations based on the known values
            self.etadot.append( array( [self.phidot[-1], self.thetadot[-1], self.psidot[-1] ] ) )
473
            self.etaddot.append( dot(inv( self.J() ), self.tao_qr_frame[-1]  -  dot(self.coriolis_matrix() , self
        .etadot[-1]) ) )
475
            # parse the etaddot vector of the new accelerations into the appropriate time series'
477         self.phiddot.append(self.etaddot[-1][0])
479         self.thetaddot.append(self.etaddot[-1][1])
481         self.psiddot.append(self.etaddot[-1][2])
483         #----------------------------- integrate new acceleration values to obtain velocity values
485         self.xdot.append(  self.xdot[-1] + self.xddot[-1] * self.h  )
            self.ydot.append(  self.ydot[-1] + self.yddot[-1] * self.h  )
487         self.zdot.append(  self.zdot[-1] + self.zddot[-1] * self.h  )
489         self.phidot.append(     self.phidot[-1]   + self.phiddot[-1] * self.h  )
            self.thetadot.append(  self.thetadot[-1] + self.thetaddot[-1] * self.h  )
491         self.psidot.append(     self.psidot[-1]   + self.psiddot[-1] * self.h  )
493         #----------------------------- integrate new velocity values to obtain position / angle values
495         self.x.append(  self.x[-1] + self.xdot[-1] * self.h  )
            self.y.append(  self.y[-1] + self.ydot[-1] * self.h  )
497         self.z.append(  self.z[-1] + self.zdot[-1] * self.h  )
499         self.phi.append(  self.phi[-1] + self.phidot[-1] * self.h  )
            self.theta.append(  self.theta[-1] + self.thetadot[-1] * self.h  )
```

```python
            self.psi.append( self.psi[-1] + self.psidot[-1] * self.h  )



        ########################################################################


        def plot_results(self,show_plot = True, save_plot = False, fig1_file_path = None,fig2_file_path = None):

            timeSeries = [self.h*i for i in range(len(self.x))]

            from mpl_toolkits.mplot3d import Axes3D
            import matplotlib.pyplot as plt
            from pylab import title
            import matplotlib.gridspec as gridspec


            fig0 = plt.figure()


            ax = fig0.add_subplot(111, projection='3d')

            ax.scatter(
                        self.x[0:len(self.x):5],
                        self.y[0:len(self.y):5],
                        self.z[0:len(self.z):5])

            ax.set_xlabel('X (m)')
            ax.set_ylabel('Y (m)')
            ax.set_zlabel('Z (m)')


            fig1 = plt.figure()
            gs1 = gridspec.GridSpec(3, 2)

            #-------------------------------------------------linear displacements
            xx = fig1.add_subplot(gs1[0,0])
            plt.plot(timeSeries, self.x,'r',
                     timeSeries, self.y,'g',
                     timeSeries, self.z,'b')
            title('x,y,z',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
            plt.ylabel('dist. (m)',fontsize=10)


            #----------------------------------------------------------------angles
            thth = fig1.add_subplot(gs1[1,0])
            plt.plot(timeSeries, self.phi,'r',
                     timeSeries, self.theta,'g',
                     timeSeries, self.psi,'b')
            title('Phi = roll, Theta = pitch, Psi = yaw',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
            plt.ylabel('(rad)',fontsize=10)
            #-----------------------------------------------------motor speeds
```

```python
            spd = fig1.add_subplot(gs1[2,0])
            plt.plot([self.h*i for i in range(len(self.w1))], self.w1,'r',
                     [self.h*i for i in range(len(self.w2))], self.w2,'g',
                     [self.h*i for i in range(len(self.w3))], self.w3,'b',
                     [self.h*i for i in range(len(self.w4))], self.w4,'k')
            title('motor speeds',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
            plt.ylabel('(rad/sec)',fontsize=10)
            #----------------------------------------------------------------torque
            spd = fig1.add_subplot(gs1[0,1])
            plt.plot([self.h*i for i in range(len(self.tao_phi))], self.tao_phi,'r',
                     [self.h*i for i in range(len(self.tao_theta))], self.tao_theta,'g',
                     [self.h*i for i in range(len(self.tao_psi))], self.tao_psi,'b')
            title('torques ',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
            plt.ylabel('(Nm)',fontsize=10)
            #----------------------------------------------------------------thrust
            spd = fig1.add_subplot(gs1[1,1])
            plt.plot([self.h*i for i in range(len(self.T))], self.T,'r',)
            title('Total Thrust',fontsize=10)
            plt.xlabel('time (s)',fontsize=10)
            plt.ylabel('(N)',fontsize=10)


            #----------------------------------------------------commanded total thrust
            t_comm = fig1.add_subplot(gs1[2,1])
            plt.plot([self.h*i for i in range(len(self.T_comm))], self.T_comm,'r')
            title('T_comm',fontsize=10)



            '''
            #--------------------------------------------------------wind velocities
            wind_plot = fig1.add_subplot( gs1[ 8:10 ,0:3 ] )

            plt.plot([self.h*i for i in range(len(self.wind_x))], self.wind_x,'-r',
                     [self.h*i for i in range(len(self.wind_y))], self.wind_y,'-g',
                     [self.h*i for i in range(len(self.wind_z))], self.wind_z,'-b'  )

            title('wind velocities , rgb = xyz', fontsize=10)
            '''
            fig1.tight_layout()

            ##########################################



            fig2 = plt.figure()
            gs2 = gridspec.GridSpec(4, 2)

            #----------------------------------------------------------------linear velocities
            lin_vel = fig2.add_subplot(gs2[0,0])
            plt.plot(timeSeries, self.xdot,'r',
                     timeSeries, self.ydot,'g',
                     timeSeries, self.zdot,'b')
```

70

```
611          title('xdot, ydot, self.zdot',fontsize=10)


613          #-----------------------------------------------------------------linear accelerations
             lin_acc = fig2.add_subplot(gs2[1,0])
615          plt.plot(timeSeries, self.xddot,'r',
                      timeSeries, self.yddot,'g',
617                   timeSeries, self.zddot,'b')
             title('xddot, yddot, self.zddot',fontsize=10)
619


621          #-----------------------------------------------------------------angular velocities
             ang_vel = fig2.add_subplot(gs2[2,0])
623          plt.plot(timeSeries, self.phidot,'r',
                      timeSeries, self.thetadot,'g',
625                   timeSeries, self.psidot,'b')
             title('phidot, thetadot, self.psidot',fontsize=10)
627


629          #-----------------------------------------------------------------commanded torques
             t_comm  = fig2.add_subplot(gs2[3,0])
631          plt.plot([self.h*i for i in range(len(self.tao_phi_comm))], self.tao_phi_comm,'r',
                      [self.h*i for i in range(len(self.tao_theta_comm))], self.tao_theta_comm,'g',
633                   [self.h*i for i in range(len(self.tao_psi_comm))], self.tao_psi_comm,'b',
                      )
635          title('tao_phi_comm,tao_theta_comm,tao_psi_comm',fontsize=10)



637


639          #-----------------------------------------------------------------angular velocities
             ang_acc = fig2.add_subplot(gs2[0,1])
641          plt.plot(timeSeries, self.phiddot,'r',
                      timeSeries, self.thetaddot,'g',
643                   timeSeries, self.psiddot,'b')
             title('phiddot, thetaddot, self.psiddot',fontsize=10)
645


647          #-----------------------------------------------------------------integral errors
             integral_errors = fig2.add_subplot(gs2[1,1])
649          plt.plot(timeSeries, self.x_integral_error,'r',
                      timeSeries, self.y_integral_error,'g',
651                   timeSeries, self.z_integral_error,'b')
             title('x_integral_error, y_integral_error, z_integral_error',fontsize=10)
653


655          #-----------------------------------------------------------------w_args
             integral_errors = fig2.add_subplot(gs2[2,1])
657          plt.plot([self.h*i for i in range(len(self.w1_arg))], self.w1_arg,'r',
                      [self.h*i for i in range(len(self.w2_arg))], self.w2_arg,'g',
659                   [self.h*i for i in range(len(self.w3_arg))], self.w3_arg,'b',
                      [self.h*i for i in range(len(self.w4_arg))], self.w4_arg,'k'
661              )
             title('w1_arg, w2_arg, w3_arg, w4_arg ',fontsize=10)
663
             #-----------------------------------------------------------------commanded phi and theta
665          integral_errors = fig2.add_subplot(gs2[3,1])
```

71

```python
            plt.plot([self.h*i for i in range(len(self.theta_comm))], self.theta_comm,'r',
                      [self.h*i for i in range(len(self.phi_comm))], self.phi_comm,'g'
                     )
            title('theta_com ,phi_com  ',fontsize=10)



            fig2.tight_layout()

            if save_plot == True:

                fig1.savefig(fig1_file_path)
                fig2.savefig(fig2_file_path)



            if show_plot == True:

                plt.show()
#-------------------------------------------------------------------------------

    def print_dump(self,n=5):

            print '\n\nself.xacc_comm[-n:] = ',around(self.xacc_comm[-n:], decimals=5)
            print '\n\nself.yacc_comm[-n:] = ',around(self.yacc_comm[-n:], decimals=5)
            print '\n\nself.zacc_comm[-n:] = ',around(self.zacc_comm[-n:], decimals=5)

            print '\n\ntheta_com[-n:] = ',around(self.theta_comm[-n:], decimals=5)

            print '\n\nphi_com[-n:] = ',around(self.phi_comm[-n:], decimals=5)

            print '\n\nT_comm[-n:] = ',around(self.T_comm[-n:], decimals=5)

            print '\n\nself.tao_phi_comm = ',around(self.tao_phi_comm[-n:], decimals=5)
            print '\n\nself.tao_theta_comm = ',around(self.tao_theta_comm[-n:], decimals=5)
            print '\n\nself.tao_psi_comm = ',around(self.tao_psi_comm[-n:], decimals=5)

            print '\n\nw1_arg[-n:] = ',around(self.w1_arg[-n:], decimals=0)
            print '\n\nw2_arg[-n:] = ',around(self.w2_arg[-n:], decimals=0)
            print '\n\nw3_arg[-n:] = ',around(self.w3_arg[-n:], decimals=0)
            print '\n\nw4_arg[-n:] = ',around(self.w4_arg[-n:], decimals=0)

            print '\n\nw1[-n:] = ',around(self.w1[-n:] , decimals=1)
            print '\n\nw2[-n:] = ',around(self.w2[-n:], decimals=1)
            print '\n\nw3[-n:] = ',around(self.w3[-n:] , decimals=1)
            print '\n\nw4[-n:] = ',around(self.w4[-n:], decimals=1)

            print '\n\nself.tao_qr_frame[-n:] = ',around(self.tao_qr_frame[-n:], decimals=5)

            print '\n\nself.T[-n:] = ',around(self.T[-n:], decimals=5)

            print '\n\nself.phi[-n:] = ',around(self.phi[-n:], decimals=5)
            print '\n\nself.theta[-n:] = ',around(self.theta[-n:], decimals=5)
            print '\n\nself.psi[-n:] = ',around(self.psi[-n:], decimals=5)
```

72

```python
        print '\n\nself.phidot[-n:] = ',around(self.phidot[-n:], decimals=5)
        print '\n\nself.thetadot[-n:] = ',around(self.thetadot[-n:], decimals=5)
        print '\n\nself.psidot[-n:] = ',around(self.psidot[-n:], decimals=5)

        print '\n\nself.phiddot[-n:] = ',around(self.phiddot[-n:], decimals=5)
        print '\n\nself.thetaddot[-n:] = ',around(self.thetaddot[-n:], decimals=5)
        print '\n\nself.psiddot[-n:] = ',around(self.psiddot[-n:], decimals=5)

        print '\n\nself.x[-n:] = ',around(self.x[-n:], decimals=5)
        print '\n\nself.y[-n:] = ',around(self.y[-n:], decimals=5)
        print '\n\nself.z[-n:] = ',around(self.z[-n:], decimals=5)

        print '\n\nself.xdot[-n:] = ',around(self.xdot[-n:], decimals=5)
        print '\n\nself.ydot[-n:] = ',around(self.ydot[-n:], decimals=5)
        print '\n\nself.zdot[-n:] = ',around(self.zdot[-n:], decimals=5)

        print '\n\nself.xddot[-n:] = ',around(self.xddot[-n:], decimals=5)
        print '\n\nself.yddot[-n:] = ',around(self.yddot[-n:], decimals=5)
        print '\n\nself.zddot[-n:] = ',around(self.zddot[-n:], decimals=5)

        print '\n\nself.x_integral_error[-n:] = ',around(self.x_integral_error[-n:], decimals=5)
        print '\n\nself.y_integral_error[-n:] = ',around(self.y_integral_error[-n:], decimals=5)
        print '\n\nself.z_integral_error[-n:] = ',around(self.z_integral_error[-n:], decimals=5)

        print '\n\n'
#-------------------------------------------------------------------------------

if __name__ == "__main__":

    a = agent(x_0 = 0,
              y_0 = 0,
              z_0 = 0,
              initial_setpoint_x = 1,
              initial_setpoint_y = 1,
              initial_setpoint_z = 1,
              agent_priority = 1)



    #the following gains worked well for a setpoint of (1,1,1)

    a.kpx = 40      # ---------------------PID proportional gain values
    a.kpy = 40
    a.kpz = 40

    a.kdx = 20          #----------------- -----PID derivative gain values
    a.kdy = 20
    a.kdz = 10


    a.kix = .2
    a.kiy = .2
    a.kiz = 40


    a.kpphi  = 4  # gains for the angular pid control laws
```

73

```python
        a.kptheta = 4
        a.kppsi   = 4

        a.kdphi   = 10
        a.kdtheta = 10
        a.kdpsi   = 5




        for i in range(a.max_iterations):


            a.ending_iteration = i   # preemptively...

            a.system_model_block()

            a.control_block()

            x_ave = sum(a.x[-100:])/100.0
            y_ave = sum(a.y[-100:])/100.0
            z_ave = sum(a.z[-100:])/100.0

            xerr = a.x_des - x_ave
            yerr = a.y_des - y_ave
            zerr = a.z_des - z_ave


            #if i%50 == 0:
            print 'x_ave = ',x_ave
            print 'y_ave = ',y_ave
            print 'z_ave = ',z_ave

            print 'i = ',i
            print 'xerr, yerr, zerr = ',xerr,',',yerr,',',zerr
            print 'sqrt( xerr**2 + yerr**2 + zerr**2 ) = ',sqrt( xerr**2 + yerr**2 + zerr**2 )
            #a.print_dump(3)



            # Stopping Criteria: if the agent is within a 5 cm error sphere for 200 time steps ( .2 sec )

            if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) < 10**-2) and (i>50):

                print 'set point reached!!'

                print 'i = ', i

                break

            if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) > 200) and (i>50):
```

```python
        print 'you are lost!!'

        print 'i = ', i

        break

    k_th_variable_list = [
                        a.xacc_comm[-1],
                        a.yacc_comm[-1],
                        a.zacc_comm[-1],
                        a.theta_comm[-1],
                        a.phi_comm[-1],
                        a.T_comm[-1],
                        a.tao_phi_comm[-1],
                        a.tao_theta_comm[-1],
                        a.tao_psi_comm[-1],
                        a.w1_arg[-1],
                        a.w2_arg[-1],
                        a.w3_arg[-1],
                        a.w4_arg[-1],
                        a.w1[-1],
                        a.w2[-1],
                        a.w3[-1],
                        a.w4[-1],
                        a.tao_qr_frame[-1][0],
                        a.tao_qr_frame[-1][1],
                        a.tao_qr_frame[-1][2],
                        a.T[-1],
                        a.phi[-1],
                        a.theta[-1],
                        a.psi[-1],
                        a.phidot[-1],
                        a.thetadot[-1],
                        a.psidot[-1],
                        a.phiddot[-1],
                        a.thetaddot[-1],
                        a.psiddot[-1],
                        a.x[-1],
                        a.y[-1],
                        a.z[-1],
                        a.xdot[-1],
                        a.ydot[-1],
                        a.zdot[-1],
                        a.xddot[-1],
                        a.yddot[-1],
                        a.zddot[-1],
                        a.x_integral_error[-1],
                        a.y_integral_error[-1],
                        a.z_integral_error[-1],
                        ]

    for k in k_th_variable_list:

        if math.isnan(k):
```

```
                    a.print_dump(1)
887
                    break
889

891        if a.phi[-1] > 5: break
           if a.theta[-1] > 5: break
893        if a.psi[-1] > 5: break

895        if math.isnan(xerr):

897            break

899    print '#############################################\n\n'

901    a.print_dump(10)

903    fig1_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig1_agent_module.png'
       fig2_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig2_agent_module.png'
905
       a.plot_results()#False, True, fig1_file_path, fig2_file_path)
```

/home/ek/Dropbox/THESIS/python_scripts/agent_module.py

Appendix B

A module for updating the PID set point - waypointNavigation.py

breakatwhitespace

```python
from agent_module import *

def go(agent):

    for i in range(agent.max_iterations):

        a.system_model_block()

        a.control_block()

        retval = stopping_criteria(agent)

        if (retval == 0) or (retval == 1):

            print 'i = ', i

            break
#-------------------------------------------------------------------------------
def stopping_criteria(agent):

    x_ave = sum(agent.x[-100:])/100.0
    y_ave = sum(agent.y[-100:])/100.0
    z_ave = sum(agent.z[-100:])/100.0
```

```python
28      xerr = agent.x_des - x_ave
        yerr = agent.y_des - y_ave
30      zerr = agent.z_des - z_ave

32      #if i%50 == 0:
            #print 'x_ave = ',x_ave
34          #print 'y_ave = ',y_ave
            #print 'z_ave = ',z_ave
36
        print 'xerr, yerr, zerr = ',xerr,',',yerr,',',zerr
38      print 'sqrt( xerr**2 + yerr**2 + zerr**2 ) = ',sqrt( xerr**2 + yerr**2 + zerr**2 )

40      if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) < 10**-2) and (len(agent.x) >50):

42          print 'set point reached!!'

44          #print 'i = ', i

46          return 1

48      if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) > 200) and (i>50):

50          print 'you are lost!!'

52
            return 0
54
        k_th_variable_list = [
56                              a.xacc_comm[-1],a.yacc_comm[-1],a.zacc_comm[-1],
                                a.theta_comm[-1],a.phi_comm[-1],a.T_comm[-1],
58                              a.tao_phi_comm[-1],a.tao_theta_comm[-1],a.tao_psi_comm[-1],
                                a.w1_arg[-1],a.w2_arg[-1],a.w3_arg[-1],a.w4_arg[-1],
60                              a.w1[-1],a.w2[-1],a.w3[-1],a.w4[-1],
                                a.tao_qr_frame[-1][0],a.tao_qr_frame[-1][1],a.tao_qr_frame[-1][2],
62                              a.T[-1],
                                a.phi[-1],a.theta[-1],a.psi[-1],
64                              a.phidot[-1],a.thetadot[-1],a.psidot[-1],
                                a.phiddot[-1],a.thetaddot[-1],a.psiddot[-1],
66                              a.x[-1],a.y[-1],a.z[-1],
                                a.xdot[-1],a.ydot[-1],a.zdot[-1],
68                              a.xddot[-1],a.yddot[-1],a.zddot[-1],
                                a.x_integral_error[-1],a.y_integral_error[-1],a.z_integral_error[-1],
70                              ]

72      for k in k_th_variable_list:

74          if math.isnan(k):

76              a.print_dump(1)

78              return 0

80
        if a.phi[-1] > 5: return 0
82
```

```
      if a.theta[-1] > 5: return 0

      if a.psi[-1] > 5: return 0

      if math.isnan(xerr): return 0

##############################################################################

if __name__ == '__main__':

    a = agent(x_0 = 0,
              y_0 = 0,
              z_0 = 0,
              initial_setpoint_x = 1,
              initial_setpoint_y = 1,
              initial_setpoint_z = 1,
              agent_priority = 1)

    #the following gains worked well for a setpoint of (1,1,1)

    a.kpx = 15      # ----------------------PID proportional gain values
    a.kpy = 15
    a.kpz = 50

    a.kdx = 10          #----------------- -----PID derivative gain values
    a.kdy = 10
    a.kdz = 50

    a.kix = 0.8
    a.kiy = 0.8
    a.kiz = 15

    a.kpphi   = 4  # gains for the angular pid control laws
    a.kptheta = 4
    a.kppsi   = 4

    a.kdphi   = 6
    a.kdtheta = 6
    a.kdpsi   = 6
    '''
    u'a0.ending_iteration': 257,                      the  optimal run
    u'a0.kdx': 10,
    u'a0.kdy': 10,
    u'a0.kdz': 50,
    u'a0.kix': 0.8,
    u'a0.kiy': 0.8,
    u'a0.kiz': 20,
    u'a0.kpx': 15,
    u'a0.kpy': 15,
    u'a0.kpz': 40,
    u'ith_runtime': 11.414505958557129,
    u'return_val2': 1,
    u'setpoint': [1, 1, 2],
    u'total_thrust': 4969.888344602483,
    u'x_crossings': 3,
```

```
138        u'x_over_shoot': 0.024969492375947366,
           u'y_crossings': 1,
140        u'y_over_shoot': 0.01858534082026475,
           u'z_crossings': 1,
142        u'z_over_shoot': 0.09928387955818296}


144



146

           '''

148

           a.max_iterations = 1000

150

           position_setpoint_list =  [[0,0,1],[1,1,2]]  #[[1,1,1],[5,5,5],[20,20,20],[100,100,100]]
            #[[1,1,1],[5,1,1],[5,5,1],[5,5,5],[1,5,5],[1,1,5],[1,1,1]] #

152

           for ss in range(len(position_setpoint_list)):

154

               a.x_des = position_setpoint_list[ss][0]
156            a.y_des = position_setpoint_list[ss][1]
               a.z_des = position_setpoint_list[ss][2]

158

               go(a)

160


162        print '#############################################\n\n'

164        a.print_dump(10)

166        fig1_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig1_agent_module.png'
           fig2_file_path = '/home/ek/Dropbox/THESIS/python_scripts/fig2_agent_module.png'
168
           a.plot_results()
```

/home/ek/Dropbox/THESIS/python_scripts/waypoint_navigation.py

Appendix C

A class of functions that are used in the brute force method - bruteForceFunctions.py

breakatwhitespace

```python
from agent_module import *

from numpy import mean

import json
#-----------------------------------------------------------------------------
#-----------------------------------------------------------------------------

def run(agent,plots = False):

    for i in range(agent.max_iterations):

        agent.ending_iteration = i

        agent.system_model_block()

        agent.control_block()


        x_ave = sum(agent.x[-100:])/100.0
        y_ave = sum(agent.y[-100:])/100.0
        z_ave = sum(agent.z[-100:])/100.0
```

```python
25          xerr = agent.x_des - x_ave
            yerr = agent.y_des - y_ave
27          zerr = agent.z_des - z_ave

29          # Stopping Criteria: if the agent is within a n cm error sphere for 200 time steps ( .2 sec )

31          if ( sqrt( xerr**2 + yerr**2 + zerr**2 ) <10**-2) and (i>50):

33              print 'i = ', i

35              print 'set point reached'

37              return 1

39          if ( abs(zerr) > 200) and (i>50):

41              print 'i = ', i

43              print 'you are lost'

45              return 'err'

47          k_th_variable_list = [  agent.xacc_comm[-1],agent.yacc_comm[-1],agent.zacc_comm[-1],
                                    agent.theta_comm[-1],agent.phi_comm[-1],agent.T_comm[-1],
49                                  agent.tao_phi_comm[-1],agent.tao_theta_comm[-1],agent.tao_psi_comm[-1],
                                    agent.w1_arg[-1],agent.w2_arg[-1],agent.w3_arg[-1],agent.w4_arg[-1],
51                                  agent.w1[-1],agent.w2[-1],agent.w3[-1],agent.w4[-1],
                                    agent.tao_qr_frame[-1][0],agent.tao_qr_frame[-1][1],agent.tao_qr_frame
            [-1][2],
53                                  agent.T[-1],
                                    agent.phi[-1],agent.theta[-1],agent.psi[-1],
55                                  agent.phidot[-1],agent.thetadot[-1],agent.psidot[-1],
                                    agent.phiddot[-1],agent.thetaddot[-1],agent.psiddot[-1],
57                                  agent.x[-1],agent.y[-1],agent.z[-1],
                                    agent.xdot[-1],agent.ydot[-1],agent.zdot[-1],
59                                  agent.xddot[-1],agent.yddot[-1],agent.zddot[-1],
                                    agent.x_integral_error[-1],agent.y_integral_error[-1],agent.z_integral_error
            [-1],
61                                  ]

63          for k in k_th_variable_list:

65              if math.isnan(k):

67                  agent.print_dump(1)

69                  return 'err'

71              if agent.phi[-1] > 5: break
                if agent.theta[-1] > 5: break
73              if agent.psi[-1] > 5: break

75              if math.isnan(xerr):
                    print 'math.isnan(xerr) = True'
```

82

```python
                    return 'err'


#-------------------------------------------------------------------------------
#-------------------------------------------------------------------------------


def take_off():

    agent0 = agent(x_0 = 0,
                   y_0 = 0,
                   z_0 = 0,
                   initial_setpoint_x = 0,
                   initial_setpoint_y = 0,
                   initial_setpoint_z = 1,
                   agent_priority = 1)


    agent0.max_iterations = 800


    #the following gains worked well for a setpoint of (1,1,1)


    agent0.kpx = 40      # ----------------------PID proportional gain values
    agent0.kpy = 40
    agent0.kpz = 40


    agent0.kdx = 25          #----------------- -----PID derivative gain values
    agent0.kdy = 25
    agent0.kdz = 40


    agent0.kix = .2
    agent0.kiy = .2
    agent0.kiz = 40


    run(agent0)


    return agent0   # return the agent instance hovering at (0,0,1)


#---------------------------------------------------------------------------
#---------------------------------------------------------------------------
def test_gain_vector(a0, set_point, gain_dictionary):

    a0.x_des = set_point[0]
    a0.y_des = set_point[1]
    a0.z_des = set_point[2]


    a0.max_iterations = 1000


    a0.kpx = gain_dictionary['kpxy']
    a0.kix = gain_dictionary['kixy']
    a0.kdx = gain_dictionary['kdxy']


    a0.kpy = gain_dictionary['kpxy']
    a0.kiy = gain_dictionary['kixy']
    a0.kdy = gain_dictionary['kdxy']


    a0.kpz = gain_dictionary['kpz']
```

```python
        a0.kiz = gain_dictionary['kiz']
        a0.kdz = gain_dictionary['kdz']


        return_val2 = run(a0)
        '''
        #-------------------------------------------------------
        variable_dictionary = {
                    'a0.xacc_comm' : a0.xacc_comm,'a0.yacc_comm' : a0.yacc_comm,'a0.zacc_comm' : a0.zacc_comm,
                    'a0.theta_comm' : a0.theta_comm,'a0.phi_comm' : a0.phi_comm,'a0.T_comm' : a0.T_comm,
                    'a0.tao_phi_comm' : a0.tao_phi_comm,'a0.tao_theta_comm' : a0.tao_theta_comm,'a0.tao_psi_comm'
          : a0.tao_psi_comm,
                    'a0.w1_arg' : a0.w1_arg,'a0.w2_arg' : a0.w2_arg,'a0.w3_arg' : a0.w3_arg,'a0.w4_arg' : a0.
          w4_arg,
                    'a0.w1' : a0.w1,'a0.w2' : a0.w2,'a0.w3' : a0.w3,'a0.w4' : a0.w4,
                    'a0.tao_qr_frame[0]' : a0.tao_qr_frame[0].tolist(),'a0.tao_qr_frame[1]' : a0.tao_qr_frame[1].
          tolist(),'a0.tao_qr_frame[2]' : a0.tao_qr_frame[2].tolist(),
                    'a0.T' : a0.T,
                    'a0.phi' : a0.phi,'a0.theta' : a0.theta,'a0.psi' : a0.psi,
                    'a0.phidot' : a0.phidot,'a0.thetadot' : a0.thetadot,'a0.psidot' : a0.psidot,
                    'a0.phiddot' : a0.phiddot,'a0.thetaddot' : a0.thetaddot,'a0.psiddot' : a0.psiddot,
                    'a0.x' : a0.x,'a0.y' : a0.y,'a0.z' : a0.z,
                    'a0.xdot' : a0.xdot,'a0.ydot' : a0.ydot,'a0.zdot' : a0.zdot,
                    'a0.xddot' : a0.xddot,'a0.yddot' : a0.yddot,'a0.zddot' : a0.zddot,
                    'a0.x_integral_error' : a0.x_integral_error,
                    'a0.y_integral_error' : a0.y_integral_error,
                    'a0.z_integral_error' : a0.z_integral_error,
                    }
        #-------------------------------------------------------
        '''
        if return_val2 != 1:


            test_run_dictionary = {'setpoint':set_point,
                                    'a0.kpx' : a0.kpx,
                                    'a0.kix' : a0.kix,
                                    'a0.kdx' : a0.kdx,
                                    'a0.kpy' : a0.kpy,
                                    'a0.kiy' : a0.kiy,
                                    'a0.kdy' : a0.kdy,
                                    'a0.kpz' : a0.kpz,
                                    'a0.kiz' : a0.kiz,
                                    'a0.kdz' : a0.kdz,
                                    'return_val2' : return_val2,
                                    'a0.ending_iteration' : a0.ending_iteration
                                    }#'variable_dictionary':variable_dictionary
                                    #}

            return test_run_dictionary



        elif return_val2 ==1:


            #need to calculate the number of times the state crosses the setpoint value:
```

```python
185         x_crossings = 0
            y_crossings = 0
187         z_crossings = 0

189         for i in range(len(a0.x)-1):

191             if sign( a0.x[i] - a0.x_des ) != sign( a0.x[i+1] - a0.x_des ) :

193                 x_crossings += 1

195
                if sign( a0.y[i] - a0.y_des ) != sign( a0.y[i+1] - a0.y_des ) :
197
                    y_crossings += 1
199

201             if sign( a0.z[i] - a0.z_des ) != sign( a0.z[i+1] - a0.z_des ) :

203                 z_crossings += 1

205

207

        #------------------------------------------------------
209

211         if (max(a0.x) - a0.x_des) > 0: x_over_shoot = max(a0.x) - a0.x_des

213         if (max(a0.y) - a0.y_des) > 0: y_over_shoot = max(a0.y) - a0.y_des

215         if (max(a0.z) - a0.z_des) > 0: z_over_shoot = max(a0.z) - a0.z_des

217

        #------------------------------------------------------
219

221
            test_run_dictionary = {'setpoint':set_point,
223                                    'a0.kpx' : a0.kpx,
                                       'a0.kix' : a0.kix,
225                                    'a0.kdx' : a0.kdx,
                                       'a0.kpy' : a0.kpy,
227                                    'a0.kiy' : a0.kiy,
                                       'a0.kdy' : a0.kdy,
229                                    'a0.kpz' : a0.kpz,
                                       'a0.kiz' : a0.kiz,
231                                    'a0.kdz' : a0.kdz,
                                       'return_val2' : return_val2,
233                                    'a0.ending_iteration' : a0.ending_iteration,
                                       'total_thrust' : sum(a0.T),
235                                    'x_over_shoot':x_over_shoot,
                                       'y_over_shoot':y_over_shoot,
237                                    'z_over_shoot':z_over_shoot,
                                       'x_crossings':x_crossings,
```

```python
                                        'y_crossings':y_crossings,
                                        'z_crossings':z_crossings
                                        }

            return test_run_dictionary

#-------------------------------------------------------------------------------
'''
{   u'a0.ending_iteration': 266,
    u'a0.kdx': 5,
    u'a0.kdy': 5,
    u'a0.kdz': 20,
    u'a0.kix': 0.8,
    u'a0.kiy': 0.8,
    u'a0.kiz': 15,
    u'a0.kpx': 5,
    u'a0.kpy': 5,
    u'a0.kpz': 30,
    u'ith_runtime': 7.14291787147522,
    u'return_val2': 1,
    u'setpoint': [1, 1, 2],
    u'total_thrust': 4973.812742102159,
    u'x_crossings': 1,
    u'x_over_shoot': 0.06537601013649552,
    u'y_crossings': 1,
    u'y_over_shoot': 0.0706587304875288,
    u'z_crossings': 1,
    u'z_over_shoot': 0.03570385076740079}

'''
#-------------------------------------------------------------------------------

if __name__ == '__main__':

    gain_dictionary = {
                        'kpxy' : 5,
                        'kpz'  : 30,
                        'kdxy' : 5,
                        'kdz'  : 20,
                        'kixy' : 0.8,
                        'kiz'  : 15}

    agent = take_off() # ----> returns the agent instance hovering at (0,0,1)

    set_point = [1,1,2]

    test_run_dictionary = test_gain_vector(agent, set_point, gain_dictionary)

    print 'test_run_dictionary = ',test_run_dictionary

    agent.plot_results()
```

/home/ek/Dropbox/THESIS/python_scripts/brute_force_functions.py

Appendix D

The brute force implementation - runSimsBruteForce.py

```
breakatwhitespace
     '''
 2   THis is a last resort , brute force approch to finding the gain vector that
     produces the lowest objective function value for a set point of (1,1,2)
 4
     each run will start with the state variable and input lists produced by the take_off
 6   function . for speed this data will be read from a json file which is produced beforehand
 8   for each run the ku gain variable will be incremented by 5 and the objective function measured
     '''
10   import sys
     from numpy import arange
12   from brute_force_functions import *
     from datetime import datetime
14   import json
     import time
16   '''
     gain_dictionary = {
18                      'kpxy' : 10,
                        'kpz'  : 40,
20                      'kdxy' : 10,
                        'kdz'  : 40,
22                      'kixy' : 0.5,
                        'kiz'  : 25}
24   '''

26   global_start_time = time.time()
```

```python
kpxy_range = arange(5,30,5)

kpz_range = arange(20,70,10)

kdxy_range = arange(5,30,5)

kdz_range = arange(20,70,10)

kixy_range = arange(0.2,1.0,0.2)

kiz_range = arange(15,45,5)

print 'kpxy_range = ',kpxy_range

print 'kpz_range = ',kpz_range

print 'kdxy_range = ',kdxy_range

print 'kdz_range = ',kdz_range

print 'kixy_range = ',kixy_range

print 'kiz_range = ',kiz_range

number_of_sims = len(kpxy_range)*len(kpz_range)*len(kdxy_range)*len(kdz_range)*len(kixy_range)*len(kiz_range)

print 'number_of_sims = ',number_of_sims


index = int(sys.argv[1])

runtimes = []
run_dictionaries = []

for kpxy in [kpxy_range[index]]:
    for kpz in kpz_range:
        for kdxy in kdxy_range:
            for kdz in kdz_range:
                for kixy in kixy_range:

                    date_and_time = datetime.now().strftime('%Y-%m-%d__%H.%M.%S')

                    filepath = '/home/ek/Dropbox/THESIS/python_scripts/brute_force_output_data/
        bruteforce_output_index'+str(index)+'_' + date_and_time+ '.json'

                    with open(filepath, 'wb') as fp:
                        json.dump(run_dictionaries, fp)
                        fp.close()


                    run_dictionaries = []

                    for kiz in kiz_range:
```

```python
82                             gain_dictionary = {

                                         'kpxy' : kpxy,
84                                       'kpz'  : kpz,
                                         'kdxy' : kdxy,
86                                       'kdz'  : kdz,
                                         'kixy' : kixy,
88                                       'kiz'  : kiz}

90                     print '\ngain_dictionary = ',gain_dictionary

92                     ith_starttime = time.time()

94                     agent = take_off() # ----> returns the agent instance hovering at (0,0,1)

96                     set_point = [1,1,2]

98                     test_run_dictionary = test_gain_vector(agent, set_point, gain_dictionary)

100                    test_run_dictionary['ith_runtime'] = time.time() - ith_starttime

102                    print 'test_run_dictionary = ',test_run_dictionary

104                    run_dictionaries.append( test_run_dictionary )

106                    #--------------------------------------------------------


108
    total_run_time = time.time() - global_start_time
110


112
    date_and_time = datetime.now().strftime('%Y-%m-%d__%H.%M.%S')
114
    filepath = '/home/ek/Dropbox/THESIS/python_scripts/brute_force_output_data/bruteforce_output_index'+str(index
          )+'_' + date_and_time+ '.json'
116
    with open(filepath, 'wb') as fp:
118     json.dump(run_dictionaries, fp)
        fp.close()
120


122 '''
    for r in run_dictionaries:
124
        for kee in r.keys():
126
            if kee != 'variable_dictionary':
128
                print kee,r[kee]
130 '''
```

/home/ek/Dropbox/THESIS/python_scripts/run_sims_brute_force.py

Appendix E

A module to sort the results of the brute force method - parseResults.py

```
breakatwhitespace
2
  import os
4 import json
  import itertools
6 from operator import itemgetter
  import pprint
8 pp = pprint.PrettyPrinter(indent=4)
  import numpy
10
  '''
12 def obj_fun(d):

14     of = d['total_thrust']

16     return of
  '''
18


20

22 # need to go through all the output files and make a list of all the sims that still need to be run:
```

```python
output_dir = '/home/ek/Dropbox/THESIS/python_scripts/brute_force_output_data/'

output_file_names = [fn for fn in os.listdir(output_dir)]

output_file_paths = [output_dir + ofn for ofn in output_file_names]


data = []

for ofp in output_file_paths:

    with open(ofp, 'rb') as fp:
        output_data = json.load(fp)

        data = data + output_data

#--------------------------------------collect the runs that actually converged

good_runs = []

for d in data:

    if d['return_val2'] == 1:

        good_runs.append(d)

number_of_convergent_runs = len(good_runs)

# -------------------------------------create a list of total thrust values from the convergent runs

T_list = [g['total_thrust'] for g in good_runs]

T_min = numpy.amin(T_list)
T_ave = numpy.mean(T_list)


# ---------------------------------------for the runs that actually converged, find the ones that satisfied
        the overshoot criteria

min_overshoot_runs = []

for g in good_runs:

    if ( g['x_over_shoot'] < 0.1 ) and ( g['y_over_shoot'] < 0.1 ) and ( g['z_over_shoot'] < 0.1 ):

        min_overshoot_runs.append(g)



min_oscillation_runs = []

for r in min_overshoot_runs:

    if (r['x_crossings'] < 4) and (r['y_crossings'] < 4) and (r['z_crossings'] < 4) :
```

```
78            min_oscillation_runs.append(r)


80


82 thrust_sorted_good_runs = sorted(min_oscillation_runs, key=itemgetter('total_thrust'))

84 for t in thrust_sorted_good_runs[:20]:
       print '\n'
86     pp.pprint(t)


88
   ############################################
90
   print "\n\nnumber_of_convergent_runs = ",  number_of_convergent_runs
92
   print "minimum thrust = ", T_min
94
   print "average total thrust = " , T_ave
96
   print "number_of_runs_with_satisfactory_overshoot = ", len(min_overshoot_runs)
98
   ave_x_crossings = numpy.mean([g['x_crossings'] for g in good_runs])
100 ave_y_crossings = numpy.mean([g['y_crossings'] for g in good_runs])
   ave_z_crossings = numpy.mean([g['z_crossings'] for g in good_runs])
102
   print 'ave_x_crossings = ', ave_x_crossings
104 print 'ave_y_crossings = ', ave_y_crossings
   print 'ave_z_crossings = ', ave_z_crossings
106
   ave_x_overshoot = numpy.mean([g['x_over_shoot']for g in good_runs])
108 ave_y_overshoot = numpy.mean([g['y_over_shoot']for g in good_runs])
   ave_z_overshoot = numpy.mean([g['z_over_shoot']for g in good_runs])
110
   print 'ave_x_overshoot = ' , ave_x_overshoot
112 print 'ave_y_overshoot = ' , ave_y_overshoot
   print 'ave_z_overshoot = ' , ave_z_overshoot
114
   print "number_of_runs_with_satisfactory_oscillations =  ", len(min_oscillation_runs)
116


118


120 # according to the available data, here is the best run...
   '''
122 {   u'a0.ending_iteration': 266,
       u'a0.kdx': 5,
124     u'a0.kdy': 5,
       u'a0.kdz': 20,
126     u'a0.kix': 0.8,
       u'a0.kiy': 0.8,
128     u'a0.kiz': 15,
       u'a0.kpx': 5,
130     u'a0.kpy': 5,
       u'a0.kpz': 30,
132     u'ith_runtime': 7.14291787147522,
```

```
          u'return_val2': 1,
134       u'setpoint': [1, 1, 2],
          u'total_thrust': 4973.812742102159,
136       u'x_crossings': 1,
          u'x_over_shoot': 0.06537601013649552,
138       u'y_crossings': 1,
          u'y_over_shoot': 0.0706587304875288,
140       u'z_crossings': 1,
          u'z_over_shoot': 0.03570385076740079}
142


144


146  '''
```

/home/ek/Dropbox/THESIS/python_scripts/parse_results.py

Appendix F

The finite difference method applied to the optimal control BVP - finiteDiffSolution.py

breakatwhitespace

```python
from os import system

from numpy import cos as c , sin as s , array as a , concatenate , arange , sqrt, reshape, log

from numpy import dot
from numpy.linalg import inv
from numpy.linalg import norm
from numpy import transpose
global ixx
global iyy
global izz

ixx = 5.0*10**-3
iyy = 5.0*10**-3
izz = 10.0*10**-3

global g
global s
global l
global b
global m
global h
global d
```

```
24
   g = -9.8
26 alpha = 0.001
   l = 0.25    # m
28 b = 0.001
   m = 1.
30
   h = 0.1
32
   d = 0.0001 # the value for adding to the input variables of f to express the finite differences
34
   #---------------------------------------------------------------the jacobian for transforming from body frame to
        inertial frame
36
   def J(ph,th):
38
       jac = a([
40     [ixx          , 0                                   , -ixx * s(th)
                      ],
       [0            , iyy*(c(ph)**2) + izz * s(ph)**2   , (iyy-izz)*c(ph)*s(ph)*c(th)
                      ],
42     [-ixx*s(th) , (iyy-izz)*c(ph)*s(ph)*c(th)        , ixx*(s(th)**2) + iyy*(s(th)**2)*(c(th)**2) + izz*(c(ph)
         **2)*(c(th)**2)]
       ])
44
       #print '\n\njac = \n',jac
46


48     return jac
50


52


54


56
   #
       ----------------------------------------------------------------------------------------------------------------------

58


60 def coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1 ,
        partial_with_respect_to ):

62     # the argument 'partial_with_respect_to' specifies the angular quantity for which the derivative is bein
        computed

64     # note that   'partial_with_respect_to'  MUST be a string

66     # if the standard coriolis matrix is needed, the argument: 'partial_with_respect_to' should be set to
        None

68     if partial_with_respect_to == 'phd':    phd =  ( ( ph_k - ph_k_minus_1 ) / h ) + d
```

```python
    else: phd = ( ph_k - ph_k_minus_1 ) / h


    if partial_with_respect_to == 'thd':   thd =  ( ( th_k - th_k_minus_1 ) / h ) + d

    else: thd =   ( th_k - th_k_minus_1 ) / h


    if partial_with_respect_to == 'psd':    psd = ( ( ps_k - ps_k_minus_1 ) / h  ) + d

    else: psd =   ( ps_k - ps_k_minus_1 ) / h


    # here are the elements in the matrix

    c11 = 0

    c12 = (iyy-izz) * ( thd*c(ph_k)*s(ph_k) + psd*c(th_k)*s(ph_k)**2 )  + (izz-iyy)*psd*(c(ph_k)**2)*c(th_k)
      - ixx*psd*c(th_k)

    c13 = (izz-iyy) * psd * c(ph_k) * s(ph_k) * c(th_k)**2

    c21 = (izz-iyy) * ( thd*c(ph_k)*s(ph_k) + psd*s(ph_k)*c(th_k) ) + (iyy-izz) * psd * (c(ph_k)**2) * c(th_k
     ) + ixx * psd * c(th_k)

    c22 = (izz-iyy)*phd*c(ph_k)*s(ph_k)

    c23 = -ixx*psd*s(th_k)*c(th_k) + iyy*psd*(s(ph_k)**2)*s(th_k)*c(th_k)

    c31 = (iyy-izz)*phd*(c(th_k)**2)*s(ph_k)*c(ph_k) - ixx*thd*c(th_k)

    c32 = (izz-iyy)*( thd*c(ph_k)*s(ph_k)*s(th_k) + phd*(s(ph_k)**2)*c(th_k) ) + (iyy-izz)*phd*(c(ph_k)**2)*c
     (th_k) + ixx*psd*s(th_k)*c(th_k) - iyy*psd*(s(ph_k)**2)*s(th_k)*c(th_k) - izz*psd*(c(ph_k)**2)*s(th_k)*
     c(th_k)

    c33 = (iyy-izz) * phd *c(ph_k)*s(ph_k)*(c(th_k)**2) - iyy * thd*(s(ph_k)**2) * c(th_k)*s(th_k) - izz*thd
     *(c(ph_k)**2)*c(th_k)*s(th_k) + ixx*thd*c(th_k)*s(th_k)


    cm = a([[c11,c12,c13],
             [c21,c22,c23],
             [c31,c32,c33]])



    #print '\n\ncm = \n',cm



    return cm
```

```python
#
      -------------------------------------------------------------------------------------------------------------


# the function f will be used as the state equations as well as for the many partial derivatives

def f(x , x_k_minus_1 , x_k_minus_2 ,
      y , y_k_minus_1 , y_k_minus_2 ,
      z , z_k_minus_1 , z_k_minus_2 ,
      ph_k , ph_k_minus_1 , ph_k_minus_2,
      th_k , th_k_minus_1 , th_k_minus_2,
      ps_k , ps_k_minus_1 , ps_k_minus_2,
      u1_k , u2_k , u3_k , u4_k ):

    T = alpha * (u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2)
    #print '\nT = ',T


    xdd = (1/h**2) * ( x - 2*x_k_minus_1 - x_k_minus_2 )

    x_residual = T/m * ( c(ps_k) * s(th_k) * c(ph_k) + s(ps_k) * s(ph_k) )   #  F1


    ydd =  (1/h**2) * ( x - 2*y_k_minus_1 - y_k_minus_2 )

    y_residual = T/m * ( s(ps_k) * s(th_k) * c(ph_k) + c(ps_k) * s(ph_k) )   #  F2


    zdd =  (1/h**2) * ( x - 2*z_k_minus_1 - z_k_minus_2 )

    z_residual = T/m * c(th_k) * c(ph_k) + g   #  F3


    # the angular equations are better kept as vectors and matrices


    input_func_vector = a([
                           l * alpha * ( -u2_k**2 + u4_k**2 ) ,
                           l * alpha * ( -u1_k**2 + u3_k**2 ) ,
                           b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
                         ])
    #print '\ninput_func_vector = ',input_func_vector

    coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, None )
    #print '\ncoriolis_k = ',coriolis_k


    ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h , (th_k - th_k_minus_1)/h , ( ps_k - ps_k_minus_1)/h ] )
    #print '\nang_vel_vector = ',ang_vel_vector
```

97

```python
174

176         # this is the large bracketed factor which is multiplied into the inverse of the jacobian

178         temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )
            #print '\ntemp_factor = ',temp_factor
180


182
            etadd = ( 1/h**2 ) * a([
184                             ph_k - 2* ph_k_minus_1 - ph_k_minus_2,
                                th_k - 2* th_k_minus_1 - th_k_minus_2,
186                             ps_k - 2* ps_k_minus_1 - ps_k_minus_2,
                            ])
188
            angular_residual = dot( inv( J(ph_k,th_k) ) , temp_factor ) - etadd
190         #print '\netadd = ',etadd

192
            state_equations_residual = a( [ x_residual , y_residual , z_residual ,angular_residual[0] ,
             angular_residual[1] , angular_residual[2] ] )
194
            #print '\n\nstate_equations_residual = \n',state_equations_residual
196


198
            return state_equations_residual
200


202

204 #
        -------------------------------------------------------------------------------------------------------------------


206 # The costate

208 def costate(x_k , x_k_minus_1 , x_k_minus_2 ,
                y_k , y_k_minus_1 , y_k_minus_2 ,
210             z_k , z_k_minus_1 , z_k_minus_2 ,
                ph_k , ph_k_minus_1 , ph_k_minus_2,
212             th_k , th_k_minus_1 , th_k_minus_2,
                ps_k , ps_k_minus_1 , ps_k_minus_2,
214             u1_k , u2_k , u3_k , u4_k,
                la1_k , la1_k_minus_1 , la1_k_minus_2,
216             la2_k , la2_k_minus_1 , la2_k_minus_2,
                la3_k , la3_k_minus_1 , la3_k_minus_2,
218             la4_k , la4_k_minus_1 , la4_k_minus_2,
                la5_k , la5_k_minus_1 , la5_k_minus_2,
220             la6_k , la6_k_minus_1 , la6_k_minus_2
                ):

222
            # this is the list of state equations differenciated with respect to phi:
224
```

```python
        ff =  f(x , x_k_minus_1 , x_k_minus_2 ,
          y , y_k_minus_1 , y_k_minus_2 ,
          z , z_k_minus_1 , z_k_minus_2 ,
          ph_k , ph_k_minus_1 , ph_k_minus_2,
          th_k , th_k_minus_1 , th_k_minus_2,
          ps_k , ps_k_minus_1 , ps_k_minus_2,
          u1_k , u2_k , u3_k , u4_k )


        f_at_phi_plus_d =  f(x , x_k_minus_1 , x_k_minus_2 ,
          y , y_k_minus_1 , y_k_minus_2 ,
          z , z_k_minus_1 , z_k_minus_2 ,
          ph_k + d, ph_k_minus_1 , ph_k_minus_2,
          th_k    , th_k_minus_1 , th_k_minus_2,
          ps_k    , ps_k_minus_1 , ps_k_minus_2,
          u1_k , u2_k , u3_k , u4_k )

        del_f_d_phi = ( f_at_phi_plus_d - ff )/d


        f_at_theta_plus_d =  f(x , x_k_minus_1 , x_k_minus_2 ,
          y , y_k_minus_1 , y_k_minus_2 ,
          z , z_k_minus_1 , z_k_minus_2 ,
          ph_k , ph_k_minus_1 , ph_k_minus_2,
          th_k + d, th_k_minus_1 , th_k_minus_2,
          ps_k    , ps_k_minus_1 , ps_k_minus_2,
          u1_k    , u2_k , u3_k , u4_k )

        del_f_d_theta = ( f_at_theta_plus_d - ff )/d



        f_at_psi_plus_d =  f(x , x_k_minus_1 , x_k_minus_2 ,
          y , y_k_minus_1 , y_k_minus_2 ,
          z , z_k_minus_1 , z_k_minus_2 ,
          ph_k    , ph_k_minus_1 , ph_k_minus_2,
          th_k    , th_k_minus_1 , th_k_minus_2,
          ps_k + d, ps_k_minus_1 , ps_k_minus_2,
          u1_k , u2_k , u3_k , u4_k )

        del_f_d_psi = ( f_at_psi_plus_d - ff )/d


        state_transition_matrix = a( [  del_f_d_phi ,
                                        del_f_d_theta,
                                        del_f_d_psi    ] )

        #print '\n\nstate_transition_matrix = ',state_transition_matrix


        lam = a( [ la1_k , la2_k , la3_k , la4_k , la5_k , la6_k ] )

        la_k_double_dot = (1/h)*a([
```

```python
                                      la1_k - 2* la1_k_minus_1 - la1_k_minus_2  ,
                                      la2_k - 2* la2_k_minus_1 - la2_k_minus_2  ,
                                      la3_k - 2* la3_k_minus_1 - la3_k_minus_2  ,
                                      la4_k - 2* la4_k_minus_1 - la4_k_minus_2  ,
                                      la5_k - 2* la5_k_minus_1 - la5_k_minus_2  ,
                                      la6_k - 2* la6_k_minus_1 - la6_k_minus_2
                                  ])


    costate_residual_vector  =  dot( state_transition_matrix , lam ) - la_k_double_dot[3:]
    #print '\n\ncostate_residual_vector = \n',costate_residual_vector
    return costate_residual_vector



#
    -----------------------------------------------------------------------------------------------------------------------


# we must compute the partials of the angular state equations ( etadd ) with respect to the angular
    velocities ( phi_dot , theta_dot , psi_dot )



# this function just evaluates the angular state equations replacing "(ph_k - ph_k_minus_1)/h "   with   "( (
    ph_k - ph_k_minus_1)/h ) + d"

def etadd_with_phi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
    u3_k , u4_k ):

    input_func_vector = a([
                            l * alpha * ( -u2_k**2 + u4_k**2 ) ,
                            l * alpha * ( -u1_k**2 + u3_k**2 ) ,
                            b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
                          ])

    coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, 'phd' )

    ang_vel_vector = a( [ ( (ph_k - ph_k_minus_1)/h ) + d , (th_k - th_k_minus_1)/h , ( ps_k - ps_k_minus_1)/
     h ] )

    temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )

    etadd_phi_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
    #print '\n\netadd_phi_plus_d = \n',etadd_phi_plus_d
    return a( etadd_phi_plus_d )



def etadd_with_theta_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
    u3_k , u4_k ):

    input_func_vector = a([
                            l * alpha * ( -u2_k**2 + u4_k**2 ) ,
                            l * alpha * ( -u1_k**2 + u3_k**2 ) ,
```

```python
                                         b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
                                    ])

    coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, 'thd' )

    ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h, ( (th_k - th_k_minus_1)/h ) + d   , ( ps_k - ps_k_minus_1)/
     h ] )

    temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )

    etadd_theta_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
    #print '\n\netadd_theta_plus_d = \n',etadd_theta_plus_d
    return a( etadd_theta_plus_d )



def etadd_with_psi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
     u3_k , u4_k ):

    input_func_vector = a([
                              l * alpha * ( -u2_k**2 + u4_k**2 ) ,
                              l * alpha * ( -u1_k**2 + u3_k**2 ) ,
                              b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
                            ])

    coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, 'psd' )

    ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h, (th_k - th_k_minus_1)/h , ( ( ps_k - ps_k_minus_1)/h ) + d
      ] )

    temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )

    etadd_psi_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
    #print '\n\netadd_psi_plus_d = \n',etadd_psi_plus_d
    return a( etadd_psi_plus_d )



# this is just the plain ole angular state equation vector

def etadd( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k , u3_k , u4_k ):

    input_func_vector = a([
                              l * alpha * ( -u2_k**2 + u4_k**2 ) ,
                              l * alpha * ( -u1_k**2 + u3_k**2 ) ,
                              b*(u1_k**2 + u2_k**2 + u3_k**2 + u4_k**2) ,
                            ])

    coriolis_k = coriolis_matrix( ph_k , th_k , ps_k , ph_k_minus_1 , th_k_minus_1 , ps_k_minus_1, None )

    ang_vel_vector = a( [ (ph_k - ph_k_minus_1)/h, (th_k - th_k_minus_1)/h , ( ps_k - ps_k_minus_1)/h ] )

    temp_factor = input_func_vector - dot( coriolis_k , ang_vel_vector )
```

```python
380      etadd_theta_plus_d = dot( inv( J(ph_k,th_k) ) , temp_factor )
         #print '\n\netadd_theta_plus_d = \n',etadd_theta_plus_d
382      return a( etadd_theta_plus_d )


384

386  #
         ---------------------------------------------------------------------------------------------------------------
         print '\n\n = \n',

388  # The algebraic costate equations

390  def algebraic_costate_equations (
                 ph_k , ph_k_minus_1, th_k , th_k_minus_1 , ps_k , ps_k_minus_1,
392              u1_k , u2_k , u3_k , u4_k,
                 la4_k ,
394              la5_k ,
                 la6_k
396              ):

398      # the pnumeonic for the following three assignments is ppd -> phi plus d
         ppd = etadd_with_phi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k ,
          u2_k , u3_k , u4_k )
400
         tpd = etadd_with_theta_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k ,
          u2_k , u3_k , u4_k )
402
         ppd = etadd_with_psi_plus_d( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k ,
          u2_k , u3_k , u4_k )
404

406      eta_douple_dot = etadd( ph_k , ph_k_minus_1 , th_k , th_k_minus_1 , ps_k , ps_k_minus_1 , u1_k , u2_k ,
          u3_k , u4_k )

408
         del_f_d_phi_dot = (ppd-eta_douple_dot)/d
410
         del_f_d_theta_dot = (tpd-eta_douple_dot)/d
412
         del_f_d_psi_dot = (ppd-eta_douple_dot)/d
414

416      algebraic_transition_matrix = a( [  del_f_d_phi_dot , del_f_d_theta_dot , del_f_d_psi_dot  ]  )#.reshape
          ([3,3])

418      #print '\n\nalgebraic_transition_matrix = ',algebraic_transition_matrix

420
         la4_through_6 = a( [ la4_k , la5_k , la6_k ] )
422      #print '\n\nla4_through_6 = ',la4_through_6

424      algebraic_costate_equations_residual_vector  =  dot( algebraic_transition_matrix , la4_through_6 )
         #print '\n\nalgebraic_costate_equations_residual_vector = \n',algebraic_costate_equations_residual_vector
426      return algebraic_costate_equations_residual_vector
```

```
428
      #-------------------------------------------------------------------------------------# stationarity
          conditions:
430


432
      def stationarity_conditions( x_k , x_k_minus_1 , x_k_minus_2 ,
434                  y_k , y_k_minus_1 , y_k_minus_2 ,
                     z_k , z_k_minus_1 , z_k_minus_2 ,
436                  ph_k , ph_k_minus_1 , ph_k_minus_2,
                     th_k , th_k_minus_1 , th_k_minus_2,
438                  ps_k , ps_k_minus_1 , ps_k_minus_2,
                     u1_k , u2_k , u3_k , u4_k,
440                  la1_k , la2_k ,la3_k , la4_k , la5_k , la6_k ):


442
          ff = f( x , x_k_minus_1 , x_k_minus_2 ,
444        y , y_k_minus_1 , y_k_minus_2 ,
           z , z_k_minus_1 , z_k_minus_2 ,
446        ph_k , ph_k_minus_1 , ph_k_minus_2,
           th_k , th_k_minus_1 , th_k_minus_2,
448        ps_k , ps_k_minus_1 , ps_k_minus_2,
           u1_k , u2_k , u3_k , u4_k )

450


452       ff_u1_k_plus_d = f( x , x_k_minus_1 , x_k_minus_2 ,
           y , y_k_minus_1 , y_k_minus_2 ,
454        z , z_k_minus_1 , z_k_minus_2 ,
           ph_k , ph_k_minus_1 , ph_k_minus_2,
456        th_k , th_k_minus_1 , th_k_minus_2,
           ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k + d, u2_k     , u3_k     ,  u4_k )
458
          ff_u2_k_plus_d = f( x , x_k_minus_1 , x_k_minus_2 ,
460        y , y_k_minus_1 , y_k_minus_2 ,
           z , z_k_minus_1 , z_k_minus_2 ,
462        ph_k , ph_k_minus_1 , ph_k_minus_2,
           th_k , th_k_minus_1 , th_k_minus_2,
464        ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k    , u2_k + d , u3_k     ,  u4_k )

466       ff_u3_k_plus_d = f( x , x_k_minus_1 , x_k_minus_2 ,
           y , y_k_minus_1 , y_k_minus_2 ,
468        z , z_k_minus_1 , z_k_minus_2 ,
           ph_k , ph_k_minus_1 , ph_k_minus_2,
470        th_k , th_k_minus_1 , th_k_minus_2,
           ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k    , u2_k     , u3_k + d , u4_k )
472
          ff_u4_k_plus_d = f( x , x_k_minus_1 , x_k_minus_2 ,
474        y , y_k_minus_1 , y_k_minus_2 ,
           z , z_k_minus_1 , z_k_minus_2 ,
476        ph_k , ph_k_minus_1 , ph_k_minus_2,
           th_k , th_k_minus_1 , th_k_minus_2,
478        ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k    , u2_k     , u3_k     , u4_k +d )


480
          # note this is the TRANSPOSE of the matrix of partials of f WRT u
```

103

```
482
        dfdq1 = (ff_u1_k_plus_d - ff)/d
484     dfdq2 = (ff_u2_k_plus_d - ff)/d
        dfdq3 = (ff_u3_k_plus_d - ff)/d
486     dfdq4 = (ff_u4_k_plus_d - ff)/d


488     lambda_k =   [ la1_k , la2_k ,la3_k , la4_k , la5_k , la6_k ]


490     individ_rows = a([ dot( dfdq1 ,lambda_k ),
                           dot( dfdq2 ,lambda_k ),
492                        dot( dfdq3 ,lambda_k ),
                           dot( dfdq4 ,lambda_k )
494                    ])



496


498     stationarity_conditions_residual_vector =  individ_rows + 2* a( [ u1_k , u2_k , u3_k , u4_k ] )
        #print '\n\nstationarity_conditions_residual_vector = \n',stationarity_conditions_residual_vector
500     return stationarity_conditions_residual_vector


502


504


506 #----------------------------------------------------------------------------------------# the objective
        function at the kth timestep


508

    def G_at_k( x_k, x_k_minus_1 , x_k_minus_2 ,
510     y_k , y_k_minus_1 , y_k_minus_2 ,
        z_k , z_k_minus_1 , z_k_minus_2 ,
512     ph_k , ph_k_minus_1 , ph_k_minus_2,
        th_k , th_k_minus_1 , th_k_minus_2,
514     ps_k , ps_k_minus_1 , ps_k_minus_2,
        u1_k , u2_k , u3_k , u4_k,
516     la1_k , la1_k_minus_1 , la1_k_minus_2,
        la2_k , la2_k_minus_1 , la2_k_minus_2,
518     la3_k , la3_k_minus_1 , la3_k_minus_2,
        la4_k , la4_k_minus_1 , la4_k_minus_2,
520     la5_k , la5_k_minus_1 , la5_k_minus_2,
        la6_k , la6_k_minus_1 , la6_k_minus_2
522     ):


524     state_vector_residual = f(x_k , x_k_minus_1 , x_k_minus_2 ,
        y_k , y_k_minus_1 , y_k_minus_2 ,
526     z_k , z_k_minus_1 , z_k_minus_2 ,
        ph_k , ph_k_minus_1 , ph_k_minus_2,
528     th_k , th_k_minus_1 , th_k_minus_2,
        ps_k , ps_k_minus_1 , ps_k_minus_2,  u1_k , u2_k , u3_k , u4_k )
530     #print '\n\nstate_vector_residual = \n',state_vector_residual


532
        costate_residual  = costate(x_k , x_k_minus_1 , x_k_minus_2 ,
534             y_k , y_k_minus_1 , y_k_minus_2 ,
                z_k , z_k_minus_1 , z_k_minus_2 ,
```

```
536              ph_k , ph_k_minus_1 , ph_k_minus_2,
                 th_k , th_k_minus_1 , th_k_minus_2,
538              ps_k , ps_k_minus_1 , ps_k_minus_2,
                 u1_k , u2_k , u3_k , u4_k,
540              la1_k , la1_k_minus_1 , la1_k_minus_2,
                 la2_k , la2_k_minus_1 , la2_k_minus_2,
542              la3_k , la3_k_minus_1 , la3_k_minus_2,
                 la4_k , la4_k_minus_1 , la4_k_minus_2,
544              la5_k , la5_k_minus_1 , la5_k_minus_2,
                 la6_k , la6_k_minus_1 , la6_k_minus_2
546              )
        #print '\n\ncostate_residual = \n',costate_residual
548


550


552      algebraic_costate_equations_residual_vector = algebraic_costate_equations(
                 ph_k , ph_k_minus_1, th_k , th_k_minus_1 , ps_k , ps_k_minus_1,
554              u1_k , u2_k , u3_k , u4_k,
                 la4_k ,
556              la5_k ,
                 la6_k
558              )
        #print '\n\nalgebraic_costate_equations_residual_vector = \n',algebraic_costate_equations_residual_vector
560


562


564      stationarity_conditions_residual_vector = stationarity_conditions(x_k , x_k_minus_1 , x_k_minus_2 ,
                 y_k , y_k_minus_1 , y_k_minus_2 ,
566              z_k , z_k_minus_1 , z_k_minus_2 ,
                 ph_k , ph_k_minus_1 , ph_k_minus_2,
568              th_k , th_k_minus_1 , th_k_minus_2,
                 ps_k , ps_k_minus_1 , ps_k_minus_2,
570              u1_k , u2_k , u3_k , u4_k,
                 la1_k , la2_k ,la3_k , la4_k , la5_k , la6_k )
572
        #print '\n\nstationarity_conditions_residual_vector = \n',stationarity_conditions_residual_vector
574


576


578      temp_array =  a( concatenate([
                                 state_vector_residual,
580                              costate_residual,
                                 algebraic_costate_equations_residual_vector,
582                              stationarity_conditions_residual_vector])
                             )
584
        kth_residual = sum( temp_array )
586      #print '\n\nkth_residual = \n',kth_residual


588

        return kth_residual
590
```

```
#------------------------------------------------------------------------------------------
        full_objective_function

# the full objective function sums up all the contributions from each time step


def full_objective_function(N,
                                x,y,z,
                                ph,th,ps,
                                u1,u2,u3,u4,
                                la1,la2,la3,la4,la5,la6):

    glist = []

    for k in arange(2,N):

        g_k = G_at_k(
                    x[k]  , x[k-1], x[k-2],
                    y[k]  , y[k-1], y[k-2],
                    z[k]  , z[k-1], z[k-2],
                    ph[k]  , ph[k-1], ph[k-2],
                    th[k]  , th[k-1], th[k-2],
                    ps[k]  , ps[k-1], ps[k-2],
                    u1[k]  , u2[k]  , u3[k]  , u4[k],
                    la1[k]  , la1[k-1]  , la1[k-2],
                    la2[k]  , la2[k-1]  , la2[k-2],
                    la3[k]  , la3[k-1]  , la3[k-2],
                    la4[k]  , la4[k-1]  , la4[k-2],
                    la5[k]  , la5[k-1]  , la5[k-2],
                    la6[k]  , la6[k-1]  , la6[k-2]
                    )

        glist.append(g_k)

    objective_function_residual =  sum(glist)

    #print '\n\nobjective_function_residual = \n',objective_function_residual

    return objective_function_residual



#------------------------------------------------------------------------------------------ gradient


def gradient(N,
            x,y,z,
```

106

```
                ph,th,ps,
646             u1,u2,u3,u4,
                la1,la2,la3,la4,la5,la6
648            ):


650     grad = []

652     input_vars_1d = concatenate([
                                    x[2:-1],    y[2:-1],   z[2:-1],
654                                 ph[2:-1],  th[2:-1],  ps[2:-1],
                                    u1[2:-1],  u2[2:-1],  u3[2:-1],  u4[2:-1],
656                                 la1[2:-1],la2[2:-1],la3[2:-1],la4[2:-1],la5[2:-1],la6[2:-1]
                                    ])
658
        obj_func_res = full_objective_function(N,
660                         x,y,z,
                            ph,th,ps,
662                         u1,u2,u3,u4,
                            la1,la2,la3,la4,la5,la6)
664
        delta = 0.0001
666
        for i in range(len(input_vars_1d)):
668
            aug_input = []
670         #print 'aug_input  = ',aug_input

672         for j in range(len(input_vars_1d)):
                if j == i:
674                 aug_input.append(a(input_vars_1d[j] + delta) )

676             else: aug_input.append(input_vars_1d[j])

678         aug_input_parsed = reshape(aug_input, ( 16 , N ))

680         #print 'aug_input_parsed = ',aug_input_parsed

682         x_aug = aug_input_parsed[0]
            y_aug = aug_input_parsed[1]
684         z_aug = aug_input_parsed[2]
            ph_aug = aug_input_parsed[3]
686         th_aug = aug_input_parsed[4]
            ps_aug = aug_input_parsed[5]
688         u1_aug = aug_input_parsed[6]
            u2_aug = aug_input_parsed[7]
690         u3_aug = aug_input_parsed[8]
            u4_aug = aug_input_parsed[9]
692         la1_aug = aug_input_parsed[10]
            la2_aug = aug_input_parsed[11]
694         la3_aug = aug_input_parsed[12]
            la4_aug = aug_input_parsed[13]
696         la5_aug = aug_input_parsed[14]
            la6_aug = aug_input_parsed[15]
698
```

```python
            aug_obj_func_res = full_objective_function(N,
                                   x_aug,y_aug,z_aug,
                                   ph_aug,th_aug,ps_aug,
                                   u1_aug,u2_aug,u3_aug,u4_aug,
                                   la1_aug,la2_aug,la3_aug,la4_aug,la5_aug,la6_aug)


            dg = ( aug_obj_func_res - obj_func_res )/delta

            #print '\n\ndg = ',dg

            grad.append(dg)      # grad returns as a one d list...


        return a(grad)


##########################################################################################################

if __name__ == '__main__':

    from time import time

    t1 = time()

    N = 10 # the number of timesteps

    # initialize the lists that will contain the solutions for each variable

    init = a( [ 1 for i in range(N) ] )  # note this list does not include the boundary values

    xterm = a([10])
    yterm = a([10])
    zterm = a([10])

    x = concatenate([ a([0,0]) , 5 * init , xterm ])
    y = concatenate([ a([0,0]) , 5 * init , yterm ])
    z = concatenate([ a([0,0]) , 5 * init , zterm ])

    ph = concatenate([ a([0,0]) , 0.1 * init , a([0])])
    th = concatenate([ a([0,0]) , 0.1 * init , a([0])])
    ps = concatenate([ a([0,0]) , 0.1 * init , a([0])])


    # the terminal conditions for the control imputs are defined by the fact that we want the quadrotor to
     end in a hovering state

    # this means that the total thrust must equal g, and that all the imputs (motor speeds) must be the same
    '''
    g = T

    g = alpha * (u1**2 + u2**2 + u3**2 + u4**2)

    g = alpha*4*u**2
```

```python
      uterm = sqrt(g)/(4*alpha)
      '''
      uhover = sqrt(abs(g))/(4*alpha)
      #print 'uterm = ',uterm


      u1 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])
      u2 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])
      u3 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])
      u4 = concatenate([ a([uhover,uhover]) , 100 * init , a([uhover])])


      la1 = concatenate( [ a([0,0]) ,  init , a([0]) ] )

      la2 = concatenate( [ a([0,0]) ,  init , a([0]) ] )

      la3 = concatenate( [ a([0,0]) ,  init , a([0]) ] )

      la4 = concatenate( [ a([0,0]) ,  init , a([0]) ] )

      la5 = concatenate( [ a([0,0]) ,  init , a([0]) ] )

      la6 = concatenate( [ a([0,0]) ,  init , a([0]) ] )

      '''
      for i in [x,y,z,ph,th,ps,u1,u2,u3,u4,la1,la2,la3,la4,la5,la6]:
          print len(i)
      '''



      #-----------------------------------------------------------------------------



      initial_objective_function_residual = full_objective_function(N,
                                     x,y,z,
                                     ph,th,ps,
                                     u1,u2,u3,u4,
                                     la1,la2,la3,la4,la5,la6)

      #print '\n\nobjective_function_residual= \n',objective_function_residual



      obj_func_res_list = [initial_objective_function_residual]
      grad_norm_list = []


      max_iterations = 10
      tol = 1

      for iteration_number in range(max_iterations):

          grad = gradient(N,
                      x,y,z,
                      ph,th,ps,
```

```
                           u1 ,u2 ,u3 ,u4 ,
810                         la1 ,la2 ,la3 ,la4 ,la5 ,la6
                           )


814        grad_norm = norm ( a ( grad ))

816        print '----------------------------------------------iteration_number = ',iteration_number
           print '\n\ngrad = \n',grad

818


820        grad_norm_list.append ( grad_norm )


822        normalized_gradient = grad/grad_norm


824        step_size = 0.5
           '''
826        if iteration_number > 10:
               step_size = 0.01
828        elif iteration_number > 40:
               step_size = 0.001
830        elif iteration_number > 60:
               step_size = 0.0001
832        '''


834        # step in the direction opposite of the gradient
           step =  a(   ( step_size ) * normalized_gradient  )

836
           print '\n\nstep = ',step

838


840        input_vars_1d = concatenate ([
                                        x[2:-1],    y[2:-1],   z[2:-1],
842                                     ph[2:-1], th[2:-1], ps[2:-1],
                                        u1[2:-1], u2[2:-1], u3[2:-1], u4[2:-1],
844                                     la1[2:-1],la2[2:-1],la3[2:-1],la4[2:-1],la5[2:-1],la6[2:-1]
                                        ])

846


848


850        new_partial_input_vector =  reshape ( input_vars_1d - step , ( 16 , N ) )         # this does not
       contain the boundary conditions hence the 'partial'


852


854


856        x   = concatenate ([ a([0,0]) , new_partial_input_vector[0] , xterm       ])
           y   = concatenate ([ a([0,0]) , new_partial_input_vector[1] , yterm       ])
858        z   = concatenate ([ a([0,0]) , new_partial_input_vector[2] , zterm       ])
           ph  = concatenate ([ a([0,0]) , new_partial_input_vector[3] , a([0])      ])
860        th  = concatenate ([ a([0,0]) , new_partial_input_vector[4] , a([0])      ])
           ps  = concatenate ([ a([0,0]) , new_partial_input_vector[5] , a([0])      ])
862        u1  = concatenate ([ a([uhover,uhover]) , new_partial_input_vector[6] , a([uhover]) ])
```

110

```python
            u2  = concatenate([ a([uhover,uhover]) , new_partial_input_vector[7] , a([uhover]) ])
            u3  = concatenate([ a([uhover,uhover]) , new_partial_input_vector[8] , a([uhover]) ])
            u4  = concatenate([ a([uhover,uhover]) , new_partial_input_vector[9] , a([uhover]) ])
            la1 = concatenate([ a([0,0]) , new_partial_input_vector[10], a([0])      ])
            la2 = concatenate([ a([0,0]) , new_partial_input_vector[11], a([0])      ])
            la3 = concatenate([ a([0,0]) , new_partial_input_vector[12], a([0])      ])
            la4 = concatenate([ a([0,0]) , new_partial_input_vector[13], a([0])      ])
            la5 = concatenate([ a([0,0]) , new_partial_input_vector[14], a([0])      ])
            la6 = concatenate([ a([0,0]) , new_partial_input_vector[15], a([0])      ])


            print '\n\nx = \n',x
            print '\n\nphi = \n',ph
            print '\n\nu1 = \n',u1
            print '\n\nla1 = \n',la1

            objective_function_residual = full_objective_function(N,
                                    x,y,z,
                                    ph,th,ps,
                                    u1,u2,u3,u4,
                                    la1,la2,la3,la4,la5,la6)

            print '\n\nobjective_function_residual = ',objective_function_residual

            obj_func_res_list.append(objective_function_residual)


    # ----------------------------------------------------TEST FOR CONVERGENCE



            if objective_function_residual > obj_func_res_list[0]:

                print '\n\n ERROR : the new value of the objective function has exceeded the initial value'
                print '\n objective_function_residual = ',objective_function_residual
                print '\n obj_func_res_list[0] = ',obj_func_res_list[0]
                break
                #step_size = step_size*0.5



            elif grad_norm < tol:

                print 'norm_del_G < tolerance.........the process has converged!!!!'
                break



            #wait = raw_input('\n\n\npress space to continue...')


    t2 = time()

    delta_t = t2-t1
```

111

```python
918       print '-------------------------------------------------'

920       print '\n\n\ndelta_t = ',delta_t

922       #########################################################################

924



926



928

      '''

930

      delta = 0.0001

932

          for i in range(len(input_vars_1d)):

934

              aug_input = []
936           #print 'aug_input   = ',aug_input

              for j in range(len(input_vars_1d)):
                  if j == i:
940                   aug_input.append(a(input_vars_1d[j] + delta) )

942               else: aug_input.append(input_vars_1d[j])

944           aug_input_parsed = reshape(aug_input, ( 16 , N ))

946           #print 'aug_input_parsed = ',aug_input_parsed

948           x_aug = aug_input_parsed[0]
              y_aug = aug_input_parsed[1]
950           z_aug = aug_input_parsed[2]
              ph_aug = aug_input_parsed[3]
952           th_aug = aug_input_parsed[4]
              ps_aug = aug_input_parsed[5]
954           u1_aug = aug_input_parsed[6]
              u2_aug = aug_input_parsed[7]
956           u3_aug = aug_input_parsed[8]
              u4_aug = aug_input_parsed[9]
958           la1_aug = aug_input_parsed[10]
              la2_aug = aug_input_parsed[11]
960           la3_aug = aug_input_parsed[12]
              la4_aug = aug_input_parsed[13]
962           la5_aug = aug_input_parsed[14]
              la6_aug = aug_input_parsed[15]
964



966

              aug_obj_func_res = full_objective_function(N,
968                               x_aug,y_aug,z_aug,
                                 ph_aug,th_aug,ps_aug,
970                               u1_aug,u2_aug,u3_aug,u4_aug,
                                 la1_aug,la2_aug,la3_aug,la4_aug,la5_aug,la6_aug)
972
```

```
974          dg = ( aug_obj_func_res - obj_func_res )/delta

976          #print '\n\ndg = ',dg

978          grad.append(dg)    # grad returns as a one d list...

980

982
         '''
```

/home/ek/Dropbox/THESIS/quadrotor_optimal_control/finiteDiffSolution.py

Bibliography

[1] diydrones. diydrones@ONLINE, 2014. URL http://diydrones.com/.

[2] Airware. Airware@ONLINE, 2014. URL http://www.airware.com/.

[3] faa. faa@ONLINE, 2014. URL http://www.faa.gov/about/initiatives/uas/.

[4] Elizabeth Bone and Christopher C Bolkcom. *Unmanned aerial vehicles: background and issues*. Nova Science Pub Incorporated, 2004.

[5] Jack W Langelaan. Long distance/duration trajectory optimization for small uavs. In *AIAA Guidance, Navigation and Control Conference and Exhibit*, 2007.

[6] Andrew T Klesh and Pierre T Kabamba. Solar-powered aircraft: Energy-optimal path planning and perpetual endurance. *Journal of guidance, control, and dynamics*, 32(4):1320–1329, 2009.

[7] Nicholas RJ Lawrance and Salah Sukkarieh. A guidance and control strategy for dynamic soaring with a gliding uav. In *Robotics and Automation, 2009. ICRA'09. IEEE International Conference on*, pages 3632–3637. IEEE, 2009.

[8] Bora Erginer and Erdinc Altug. Modeling and pd control of a quadrotor vtol vehicle. pages 894–899, 2007.

[9] Samir Bouabdallah, Andre Noth, and Roland Siegwart. Pid vs lq control techniques applied to an indoor micro quadrotor. 3:2451–2456, 2004. URL http://citeseerx.ist.psu.edu/viewdoc/download?rep=rep1&type=pdf&doi=10.1.1.149.6169.

[10] Teppo Luukkonen. Modelling and control of quadcopter. *Aalto University*, August 2011.

[11] Jerry B Marion and Stephen T Thornton. *Classical dynamics of particles and systems.* Saunders College Pub., 1995.

[12] Cornelius Lanczos. *The variational principles of mechanics*, volume 4. Courier Dover Publications, 1970.

[13] J. Bernoulli. *Bending of light rays in transparent non-uniform media and the Solution to the problem of determing the Brachistochrone curve.* 1697.

[14] L.Euler. *Methodus Inveniendi Lineas Curvas Maximi Minimive Proprietate Gaudentes sive Solutio Problematis Isoperimetrici Latissimo Sensu Accepti (The Method of Finding Plane Curves that Show Some Property of Maximum or Minimum.* 1744.

[15] L.S. Pontryagin V.G. Boltyanskii, R.V. Gamkrelidze. *Towards a theory of optimal processes, (Russian).* Reports Acad. Sci. USSR, vol.110(1), 1956.

[16] Frank L Lewis, Draguna Vrabie, and Vassilis L Syrmos. *Optimal control.* Wiley. com, 2012.

[17] A. E. Bryson and Y. C. Ho. *Applied Optimal Control.* Blaisdell, New York, 1969.

[18] Arturo Locatelli. *Optimal control: An introduction.* Springer, 2001.

[19] Michael Athans and Peter L Falb. *Optimal control: an introduction to the theory and its applications.* Courier Dover Publications, 2006.

[20] L Richard and J Burden. Douglas faires, numerical analysis, 1988.

[21] Singiresu S Rao and SS Rao. *Engineering optimization: theory and practice.* John Wiley & Sons, 2009.

[22] Herbert Bishop Keller. *Numerical methods for two-point boundary-value problems.* Dover Publications New York, NY, 1992.

[23] Aidan O'Dwyer. Reducing energy costs by optimizing controller tuning. In *Conference papers*, page 66, 2006.

[24] B Wayne Bequette. *Process control: modeling, design, and simulation.* Prentice Hall Professional, 2003.

[25] Chong G.C.Y. Ang, K.H. and Y. Li. Pid control system analysis, design, and technology. 2005.

[26] Stuart Bennett. A history of control engineering, 1800-1930. 1986.

[27] G.G. Coriolis. Mémoire sur les équations du mouvement relatif des systèmes de corps. 1835.

[28] David Hestenes. *New Foundations for Classical Mechanics.* The Netherlands: Kluwer Academic Publishers. p. 312. ISBN 90-277-2526-8., 1990.

[29] Singiresu S Rao. *Applied numerical methods for engineers and scientists.* Prentice Hall Professional Technical Reference, 2001.

[30] JG Ziegler and NB Nichols. Optimum settings for automatic controllers. *trans. ASME*, 64(11), 1942.

[31] Ziegler-nichols-method @ONLINE, 2014. URL http://en.wikipedia.org/wiki/Ziegler-Nichols_method.