

# RW778: Implementation and Application of Automata, 2006 Week 6 Lecture 1

L. van Zijl

Department of Computer Science  
University of Stellenbosch

2006

# Cryptology with $\oplus$ -NFAs

## References:

1. Chaudhuri, Design of CA-based Cipher System, Chapter 7 (and earlier chapters for terminology clarification)
2. Cryptanalysis, Chapter 42.
3. Van Zijl,  $\oplus$ -NFAs as Block Cipher Systems. Course notes.

# Cryptology with $\oplus$ -NFAs

- ▶ What is cryptology?
  - ▶ Plain text, encoding text, decoding text, key
- ▶ How good is a cipher? Cryptanalysis: study of breaking ciphers (read up on Turing's Enigma work).
- ▶ Stream-based vs block-based cipher systems.
- ▶ Relationship between unary  $\oplus$ -NFA and null-boundary XNOR CA

# Cryptology with $\oplus$ -NFAs

- Definition of  $\oplus$ -NFAs:  $\delta(A, b) = \oplus_{q \in A} \delta(q, b)$

# Cryptology with $\oplus$ -NFAs

- ▶ Definition of  $\oplus$ -NFAs:  $\delta(A, b) = \bigoplus_{q \in A} \delta(q, b)$

$\delta$	$a$
0	$\{0\}$
1	$\{0, 1\}$
2	$\{1, 2\}$
3	$\{2, 3\}$

- ▶ Example:

# Cryptology with $\oplus$ -NFAs

- ▶ Definition of  $\oplus$ -NFAs:  $\delta(A, b) = \oplus_{q \in A} \delta(q, b)$

$\delta$	$a$
0	$\{0\}$
1	$\{0, 1\}$
2	$\{1, 2\}$
3	$\{2, 3\}$

- ▶ Example:



$$\begin{aligned} 0 &\rightarrow \overline{0} = 123 \rightarrow \overline{\{03\}} = 12 \rightarrow \overline{\{02\}} = 13 \\ &\rightarrow \overline{\{0123\}} = \emptyset \rightarrow \overline{\emptyset} = 0123 \\ &\rightarrow \overline{\{3\}} = 012 \rightarrow \overline{\{2\}} = 013 \rightarrow \overline{\{123\}} = 0 \end{aligned}$$

# Cryptology with $\oplus$ -NFAs

- ▶ Good rules:

# Cryptology with $\oplus$ -NFAs

- ▶ Good rules:
  - ▶  $\delta(q_i, a) = \overline{\{q_i\}}$ , for  $0 \leq i \leq n - 1$ .



# Cryptology with $\oplus$ -NFAs

► Good rules:

- $\delta(q_i, a) = \overline{\{q_i\}}$ , for  $0 \leq i \leq n - 1$ .
- $\delta(q_i, a) = \overline{\{q_i, q_{i+1}\}}$ , for  $0 \leq i \leq n - 2$  and  $\delta(q_{n-1}, a) = \overline{\{q_{n-1}\}}$ .

# Cryptology with $\oplus$ -NFAs

► Good rules:

- $\delta(q_i, a) = \overline{\{q_i\}}$ , for  $0 \leq i \leq n - 1$ .
- $\delta(q_i, a) = \overline{\{q_i, q_{i+1}\}}$ , for  $0 \leq i \leq n - 2$  and  $\delta(q_{n-1}, a) = \overline{\{q_{n-1}\}}$ .
- $\delta(q_i, a) = \overline{\{q_{i-1}, q_i\}}$ , for  $1 \leq i \leq n - 2$  and  $\delta(q_0, a) = \overline{\{q_0\}}$ .

# Cryptology with $\oplus$ -NFAs

- ▶ Good rules:
  - ▶  $\delta(q_i, a) = \overline{\{q_i\}}$ , for  $0 \leq i \leq n - 1$ .
  - ▶  $\delta(q_i, a) = \overline{\{q_i, q_{i+1}\}}$ , for  $0 \leq i \leq n - 2$  and  $\delta(q_{n-1}, a) = \overline{\{q_{n-1}\}}$ .
  - ▶  $\delta(q_i, a) = \overline{\{q_{i-1}, q_i\}}$ , for  $1 \leq i \leq n - 2$  and  $\delta(q_0, a) = \overline{\{q_0\}}$ .
- ▶ All cycles same and even length (permutation groups).

# Cryptology with $\oplus$ -NFAs

- ▶ Good rules:
  - ▶  $\delta(q_i, a) = \overline{\{q_i\}}$ , for  $0 \leq i \leq n - 1$ .
  - ▶  $\delta(q_i, a) = \overline{\{q_i, q_{i+1}\}}$ , for  $0 \leq i \leq n - 2$  and  $\delta(q_{n-1}, a) = \overline{\{q_{n-1}\}}$ .
  - ▶  $\delta(q_i, a) = \overline{\{q_{i-1}, q_i\}}$ , for  $1 \leq i \leq n - 2$  and  $\delta(q_0, a) = \overline{\{q_0\}}$ .
- ▶ All cycles same and even length (permutation groups).
- ▶ Each cycle forms permutation  $\pi$  of length  $2r$ .

# Cryptology with $\oplus$ -NFAs

- ▶ Good rules:
  - ▶  $\delta(q_i, a) = \overline{\{q_i\}}$ , for  $0 \leq i \leq n - 1$ .
  - ▶  $\delta(q_i, a) = \overline{\{q_i, q_{i+1}\}}$ , for  $0 \leq i \leq n - 2$  and  $\delta(q_{n-1}, a) = \overline{\{q_{n-1}\}}$ .
  - ▶  $\delta(q_i, a) = \overline{\{q_{i-1}, q_i\}}$ , for  $1 \leq i \leq n - 2$  and  $\delta(q_0, a) = \overline{\{q_0\}}$ .
- ▶ All cycles same and even length (permutation groups).
- ▶ Each cycle forms permutation  $\pi$  of length  $2r$ .
- ▶ Therefore,  $\pi^r$  gives mapping.

# Cryptology with $\oplus$ -NFAs: Algorithm

## Algorithm

- ▶ Take  $k$   $\oplus$ -NFAs  $M_i$  with 'good' rules, and such that all cycles same and even length.

# Cryptology with $\oplus$ -NFAs: Algorithm

## Algorithm

- ▶ Take  $k$   $\oplus$ -NFAs  $M_i$  with 'good' rules, and such that all cycles same and even length.
- ▶ Use  $M_i$  to construct permutations  $p_1, p_2, \dots, p_k$ .

# Cryptology with $\oplus$ -NFAs: Algorithm

## Algorithm

- ▶ Take  $k$   $\oplus$ -NFAs  $M_i$  with 'good' rules, and such that all cycles same and even length.
- ▶ Use  $M_i$  to construct permutations  $p_1, p_2, \dots, p_k$ .
- ▶ For all permutations  $p_i$ , calculate  $p_i^{r_i}$ .



# Cryptology with $\oplus$ -NFAs: Algorithm

## Algorithm

- ▶ Take  $k$   $\oplus$ -NFAs  $M_i$  with 'good' rules, and such that all cycles same and even length.
- ▶ Use  $M_i$  to construct permutations  $p_1, p_2, \dots, p_k$ .
- ▶ For all permutations  $p_i$ , calculate  $p_i^{r_i}$ .
- ▶ Divide plaintext into blocks  $B_j$ .

# Cryptology with $\oplus$ -NFAs: Algorithm

## Algorithm

- ▶ Take  $k$   $\oplus$ -NFAs  $M_i$  with 'good' rules, and such that all cycles same and even length.
- ▶ Use  $M_i$  to construct permutations  $p_1, p_2, \dots, p_k$ .
- ▶ For all permutations  $p_i$ , calculate  $p_i^{r_i}$ .
- ▶ Divide plaintext into blocks  $B_j$ .
- ▶ Apply function  $p_1^{r_1} p_2^{r_2} \dots p_k^{r_k}$  to each message block.

# Cryptology with $\oplus$ -NFAs: Algorithm

## Algorithm

- ▶ Take  $k$   $\oplus$ -NFAs  $M_i$  with 'good' rules, and such that all cycles same and even length.
- ▶ Use  $M_i$  to construct permutations  $p_1, p_2, \dots, p_k$ .
- ▶ For all permutations  $p_i$ , calculate  $p_i^{r_i}$ .
- ▶ Divide plaintext into blocks  $B_j$ .
- ▶ Apply function  $p_1^{r_1} p_2^{r_2} \dots p_k^{r_k}$  to each message block.
- ▶ To decode, calculate  $(p_1^{r_1} p_2^{r_2} \dots p_k^{r_k})^{-1}$  for each message block.

# Cryptology with $\oplus$ -NFAs

## Example continued

- ▶ Let  $k = 1$ , and let the message blocks be 1111, 1010 and 0011.

# Cryptology with $\oplus$ -NFAs

## Example continued

- ▶ Let  $k = 1$ , and let the message blocks be 1111, 1010 and 0011.
- ▶ Then the encoded message is 1110, 0001 and 1010.

# Cryptology with $\oplus$ -NFAs

## Homework

**Homework:** Implement a system to encode and decode text using a block cipher based on  $\oplus$ -NFAs.