
Contact Network Heterogeneity and Persistence of Endemic Disease

Daniel T. Citron
Christopher R. Myers
Department of Physics
Cornell University

Endemic Infection


- Susceptibles are replenished
- Example: SIR with waning immunity



Persistence of infected individuals in a population


Spontaneous Extinctions

Endemic states not stable in finite populations




Spontaneous Extinctions

- Endemic states not stable in finite populations
- Stochastic fluctuations bring infection level to 0




Spontaneous Extinctions

- Endemic states not stable in finite populations
- Stochastic fluctuations bring infection level to 0




Endemic State Lifetimes


- Characteristic Lifetime
- Depends on
 - Mean Infection µ
 - Fluctuation Size σ



Network Effects

- Change contact network topology
- What happens to the endemic state lifetime?







Heterogeneous Graph

Our Simulations

- SIRS model
- Annealed networks




- Vary degree heterogeneity <σ_k>
- Generate ensembles of trajectories
- Measure lifetime of endemic state



Results

500 nodes, mean degree 10, $\langle \sigma_k \rangle = 10$


Mean Infection Level




Results

500 nodes, mean degree 10, $\langle \sigma_k \rangle = 10$


Mean Infection Level




Mean Time to Extinction



Results: Across Graphs




Results: Across Graphs




- Heterogeneous graphs have longer persistence
- Endemic lifetimes depend on topology

Can we predict endemic state lifetimes?

Can we predict endemic state lifetimes?




Can we predict endemic state lifetimes?




Fluctuation/mean ratio σ/μ is sufficient

Can we predict endemic state lifetimes?




- Fluctuation/mean ratio σ/μ is sufficient
- Corrections from changing topology

Analytical technique that predicts both means and fluctuation sizes





 Analytical technique that predicts both means and fluctuation sizes




Good agreement for annealed networks

- Analytical technique that predicts both means and fluctuation sizes
- Good agreement for annealed networks
- Hypothesis: moment closure for predicting lifetimes





- Analytical technique that predicts both means and fluctuation sizes
- Good agreement for annealed networks
- Hypothesis: moment closure for predicting lifetimes



Summary

- Network topology can affect the persistence of endemic disease
- Higher degree heterogeneity leads to longer lifetimes
- Moment closure may be useful for predicting lifetimes

Acknowledgments

- Christopher R. Myers
- Sarabjeet Singh
- Jason Hindes

- Andrew Dolgert
- NSF Graduate Research Fellowship under Grant No. DGE-1144153

Bibliography

- M. Keeling and P. Rohani, Modeling Infectious Diseases in Humans and Animals
- N. T. J. Bailey, *The Elements of Stochastic Processes*
- A. Barrat et al., Dynamical Processes on Complex Networks
- •I. Nåsell, Mathematical Biosciences 179, 1 (2002)
- D. Clancy and S. T. Mendy, J of Math. Biology 61, 527 (2009)

Constant Mean Infection Level

- Measure means, fluctuations
- Can we predict the lifetime?
- Vary graph topology

Constant Mean Infection Level

- Measure means, fluctuations
- Can we predict the lifetime?
- Vary graph topology
- Finite size effects
- High and low degree classes

- 500 Nodes
- $\langle I \rangle = 35$ Infected

