DLP TEST

Test Your DLP. Prove It Actually Blocks.

DLPTest.com is a free testing resource for Data Loss Prevention software. If your DLP is configured correctly, the endpoints here will demonstrate it. We provide sample data, HTTP POST test endpoints over both plain HTTP and HTTPS, and a public FTP server. They are designed to be safe targets that your DLP can detect and block.

Try the default HTTPS POST

Try the cleartext HTTP POST

dlp-test — curl

```
$ curl -X POST https://dlptest.com/api/http-post/ \
    -F "ssn=123-45-6789" \
    -F "cc=5555-4444-3333-2222"

HTTP/1.1 200 OK
# Your DLP should have blocked this.
```

Sample Data Library

Browse curated datasets of fake PII and PCI — names paired with SSNs, credit cards with ZIP codes, dates of birth with emails. Every record passes the structural checks DLP engines look for (Luhn for cards, valid SSN area-group-serial), so it actually trips real policies. Copy rows from the table or download CSV, PDF, or Excel files.

Browse sample data →

Data Generator

Build a custom dataset on demand. Pick the fields you need — SSN, credit card, IBAN, NPI, driver's license, passport, EU VAT, and more — set a row count, optionally seed for reproducibility, and export as CSV. Useful when the library doesn't match the schema you need to test against.

Generate sample data →

Data In Use (Endpoint DLP)

Data In Use, also known as Endpoint DLP, involves installing an endpoint agent on user devices such as laptops, desktops, and virtual desktops with OS support for Windows, macOS, or Linux. Once installed, the agent can monitor local channels like Bluetooth transfers, USB transfers, CD/DVD burning, and network share copies. Agents also provide visibility into network layer movement across web browsers, FTP transfers, cloud storage, and GenAI apps. With network visibility, this is typically done with a browser extension or a locally running man-in-the-middle proxy. Supported OSs and channels vary by vendor.

Data In Motion (SSE and SASE)

Data In Motion refers to monitoring traffic across protocols like HTTP, HTTPS, FTP, and SMTP. Historically, this was split into a network monitor that would sit off a network SPAN or tap, an email MTA between Exchange and the edge, and an ICAP integration with a web proxy. The modern approach to HTTP and HTTPS is to incorporate DLP into a Secure Service Edge (SSE) that monitors all user traffic, regardless of location. For email (SMTP) traffic, many customers now use built-in Microsoft Purview or Google Workspace DLP controls. There are also 3rd-party email providers that have started building blocking with API integrations.

Quick start

Sample Data

HTTP(S) POST test

Names, SSNs, credit card numbers, and other PII you can copy or download.

Browse sample data →

Submit text and files with the HTTP POST method, over plain HTTP or TLS, to a safe endpoint that accepts and discards them. Trip your DLP without leaking data.

HTTP POST Test → · HTTPS POST Test →

FTP Test

Public FTP server with credentials. Files are deleted after 10 minutes.

Get FTP credentials →

Why use dlptest.com?

DLPTest.com is a testing resource for Data Loss Prevention (DLP) software. When DLP has been installed and configured correctly, this site can demonstrate that sensitive data is protected when DLP is in blocking mode. Data Loss Prevention has historically been divided into three categories: Data in Use (DIU), Data at Rest (DAR), and Data in Motion (DIM). DLPTest currently offers features to test Data in Use and Data in Motion.

What is Data Loss Prevention?

Data Loss Prevention (DLP) is a strategy and set of technologies designed to prevent sensitive or confidential data from being disclosed, shared, or used in unauthorized ways that violate an organization's policies. DLP technologies can be software, hardware, or a combination of both.

DLP can identify, classify, and protect data based on sensitivity and can be configured to take different actions when sensitive data is detected. For example, a DLP solution might prevent an email from being sent if it contains sensitive information, alert an administrator when sensitive data is accessed or copied, or encrypt data to prevent unauthorized access. Organizations use DLP to comply with regulations such as data privacy laws, and to protect sensitive business information.

Frequently Asked Questions

What sample data should I use to test DLP?

How do I measure DLP detection accuracy and tune for false positives?

Should I test in monitor mode or blocking mode?

How often should I re-test DLP?

How to run an FTP Upload (FTP PUT)

How to test web DLP (ICAP-based proxies)

How to test web DLP via SSE / SASE

How to test Email DLP

How to test a Network Monitor

How to test Data-in-Use (Endpoint DLP)

How to test Data-at-Rest (DAR) scanning

How to test DLP for cloud and SaaS apps

How to test DLP against AI tools like ChatGPT and Copilot

How to test exact data matching and indexed document matching

How to test DLP on macOS

Best practices for deploying Endpoint DLP?

How do I prove DLP is working to an auditor?

Subscribe to Updates

Get notified about new test tools, sample data, and data security news.

Email *

you@example.com

Name *

Your name

Company (optional)

Your company

Subscribe

By subscribing, you agree to receive our communications.

Data security news

Industry news and analysis on DLP, DSPM, insider risk, and the broader data-security market. See all news →

© 2026 DLP Test. Created by Brian Hileman.