

```
Champlain-Router#show crypto ipsec sa

interface: FastEthernet0/0
  Crypto map tag: VPN-MAP, local addr 216.93.144.2

  protected vrf: (none)
  local ident (addr/mask/prot/port): (172.16.84.0/255.255.255.0/0/0)
  remote ident (addr/mask/prot/port): (192.168.25.0/255.255.255.0/0/0)
  current_peer 140.230.18.2 port 500
    PERMIT, flags={origin_is_acl,}
    #pkts encaps: 11, #pkts encrypt: 11, #pkts digest: 0
    #pkts decaps: 10, #pkts decrypt: 10, #pkts verify: 0
    #pkts compressed: 0, #pkts decompressed: 0
    #pkts not compressed: 0, #pkts compr. failed: 0
    #pkts not decompressed: 0, #pkts decompress failed: 0
    #send errors 1, #recv errors 0

    local crypto endpt.: 216.93.144.2, remote crypto endpt.:140.230.18.2
    path mtu 1500, ip mtu 1500, ip mtu idb FastEthernet0/0
    current outbound spi: 0x542E21AA(1412309418)

  inbound esp sas:
    spi: 0xE4104C1F(3826273311)
      transform: esp-aes esp-sha-hmac ,
      in use settings ={Tunnel, }
      conn id: 2008, flow_id: FPGA:1, crypto map: VPN-MAP
      sa timing: remaining key lifetime (k/sec): (4525504/3496)
      IV size: 16 bytes
      replay detection support: N
      Status: ACTIVE

  inbound ah sas:

  inbound pcp sas:

  outbound esp sas:
    spi: 0x542E21AA(1412309418)
      transform: esp-aes esp-sha-hmac ,
      in use settings ={Tunnel, }
      conn id: 2009, flow_id: FPGA:1, crypto map: VPN-MAP
      sa timing: remaining key lifetime (k/sec): (4525504/3496)
      IV size: 16 bytes
      replay detection support: N
      Status: ACTIVE

  outbound ah sas:

  outbound pcp sas:

Champlain-Router#
```

Middle-Router#show crypto ipsec sa

interface: FastEthernet0/0

Crypto map tag: VPN-MAP, local addr 140.230.18.2

protected vrf: (none)

local ident (addr/mask/prot/port): (192.168.25.0/255.255.255.0/0/0)

remote ident (addr/mask/prot/port): (172.16.84.0/255.255.255.0/0/0)

current\_peer 216.93.144.2 port 500

PERMIT, flags={origin\_is\_acl,}

#pkts encaps: 10, #pkts encrypt: 10, #pkts digest: 0

#pkts decaps: 11, #pkts decrypt: 11, #pkts verify: 0

#pkts compressed: 0, #pkts decompressed: 0

#pkts not compressed: 0, #pkts compr. failed: 0

#pkts not decompressed: 0, #pkts decompress failed: 0

#send errors 0, #recv errors 0

local crypto endpt.: 140.230.18.2, remote crypto endpt.:216.93.144.2

path mtu 1500, ip mtu 1500, ip mtu idb FastEthernet0/0

current outbound spi: 0xE4104C1F(3826273311)

inbound esp sas:

spi: 0x542E21AA(1412309418)

transform: esp-aes esp-sha-hmac ,

in use settings ={Tunnel, }

conn id: 2008, flow\_id: FPGA:1, crypto map: VPN-MAP

sa timing: remaining key lifetime (k/sec): (4525504/3433)

IV size: 16 bytes

replay detection support: N

Status: ACTIVE

inbound ah sas:

inbound pcp sas:

outbound esp sas:

spi: 0xE4104C1F(3826273311)

transform: esp-aes esp-sha-hmac ,

in use settings ={Tunnel, }

conn id: 2009, flow\_id: FPGA:1, crypto map: VPN-MAP

sa timing: remaining key lifetime (k/sec): (4525504/3433)

IV size: 16 bytes

replay detection support: N

Status: ACTIVE

outbound ah sas:

outbound pcp sas:

Middle-Router#