The University of Alabama in Huntsville
Electrical & Computer Engineering Department
CPE 431 01
Test 2
November 14, 2013

Name: _____

Show all work. You will not receive full credit for a problem if you do not show your work!

1. (1 point) _____ locality is the principle stating that if a data location is references then it will tend to be referenced again soon.
2. (1 point) A memory _____ is a structure that uses multiple levels of memories.
3. (1 point) _____ is a scheme in which writes always update both the cache and the next lower level of the memory hierarchy.
4. (1 point) _____ is the process by which a virtual address is mapped to an address used to access memory.
5. (1 point) _____ is the space on the disk reserved for the full virtual memory space of a process.
6. (10 points) A cache designer wants to increase the size of a 4 KB virtually indexed, physically tagged cache. Given a page size of 16 KB, is it possible to make a 16 KB direct-mapped cache, assuming 2 words per block? If not, how would the designer increase the size of the cache? If so, is 16 KB the largest direct-mapped cache size possible?

7. (15 points) Consider executing the following code on a pipelined datapath like the one shown except that 1) it supports j instructions that complete in the ID stage, and 2) it has MEM/WB forwarding only. The register file does support writing in the first half cycle and reading in the second half cycle.




```
sort:     addi  $sp, $sp, -20
          sw    $ra, 16($sp)
          sw    $s3, 12($sp)
          sw    $s2, 8($sp)
          sw    $s1, 4($sp)
          sw    $s0, 0($sp)
          add   $s2, $a0, $zero
          add   $s3, $a1, $zero
⇒         add   $s0, $zero, $zero
for1tst:  slt   $t0, $s0, $s3
          beq   $t0, $zero, exit1
          addi  $s1, $s0, -1
for2tst:  slt   $t0, $s1, $zero
          bne   $t0, $zero, exit2
          add   $t1, $s1, $s1
          add   $t1, $t1, $t1
          add   $t2, $s2, $t1
          lw    $t3, 0($t2)
          lw    $t4, 4($t2)
          slt   $t0, $t4, $t3
          beq   $t0, $zero, exit2
          add   $a0, $s2, $zero
          add   $a1, $s1, $zero
          jal   swap
          addi  $s1, $s1, -1
          j     for2tst
exit2:    addi  $s0, $s0, 1
          j     for1tst
exit1:    lw    $s0, 0($sp)
          lw    $s1, 4($sp)
          lw    $s2, 8($sp)
          lw    $s3, 12($sp)
          lw    $ra, 16($sp)
          addi  $sp, $sp, 20
          jr    $ra
```

If the `add $s0` instruction one instructions before the `for1tst` label begins executing in cycle 1 and the `beq $t0, $zero, exit1` is taken, what instructions are found in each of the five stages of the pipeline in the 9th cycle? Show the instructions being executed in each stage of the pipeline during each cycle. What value is stored in the ALUResult of the EX/MEM pipeline register in the 9th cycle? Assume that before the instructions are executed, the state of the machine was as follows:

The PC has the value 200_{10}, the address of the add $s0 instruction
Every register has the initial value 20_{10} plus the register number.
Every memory word accessed as data has the initial value 10000_{10} plus the byte address of the word.

Cycle	IF	ID	EX	MEM	WB
1					
2					
3					
4					
5					
6					
7					
8					
9					
10					
11					
12					

8. (10 points) Consider a pipeline for a register-memory architecture. The architecture has two instruction formats: a register-register format and a register-memory format. There is a single memory addressing mode (offset + base register). There is a set of ALU operations as follows:

ALUop← Rdest,Rsrc1,Rsrc2,offset
Rdest ← Rsrc1 ALUop Rsrc2
or Rdest ← Rsrc1 ALUop MEM[Rsrc2 + offset]
or
Rdest ← MEM[Rsrc2 + offset]
or
MEM[Rsrc2 + offset] ← Rsrc1

where the ALUop is one of the following:

Add, Subtract, And, Or(with or without offset)
Load(Rsrc1 omitted)
Store(Rdest omitted)

Rdest, Rsrc1 and Rsrc2 are registers.

Branches use a full compare of two registers and are PC-relative. Assume that this machine is pipelined so that a new instruction is started every clock cycle. The pipeline structure is

IF	RF	ALU1	MEM	ALU2	WB					
	IF	RF	ALU1	MEM	ALU2	WB				
		IF	RF	ALU1	MEM	ALU2	WB			
			IF	RF	ALU1	MEM	ALU2	WB		
				IF	RF	ALU1	MEM	ALU2	WB	
					IF	RF	ALU1	MEM	ALU2	WB

The first ALU stage is used for effective address calculation for memory references and branches. The second ALU stage is used for operations and branch comparisons. RF is both a decode and register-fetch stage. Assume that when a register read and a register write of the same register occur in the same clock cycle, the write data is forwarded. For the following code fragment:

```
add   $1, $1, 0($15)
add   $2, $1, 4($15)
add   $3 ,$2, 0($1)
add   $2, $2, 4($1)
store $3, 8($1)
```

identify the data dependencies and draw a figure (using the multiple clock style) showing them as lines.

9. (25 points) a) (5 points) Consider the following loop executing on a MIPS pipeline with full forwarding. Calculate the number of cycles it takes to execute this loop, neglecting pipeline fill cycles. b) (15 points) Unroll the loop so that 3 iterations of the loop are executed at once and schedule the unrolled code on a 2-issue pipeline in which any instruction can be issued in any slot. c) (5 points) Calculate the speedup from the original loop to the unrolled loop scheduled on a 2-issue pipeline.

```
      add   $s1, $zero, $zero
      addi  $t1, $s0, -240
Loop: add   $t4, $t2, $t1
      lw    $t3, 0($t4)
      lw    $t3, 0($t3)
      add   $s1, $s1, $t3
      addi  $t1, $t1, 4
      bne   $t1, $s0, Loop
```

Cycle	Issue Slot 1	Issue Slot 2
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		

10. (5 points) The following code is written in MATLAB, where elements within the same column are stored contiguously. Does `C(1, I)` exhibit spatial locality? temporal locality? Explain your answers. A, B, and C are all arrays of integers 8000 by 8000.

```
for I=1:8000
  for J=1:8
      A(I,J) = B(J,1) + A(J, I) + C(1, I);
```

11. (15 points) Here is a series of address references given as byte addresses: 118, 483, 2069, 321, 368, 1077, 1505, 812, 2832, 373, 1411, 511, 1463, 690, 4820, 1714, 1508. Assuming a two-way set associative-mapped cache with four-word blocks and a total size of 32 words that is initially empty and uses LRU, (a) label each reference in the list as a hit or a miss and (b) show the entire history of the cache, including tag and data.

12. (15 points) Virtual memory uses a page table to track the mapping of virtual addresses to physical addresses. Consider this stream of virtual addresses as seen on a system: 9452, 30964, 19136, 46502, 38110, 16653, 48480. Assume 8KB pages, a four-entry fully associative TLB, and true LRU replacement. If pages must be brought in from disk, increment the next largest page number.

TLB

Valid	Tag	Physical Page Number
1	11	12
1	7	4
1	3	6
0	4	9

Page table

Valid	Physical page or in disk
1	5
0	Disk
0	Disk
1	6
1	9
1	11
0	Disk
1	4
0	Disk
0	Disk
1	3
1	12