



2 NEW ENCODERS ADDED



SECURITY PIR & ULTRASOUND
Deactivate as soon as somebody its too close
NEW!



DS3231



PIN Receptor?



UART1

UART0

UART2

The ESP32 chip has the following strapping pins:

GPIO 0 (must be LOW to enter boot mode)
GPIO 2 (must be floating or LOW during boot)
GPIO 4
GPIO 5 (must be HIGH during boot)
GPIO 12 (must be LOW during boot)
GPIO 15 (must be HIGH during boot)



Truth Table multiplexer


Truth Table multiplexer



NEW



MOSFET VENTILADOR



CODIGO

<https://github.com/mirkopetrovich/osclinga>

PELICASE

Außenmaße: 27 x 24,6 x 12,4 cm

Innenmaße: 24 x 18,5 x 11 cm

PCBA Sn Ag Cu 260°C Solderpaste

DISIPADOR y clevija 2.5
Como apaga la fuente principal de los leds
mandar pulso fisis de PWM apagado
Panel y caja de control
registas y reles
conectores, panel y caja
ESP32 Wifi- dev kit lnto
sch: <https://r1ngur.com/EPE4dGj.jpg>
<https://www.bastelgarage.ch/image/catalog/artikel/420571-420580/420571-Pinout.jpg>
Modo transmisor
https://nayslampechatronics.com/blog/s7_comunicacion-rs485-con-arduino.html