

# Access Wideband Audiology Immitance database using R and dplyr (Voss PI)

*Nicholas Horton (nhorton@amherst.edu)*

*June 23, 2016*

## Introduction

This document is intended to describe how to access data from a MySQL database using R. It utilizes a database of wideband acoustic immitance variables from humans with normal hearing (see [https://projectreporter.nih.gov/project\\_info\\_description.cfm?aid=8769352&icde=30039221&ddparam=&ddvalue=&ddsub=&cr=10&csb=default&cs=ASC](https://projectreporter.nih.gov/project_info_description.cfm?aid=8769352&icde=30039221&ddparam=&ddvalue=&ddsub=&cr=10&csb=default&cs=ASC) for more details).

A relevant paper on the topic of data management and databases in R can be found at <http://chance.amstat.org/2015/04/setting-the-stage>.

## Accessing data using SQL commands

First I will demonstrate how to access data using SQL (structured query language) commands and the `dbGetQuery()` function. First a connection to the database is set up.

```
library(mosaic)
library(RMySQL)

## Loading required package: DBI

con <- dbConnect(MySQL(), host = "scidb.smith.edu",
                  user = "waiuser", password = "smith_waiDB",
                  dbname = "wai")
```

Next a series of SQL queries can be sent to the database. These return R dataframes.

```
dbGetQuery(con, "SHOW TABLES")
```

```
## Tables_in_wai
## 1 Measurements
## 2 PI_Info
## 3 Subject
```

```
dbGetQuery(con, "EXPLAIN PI_Info")
```

```
##      Field      Type Null Key Default Extra
## 1 Identifier varchar(20) YES      <NA>
## 2 PI_Year      int(11) YES      <NA>
## 3 PI           varchar(40) YES      <NA>
## 4 Affiliation  varchar(500) YES      <NA>
## 5 Email        varchar(30) YES      <NA>
## 6 Title        varchar(140) YES      <NA>
## 7 Pub          varchar(30) YES      <NA>
## 8 Date         char(20) YES      <NA>
## 9 URL          varchar(140) YES      <NA>
## 10 PI_Notes    varchar(1500) YES      <NA>
```

```
ds <- dbGetQuery(con, "SELECT * from Measurements LIMIT 10")
ds
```

```
##      Identifier Sub_Number Session Left_Ear MEP Instrument Ear_Area   Freq
## 1 Voss_ASA14      1         1      0    0      1 0.0000442 210.938
## 2 Voss_ASA14      1         1      0    0      1 0.0000442 234.375
## 3 Voss_ASA14      1         1      0    0      1 0.0000442 257.812
## 4 Voss_ASA14      1         1      0    0      1 0.0000442 281.250
## 5 Voss_ASA14      1         1      0    0      1 0.0000442 304.688
## 6 Voss_ASA14      1         1      0    0      1 0.0000442 328.125
## 7 Voss_ASA14      1         1      0    0      1 0.0000442 351.562
## 8 Voss_ASA14      1         1      0    0      1 0.0000442 375.000
## 9 Voss_ASA14      1         1      0    0      1 0.0000442 398.438
## 10 Voss_ASA14     1         1      0    0      1 0.0000442 421.875
##      Absorbance      Zmag      Zang
## 1  0.0417482 82170700 -0.234778
## 2  0.0430154 78968100 -0.234903
## 3  0.0471408 68093700 -0.235638
## 4  0.0599458 60912400 -0.233472
## 5  0.0729253 56467300 -0.231156
## 6  0.0817873 51378900 -0.230572
## 7  0.0925911 48610600 -0.228987
## 8  0.1148400 45332000 -0.225251
## 9  0.1222960 42558100 -0.225022
## 10 0.1383710 39362700 -0.223418
```

## Accessing using dplyr commands

Alternatively, a connection can be made to the server by creating a series of dplyr table objects.

```
library(mosaic)
db <- src_mysql(dbname = "wai", host = "scidb.smith.edu", user = "waiuser",
  password="smith_waiDB")
Measurements <- tbl(db, "Measurements")
PI_Info <- tbl(db, "PI_Info")
Subject <- tbl(db, "Subject")
```

Let's explore the PI\_Info table.

```
PI_Info %>% collect() %>% data.frame()
```

```
##      Identifier PI_Year
## 1 Voss_2014      2014
## 2 Rosowski_2012 2012
## 3 Voss_ASA14    2014 Susan E. Voss; Defne Abur; Hiwot Kassaye
##
## 1
## 2 Eaton-Peabody Laboratory, Massachusetts Eye and Ear Infirmary, Boston; Department of Otology and L
## 3
##      Email
## 1 svoss@smith.edu
## 2 John_Rosowski@meei.harvard.edu
## 3 svoss@smith.edu
```

```
##
## 1                                     Title
## 2                                     Intrasubject Variability in Power Reflectance
## 3 Ear-Canal Reflectance, Umbo Velocity, and Tympanometry in Normal-Hearing Adults
## 3 Comparisons of reflectance measurements across measurements sessions, instruments, and ages
##                                     Pub      Date
## 1                                     J Am Acad Audiol 10/04/2014
## 2                                     Ear & Hearing 11/06/2015
## 3 Acoustical Society of America      2014
##                                     URL
## 1 http://www.ncbi.nlm.nih.gov/pubmed/?term=abur+voss+2014
## 2 http://www.ncbi.nlm.nih.gov/pubmed/21857517
## 3 http://dx.doi.org/10.1121/1.4877464
##
## 1
## 2 HearID (Mimosa Acoustics); \nNormal Criteria as follows: \n(1) There was no history of significant
## 3
```

Let's explore the Subjects table.

```
Subject %>% collect()
```

```
## Source: local data frame [52 x 11]
##
##      Identifier Sub_Number Session_Total Age Female Race Ethnicity
##      (chr)      (chr)      (int) (int) (int) (int) (int)
## 1 Voss_2014      1          4    20     1     0     0
## 2 Voss_2014      2          8    20     1     0     0
## 3 Voss_2014      3          7    21     1     0     0
## 4 Voss_2014      4          4    20     1     0     0
## 5 Voss_2014      5          4    19     1     0     0
## 6 Voss_2014      6          6    20     1     0     0
## 7 Voss_2014      8          3    20     1     0     0
## 8 Voss_2014      9          4    22     1     0     0
## 9 Rosowski_2012  3          1    30     1     5     2
## 10 Rosowski_2012 6          1    29     0     5     2
## ..          ...      ...      ...    ...    ...    ...
## Variables not shown: Left_Ear_Status (int), Right_Ear_Status (int),
## Sub_Notes (chr), ID (dbl)
```

Let's explore the Measurements table.

```
Measurements %>% summarise(total = n())
```

```
## Source: mysql 5.5.47-0ubuntu0.14.04.1 [waiuser@scidb.smith.edu:/wai]
## From: <derived table> [?? x 1]
##
##      total
##      (dbl)
## 1 107226
## ..      ...
```

Let's download the data from a given subject

```

onesubj <-
  Measurements %>%
  filter(Identifier=="Voss_2014", Sub_Number==1) %>%
  collect %>%
  mutate(SessionNum = as.factor(Session))
head(onesubj)

```

```

## Source: local data frame [6 x 12]
##
##   Identifier Sub_Number Session Left_Ear  MEP Instrument Ear_Area  Freq
##   (chr)      (chr)      (int)  (int) (chr)      (int)      (chr) (dbl)
## 1 Voss_2014      1        1      0    0          1      NaN    211
## 2 Voss_2014      1        1      0    0          1      NaN    234
## 3 Voss_2014      1        1      0    0          1      NaN    258
## 4 Voss_2014      1        1      0    0          1      NaN    281
## 5 Voss_2014      1        1      0    0          1      NaN    305
## 6 Voss_2014      1        1      0    0          1      NaN    328
## Variables not shown: Absorbance (dbl), Zmag (dbl), Zang (dbl), SessionNum
##   (fctr)

```

Finally we can plot the results

```

onesubj <- mutate(onesubj, Ear=ifelse(Left_Ear==1, "Left", "Right"))
xyplot(Absorbance ~ Freq | SessionNum, group=Ear, auto.key=TRUE,
       scales=list(x=list(log=TRUE)), cex=0.2, data=onesubj)

```

