

UNIX BUILD NOTES

Some notes on how to build Sequence in Unix.

Building requirements for Unix based Systems : 3GB

Note

Always use absolute paths to configure and compile Sequence and the dependencies,
for example, when specifying the the path of the dependency:

```
../dist/configure --enable-cxx --disable-shared --with-pic --pre
```

Here BDB_PREFIX must absolute path - it is defined using \$(pwd) which ensures
the usage of the absolute path.

To Build

```
./autogen.sh  
./configure  
make  
make install # optional
```

This will build sequence-qt as well if the dependencies are met.

Dependencies

These dependencies are required:

Library	Purpose	Description
libssl	SSL Support	Secure communications
libboost	Boost	C++ Library

Optional dependencies:

Library	Purpose	Description
miniupnpc	UPnP Support	Firewall-jumping support
libdb4.8	Berkeley DB	Wallet storage (only needed when wallet enabled)
qt	GUI	GUI toolkit (only needed when GUI enabled)
protobuf	Payments in GUI	Data interchange format used for payment protocol (only needed when GUI enabled)
libqrencode	QR codes in GUI	Optional for generating QR codes (only needed when GUI enabled)

For the versions used in the release, see [release-process.md](#) under *Fetch and build inputs*.

System requirements

C++ compilers are memory-hungry. It is recommended to have at least 1 GB of memory available when compiling Sequence. With 512MB of memory or less compilation will take much longer due to swap thrashing.

Dependency Build Instructions: Ubuntu & Debian

Build requirements:

```
sudo apt-get install git build-essential libtool autotools-dev a
```

for Ubuntu 12.04 and later or Debian 7 and later libboost-all-dev has to be installed:

```
sudo apt-get install libboost-all-dev
```

db4.8 packages are available [here](#).

You can add the repository using the following command:

```
sudo add-apt-repository ppa:bitcoin/bitcoin
sudo apt-get update
```

Ubuntu 12.04 and later have packages for libdb5.1-dev and libdb5.1++-dev, but using these will break binary wallet compatibility, and is not recommended.

for Debian 7 (Wheezy) and later:

The oldstable repository contains db4.8 packages.

Add the following line to /etc/apt/sources.list, replacing [mirror] with any official debian mirror.

```
deb http://[mirror]/debian/ oldstable main
```

To enable the change run

```
sudo apt-get update
```

for other Debian & Ubuntu (with ppa):

```
sudo apt-get install libdb4.8-dev libdb4.8++-dev
```

Optional:

```
sudo apt-get install libminiupnpc-dev (see --with-miniupnpc and
```

Dependencies for the GUI: Ubuntu & Debian

If you want to build Sequence-Qt, make sure that the required packages for Qt development

are installed. Qt 5 is necessary to build the GUI.

If both Qt 4 and Qt 5 are installed, Qt 5 will be used. Pass `--with-gui=qt5`

to configure to choose Qt5.

To build without GUI pass `--without-gui`.

For Qt 5 you need the following:

```
sudo apt-get install libqt5gui5 libqt5core5a libqt5dbus5 qttools
```

libqrencode (optional) can be installed with:

```
sudo apt-get install libqrencode-dev
```

Once these are installed, they will be found by configure and a sequence-qt executable will be built by default.

Notes

The release is built with GCC and then "strip sequenced" to strip the debug symbols, which reduces the executable size by about 90%.

miniupnpc

[miniupnpc](#) may be used for UPnP port mapping. It can be downloaded from [here](#). UPnP support is compiled in and turned off by default. See the configure options for upnp behavior desired:

<code>--without-miniupnpc</code>	No UPnP support miniupnp not required
<code>--disable-upnp-default</code>	(the default) UPnP support turned off b
<code>--enable-upnp-default</code>	UPnP support turned on by default at ru

To build:

```
tar -xzf miniupnpc-1.6.tar.gz
cd miniupnpc-1.6
make
sudo su
make install
```

Berkeley DB

It is recommended to use Berkeley DB 4.8. If you have to build it yourself:

```
SEQUENCE_ROOT=$(pwd)

# Pick some path to install BDB to, here we create a directory w
BDB_PREFIX="${SEQUENCE_ROOT}/db4"
mkdir -p $BDB_PREFIX

# Fetch the source and verify that it is not tampered with
wget 'http://download.oracle.com/berkeley-db/db-4.8.30.NC.tar.gz'
echo '12edc0df75bf9abd7f82f821795bcee50f42cb2e5f76a6a281b8573279'
# -> db-4.8.30.NC.tar.gz: OK
tar -xzvf db-4.8.30.NC.tar.gz

# Build the library and install to our prefix
cd db-4.8.30.NC/build_unix/
# Note: Do a static build so that it can be embedded into the e
../dist/configure --prefix=/usr/local --enable-cxx
make
sudo make install

# Configure Sequence to use our own-built instance of BDB
cd $SEQUENCE_ROOT
./configure (other args...) LDFLAGS="-L${BDB_PREFIX}/lib/" CPPFL
```

Note: You only need Berkeley DB if the wallet is enabled (see the section *Disabling-Wallet mode* below).

Boost

If you need to build Boost yourself:

```
sudo su
./bootstrap.sh
./bjam install
```

Security

To help make your Sequence installation more secure by making certain attacks impossible to exploit even if a vulnerability is found, binaries are hardened by default. This can be disabled with:

Hardening Flags:

```
./configure --enable-hardening  
./configure --disable-hardening
```

Hardening enables the following features:

- Position Independent Executable
Build position independent code to take advantage of Address Space Layout Randomization offered by some kernels. An attacker who is able to cause execution of code at an arbitrary memory location is thwarted if he doesn't know where anything useful is located.
The stack and heap are randomly located by default but this allows the code section to be randomly located as well.

On an Amd64 processor where a library was not compiled with -fPIC, this will cause an error such as: "relocation R_X86_64_32 against `.....' can not be used when making a shared object;"

To test that you have built PIE executable, install scanelf, part of paxutils, and use:

```
scanelf -e ./sequenced
```

The output should contain:

TYPE

ET_DYN

- Non-executable Stack

If the stack is executable then trivial stack based buffer overflow exploits are possible if vulnerable buffers are found. By default, sequence should be built with a non-executable stack but if one of the libraries it uses asks for an executable stack or someone makes a mistake and uses a compiler extension which requires an executable stack, it will silently build an executable without the non-executable stack protection.

To verify that the stack is non-executable after compiling use:

```
scanelf -e ./sequenced
```

the output should contain:

STK/REL/PTL

RW- R-- RW-

The STK RW- means that the stack is readable and writeable but not executable.

Disable-wallet mode

When the intention is to run only a P2P node without a wallet, sequence may be compiled in disable-wallet mode with:

```
./configure --disable-wallet
```

In this case there is no dependency on Berkeley DB 4.8.

Mining is also possible in disable-wallet mode, but only using the `getblocktemplate` RPC call not `getwork`.

Example Build Command

Qt Wallet and Deamon, CLI version build:

```
./autogen.sh && ./configure --with-gui=qt5 && make
```

CLI and Deamon Only Buld:

```
./autogen.sh && ./configure --without-gui && make
```