

Dynamic (DYN) v2.4.0.0



Copyright (c) 2016-2019 [Duality Blockchain Solutions](#)

What is **Dynamic**?

- Coin Suffix: DYN
- PoW Mining Algorithm: Argon2d
- PoW Difficulty Algorithm: Digishield V3
- PoW Period: Unlimited
- PoW Target Spacing: 128 Seconds
- PoW Reward per Block: Controlled via Fluid Protocol
- PoW Reward Start Height: Block 5,137
- Maturity: 10 Blocks
- PoW Blocks: ~675 per day
- Dynode Collateral Amount: 1000 DYN
- Dynode Min Confirmation: 17 Blocks
- Dynode Reward: Controlled via Fluid Protocol
- Dynode Reward Start Height: Block 10,273
- Total Coins: $2^{63} - 1$
- Min TX Fee: 0.0001 DYN

Dynamic(DYN) allows fast, secure, verifiable transfers of data using blockchain technology and enables third-party developers to build low-cost solutions across varied industry using the BDAP protocol. Dynamic can be used to run incentivized Dynodes; the second tier of nodes on the network processing, verifying, validating and storing data.

MainNet Parameters

P2P Port = 33300

RPC Port = 33350

Dynodes = 33300

Magic Bytes: 0x5e 0x61 0x74 0x80

TestNet Parameters

P2P Port = 33400

RPC Port = 33450

Dynodes = 33400

Magic Bytes: 0x2f 0x32 0x15 0x40

RegTest Parameters

P2P Port = 33500

RPC Port = 33550

Dynodes = 33500

Magic Bytes = 0x2f 0x32 0x15 0x3f

UNIX BUILD NOTES

Some notes on how to build [Dynamic](#) in Unix.

Note

Always use absolute paths to configure and compile Dynamic and the dependencies, for example, when specifying the path of the dependency:

```
../dist/configure --enable-cxx --disable-shared --with-pic --prefix=$BDB_PREFIX
```

Here BDB_PREFIX must absolute path - it is defined using \$(pwd) which ensures the usage of the absolute path.

To Build

```
bash
./autogen.sh
./configure
make
make install # optional
```

This will build dynamic-qt as well if the dependencies are met.

Dependencies

These dependencies are required:

Library	Purpose	Description
libssl	SSL Support	Secure communications
libboost	Boost	C++ Library
libevent	Networking	OS independent asynchronous networking

Optional dependencies:

Library	Purpose	Description
miniupnpc	UPnP Support	Firewall-jumping support
libdb4.8	Berkeley DB	Wallet storage (only needed when wallet enabled)
qt	GUI	GUI toolkit (only needed when GUI enabled)
protobuf	Payments in GUI	Data interchange format used for payment protocol (only needed when GUI enabled)
libqrencode	QR codes in GUI	Optional for generating QR codes (only needed when GUI enabled)
libzmq3	ZMQ notification	Optional, allows generating ZMQ notifications (requires ZMQ version $\geq 4.x$)

For the versions used in the release, see [release-process.md](#) under *Fetch and build inputs*.

System requirements

C++ compilers are memory-hungry. It is recommended to have at least 3 GB of memory available when compiling Dynamic.

Dependency Build Instructions: Ubuntu & Debian

It is required to build Dynamic on Ubuntu 18.04LTS(Bionic) or later due to C++14/GCC7 requirements. Also OpenSSL 1.1.0g is included in Ubuntu 18.04LTS and later, however it is suggested to use OpenSSL 1.1.1LTS.

Build requirements:

```
sudo apt-get install build-essential libtool autotools-dev autoconf pkg-config libssl-dev libcrypto++-dev libevent-dev git
```

For Ubuntu 18.04LTS(Bionic) and later, or Debian 7 and later; libboost-all-dev has to be installed:

```
sudo apt-get install libboost-all-dev
```

db4.8 packages are available [here](#). You can add the repository using the following command:

```
sudo add-apt-repository ppa:bitcoin/bitcoin
sudo apt-get update
```

Ubuntu 18.04 and later have packages for libdb 5.3.21 but using these will break binary wallet compatibility, and is not recommended.

for Debian 7 (Wheezy) and later:

The oldstable repository contains db4.8 packages. Add the following line to /etc/apt/sources.list, replacing [mirror] with any official debian mirror.

```
deb http://[mirror]/debian/ oldstable main
```

To enable the change run

```
sudo apt-get update
```

for other Debian & Ubuntu (with ppa):

```
sudo apt-get install libdb4.8-dev libdb4.8++-dev
```

Optional (see --with-miniupnpc and --enable-upnp-default):

```
sudo apt-get install libminiupnpc-dev
```

ZMQ dependencies (provides ZMQ API 4.x):

```
sudo apt-get install libzmq3-dev
```

Dependencies for the GUI: Ubuntu & Debian

If you want to build Dynamic-Qt, make sure that the required packages for Qt development are installed. Qt 5 is necessary to build the GUI. If both Qt 4 and Qt 5 are installed, Qt 5 will be used. Pass `--with-gui=qt5` to configure to choose Qt5. To build without GUI pass `--without-gui`.

For Qt 5 you need the following:

```
sudo apt-get install libqt5gui5 libqt5core5a libqt5dbus5 qttools5-dev qttools5-dev-tools libprotobuf-dev protobuf-compiler libcryptopp-dev
```

libqrencode (optional) can be installed with:

```
sudo apt-get install libqrencode-dev
```

Once these are installed, they will be found by configure and a dynamic-qt executable will be built by default.

Notes

The release is built with GCC and then "strip dynamicd" to strip the debug symbols, which reduces the executable size by about 90%.

miniupnpc

The dependencies for miniupnpc are included above within the 'Dependency Build Instructions: Ubuntu & Debian' section, however, for any reason you wish to build the source, please follow these instructions.

[miniupnpc](#) may be used for UPnP port mapping. It can be downloaded from [here](#). UPnP support is compiled in and turned off by default. See the configure options for upnp behavior desired:

`--without-miniupnpc` No UPnP support miniupnp not required
`--disable-upnp-default` (the default) UPnP support turned off by default at runtime
`--enable-upnp-default` UPnP support turned on by default at runtime

To build:

```
tar -xzvf miniupnpc-1.6.tar.gz
cd miniupnpc-1.6
make
sudo su
make install
```

Berkeley DB

It is recommended to use Berkeley DB 4.8 and is included in the dependencies above in the 'Dependency Build Instructions: Ubuntu & Debian' section.

If you have to, or wish to build Berkeley DB 4.8 yourself:

```
bash
DYNAMIC_ROOT=$(pwd)

# Pick some path to install BDB to, here we create a directory within the dynamic
directory
BDB_PREFIX="${DYNAMIC_ROOT}/db4"
mkdir -p $BDB_PREFIX

# Fetch the source and verify that it is not tampered with
wget 'http://download.oracle.com/berkeley-db/db-4.8.30.NC.tar.gz'
echo '12edc0df75bf9abd7f82f821795bcee50f42cb2e5f76a6a281b85732798364ef
db-4.8.30.NC.tar.gz' | sha256sum -c

# -> db-4.8.30.NC.tar.gz: OK
tar -xzvf db-4.8.30.NC.tar.gz

# Build the library and install to our prefix
cd db-4.8.30.NC/build_unix/

# Note: Do a static build so that it can be embedded into the executable, instead
of having to find a .so at runtime
../dist/configure --prefix=/usr/local --enable-cxx
make
sudo make install

# Configure Dynamic to use our own-built instance of BDB
cd $DYNAMIC_ROOT ./configure (other args...) LDFLAGS="-L${BDB_PREFIX}/lib/"
CPPFLAGS="-I${BDB_PREFIX}/include/"
```

Boost

If you need to build Boost yourself, in terminal enter:

```
sudo su
./bootstrap.sh
./bjam install
```

Security

To help make your Dynamic installation more secure by making certain attacks impossible to exploit even if a vulnerability is found, binaries are hardened by default.

This can be disabled with:

Hardening Flags:

```
./configure --enable-hardening
./configure --disable-hardening
```

Hardening enables the following features:

- Position Independent Executable

Build position independent code to take advantage of Address Space Layout Randomization

offered by some kernels. An attacker who is able to cause execution of code at an arbitrary memory location is thwarted if he doesn't know where anything useful is located.

The stack and heap are randomly located by default but this allows the code section to be randomly located as well.

On an Amd64 processor where a library was not compiled with -fPIC, this will cause an error

such as: "relocation R_X86_64_32 against `.....' can not be used when making a shared object;"

To test that you have built PIE executable, install scanelf, part of paxutils, and use: scanelf -e ./dynamiccd

The output should contain:

TYPE

ET_DYN

- Non-executable Stack

If the stack is executable then trivial stack based buffer overflow exploits are possible if

vulnerable buffers are found. By default, dynamic should be built with a non-executable stack

but if one of the libraries it uses asks for an executable stack or someone makes a mistake

and uses a compiler extension which requires an executable stack, it will silently build an executable without the non-executable stack protection.

To verify that the stack is non-executable after compiling use: `scanelf -e ./dynamicd`

the output should contain:

STK/REL/PTL

RW- R-- RW-

The STK RW- means that the stack is readable and writeable but not executable.

Disable-wallet mode

When the intention is to run only a P2P node without a wallet, dynamic may be compiled in disable-wallet mode with:

```
./configure --disable-wallet
```

In this case there is no dependency on Berkeley DB 4.8.

Mining is also possible in disable-wallet mode, but only using the getblock template RPC call not getwork .

AVX2 Mining Optimisations

For increased performance when mining, AVX2 optimisations can be enabled.

At configure time:

`--enable-avx2`

CPU's with AVX2 support:

Intel

Haswell processor, Q2 2013

Haswell E processor, Q3 2014

Broadwell processor, Q4 2014

Broadwell E processor, Q3 2016

Skylake processor, Q3 2015

Kaby Lake processor, Q3 2016(ULV mobile)/Q1 2017(desktop/mobile)

Coffee Lake processor, Q4 2017

AMD

Carrizo processor, Q2 2015

Ryzen processor, Q1 2017

AVX512 Mining Optimisations

For increased performance when mining, AVX512 optimisations can be enabled.

At configure time:

`--enable-avx512f`

CPU's with AVX512 support:

Intel

Xeon Phi x200/Knights Landing processor, 2016

Knights Mill processor, 2017

Skylake-SP processor, 2017

Skylake-X processor, 2017

Cannonlake processor, expected in 2019

Ice Lake processor, expected in 2019

GPU Mining

To enable GPU mining within the wallet, OpenCL or CUDA can be utilised. Please use GCC/G++ 6.4 or newer and for CUDA to be utilised please use CUDA 9.1 or newer and ensure you have graphics drivers installed.

For OpenCL you need the following:

```
sudo apt-get install ocl-icd-openssl-dev
```

For CUDA please visit: <https://docs.nvidia.com/cuda/cuda-installation-guide-linux/index.html>

At configure time for OpenCL(Nvidia/AMD):

```
--enable-gpu
```

At configure time for CUDA(Nvidia):

```
--enable-gpu --enable-cuda
```

Example Build Command

Qt Wallet and Daemon, CLI version build without GPU support and without AVX support:

```
./autogen.sh && ./configure --with-gui --disable-gpu && make
```

CLI and Daemon Only build without GPU support and without AVX support:

```
./autogen.sh && ./configure --without-gui --disable-gpu && make
```

Use Qt Creator as IDE

You can use Qt Creator as IDE, for debugging and for manipulating forms, etc. Download Qt Creator from <http://www.qt.io/download/>. Download the "community edition" and only install Qt Creator (uncheck the rest during the installation process).

1. Make sure you installed everything through homebrew mentioned above
2. Do a proper `./configure --with-gui=qt5 --enable-debug`

3. In Qt Creator do "New Project" -> Import Project -> Import ExistingProject
4. Enter "dynamic-qt" as project name, enter src/qt as location
5. Leave the file selection as it is
6. Confirm the "summary page"
7. In the "Projects" tab select "Manage Kits..."
8. Select the default "Desktop" kit and select "Clang (x86 64bit in /usr/bin)" as compiler
9. Select LLDB as debugger (you might need to set the path to your installation)
10. Start debugging with Qt Creator