

Granola Oven Speed Guide

Quick daily reference for tunnel belt and hopper spreader speed changes.

**Start slow
increase gradually**
Helps control finished
granola moisture

Why the slow start matters

Starting too fast can leave granola too high in moisture. Begin slowly so the product has enough time in the oven.

Hopper spreader

Drops granola onto the oven belt. Keep both sides matched to the speed shown in the guide.

SPEED RAMP-UP SEQUENCE

STEP	WHEN TO USE	TUNNEL BELT	HOPPER SPREADER
1 Gentle Start Initial oven loading	Use at start-up while granola begins travelling through the oven.	12 Hz	4.2 Hz / 4.2 Hz
2 Kibbler Transition First granola exits oven	When granola comes out of the oven and drops to the kibbler, increase speed.	14.5 Hz	5.3 Hz / 5.3 Hz
3 10-Minute Increase After kibbler transition	After 10 minutes at the kibbler transition setting.	16 Hz	6.5 Hz / 6.5 Hz
4 20-Minute Running Speed Final ramp step	After another 10 minutes, use final running speed.	17.2 Hz	7.7 Hz / 7.7 Hz

Hopper spreader values show left side / right side settings.

Tunnel belt delay

If any interval on the tunnel belt exceeds 5 minutes, revert to the Kibbler Transition setting:

Tunnel belt **14.5 Hz**

Hopper spreader **5.3 Hz / 5.3 Hz**

Temperature limit

Maximum oven temperature at any time:

150 C

DAILY CHECKS TO REMEMBER

- ☐ Pre-heat the oven before production setup begins.
- ☐ Start Transport, Cooling, and Heating.
- ☐ Wait until B3 / Burner 3 Actual Power is under 50% before starting production.
- ☐ Start with the Gentle Start setting: 12 Hz belt and 4.2 Hz / 4.2 Hz hopper spreader.
- ☐ When granola reaches the kibbler, follow the 10-minute ramp-up sequence.
- ☐ Keep the oven temperature at or below 150 C.

Granola oven speed guide - read before changing tunnel belt or hopper spreader speeds.