

S1R72U16
Connection Guide
For connecting to local 16-bit
CPU bus (memory bus)

NOTICE

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. This material or portions thereof may contain technology or the subject relating to strategic products under the control of the Foreign Exchange and Foreign Trade Law of Japan and may require an export license from the Ministry of Economy, Trade and Industry or other approval from another government agency.

All other product names mentioned herein are trademarks and/or registered trademarks of their respective companies.

Table of Contents

1. Requirements for using the S1R72U16 connected to a local 16-bit CPU bus (memory bus)	1
2. Modifying I/O register addresses	2
3. Changing the data transfer method	3
4. Changing interrupt processing	3

1. Requirements for using the S1R72U16 connected to a local 16-bit CPU bus (memory bus)

The following drivers can be used when the S1R72U16 is connected to a local 16-bit CPU bus (hereafter “CPU bus”).

- ATA/ATAPI driver
- CF driver

These drivers can be obtained from the following sources:

- Use drivers included with the CPU, operating system, or file system.
- Purchase drivers from a software developer.
- Use the sample ATA/ATAPI (CF) driver provided by Seiko Epson.*
 - * Use of software provided by Seiko Epson requires acceptance of the terms of the license agreement.
 - * The sample ATA/ATAPI (CF) driver is based on μ ITRON specifications. There are no plans to implement support for other operating systems.

Using S1R72U16 with these drivers requires the following modifications:

- Change I/O register addresses.

The following modifications may also be required:

- Changes in data transfer method for data transfers via DMA.
- Changes in interrupt processing for device interrupts.

Complete these modifications, as follows:

2. Modifying I/O register addresses

2. Modifying I/O register addresses

Drivers access the registers indicated in Table 2-1 for device control.

Table 2-1 I/O registers

ATA task file registers (*1)		
Operation	READ	WRITE
Register name	Data	
	Error	Features
	Sector Count	
	LBA Low (Sector Number *2, *3)	
	LBA Mid (Cylinder Low *2, *3)	
	LBA High (Cylinder High *2, *3)	
	Device (Device/Head *2) (Select Card/Head *3)	
	Status	Command
	Alternate Status	Device Control

*1 These registers are known collectively as “ATA task file registers.” They are sometimes referred to as “task file registers.”

*2 Register names as defined in specifications prior to AT Attachment with Packet Interface—5 (ATA/ATAPI-5).

*3 Register names as defined in the CompactFlash Specifications.

When the S1R72U16 is connected to a CPU bus, the registers indicated in Table 2-1 are mapped to CPU memory space as shown in Table 2-2.

Modify I/O register addresses defined by the driver so that they correspond to the S1R72U16 I/O register addresses mapped to CPU memory space.

Table 2-2 S1R72U16 register map

OFFSET (*)	ATA task file registers	
	READ	WRITE
00h	Data (16bit)	
01h		
02h	Error	Feature
03h		
04h	Sector Count	
05h		
06h	LBA Low	
07h		
08h	LBA Mid	
09h		
0Ah	LBA High	
0Bh		
0Ch	Device	
0Dh		
0Eh	Status	Command

OFFSET (*)	ATA task file registers	
	READ	WRITE
10h	none	
11h		
12h	none	
13h		
14h	none	
15h		
16h	none	
17h		
18h	none	
19h		
1Ah	none	
1Bh		
1Ch	Alternate Status	Device Control
1Dh		
1Eh	none	

* OFFSET: Start addresses of the memory space allocated for S1R72U16 I/O registers.

3. Changing the data transfer method

For data transfers with the S1R72U16 via DMA,* use a DMA controller capable of transferring data between the device connected to the CPU bus and memory. For information on DMA controller control methods, consult the CPU documentation or contact the CPU manufacturer.

- * When the S1R72U16 is connected to the CPU bus, you cannot use Ultra DMA as defined in AT Attachment with Packet Interface—4 (ATA/ATAPI-4) or later specifications. Use multi-word DMA instead.

4. Changing interrupt processing

To use S1R72U16 interrupts with the driver, use an XINT signal and modify an interrupt handler or the like to notify the driver of interrupts.

AMERICA

EPSON ELECTRONICS AMERICA, INC.**HEADQUARTERS**

2580 Orchard Parkway
San Jose, CA 95131, USA
Phone: +1-800-228-3964 FAX: +1-408-922-0238

SALES OFFICES**Northeast**

301 Edgewater Place, Suite 210
Wakefield, MA 01880, U.S.A.
Phone: +1-800-922-7667 FAX: +1-781-246-5443

EUROPE

EPSON EUROPE ELECTRONICS GmbH**HEADQUARTERS**

Riesstrasse 15
80992 Munich, GERMANY
Phone: +49-89-14005-0 FAX: +49-89-14005-110

ASIA

EPSON (CHINA) CO., LTD.

23F, Beijing Silver Tower 2# North RD DongSanHuan
ChaoYang District, Beijing, CHINA
Phone: +86-10-6410-6655 FAX: +86-10-6410-7320

SHANGHAI BRANCH

7F, High-Tech Bldg., 900, Yishan Road,
Shanghai 200233, CHINA
Phone: +86-21-5423-5522 FAX: +86-21-5423-5512

EPSON HONG KONG LTD.

20/F., Harbour Centre, 25 Harbour Road
Wanchai, Hong Kong
Phone: +852-2585-4600 FAX: +852-2827-4346
Telex: 65542 EPSCO HX

EPSON Electronic Technology Development (Shenzhen) LTD.

12/F, Dawning Mansion, Keji South 12th Road,
Hi-Tech Park, Shenzhen
Phone: +86-755-2699-3828 FAX: +86-755-2699-3838

EPSON TAIWAN TECHNOLOGY & TRADING LTD.

14F, No. 7, Song Ren Road,
Taipei 110
Phone: +886-2-8786-6688 FAX: +886-2-8786-6660

EPSON SINGAPORE PTE., LTD.

1 HarbourFront Place,
#03-02 HarbourFront Tower One, Singapore 098633
Phone: +65-6586-5500 FAX: +65-6271-3182

SEIKO EPSON CORPORATION**KOREA OFFICE**

50F, KLI 63 Bldg., 60 Yoido-dong
Youngdeungpo-Ku, Seoul, 150-763, KOREA
Phone: +82-2-784-6027 FAX: +82-2-767-3677

GUMI OFFICE

2F, Grand B/D, 457-4 Songjeong-dong,
Gumi-City, KOREA
Phone: +82-54-454-6027 FAX: +82-54-454-6093

SEIKO EPSON CORPORATION**SEMICONDUCTOR OPERATIONS DIVISION****IC Sales Dept.****IC International Sales Group**

421-8, Hino, Hino-shi, Tokyo 191-8501, JAPAN
Phone: +81-42-587-5814 FAX: +81-42-587-5117