

HDF5 telemetry log format (TLMC)

This file describes the content of the so-called `tlmc` format. `tlmc` stands for compressed telemetry: it is simply a standard HDF5 file with compression enabled, that can be opened with any HDF5 reader. This document specifies the organization of data in this file.

The telemetry of the robot outputs two different types of object: constants and variables. They must have a unique name and can have various basic types. Constants are (key, value) pairs and variables consists of two time series: one for time, one for values. Unlike constants, variables can have metadata associated to them.

The `tlmc` will be organized as follows:

- The root group shall contain an attribute `'VERSION'`, which stores an int specifying the version of the `tlmc` standard use. This document describes `VERSION=1`.
- The root group shall contain an attribute `'START_TIME'`, which stores a long specifying the absolute start time of the log, in second relative to the UNIX epoch.
- A group `constants` will store the telemetry constants in its attribute dictionary for scalar data of any type or as independent `constantName` 0D datasets without filter nor compression for null-padded byte arrays exclusively. The former only supports data of up to 64K bytes as per the HDF5 standard, while the latter as no size limitation and is convenient for pre-serialized data.
- A second group `variables` will store the variables.
 - Each subgroup `variableName` represents a variable, originally named `variableName`. Each variable group contains:
 - * A `value` 1D dataset representing the variable's values through time.
 - * A `time` 1D dataset representing the time instants relative to the `'START_TIME'` file constant. This dataset will contain an attribute `unit` specifying the ratio to SI unit (i.e. 1 second). For instance when using nanoseconds, `file["variables/myvariable/time"].attrs["unit"]` evaluates to `1.0e-9`.
 - * Variable-specific metadata stored in the group's attribute.

For storage efficiency, all datasets for variables will be stored using the `'gzip'` filter with compression level of 4, and the `'shuffle'` filter. The chunk size is equal to the number of timestamps to maxing-out reading performances. These are enabled in `h5py` using the following flags:

```
f.create_dataset(name,
                  data=data_array,
                  compression='gzip',
                  shuffle=True,
                  chunks=(len(data_array),))
```

The examples in this document are made using the `h5py` library ; `file` is an `h5py.File` object.

Here is a python snippet for parsing a tlmc file:

```
import h5py

file = h5py.File('my_file.tlmc', 'r')

print(file.attrs['VERSION']) # Prints 1
print("The log contains the following constants:")
for k, v in file['constants'].attrs.items():
    print(k, v)
for k, dataset in file['constants'].items():
    v = bytes(dataset[()])
    v += b'\0' * (dataset.nbytes - len(v)) # Append missing null char '\0' at end
    print(k, v)
print(f"Log start time: {file.attrs['START_TIME']}")
print("The log contains the following variables:")
for variable_name in file['variables']:
    print(variable_name)
```

Examples

Here is a (simplified) view of a tlmc file using the `h5dump -p`

```
HDF5 "data/20200921T101310Z_LogFile.tlmc" {
GROUP "/" {
  ATTRIBUTE "START_TIME" {
    DATATYPE  H5T_IEEE_F64LE
    DATASPACE SCALAR
    DATA {
      (0): 1607002673
    }
  }
  ATTRIBUTE "VERSION" {
    DATATYPE  H5T_STD_I32LE
    DATASPACE SCALAR
    DATA {
      (0): 1
    }
  }
}
GROUP "constants" {
  ATTRIBUTE "NumIntEntries" {
    DATATYPE  H5T_STD_I32LE
    DATASPACE SCALAR
    DATA {
      (0): 1
    }
  }
  DATASET "HighLevelController.controlOffsetTimestamp" {
```

```

        DATATYPE H5T_STRING {
            STRSIZE 8;
            STRPAD H5T_STR_NULLPAD;
            CSET H5T_CSET_ASCII;
            CTYPE H5T_C_S1;
        }
        DATASPACE SCALAR
        DATA {
            (0): "1.680000"
        }
    }
    ...
}
GROUP "variables" {
    GROUP "HighLevelController.currentPositionLeftSagittalHip" {
        DATASET "time" {
            DATATYPE H5T_STD_I64LE
            DATASPACE SIMPLE { ( 338623 ) / ( 338623 ) }
            ATTRIBUTE "unit" {
                DATATYPE H5T_IEEE_F64LE
                DATASPACE SCALAR
                DATA {
                    (0): 1e-09
                }
            }
        }
        DATASET "value" {
            DATATYPE H5T_IEEE_F64LE
            DATASPACE SIMPLE { ( 338623 ) / ( 338623 ) }
            STORAGE_LAYOUT {
                CHUNKED ( 338623 )
                SIZE 2708984 (1.000:1 COMPRESSION)
            }
            FILTERS {
                PREPROCESSING SHUFFLE
                COMPRESSION DEFLATE { LEVEL 4 }
            }
        }
    }
    ...
}
}
}

```