

Advanced Programming for HPC - Report 5

Dinh Anh Duc

November 5, 2021

Implementation

```
--global-- void gaussianNoShared(uchar3 *input, uchar3 *output, int imgWidth, int imgHeight){
    float gaussianBlur[7][7]={
        {0, 0, 1, 2, 1, 0, 0},
        {0, 3, 13, 22, 13, 3, 0},
        {1, 13, 59, 97, 59, 13, 1},
        {2, 22, 97, 159, 97, 22, 2},
        {1, 13, 59, 97, 59, 13, 1},
        {0, 3, 13, 22, 13, 3, 0},
        {0, 0, 1, 2, 1, 0, 0}
    };
    int col = threadIdx.x + blockIdx.x * blockDim.x;
    int row = threadIdx.y + blockIdx.y * blockDim.y;
    int tid = row * imgWidth + col;
    int sumR = 0;
    int sumG = 0;
    int sumB = 0;
    for (int j = 0; j < 7; j++) {
        for (int i = 0; i < 7; i++) {
            int cell_id = tid + i + j * imgWidth;
            sumR += input[cell_id].x * gaussianBlur[j][i];
            sumG += input[cell_id].y * gaussianBlur[j][i];
            sumB += input[cell_id].z * gaussianBlur[j][i];
        }
    }

    output[tid].x = sumR/1003;
    output[tid].y = sumG/1003;
    output[tid].z = sumB/1003;
}

--global-- void gaussianShared(uchar3 *input, uchar3 *output, int imgWidth, int imgHeight){
    float gaussianBlur[7][7]={
        {0, 0, 1, 2, 1, 0, 0},
        {0, 3, 13, 22, 13, 3, 0},
        {1, 13, 59, 97, 59, 13, 1},
        {2, 22, 97, 159, 97, 22, 2},
        {1, 13, 59, 97, 59, 13, 1},
        {0, 3, 13, 22, 13, 3, 0},
        {0, 0, 1, 2, 1, 0, 0}
    };

    int col = threadIdx.x + blockIdx.x * blockDim.x;
    int row = threadIdx.y + blockIdx.y * blockDim.y;
    int tid = row * imgWidth + col;

    __shared__ float gb[7][7];
    gb[threadIdx.x][threadIdx.y] = gaussianBlur[row][col];
    __syncthreads();

    int sumR = 0;
    int sumG = 0;
    int sumB = 0;
    for (int j = 0; j < 7; j++) {
        for (int i = 0; i < 7; i++) {
```

```

        int cell_id = tid + i + j * imgWidth;
        sumR += input[cell_id].x * gb[threadIdx.x][threadIdx.y];
        sumG += input[cell_id].y * gb[threadIdx.x][threadIdx.y];
        sumB += input[cell_id].z * gb[threadIdx.x][threadIdx.y];
    }
}

output[tid].x = sumR/1003;
output[tid].y = sumG/1003;
output[tid].z = sumB/1003;
}

void Labwork::labwork5_GPU(bool shared) {
    // Calculate number of pixels
    int pixelCount = inputImage->width * inputImage->height;

    // Allocate CUDA memory
    uchar3 *devInput;
    uchar3 *devOutput;
    cudaMalloc(&devInput, pixelCount);
    cudaMalloc(&devOutput, pixelCount);

    // Copy CUDA Memory from CPU to GPU
    cudaMemcpy(devInput, inputImage, pixelCount, cudaMemcpyHostToDevice);

    // Processing
    dim3 blockSize = dim3(32, 32);
    dim3 gridSize = ((int) ((inputImage->width + blockSize.x - 1)/blockSize.x), (int)((inputImage->height +
    if(shared == false){
        gaussianNoShared<<<gridSize, blockSize>>>(devInput, devOutput, inputImage->width, inputImage->height);
    }else{
        gaussianShared<<<gridSize, blockSize>>>(devInput, devOutput, inputImage->width, inputImage->height);
    }
    // Copy CUDA Memory from GPU to CPU
    cudaMemcpy(inputImage, devOutput, pixelCount, cudaMemcpyHostToDevice);

    // Cleaning
    //free(hostInput);
    cudaFree(devInput);
    cudaFree(devOutput);
}

```

Result



Figure 1: Original input image



Figure 2: Output image

Without using shared memory mode

USTH ICT Master 2018, Advanced Programming for HPC.
Warming up...
Starting labwork 5
labwork 5 elapsed 222,5ms

Using shared memory mode

USTH ICT Master 2018, Advanced Programming for HPC.
Warming up...
Starting labwork 5
labwork 5 elapsed 228.6ms