

Eight-model performance on identical six candidate trajectories

nuScenes custom scene-isolated CV; 630 scenes; Overall n=260,151; V n=191,026; P n=66,145; Moving V n=41,728

Method	Params	FDE (m)	ADE (m)	Vehicle FDE (m)	Pedestrian FDE (m)	Moving V. FDE (m)	minFDE6 (m)	HitRate (%)	Head ms/1024	Whole s/16 windows
R0	0	2.373	1.056	2.731	1.353	10.875	1.266	45.18	0.08	0.066
R2	673	2.347	1.044	2.699	1.346	10.725	1.266	45.50	2.05	0.210
NG-A	7,425	2.376	1.065	2.741	1.340	10.864	1.266	43.93	4.79	0.223
NG-C	7,425	2.307	1.021	2.648	1.335	10.471	1.266	46.45	4.80	0.223
G-A	24,066	2.362	1.064	2.720	1.344	10.715	1.266	44.02	10.42	0.239
G-C	24,066	2.261	1.000	2.588	1.330	10.211	1.266	47.04	10.43	0.236
Matched-NG-C	24,001	2.284	1.009	2.616	1.338	10.324	1.266	46.75	6.59	0.232
Adapted TNT	16,001	2.422	1.083	2.795	1.360	11.111	1.266	48.94	5.14	0.081

HitRate: selected mode equals endpoint-FDE oracle (not a distance-threshold success rate). Parameters: scoring head only.

Compute: equal fold means; cached head forward and full path on 16 fixed InnerDev windows. Excludes raw I/O; actor counts vary by fold.

Adapted TNT uses frozen HiVT context; the external comparison is supplementary and not an official leaderboard result.