$% \ gcc217 \ hello.c -o \ hello$ 

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

% ./hello

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

Writes:

22386 hello

```
int main(void)
{
  pid_t iPid;
  iPid = getpid()
  printf("%d nello\n", (int)iPiN;
  return 0;
}
```

9

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

% ./hello

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d hello\n", (int)iPid);
   return 0;
}
```

Writes:

22387 hello

```
int main(void)
{
   pid_t iPid;
   iPid = getpid();
   printf("%d Hello\n", (int)iPiN;
   return 0;
}
```

%