Princeton University
COS 217: Introduction to Programming Systems
The "const" Keyword with Pointers

Pointer to Constant

```
1:  const int i1 = 100;
2:  const int i2 = 200;
3:  const int *pi = &i1;        /* pi is a "pointer to a constant." */
4:  i1 = 300;                   /* Error.  Cannot change i1. */
5:  i2 = 400;                   /* Error.  Cannot change i2. */
6:  pi = &i2;                   /* OK. */
7:  *pi = 500;                  /* Error.  Cannot change *pi. */
```

Constant Pointer

```
1:  int i1 = 100;
2:  int i2 = 200;
3:  int *const pi = &i1;        /* pi is a "constant pointer." */
4:  i1 = 300;                   /* OK. */
5:  i2 = 400;                   /* OK. */
6:  pi = &i2;                   /* Error.  Cannot change pi. */
7:  *pi = 500;                  /* OK. */
```

Constant Pointer to Constant

```
1:  const int i1 = 100;
2:  const int i2 = 200;
3:  const int *const pi = &i1;    /* pi is a "constant pointer to a constant." */
4:  i1 = 300;                     /* Error.  Cannot change i1. */
5:  i2 = 400;                     /* Error.  Cannot change i2. */
6:  pi = &i2;                     /* Error.  Cannot change pi. */
7:  *pi = 500;                    /* Error.  Cannot change *pi. */
```

Disallowed Mismatch

```
1:  const int i1 = 100;
2:  const int i2 = 200;
3:  int *pi = &i1;          /* Error.  Subversive.
                               Subsequently changing *pi would change i1. */
```

Disallowed Mismatch in Function Calls

```
1:  void f(int *pi)
2:  {
3:      ...
4:  }

   ...

5:  const int i1 = 5;
6:  const int *pi2 = &i1;
7:  f(pi2);                 /* Error.  Subversive.
                               If f() changes *pi, then *pi2 also would change. */
```

Allowed Mismatch

```
1:  int i1 = 100;
2:  int i2 = 200;
3:  const int *pi = &i1;  /* OK, even though subsequently changing i1 would change *pi. */
4:  i1 = 300;             /* OK.  Also changes *pi. */
5:  i2 = 400;             /* OK. */
6:  pi = &i2;             /* OK, even though subsequently changing i2 would change *pi. */
7:  *pi = 500;            /* Error.  Cannot change *pi. */
```

Allowed Mismatch in Function Calls

```
1:  void f(const int *pi)
2:  {
3:      ...
4:  }

   ...

5:  int i1 = 5;
6:  int *pi2 = &i1;
7:  f(pi2);                 /* OK.  *pi2 is protected against accidental change by f(). */
```