

# Coupling

YEGOR BUGAYENKO

Lecture #6 out of 24

80 minutes

The slidedeck was presented by the author in this [YouTube Video](#)


All visual and text materials presented in this slidedeck are either originally made by the author or taken from public Internet sources, such as web sites. Copyright belongs to their respected authors.



WAYNE P. STEVENS,  
GLENFORD J. MYERS, AND  
LARRY L. CONSTANTINE

“The fewer and simpler the connections between modules, the easier it is to understand each module without reference to other modules.”

— Wayne P. Stevens, Glenford J. Myers, and Larry L. Constantine. Structured Design. *IBM Systems Journal*, 13(2):115–139, 1974. doi:[10.1147/sj.132.0115](https://doi.org/10.1147/sj.132.0115)



Source: <https://www.geeksforgeeks.org/coupling-in-java/>



GLENFORD MYERS

“Coupling is the measure of the strength of association established by a connection from one module to another. Strong coupling complicates a system since a module is harder to understand, change, or correct by itself if it is highly interrelated with other modules. Complexity can be reduced by designing systems with the weakest possible coupling between modules.”

— Wayne P. Stevens, Glenford J. Myers, and Larry L. Constantine. Structured Design. *IBM Systems Journal*, 13(2):115–139, 1974. doi:[10.1147/sj.132.0115](https://doi.org/10.1147/sj.132.0115)



Source: <https://www.javatpoint.com/software-engineering-coupling-and-cohesion>



WAYNE P. STEVENS

“The degree of coupling established by a particular connection is a function of several factors, and thus it is difficult to establish a simple index of coupling. Coupling depends (1) on how complicated the connection is, (2) on whether the connection refers to the module itself or something inside it, and (3) on what is being sent or received.”

— Wayne P. Stevens, Glenford J. Myers, and Larry L. Constantine. Structured Design. *IBM Systems Journal*, 13(2):115–139, 1974. doi:[10.1147/sj.132.0115](https://doi.org/10.1147/sj.132.0115)



Source: <https://nordicapis.com/the-difference-between-tight-coupling-and-loose-coupling/>



“Coupling Between Objects (CBO) — for a class is a count of the number of other classes to which it is coupled.”

— Shyam R. Chidamber and Chris F. Kemerer. A Metrics Suite for Object Oriented Design. *IEEE Transactions on Software Engineering*, 20(6):476–493, 1994. doi:10.1109/32.295895





“Direct Class Coupling (DCC) — this metric is a count of the different number of classes that a class is directly related to. The metric includes classes that are directly related by attribute declarations and message passing (parameters) in methods.”

— J. Bansiya and C.G. Davis. A Hierarchical Model for Object-Oriented Design Quality Assessment. *IEEE Transactions on Software Engineering*, 2002. doi:[10.1109/32.979986](https://doi.org/10.1109/32.979986)

JAGDISH BANSIYA AND CARL G. DAVIS



MARTIN FOWLER

“The biggest problems come from uncontrolled coupling at the upper levels. I don’t worry about the number of modules coupled together, but I look at the pattern of dependency relationship between the modules.”

— M. Fowler. Reducing Coupling. *IEEE Software*, 2001.  
[doi:10.1109/ms.2001.936226](https://doi.org/10.1109/ms.2001.936226)



STEVE McCONNELL

“Low-to-medium fan-out means having a given class use a low-to-medium number of other classes. High fan-out (more than about seven) indicates that a class uses a large number of other classes and may therefore be overly complex. High fan-in refers to having a high number of classes that use a given class. High fan-in implies that a system has been designed to make good use of utility classes at the lower levels in the system.”

— Steve McConnell. *Code Complete*. Pearson Education, 2004.  
[doi:10.5555/1096143](https://doi.org/10.5555/1096143)

**Fan-in** = number of ingoing dependencies  
**Fan-out** = number of outgoing dependencies



**Heuristic:** a high fan-in/fan-out indicates a high complexity

(c) Natalia Kokash, Leiden Institute of Advanced Computer Science



Fan-out, as a metric, is supported by a few tools:

- Checkstyle for Java
- CCCC for C++, C, and Java
- module-coupling-metrics for Python



DEREK COMARTIN

“Afferent coupling (denoted by **Ca**) is a metric that indicates the total number of other projects/boundaries that are dependent upon it. Efferent coupling (denoted by **Ce**) is another metric that is the verse of Afferent Coupling. It is the total number of projects that a given project depends on. Instability another metric that is a ratio:  $I = Ce / (Ce + Ca)$ . This metric is a ratio between 0 and 1. With 0 meaning it’s totally stable and 1 meaning it’s unstable.”

— Derek Comartin. Write Stable Code Using Coupling Metrics. <https://codeopinion.com/write-stable-code-using-coupling-metrics/>, 2021. [Online; accessed 15-03-2024]

## Types of Coupling (some of them)

- Content Coupling is when one module modifies or relies on the internal workings of another module (e.g., accessing local data of another module).
- Global Coupling is when two modules share the same global data (e.g., a global variable).
- External Coupling occurs when two modules share an externally imposed data format, communication protocol, or device interface.
- Control Coupling is one module controlling the flow of another, by passing it information on what to do (e.g., passing a what-to-do flag).
- Stamp Coupling is when modules share a composite data structure and use only a part of it, possibly a different part (e.g., passing a whole record to a function that only needs one field of it).
- Data Coupling is when modules share data through, for example, parameters. Each datum is an elementary piece, and these are the only data shared (e.g., passing an integer to a function that computes a square root).
- Message Coupling can be achieved by state decentralization (as in objects) and component communication is done via parameters or message passing (see Message passing).
- Subclass Coupling describes the relationship between a child and its parent. The child is connected to its parent, but the parent isn't connected to the child.
- Temporal Coupling is when two actions are bundled together into one module just because they happen to occur at the same time.

Source:

[https://wiki.edunitas.com/IT/en/114-10/Coupling-\(computer-programming\)\\_1430\\_eduNitas.html](https://wiki.edunitas.com/IT/en/114-10/Coupling-(computer-programming)_1430_eduNitas.html)



## Fear of Decoupling

```
1 interface Money {  
2     double cents();  
3 }  
4  
5 void send(Money m) {  
6     double c = m.cents();  
7     // Send them over via the API...  
8 }  
9  
10 class OneDollar implements Money {  
11     @Override  
12     double cents() {  
13         return 100.0d;  
14     }  
15 }
```

```
1 class EmployeeHourlyRate  
2     implements Money {  
3     @Override  
4     double cents() {  
5         // Fetch the exchange rate;  
6         // Update the database;  
7         // Calculate the hourly rate;  
8         // Return the value.  
9     }  
10 }
```

“Polymorphism makes software more fragile ... to make it more robust!”

## Temporal Coupling

Tight coupling (**not good**):

```
1 List<String> list =  
2   new LinkedList<>();  
3 Foo.append(list, "Jeff");  
4 Foo.append(list, "Walter");  
5 return list;
```

Loose coupling (**good**):

```
1 return Foo.with(  
2   Foo.with(  
3     new LinkedList<>(),  
4     "Jeff"  
5   ),  
6   "Walter"  
7 );
```

<https://www.yegor256.com/2015/12/08/temporal-coupling-between-method-calls.html>

## Distance of Coupling

```
1 class Temperature {  
2     private int t;  
3     public String toString() {  
4         return String.format("%d F", this.t);  
5     }  
6 }  
7  
8 Temperature x = new Temperature();  
9 String txt = x.toString();  
10 String[] parts = txt.split(" ");  
11 int t = Integer.parseInt(parts[0]);
```

“The larger the number (or the mean of all numbers), the worse the design: in good design we are not supposed to take something out of a method and then do some complex processing. The distance metric will tell us exactly that: how many times, and by how much, we violated the principle of loose coupling.”

<https://www.yegor256.com/2020/10/27/distance-of-coupling.html>

## Read this:

New Metric: the Distance of Coupling (2020)

Fear of Decoupling (2018)

Reflection Means Hidden Coupling (2022)

# References

J. Bansiya and C.G. Davis. A Hierarchical Model for Object-Oriented Design Quality Assessment. *IEEE Transactions on Software Engineering*, 2002. doi:[10.1109/32.979986](https://doi.org/10.1109/32.979986).

Shyam R. Chidamber and Chris F. Kemerer. A Metrics Suite for Object Oriented Design. *IEEE Transactions on Software Engineering*, 20(6): 476–493, 1994. doi:[10.1109/32.295895](https://doi.org/10.1109/32.295895).

Derek Comartin. Write Stable Code Using Coupling Metrics. <https://codeopinion.com/write-stable-code-using-coupling-metrics/>, 2021. [Online; accessed 15-03-2024].

M. Fowler. Reducing Coupling. *IEEE Software*, 2001. doi:[10.1109/ms.2001.936226](https://doi.org/10.1109/ms.2001.936226).

Steve McConnell. *Code Complete*. Pearson Education, 2004. doi:[10.5555/1096143](https://doi.org/10.5555/1096143).

A. Mubarak, S. Counsell, and R.M. Hierons. An Evolutionary Study of Fan-In and Fan-Out Metrics in OSS. In *Proceedings of the Fourth International Conference on Research Challenges in Information Science (RCIS)*, 2010. doi:[10.1109/rcis.2010.5507329](https://doi.org/10.1109/rcis.2010.5507329).

Wayne P. Stevens, Glenford J. Myers, and Larry L. Constantine. Structured Design. *IBM Systems Journal*, 13(2):115–139, 1974. doi:[10.1147/sj.132.0115](https://doi.org/10.1147/sj.132.0115).