CHALLENGE SHEET

Snapconnect

SnapConnect is a small social app with profiles and avatars, served by a GraphQL API.

DIFFICULTY	TRACK	HOST PORT	LAB ID
EASY	WEB	8081	snapconnect

EASY | MEDIUM | HARD | INSANE

VERIFY THE SOLVE

```
python3 ../scripts/check.py snapconnect
```

Brief

SnapConnect is a small social app. Members get a profile with a handle, a bio, and an avatar, and everything runs through a GraphQL API at POST `/graphql`.

The app keeps a secret in `/var/www/flag.txt`. That path is outside the web root, so no URL reaches it. Read the file through the application and you have the flag.

Difficulty is easy. Expect to spend 15 to 30 minutes.

Prerequisites

- GraphQL queries, mutations, and introspection
- The `graphql-multipart-request` format
- A tool that sends raw HTTP, such as `curl`, Burp, or Insomnia

Setup

Start the lab:

```
docker compose up -d --build
```

- App: `http://localhost:8081`
- Health: `http://localhost:8081/health.php`
- API: POST `http://localhost:8081/graphql`
- API reference: `http://localhost:8081/docs`

Registration is open. Create an account to get a session token.

Goal

Read `/var/www/flag.txt` through the service. Verify your solve from the repository root:

```
python3 scripts/check.py labs/web/snapconnect
```

See how to play for the usual solve loop.

Reset

```
docker compose down -v
docker compose up -d --build
```

Reset clears uploads and sessions and reseeds the database.

Flag format

`duck{...}` with lowercase letters, digits, and underscores between the braces.

Rules

- The lab runs on your machine. Point your tools at `localhost:8081` only.
- No brute force is needed.
- Destroying the service is not the goal. The container resets anyway.