CHALLENGE SHEET

Last Reel

A film restoration archive with a restricted release-clearance record.

DIFFICULTY	TRACK	HOST PORT	LAB ID
EASY	WEB	8080	last-reel

EASY MEDIUM HARD INSANE

VERIFY THE SOLVE

```
python3 ../scripts/check.py last-reel
```

Brief

Last Reel is an **easy Web** lab. The public search page accepts film titles. Your goal is to retrieve the runtime flag from the restricted release-clearance record for the unreleased restoration.

The scenario, films, people, and records are fictional. Use only the supplied local lab instance.

Setup

Prerequisites:

- Docker Desktop using Linux containers, or Docker Engine on Linux, with Docker Compose `v2.17.0` or later.
- Python 3.10 or later on the host for hash synchronization, reset, and the local checker; no additional Python packages are required.
- A browser or an HTTP client, and an available local port `8080`.
- The first build requires internet access to download the pinned base image and Python packages. The running lab needs no external service.

Run the commands from this lab directory. Substitute `python3` for `python` if needed.

```
docker compose up -d --build --wait
python scripts/sync_flag_hash.py
```

Open `http://127.0.0.1:8080`.

The only published host port is `127.0.0.1:8080`. The application and its SQLite archive are not published directly.

To reset the instance and refresh the checker digest:

```
python reset.py
```

The reset creates a new runtime flag. Any flag captured before reset will no longer be valid.

Goal

Find the current final flag in the form `duck{...}` through the local web interface or an HTTP client. Check it from this directory:

```
python ../../../scripts/check.py .
```

The checker stores and compares only the SHA-256 digest in `lab.yml`.

Notes

- This lab is intentionally vulnerable. Do not apply the technique to systems you do not own or have permission to test.
- The reset script operates only on the `last-reel` Compose project. It does not pull images or rebuild during reset.
- In hosted delivery, only the assigned HTTP(S) endpoint is in scope. Host, Docker, database, image, source, and reset controls belong to the operator and are not player-accessible assets.