



iPixel LED Shiji Lighting

Add:5F A2 Huafeng Zhenbao Industrial Park,BeiHuan Rd ,Shiyan,Baoan,Shenzhen,China. 518108

Tel: 0086-755-23125058 Fax:0086-755-23125658 Web:www.shiji-led.com

E-mail: contact@shiji-led.com

Web:www.ipixelled.cn

Technical Parameters:

Light source: 5050 Epistar SMD LEDs 4in one

Beam angle: 140 deg.

Operating voltage:12V DC

Current per 3 LEDs(seperable every 3LEDs)

Consumption watts per roll: 72W(Max)

Entire roll size: 5000mm x 12mm

IP 65 Strip thickness: 4mm

Entire roll LED quantity: 300pcs

Operation Temperature:-20°C-60°C

Storage Temperature:-20°C-30°C

Wire length: 150mm (at both end)

Packing: 5meter a roll

Full view:



Features and Benefits:

- Flexible
- 3M tape attached on back side of strip (IP20)
- 10pcs silicon clips & 10pcs screw for waterproof strip (without tape)
- Cut-able every 5cm(3 LEDs)
- IP20 Non-waterproof/IP65 silicon tube waterproof
- CE and RoHS complian



Part Number	Color	CRI	Flux(±15%)	White CCT	View Angle	Packing	IP grade
SJ-10060-RGBW	RGB+White	80RA	300X20LM	2800K-3000K	120°	5m/reel	IP20/65
SJ-10061-RGBW-F	RGB+White	80RA	360X20LM	6500K-7000K	120°	5m/reel	IP20/65

Outline Dimension:

Unit: mm

