EVE-NG topology (campus + WAN) -- physical layout, interfaces and link subnets

Provider cloud (outside TVI)

ISP-A AS 65100 (203.0.113.0/24) | ISP-B AS 65200 (198.51.100.0/24)

ISP-A
SaaS 192.0.2.10 DNS 192.0.2.53

ISP-B
Cloud-B 198.51.100.200

Gi0/4 — 203.0.113.248/30 — Gi0/4
ISP-A Gi0/2 — 203.0.113.4/30 — HAN-EDG1 Gi0/1
ISP-A Gi0/3 — 203.0.113.0/30 — HCM-EDG1 Gi0/1
ISP-A Gi0/4 — 203.0.113.248/30 — ISP-B Gi0/4
ISP-B Gi0/2 — 198.51.100.4/30 — HAN-EDG2 Gi0/1
ISP-B Gi0/3 — 198.51.100.0/30 — HCM-EDG2 Gi0/1
ISP-B Gi0/3 — 198.51.100.8/30 — DAD-EDG2 Gi0/1
HCM-EDG1 Gi0/1 — 203.0.113.8/30 — DAD-EDG1 Gi0/1

HAN -- Hanoi R&D

OSPF 20 | AS 65020 | router-on-a-stick + HSRP

HAN-EDG1
Lo0 10.20.255.1
mgmt 172.16.99.21

HAN-EDG2
Lo0 10.20.255.2
mgmt 172.16.99.22

HAN-EDG1 Gi0/3 — 10.20.254.0/30 — HAN-EDG2 Gi0/3
HAN-EDG1 Gi0/2 — 802.1Q — HAN-ACC1 Gi0/1
HAN-EDG2 Gi0/2 — 802.1Q — HAN-ACC1 Gi0/2

HAN-ACC1
VLAN99 10.20.31.15
mgmt 172.16.99.25

HAN-ACC1 Gi1/0 — **HAN-ENG**
VLAN 20 RND_ENGINEERING
10.20.0.0/24

HAN-ACC1 Gi1/1 — **HAN-PHONE**
VLAN 40 VOICE
10.20.16.0/24

HAN-ACC1 Gi1/2 — **HAN-GUEST**
VLAN 60 GUEST
10.20.24.0/24

HCM -- Ho Chi Minh City HQ

OSPF 10 | AS 65010 | collapsed core + HSRP + LACP

HCM-EDG1
Lo0 10.10.255.1
mgmt 172.16.99.11

HCM-EDG2
Lo0 10.10.255.2
mgmt 172.16.99.12

HCM-EDG1 Gi0/4 — 10.10.254.16/30 — HCM-EDG2 Gi0/4
HCM-EDG1 Gi0/2 — 10.10.254.0/30 — HCM-CORE1 Gi1/0
HCM-EDG1 Gi0/3 — 10.10.254.4/30 — HCM-CORE2 Gi1/1
HCM-EDG2 Gi0/2 — 10.10.254.8/30 — HCM-CORE1 Gi1/0
HCM-EDG2 Gi0/3 — 10.10.254.12/30 — HCM-CORE2 Gi1/1

HCM-CORE1
Lo0 10.10.255.3
mgmt 172.16.99.13

HCM-CORE1 Gi0/1-2 — Po1 LACP trunk + VLAN900 10.10.254.20/30 — HCM-CORE2 Gi0/1-2

HCM-CORE2
Lo0 10.10.255.4
mgmt 172.16.99.14

HCM-CORE1 Gi0/3 — 802.1Q — HCM-ACC1 Gi0/1
HCM-CORE2 Gi0/3 — 802.1Q — HCM-ACC1 Gi0/2

HCM-ACC1
VLAN99 10.10.44.15
mgmt 172.16.99.15

HCM-ACC1 Gi1/0 — **HCM-EXEC**
VLAN 10 EXEC_FINANCE
10.10.32.0/24

HCM-ACC1 Gi1/1 — **HCM-CORP**
VLAN 12 CORP_STAFF
10.10.0.0/24

HCM-ACC1 Gi1/2 — **HCM-GUEST**
VLAN 60 GUEST
10.10.36.0/24

HCM-ACC1 Gi1/3 — **HCM-PHONE**
VLAN 40 VOICE
10.10.16.0/24

HCM-ACC1 Gi2/0 — **HCM-SRV1**
VLAN 80 10.10.43.10
DHCP / DNS / NTP / IP SLA

DAD -- Da Nang Logistics

OSPF 30 | AS 65030 | router-on-a-stick + HSRP

DAD-EDG1
Lo0 10.30.255.1
mgmt 172.16.99.31

DAD-EDG2
Lo0 10.30.255.2
mgmt 172.16.99.32

DAD-EDG1 Gi0/3 — 10.30.254.0/30 — DAD-EDG2 Gi0/3
DAD-EDG1 Gi0/2 — 802.1Q — DAD-ACC1 Gi0/1
DAD-EDG2 Gi0/2 — 802.1Q — DAD-ACC1 Gi0/2

DAD-ACC1
VLAN99 10.30.144.15
mgmt 172.16.99.35

DAD-ACC1 Gi1/0 — **DAD-LOG**
VLAN 30 LOGISTICS_OPS
10.30.128.0/24

DAD-ACC1 Gi1/1 — **DAD-IOT**
VLAN 50 IOT_DEVICES
10.30.0.0/24

DAD-ACC1 Gi1/2 — **DAD-PHONE**
VLAN 40 VOICE
10.30.136.0/24

DAD-ACC1 Gi1/3 — **DAD-GUEST**
VLAN 60 GUEST
10.30.140.0/24

Out-of-band management (not drawn):
Gi0/0 of every node -> EVE-NG Cloud0
172.16.99.0/24, automation host .1

Overlay tunnels: see routing diagram.
vIOS: set 6 NICs (uses Gi0/0-Gi0/4)

DC fabric: HCM-CORE1/2 Gi1/2 ->
DC-LEAF1/2 Eth5 (see DC diagram)