

## Contents

- [Tai Duc Nguyen, Hieu Mai - 02/01/2020 - ECES 435](#)
- [PART 1](#)
- [PART 2](#)

## Tai Duc Nguyen, Hieu Mai - 02/01/2020 - ECES 435

```
clear all; close all;
```

### PART 1

```
peppers_org = imread("peppers.tif");  
baboon_org = imread("baboon.tif");
```

```
fprintf('| %10s | %10s | %10s | %10s |\n', "Images", "Quality", "Size", "PSNR");  
fprintf('-----\n');  
  
quality_factors = [90, 70, 50, 30, 10];  
  
for i = 1:length(quality_factors)  
    filename = strcat('peppers_', num2str(quality_factors(i)), '.jpg');  
    imwrite(peppers_org, filename, 'Quality', quality_factors(i));  
    tmp_img = imread(filename);  
    PSNR = 20*log10(255) - 10*log10(mse(tmp_img, peppers_org));  
    fprintf('| %10s | %10d | %10lu | %10f |\n', "peppers", quality_factors(i), imfinfo(filename).FileSize, PSNR);  
end  
  
for i = 1:length(quality_factors)  
    filename = strcat('baboon_', num2str(quality_factors(i)), '.jpg');  
    imwrite(baboon_org, filename, 'Quality', quality_factors(i));  
    tmp_img = imread(filename);  
    PSNR = 20*log10(255) - 10*log10(mse(tmp_img, baboon_org));  
    fprintf('| %10s | %10d | %10lu | %10f |\n', "baboon", quality_factors(i), imfinfo(filename).FileSize, PSNR);  
end  
  
fprintf("\r\n");  
  
fprintf(['Question PART 1:\n', ...  
    '1. The higher the image quality, the larger the image size.\n', ...  
    '2. JPEG Compression introduce lossy artifacts -- makes the image looks blocky.\n',...  
    '3. They occurs because of quantization.\n',...  
    '4. At quality factor of about 30 (PSNR=38.39), the distortion become strong.\n']);
```

	Images	Quality	Size	PSNR
	peppers	90	48956	53.581544
	peppers	70	33276	49.503164
	peppers	50	27405	39.497821
	peppers	30	15902	38.399239
	peppers	10	8221	34.749630
	baboon	90	105820	40.367722
	baboon	70	57172	34.604096
	baboon	50	41548	33.198784
	baboon	30	29624	32.241234
	baboon	10	13258	30.773405

Question PART 1:

1. The higher the image quality, the larger the image size.
2. JPEG Compression introduce lossy artifacts -- makes the image looks blocky.
3. They occurs because of quantization.
4. At quality factor of about 30 (PSNR=38.39), the distortion become strong.

## PART 2

```
current_dir = strcat(mfilename('fullpath'), '.m');
[current_dir,~,~] = fileparts(current_dir);

lum_quant = ...
[ 16 11 10 16 24 40 51 61;
 12 12 14 19 26 58 60 55;
 14 13 16 24 40 57 69 56;
 14 17 22 29 51 87 80 62;
 18 22 37 56 68 109 103 77;
 24 35 55 64 81 104 113 92;
 49 64 78 87 103 121 120 101;
 72 92 95 98 112 100 103 99;];

[zz_quant_dct_blks, enc_size] = JPEG_encode(peppers_org, current_dir, lum_quant);
[iZZDCTQIm, dec_img] = JPEG_decode(current_dir);
PSNR = 20*log10(255) - 10*log10(mse(uint8(dec_img), peppers_org));

hFig = figure(1);
hAxes = axes( figure );
imshow(uint8(dec_img), 'Parent', hAxes);
title(hAxes, ['Standard JPEG luminance quantization table. PSNR=', num2str(PSNR), ' Size=', num2str(enc_size)]);

lum_quant = ...
[ 80 55 50 80 120 200 255 255;
 60 60 70 95 130 255 255 255;
 70 65 80 120 200 255 255 255;
 70 85 110 145 255 255 255 255;
 90 110 185 255 255 255 255 255;
 120 175 255 255 255 255 255 255;
 255 255 255 255 255 255 255 255;
 255 255 255 255 255 255 255 255;];

[zz_quant_dct_blks, enc_size] = JPEG_encode(peppers_org, current_dir, lum_quant);
[iZZDCTQIm, dec_img] = JPEG_decode(current_dir);
PSNR = 20*log10(255) - 10*log10(mse(uint8(dec_img), peppers_org));

hFig = figure(2);
hAxes = axes( figure );
imshow(uint8(dec_img), 'Parent', hAxes);
title(hAxes, ['New JPEG luminance quantization table 1. PSNR=', num2str(PSNR), ' Size=', num2str(enc_size)]);
% Source: http://mail.ipb.ac.rs/~rakaj/home/fajpg.pdf

lum_quant = ...
[ 7 5 9 2 18 226 231 255;
 26 17 35 68 177 254 255 255;
 8 35 15 84 252 255 255 255;
 118 172 244 247 255 255 255 255;
 243 250 252 255 255 255 255 255;
 138 201 255 255 255 255 255 255;
 133 255 255 255 255 255 255 255;
 255 255 255 255 255 255 255 255;];

[zz_quant_dct_blks, enc_size] = JPEG_encode(peppers_org, current_dir, lum_quant);
[iZZDCTQIm, dec_img] = JPEG_decode(current_dir);
PSNR = 20*log10(255) - 10*log10(mse(uint8(dec_img), peppers_org));

hFig = figure(3);
hAxes = axes( figure );
imshow(uint8(dec_img), 'Parent', hAxes);
title(hAxes, ['New JPEG luminance quantization table 2. PSNR=', num2str(PSNR), ' Size=', num2str(enc_size)]);
% Source: http://mail.ipb.ac.rs/~rakaj/home/fajpg.pdf
```

```
fprintf(['Question PART 2:\n', ...
'It is not possible to achieve both a lower file size and a higher PSNR. Because the lossless\n', ...
'encoder will only be able to reduce the number of bits representing the sequence when the \n',...
'sequence is "regular". If the quantization interval is high, then most of the numbers after\n',...
'qunatization become highly regular, but the error is higher.\n']);
```

```
function [zz_quant_dct_blks, enc_size] = JPEG_encode(X, current_dir, lum_quant)

[nrow, ncol] = size(X);
image_flat = X(:);

block_size = 8;
blocks = zeros(int16(length(image_flat)/(block_size^2)), block_size^2);
k = 1;
i = 1;
while i <= length(image_flat)
    for j = 0:block_size-1
        m = i + ncol*j;
        n = j*block_size + 1;
        blocks(k,n:n+block_size-1) = image_flat(m:m+block_size-1);
    end

    if (mod(k,int16(ncol/block_size)))
        i = i + block_size;
    else
        i = block_size^2*k + 1;
    end
    k = k + 1;
end

zz_quant_dct_blks = zeros(size(blocks));

for i = 1:size(zz_quant_dct_blks,1)
    blk_dct = round(dct2(reshape(blocks(i,:), block_size, block_size))./(lum_quant));
    zz_quant_dct_blks(i,:) = ZigzagMtx2Vector(blk_dct);
end

enc_size = JPEG_entropy_encode(nrow, ncol, block_size, ...
    lum_quant, zz_quant_dct_blks, current_dir, []);

end

function [iZZDCTQIm, dec_img] = JPEG_decode(current_dir)
[nrow,ncol,dct_block_size,iQ,iZZDCTQIm] = JPEG_entropy_decode(current_dir);

dec_img = zeros(nrow, ncol);

k = 1;
for i = 1:dct_block_size:nrow
    for j = 1:dct_block_size:ncol
        dec_img(j:j+dct_block_size-1, i:i+dct_block_size-1) = ...
            idct2((iQ).*Vector2ZigzagMtx(iZZDCTQIm(k,:)));
        k = k + 1;
    end
end

end

end
```

```
wine /home/sweet/2-coursework/435eces/assgn2/jpeg_entropy_encode.exe: Signal 24
wine /home/sweet/2-coursework/435eces/assgn2/jpeg_entropy_decode.exe: Signal 100
wine /home/sweet/2-coursework/435eces/assgn2/jpeg_entropy_encode.exe: Signal 24
wine /home/sweet/2-coursework/435eces/assgn2/jpeg_entropy_decode.exe: Signal 100
wine /home/sweet/2-coursework/435eces/assgn2/jpeg_entropy_encode.exe: Signal 24
wine /home/sweet/2-coursework/435eces/assgn2/jpeg_entropy_decode.exe: Signal 100
Question PART 2:
```

It is not possible to achieve both a lower file size and a higher PSNR. Because the lossless encoder will only be able to reduce the number of bits representing the sequence when the sequence is "regular". If the quantization interval is high, then most of the numbers after quantization become highly regular, but the error is higher.

Standard JPEG luminance quantization table. PSNR=39.5906 Size=25300





