Forensic Knowledge Graphs as investigative infrastructure: proposal and case studies

Tai Nguyen · October 27, 2026

For Jane and her student. A synthetic feasibility study, not a paper draft: what we propose, why it is new, the evidence so far, and the decisions the paper needs. Sections 1 to 4 give the idea (five minutes), 5 to 7 the evidence, 8 to 10 what to decide and run next. Every number reproduces from the code in section 11.

1. The proposal at a glance

The FKG paper [1] turns one image's forensic analysis into an explainable knowledge graph. **We propose to treat each FKG record as linked data that shares identifiers with how the image was posted, what was claimed about it, which credentials it carries and which detector produced the analysis.** Investigative questions that neither forensic analysis nor platform context can answer alone then become graph queries, written by an analyst or by an LLM agent.

	Contribution	What it is	Where
C1	**Encoding**	FKG in OWL 2 and RDF with a SHACL profile, plus a thin context layer that reuses existing standards (Activity Streams 2.0, schema.org Claim and ClaimReview, C2PA and IPTC, PROV-O). Named graphs keep track of who asserted what.	§2, §8
C2	**Expressiveness**	18 investigative use cases in four families, each a competency question with a SPARQL query.	§4, App. A
C3	**Evidence**	Four case studies on synthetic worlds with planted ground truth. The integrated query beats each single layer and degrades gracefully up to 50% noise.	§5, §6
C4	**Agentic investigation**	LLM agents that see only the schema write queries that match or beat hand-written ones, and one rediscovered the campaign join unaided.	§7

Four things to take away

- **The gain comes from integration, not detection.** Every arm of every study reads the same detector outputs; only the joins differ. The forensic layer alone cannot see time, claims or accounts, and the context layer alone cannot see what was altered.
- **Errors are misses, not false accusations.** Joins rarely invent evidence, so noise lowers recall while precision holds: 1.00 at every noise rate for CS3 triage, at least 0.81 for CS1 recycled-media flags up to $\eta = 0.5$.
- **Defence is a new query, not a new model.** In the campaign study, each attack that broke detection was answered by a new query over the same records (five of eleven fixed, two partly, four open). This is the empirical case for FKG as a living system rather than a fixed detector.
- **The schema is enough for agents.** Agents given only a page of data notes wrote correct investigative SPARQL (held-out mean 0.92 to 0.96 against 0.91 by hand). This is what makes




Figure 1: Headline results, one row per investigative question. Section 5 gives each study's setup; section 6 shows how the gaps hold under noise.




Figure 2: Architecture. The FKG record is unchanged from [1]; everything around it reuses an existing standard. Labels on the arrows are the join keys.

FKG usable by analysts who do not write queries.

2. How it fits together

- **The forensic layer is FKG as published** [1]: per image, regions, each region's source (camera model or AI generator, with confidence), the post-processing chain, compression and depicted content, rolled up into a record and conclusion. We add nothing to its semantics.

- **The context layer is mostly borrowed.** Posts and accounts are Activity Streams 2.0, claims and verdicts are schema.org Claim and ClaimReview, credentials summarise C2PA manifests with IPTC source types, and detector runs are PROV-O activities. The new vocabulary is a handful of terms (for example a post's platform, a platform's transcoding profile, a known detector issue).
- **Three identifiers do the joining**: the image IRI (shared by the post that attaches it, its credential and its FKG record), the entity IRI (shared by a claim's subject and the content FKG says was altered) and the detector run (shared by the record and the fact-check that cites it).
- **Named graphs record who asserted what**, so a query can trust the detector but not the uploader, or ask which conclusions rest only on a publisher's own credential.
- **SHACL validates every record**; the competency questions run as plain SPARQL 1.1 with no reasoner.

3. What is new

Novelty in one sentence: forensic observations become first-class linked data, so an investigation is a composition of standard queries over shared identifiers rather than a bespoke pipeline per question.

Line of work	What it gives	What it cannot do alone	What FKG as linked data adds	Shown in
FKG [1]	An explainable forensic record per image	Nothing about posts, claims, time or other images	The same record, joinable across images, posts and claims	all
Content credentials (C2PA, IPTC) [7, 8]	Signed provenance asserted by the publisher	An assertion, not an observation; stripped on re-upload; can be wrong	Assertions checked against forensic observations	CS3
Image provenance analysis [11]	Near-duplicate graphs from pixel similarity	Edge direction and what each edit did stay ambiguous; no claims or accounts	Copies ordered by forensic traces (compression, resampling, inserted regions) and tied to posts and accounts	CS2
Out-of-context detection [10]	Image and caption mismatch from learned embeddings	No time, no earliest appearance, no evidence trail	Recycled media as a temporal join over claims, events and first appearance	CS1
Fact-check data (ClaimReview) [6]	Verdicts linked to claims	Verdicts are not linked to the evidence or the tool version behind them	Verdict to record to detector run, so a detector bug has a queryable blast radius	CS3
Coordinated behaviour detection [12]	Co-posting and co-sharing networks	Flags sincere believers; misses operations that share a toolchain but not content	A forensic TTP join (same generator and processing recipe) combined with narrative and timing	CS4

Line of work	What it gives	What it cannot do alone	What FKG as linked data adds	Shown in
Threat intelligence (STIX, DISARM) [13, 14]	Vocabulary for tactics, techniques and campaigns	TTPs are entered by analysts, not inferred from the media	TTPs inferred from forensic records, ready to export (proposed, not built)	—

Why it should get published: each row above is an established community whose artefacts FKG can now join, and every join is shown to matter on a measurable task. The paper's contribution is the bridge, the competency questions that exercise it, and evidence that both hand-written and agent-written queries can use it.

4. Use-case landscape

Eighteen use cases fall into four families. Twelve are scored in the case studies; six have sketch queries only (full catalog in Appendix A).

Family	Question it answers	Use cases	Context it needs	Evidence
Time and origin	When did this first appear, and is it presented as something it predates?	UC1 recycled media, UC2 earliest appearance, UC10 anachronistic attribution	Posts and timestamps, events, generator release dates	CS1, CS3
Copies and lineage	How did this file travel and change, and who changed it?	UC3 patient zero, UC4 lineage, UC5 source laundering, UC6 hidden platform hop, UC13 toolkit fingerprint, UC14 shared device	Posts, accounts, platform transcoding profiles	CS2 (UC3 to UC6); UC13 and UC14 sketched
Claims and intent	Does the alteration matter for what is claimed, and who is pushing it?	UC7 materiality, UC8 credential contradiction, UC9 presentation and intent, UC12 coordinated campaign, UC17 generator exposure	Claims and their subjects, disclosures, credentials, accounts	CS3 (UC7 to UC9), CS4 (UC12); UC17 sketched
Auditing the analysis	Which conclusions rest on which evidence, and what changes when a detector is wrong?	UC11 recall impact, UC15 detector consistency, UC16 audit trail, UC18 reported versus inferred	Detector runs and versions, ClaimReview, credentials	CS3 (UC11); others sketched

The first three families are what an investigator asks; the fourth is what an auditor or a court asks of the investigation itself. The fourth is where an explicit, queryable record of analysis provenance has no substitute, and it is the least developed here.

5. Case studies

Each study plants ground truth in a seeded synthetic world and scores the integrated query against a **forensic-only** baseline (the FKG layer alone), a **context-only** baseline (posts, time, credits, claims) and **ablations** that remove one FKG-based guard. The worlds also plant the failures a real pipeline has: detector false positives and weak true positives near the 0.7 confidence threshold, near-duplicate clusters that wrongly merge different photos, and an incomplete crawl.

	CS1	**CS2**	**CS3**	**CS4**
Scenario	Claim posts about two current events	Eight outlet photos spreading across five platforms	Posts about five public figures, some altered	A flood-rumour influence operation
Size	105 claim posts, 63 accounts, 10k quads	241 image instances, 6 AI edits	204 posts, 68 accounts	168 accounts, about 770 posts and 650 images
Use cases	UC1, UC2	UC3 to UC6	UC7 to UC11	UC12

CS1. Recycled media: is an authentic photo presented as showing an event it predates?

- **Why one layer fails.** The photo is forensically clean, so the forensic layer cannot flag it (recycled-class F1 0). Context alone is fooled when near-duplicate clustering merges a current photo with an old one.
- **The join.** Flag a post whose image has no reliable AI region and whose near-duplicate cluster holds a copy published before the claimed event's start date **and attributed to the same camera model**. That camera-agreement guard defeats false merges.

Measure	**Integrated**	**Forensic only**	**Context only**
Recycled posts flagged (CQ1.1)	P 1.00, R 0.88	F1 0	—
Earliest appearance found (CQ1.2)	22 of 22	—	—
Four-way label accuracy (CQ1.3)	**0.952**	0.743	0.657
Ablations (accuracy)	no camera guard 0.924; no confidence threshold 0.943		

Takeaway. The recall ceiling of 0.88 is the open world made visible: three recycled photos have no pre-event copy in the crawl, and the graph declines to guess rather than accuse.

CS2. Lineage and laundering: which copy added the synthetic region, and who is misattributing it?

- **Why one layer fails.** Timestamps order copies but cannot say which one changed the content. Forensic records describe each file but not who posted it, where, or whom it credits.
- **The joins.**
  - *Lineage* is two CONSTRUCT rules. The first proposes earlier copies in the same cluster that satisfy forensic monotonicity (AI regions survive, resolution never grows, a pass-through keeps its compression). The second picks one by parsimony and writes prov:wasDerivedFrom plus the edit step.

– *Laundering*: the post credits an outlet, the generator and content pair is corroborated, and the outlet never posted that pair.
– *Hidden hop*: a pass-through file's quality factor is matched to the platforms' transcoding profiles.

Measure	Integrated	Best baseline
Hidden platform hop (CQ2.4)	**50 of 50**	previous post's platform: 15 of 50
Laundering (CQ2.3)	**P 1.00, R 1.00**	every outlet-crediting post: P 0.137
Lineage, parent in the right variant (CQ2.2)	1.000	timestamps only: 0.893
Lineage, exact parent	0.288	timestamps only: 0.176
Edit steps found	6 of 6, P 0.86	not expressible without forensics
Patient zero (CQ2.1)	P 0.75, R 0.50 (F1 0.56 over 10 seeds)	earliest post in cluster: 0

Takeaway. Forensic traces orient the copy graph that pixel similarity leaves undirected. Patient zero is the weak spot: a content-driven detector error recurs on copies, so recurrence is weak evidence that an edit is real. Agents found a sharper cue (§7).

CS3. Materiality and intent: does the alteration matter for what is claimed, and was it disclosed?

- **Why one layer fails.** Forensics alone queues every AI-altered post, including disclosed art and sky replacements (precision 0.284). Context alone queues every undisclosed claim post, altered or not (0.420).
- **The join.** The altered region's content links to **the same entity IRI the claim is about**, and nothing discloses it (no platform label, caption or credential). A CONSTRUCT rule writes the presentation category back as an inferred conclusion with its provenance.
- **Auditing the analysis.** Credentials are checked against forensics; attributions are checked against generator release dates; fact-checks are traced through their record to the detector version and its known issue.

Measure	Integrated	Forensic only	Context only
Triage queue precision (CQ3.1)	**1.00** at recall 0.912	0.284	0.420
Same, without the materiality join	0.646		
Presentation category accuracy (CQ3.3)	**0.971**	0.603	0.740
Credentials contradicted by forensics (CQ3.2)	8 of 8		
Attributions to an unreleased generator (CQ3.4)	3 of 3		
Fact-checks resting on the faulty detector (CQ3.5)	5 of 5		

Takeaway. Materiality is the whole effect, and it needs one shared entity IRI. "Intent" is deliberately modest: the graph infers how content was presented, which is evidence about intent, not intent.




Figure 3: CS4 results from the companion study. Here η is the error rate of detectors and claim matchers, not the per-failure rate used in CS1 to CS3. At $\eta = 1.0$ detector output is mostly noise and every forensic query collapses, as it should.

CS4. Coordinated campaign: which accounts run a manipulated-media operation? (companion study)

Run as a separate, deeper study; full write-up and code in the repository's `coordinated-campaign/` folder.

- **Why one layer fails.** The world hides 12 operator accounts among decoys that each defeat one signal. Forensics alone flags a brand campaign that also runs one image pipeline (F1 0.70). Claims and timing alone flag 20 sincere believers (precision 0.25, F1 0.40).
- **The join, one SPARQL query.** A forensic TTP match (same generator, at least two processing operations with parameters within 15%), not a re-upload, a shared fact-checked false claim, and a 72-hour window. A second hop adds the two text-only amplifiers.

- **Agents rediscovered the join.** Three LLM investigators given only a schema card and the analyst's question each found exactly the 12 accounts and independently wrote the same forensic-and-claim rule. Detectors written from noisy data reach F1 0.92 and 0.94 at $\eta = 0.7$ on held-out worlds; the one written from clean data is too strict (0.31).
- **Six rounds of attack and defence**, in worlds up to 30× larger (745k quads) and calibrated to published measurements. Every defence is a new query over the same records:

Attack (F1 at $\eta = 0.3$)	What broke	Defender's new query	After
Per-persona processing presets	joined query 0.05	self-consistent processing per account	0.78
30× organic population	precision 0.37	gate on self-consistency	precision 1.0
Five calibrated realism models at once	0.63	open-world: claim need only be not rated true	0.76




Figure 4: Noise sweep for CS1 and CS3. Every failure mode (detector false positives, a quarter above threshold; weak true positives; false cluster merges; missing earliest appearances) is drawn independently at rate η.

Attack (F1 at $\eta = 0.3$)	**What broke**	**Defender's new query**	**After**
Debunkers repost campaign images	precision 0.70	stance filter on claim links	precision 0.93
One or two posts per persona	at most 0.34	union with a behavioural rule	0.63
Per-persona processing on aged accounts	0.02	repost ties plus an age-free amplifier hop	0.59
Operator also stops reposting its personas	0.26	one agreeing operation suffices	0.42
Random processing per image; 12-day spread; platform-scale query cost			open

- **Detection is evidence-limited.** All campaign accounts have acted by 24 hours, yet the best F1 at $\eta = 0.3$ is 0.36 at 24 hours and 0.53 at 36 hours, because personas need time to post two matching images.

Takeaway. The forensic records carry the evidence that is hardest for an operator to remove, and every attack was met by a query, not a retrained model. The paper should claim that the join **raises the cost of running a campaign** and finds it as it completes, not that it cannot be evaded.

6. Robustness to noise

The single-seed tables fix the number of planted failures, so each CS1 and CS3 world was regenerated with every failure mode at rate η (five seeds per rate). CS2 was rerun over ten fresh seeds, since its spread trees already vary by seed.

- **The ordering never flips.** At $\eta = 0.5$, where half of all items carry a failure, CS1 still reaches 0.786 against 0.594 for forensics alone, and the CS3 queue 0.798 against 0.607 for context alone.




Figure 5: Agent and hand-written query sets, mean over the 12 questions of CS1 to CS3. The dashed line marks the hand-written held-out mean. Per-question scores are in Appendix D.

- **Noise costs recall, not precision.** CS3 triage precision is exactly 1.00 at every rate while recall falls from 0.983 to 0.665; CS1 recycled-media precision stays at or above 0.81.
- **FKG guards matter more as noise grows.** Without the camera-agreement guard, CS1 accuracy is 0.766 instead of 0.882 at $\eta = 0.3$, and 0.615 instead of 0.804 at $\eta = 0.5$.
- **CS2 over ten seeds.** Parent in the right variant 0.994, laundering F1 0.96 (precision 0.98), hidden hops 1.00 in every seed; patient zero F1 0.56 $\pm$ 0.17 at precision 0.905, its variance being how many edits happen to spread.
- **What the sweep does not show.** The CS3 context-only line is flat because no noise touches context, and the credential, anachronism and recall-impact queries stay at 1.00 because nothing they read is perturbed. That is a property of the sweep, not evidence of robustness.

7. Agentic investigation

Can an LLM agent turn an investigator's question into correct SPARQL from the schema alone? Each agent received the 12 natural-language questions of CS1 to CS3, the two ontology files and one page of data notes, with no queries and no hint of the hand-written rules.

Arm	What it could see
Hand-written	everything (written by the study author)
A1, A2	questions, ontology, notes; no data (tested on toy graphs they built)
B1, B2	the same, plus query access to the three worlds
B1r, B2r	as B1 and B2, fresh agents run after the leak fix

- **Agents match or beat hand-written queries** on held-out worlds (0.922 to 0.964 against 0.911). Every agent found the guards the hand-written queries rely on: camera agreement, the reliability threshold, the entity-to-claim join and the walk from fact-check to detector version.
- **Three agent ideas are worth adopting.** Treating an attribution seen only on a cluster's earliest copy as a detector error (patient zero 0.545 to between 0.875 and 0.933). A single-

compression cue for pasted regions (patient zero and laundering 1.00; an upper bound, since the simulator records that trace without noise). Checking the resampling scale between parent and child (exact parent 0.299 to 0.456).

- **Where agents did worse, the cause was the question or the access.** A1 and A2 read an underspecified credential question differently (0.762). A1's lineage query is correct but takes 540 to 800 seconds; without data access an agent cannot see that a query is too slow.
- **An agent found a flaw in our simulator.** B2 noticed that planted false positives were separable from real ones, which exposed a label leak in the first generators (Appendix C). Agents as auditors of synthetic benchmarks is a small result in its own right.
- **In CS4,** three investigators given only a schema card recovered the campaign join unaided (§5).

8. Encoding decisions for Jane

CS1 to CS3 and CS4 were built in parallel and made different, reversible choices. The paper needs one answer per row.

#	Decision	CS1 to CS3	CS4	Question for Jane
1	Where new terms live	All new terms in a separate ctx: vocabulary; nothing added to fkg:	One new fkg: term (FullySynthetic)	Should the context vocabulary join FKG 0.2, or ship as a profile that imports it?
2	Fully synthetic images	ctx:SyntheticImage	fkg:FullySynthetic as a manipulation type	A verdict value, a manipulation type, or both?
3	Named graphs	One per forensic record, plus reference and context graphs	One per producer (forensics, platform, fact-check, provenance)	Per record (fine-grained provenance), per producer (simple trust policies), or both?
4	Observation layer	Keeps the record layer (record, conclusion, verdict, evidence status, limitation note); no per-assertion observations	Drops evidence status and limitation note; one PROV activity per image; adds localization status	Named graphs or RDF 1.2 triple terms for statement-level provenance? Must the paper keep per-observation nodes?
5	Image identifiers	example.org IRIs	Content-derived ni:///sha-256 IRIs (RFC 6920)	Adopt content-derived IRIs, which make the join key independent of any platform?
6	Compression	Node typed both LastCompressed and ReCompressed, plus a boolean	ReCompressed plus a boolean	Are the two subclasses disjoint? If so, keep only the boolean.
7	Entity links from content	ctx:depictsEntity IRI beside the free-text description	Free text only	Should Content carry entity IRIs natively, ideally to an external KG? CS3 depends on it.

#	Decision	CS1 to CS3	CS4	Question for Jane
8	Axioms SHACL cannot check	Functional source, disjointness and cardinalities checked; Axiom 1 (regions partition the image) and Axiom 4 (causal order) not	Same	Region masks for Axiom 1? SHACL-SPARQL for Axiom 4?
9	Reliability threshold	0.7 hard-coded in every query	Thresholds set per query	Materialise a reliability class once, from detector metadata?
10	Presentation and intent	ctx:IntentAssessment as an inferred ForensicConclusion	Not modelled	Inside FKG's record layer, or a separate conclusion type outside it?

Our suggestion, for discussion: per-producer named graphs and content-derived IRIs (from CS4), entity IRIs on Content and the record layer (from CS1 to CS3), and a single term for fully synthetic images.

9. Limitations

- **Synthetic only.** Detector behaviour is parametric, platforms are a few transcoding profiles, credentials are summarised to four fields, and posts are Activity Streams objects rather than platform records. The numbers measure whether queries recover planted structure, not how an FKG pipeline performs on real media. The paper's evaluation should open with this.
- **Circularity risk.** The same author designed the worlds and the hand-written queries. Mitigations: agents that never saw those queries (two never saw the data), fresh seeds and noise rates, and held-out worlds.
- **Leaks were found and fixed.** Both simulators first leaked ground truth into attributes a query could read; both were audited and fixed (Appendix C). The audits should be rerun whenever a generator changes.
- **Upper bounds by design.** A pasted region's single-compression trace is recorded without noise, and CS4's processing-chain detection rates are assumed, since no published benchmark measures how well processing chains are estimated.
- **Limits of the evidence itself.** An uncrawled earliest copy caps recall. FKG identifies camera and generator models, not devices or accounts, so toolkit and device linking (UC13, UC14) yields candidates, not attributions. Exact parents among identical copies are underdetermined.
- **Scale.** CS1 to CS3 worlds hold about 10k quads and CS4 up to 745k; CS4 query cost grows about quadratically. Real crawls are orders of magnitude larger and need incremental candidate generation and materialised rules.
- **Agents.** One run per arm, and the notes named the caveats, so the study does not show that agents discover failure modes unprompted. The model and version used are for the authors to fill in.

10. Suggested next steps for the paper

Experiment	What it would establish	Effort
Run a real FKG pipeline on a public benchmark (an out-of-context set such as [10]; a provenance set such as the one in [11])	That the joins still help with real detector outputs, replacing the parametric detector	Medium
Join real fact-checks (published ClaimReview markup) to the images they cite	That the claim layer works on real, messy claim data	Medium
Settle §8 and release FKG 0.2, the context profile, SHACL shapes and the 18 competency questions	A reusable benchmark for query-based forensic investigation	Low
Controlled agent study: several models, repeated runs, notes with and without caveats, cost guards	How reliably agents turn questions into correct, affordable queries, and how they fail	Medium
Scale test at 10^7 to 10^8 quads with incremental TTP candidates and materialised lineage	Latency at crawl scale	Medium to high
Calibrate CS4's processing-chain rates against a real estimator	Whether the campaign result holds with realistic TTP estimates	High

How the material could map onto a paper:

- Motivation and the proposal: §1 and §2
- Related work, organised by the rows of §3
- Encoding and competency questions: §8 decisions, §4 and Appendix A
- Evaluation: CS1 to CS3 as breadth, CS4 as depth, §6 for robustness
- Agentic investigation: §7 and the CS4 agents
- Limitations: §9, stated up front in the evaluation

11. Code and reproduction

Where: the private GitHub repository ductai199x/fkg-case-studies, which Tai will share with Jane and her student. Dependencies are managed with uv (`pyproject.toml`, locked in `uv.lock`), so every command below runs through `uv run`. `make check` audits every SPARQL query in the repository (it parses, uses only terms the ontology declares and the worlds contain, and runs) and reruns the numbers this report quotes.

```
uv sync      # create .venv from uv.lock (Python 3.12+, pyoxigraph, rdflib, pyshacl, matplotlib)
make all     # validate, CS1 to CS3, catalog, CS4 base evaluation, figures
make check   # query audit and reported-number tests (uv run pytest), a few minutes
make help    # every target
```

Result in this report	Command	Time
SHACL conformance of the worlds	`make validate`	seconds
CS1, CS2, CS3 tables (§5)	`make cs1`, `make cs2`, `make cs3`	under a minute each
Noise sweep (§6)	`make sweep`	about 10 minutes
Leak audit (Appendix C)	`make audit`	minutes

Result in this report	Command	Time
Agent comparison (§7, Appendix D)	`make agents`	about an hour
CS4 base results (§5)	`make campaign`	minutes
CS4 attack and defence rounds	`coordinated-campaign/scripts/10_*.sh` to `16_*.sh`	hours each
Figures	`make figures`	seconds

Folder	What it holds
`_shared/`	FKG core ontology, context vocabulary, SHACL shapes, world builder, SPARQL runner, metrics
`cs1_recycled_media/`, `cs2_lineage_laundering/`, `cs3_intent_materiality/`	Generator, queries, baselines, ablations, results
`coordinated-campaign/`	CS4: its own ontology copy, simulator, queries, agent runs, stress tests, one script per result
`_catalog/`, `agent_eval/`, `_audit/`	Use-case catalog and sketches; agent answer sets and scorer; leak audits

Everything is synthetic and seeded, so a rerun gives the same worlds and scores. CS4's generated worlds (about 160 MB) are not committed; `make campaign` regenerates them.

Appendix A. Use-case catalog

Each use case is a competency question with a SPARQL query in `_catalog/`. "Scored" means a case study plants ground truth for it; "sketch" means the query runs but nothing is planted.

Use case	Competency question	Forensic layer	Context layer	Status
UC1 Recycled media	Is an authentic photo presented as showing an event it predates?	CameraModel, confidence	schema:Event, schema:Claim, as:published, clusters	CS1, scored
UC2 Earliest appearance	Where and when did this photograph first appear?	CameraModel	as:Note, clusters	CS1, scored
UC3 Patient zero	Which post and account first carried a given AI insertion?	AIGenerator, Content	as:Note, as:attributedTo, clusters	CS2, scored
UC4 Lineage	What is each copy's immediate parent, and which step added synthetic content?	Region, Resampling, Compression	prov:wasDerivedFrom, platform profiles	CS2, scored
UC5 Source laundering	Which posts credit an outlet for an insertion the outlet never published?	AIGenerator, Content	ctx:creditsSource, account genre	CS2, scored

Use case	Competency question	Forensic layer	Context layer	Status
UC6 Hidden platform hop	Which platform did a pass-through upload last pass through?	Compression factor	platform transcode profiles	CS2, scored
UC7 Materiality triage	Which undisclosed alterations change the entity the claim is about?	AIGenerator, Content	schema:Claim about, disclosures, credentials, reach	CS3, scored
UC8 Credential contradiction	Which signed credentials assert a capture the forensics contradict?	CameraModel, AIGenerator	C2PA credential, IPTC source type	CS3, scored
UC9 Intent and disclosure	How is each post presented: disclosed, satire, material or peripheral alteration?	Region, ForensicConclusion	IntentAssessment, PROV, account genre	CS3, scored
UC10 Anachronism	Which attributions name a generator not yet released at posting time?	hasGeneratorModel	generator release dates	CS3, scored
UC11 Recall impact	Which fact-checks rest on records from a detector version with a known issue?	ForensicRecord	PROV run, KnownIssue, ClaimReview	CS3, scored
UC12 Coordinated campaign	Which accounts share forensic TTPs and a narrative in a short window?	AIGenerator, PostProcessing	as:Note, schema:Claim, DISARM/STIX	sibling task
UC13 Toolkit fingerprint	Which accounts share one generator plus post-processing recipe?	PostProcessing chain, Parameter	as:attributedTo	sketch
UC14 Shared-device linking	Which accounts post first-generation originals from one rare camera model?	CameraModel, LastCompressed	as:attributedTo	sketch
UC15 Detector consistency	Which attributions on an original are reproduced by none of its copies?	AIGenerator, confidence	clusters, as:published	sketch, scored 0 of 2
UC16 Audit trail	What chain of evidence supports a given fact-check?	Record, Region, Source, Content	ClaimReview, PROV run, detector version	sketch
UC17 Generator exposure	Which entities are depicted by which generators, by month and reach?	AIGenerator, Content	depictsEntity, as:published, share count	sketch

Use case	Competency question	Forensic layer	Context layer	Status
UC18 Reported vs inferred	Which images rest only on a source's own credential, uncorroborated?	Conclusion, evidenceStatus	C2PA credential	sketch

Appendix B. How the key joins look in SPARQL

Prefixes omitted. Full queries are in each study's `queries/` folder.

CS1 recycled media. The camera-agreement guard is the last line.

```
SELECT DISTINCT ?post ?event WHERE {
  ?claim a schema:Claim ; schema:appearance ?post ; ctx:assertsDepictionOf ?event .
  ?event schema:startDate ?evStart .  ?post as:attachment ?img .
  FILTER NOT EXISTS { ?img fkg:hasRegion/fkg:produced_by ?g .
                      ?g a fkg:AIGenerator ; fkg:hasConfidence ?gc . FILTER(?gc >= 0.7) }
  ?img fkg:hasRegion/fkg:produced_by ?cs . ?cs a fkg:CameraModel ; fkg:hasCameraModel ?cam .
  ?img ctx:inCluster ?cl . ?prior ctx:inCluster ?cl . FILTER(?prior != ?img)
  ?priorPost as:attachment ?prior ; as:published ?pt . FILTER(?pt < ?evStart)
  ?prior fkg:hasRegion/fkg:produced_by/fkg:hasCameraModel ?cam .
}
```

CS3 materiality. One shared entity IRI turns "altered" into "altered in a way that matters".

```
SELECT ?post ?entity ?shares WHERE {
  ?claim a schema:Claim ; schema:appearance ?post ; schema:about ?entity .
  ?post as:attachment ?img ; as:attributedTo ?acct ; ctx:shareCount ?shares .
  ?img fkg:hasRegion ?r . ?r fkg:produced_by ?s ; fkg:depict/ctx:depictsEntity ?entity .
  ?s a fkg:AIGenerator ; fkg:hasConfidence ?c . FILTER(?c >= 0.7)
  FILTER NOT EXISTS { ?post ctx:hasDisclosure ?d }
  FILTER NOT EXISTS { ?cr ctx:credentialFor ?img ; ctx:signatureValid true ; ctx:
    digitalSourceType ?t .
    FILTER(?t IN (iptc:trainedAlgorithmicMedia, iptc:compositeWithTrainedAlgorithmicMedia)) }
} ORDER BY DESC(?shares)
```

CS3 recall impact. A detector bug becomes a query over analysis provenance.

```
SELECT DISTINCT ?review ?claim ?record ?version WHERE {
  ?issue a ctx:KnownIssue ; ctx:affectsVersion ?version ; ctx:affectsProperty ?prop .
  ?review a schema:ClaimReview ; schema:itemReviewed ?claim ; schema:isBasedOn ?record .
  ?record prov:wasGeneratedBy/prov:wasAssociatedWith ?version ; fkg:aboutImage ?img .
  ?img fkg:hasRegion/fkg:produced_by ?s . ?s a fkg:AIGenerator ; ?p ?any .
  FILTER(STR(?p) = STR(?prop))
}
```

CS4 forensic TTP join (excerpt). Two images match when they share a generator and at least two operations with parameters within 15%; per-producer named graphs keep each source's assertions apart.

```
SELECT ?i1 ?i2 WHERE {
  GRAPH g:forensics {
    ?r1 fkg:contained_in ?i1 ; fkg:produced_by ?s1 . ?s1 a fkg:AIGenerator ; fkg:
    hasGeneratorModel ?gen .
```

```
    ?r2 fkg:contained_in ?i2 ; fkg:produced_by ?s2 . ?s2 a fkg:AIGenerator ; fkg:
    hasGeneratorModel ?gen .
    FILTER(?i1 != ?i2)
    ?r1 fkg:modified_by ?o1 . ?o1 a ?op ; fkg:hasParameter [ fkg:hasParameterName ?pn ; fkg:
    hasParameterValue ?v1 ] .
    ?r2 fkg:modified_by ?o2 . ?o2 a ?op ; fkg:hasParameter [ fkg:hasParameterName ?pn ; fkg:
    hasParameterValue ?v2 ] .
    FILTER(ABS(?v1 - ?v2) <= 0.15 * ?v1)
  }
} GROUP BY ?i1 ?i2 HAVING (COUNT(DISTINCT ?op) >= 2)
```

The full query then requires both posts within 72 hours, no prov:wasDerivedFrom link (not a re-upload), a shared claim rated 2 or lower in g:factcheck, and at least two such peers per account.

Appendix C. Simulator leak audits

A synthetic benchmark can write the answer into its own records. Both simulators were audited by scoring every readable attribute alone against the labels (five-fold cross-validated lookup, balanced accuracy; 0.5 means no signal).

CS1 to CS3 (found by agent B2). Planted false positives were always non-object regions with their own descriptions and, in CS2 and CS3, a near-constant confidence. The fix draws every AI region's description and objectness the same way whether the attribution is right or wrong, overlaps the confidence bands, and lets a false positive recur on copies of the same photo.

Can one attribute tell a real AI region from a false one?	**CS1 before → after**	**CS2 before → after**	**CS3 before → after**
Objectness	0.79 → 0.47	1.00 → 0.57	1.00 → 0.53
Object description	0.79 → 0.48	1.00 → 0.58	0.86 → 0.47
Confidence (AUC)	0.71 → 0.70	0.88 → 0.77	1.00 → 0.84

What moved: CS1 and CS3 hand-written results are unchanged. CS2 patient-zero precision fell from 1.00 to 0.75, because a recurring false positive now looks like corroboration; the UC15 sketch went from 2 of 2 to 0 of 2; B2's lead on one CS3 question disappeared.

CS4 (found by its own audit).

Attribute	**Why it leaked**	**Before**	**After**
Order of repost identifiers	campaign reposts were written first	0.98	0.68
Image has two regions	only the campaign made partly AI-edited images	0.80	0.69
Detector confidence	right and wrong calls had separate ranges	0.66	0.62
Object description	only the campaign depicted flood scenes	0.88	0.82
Account creation year (intended)	creation burst	0.93	0.93
Processing operations (intended)	the TTP	0.77	0.76

No CS4 detector reads any leaked attribute; after the fixes, key results moved by 0.01 to 0.09 F1. The audits should be rerun whenever a generator changes.

Appendix D. Agent scores per question

Held-out worlds (fresh seed, noise 0.2 in CS1 and CS3). F1 for sets, macro-F1 for labels, parent in the right variant for lineage, accuracy for hops.

Question	Hand	A1 (schema)	A2 (schema)	B1 (data)	B2 (data)	B1r (rerun)	B2r (rerun)
Q1.1 recycled media	0.870	0.870	0.870	0.870	0.833	0.870	0.870
Q1.2 earliest appearance	0.976	0.976	0.976	0.976	0.930	0.976	0.976
Q1.3 four-way labels	0.891	0.891	0.881	0.891	0.852	0.891	0.891
Q2.1 patient zero	0.545	0.875	0.875	0.933	0.933	1.000	1.000
Q2.2 lineage	0.996	1.000	1.000	1.000	1.000	1.000	1.000
Q2.3 laundering	0.828	0.909	0.909	0.938	0.938	1.000	1.000
Q2.4 hidden hop	1.000	0.950	1.000	1.000	1.000	1.000	1.000
Q3.1 triage queue	0.938	0.938	0.938	0.938	0.938	0.938	0.938
Q3.2 credential contradiction	1.000	0.762	0.762	1.000	1.000	1.000	1.000
Q3.3 presentation category	0.892	0.892	0.892	0.892	0.885	0.892	0.892
Q3.4 anachronism	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Q3.5 recall impact	1.000	1.000	1.000	1.000	1.000	1.000	1.000
Mean	**0.911**	**0.922**	**0.925**	**0.953**	**0.942**	**0.964**	**0.964**

References

1. T. D. Nguyen and M. C. Stamm, "Trustworthy Image Authentication using Forensic Knowledge Graphs," arXiv:2606.23917, 2026.
2. M. Grüninger and M. S. Fox, "Methodology for the Design and Evaluation of Ontologies," Workshop on Basic Ontological Issues in Knowledge Sharing, IJCAI-95, Montreal, 1995.
3. T. Lebo, S. Sahoo and D. McGuinness (eds.), PROV-O: The PROV Ontology, W3C Recommendation, 30 April 2013.
4. S. Harris and A. Seaborne (eds.), SPARQL 1.1 Query Language, W3C Recommendation, 21 March 2013.
5. J. Snell and E. Prodromou (eds.), Activity Streams 2.0, W3C Recommendation, 23 May 2017.
6. Schema.org, ClaimReview and Claim types.
7. Coalition for Content Provenance and Authenticity, C2PA Technical Specification 2.3, 2025.
8. IPTC, Digital Source Type NewsCodes vocabulary.
9. H. Knublauch and D. Kontokostas (eds.), Shapes Constraint Language (SHACL), W3C Recommendation, 20 July 2017.
10. G. Luo, T. Darrell and A. Rohrbach, "NewsCLIPpings: Automatic Generation of Out-of-Context Multimodal Media," EMNLP 2021, arXiv:2104.05893.
11. D. Moreira et al., "Image Provenance Analysis at Scale," IEEE Transactions on Image Processing, 2018, arXiv:1801.06510.

12. D. Pacheco et al., "Uncovering Coordinated Networks on Social Media: Methods and Case Studies," ICWSM 2021, arXiv:2001.05658.

13. B. Jordan, R. Piazza and T. Darley (eds.), STIX Version 2.1, OASIS Standard, June 2021.

14. DISARM Foundation, DISARM framework for describing disinformation tactics, techniques and procedures.

All citations were checked against their sources except where the sibling background draft already verified them (C2PA 2.3, STIX 2.1, DISARM). One candidate, Dias, Rocha and Goldenstein on image phylogeny by minimum spanning trees, could not be confirmed and is deliberately left out.