ASSET®
water technology

Under counter

Erogatore d'acqua naturale, gassata e fredda, microfiltrata e debatterizzata

Room temperature, cold and sparkling microfiltered and debacterialized water dispenser

Home-Family

Il sottolavello Undercounter è disponibile nelle versioni con Telecomando (Wireless), Elettromeccanica ed Elettronica.
Silenzioso, compatto ed elegante, consente di avere sempre a disposizione una microfiltrazione d'acqua naturale, fredda e gassata.
L'installazione è semplice ed adattabile alle varie esigenze., anche in ambienti dove lo spazio talvolta può essere limitato.
E' gestito da un microprocessore che, attraverso sensori speciali, segnala il guasto e blocca il funzionamento, come nel caso di una perdita d'acqua.
Possiede un sistema di monitoraggio che, con l'ausilio della chip card, controlla la durata del filtro e segnala il momento della sostituzione.
Il basso consumo energetico lo rende un prodotto allineato alle normative più rigorose e l'esclusiva debatterizzazione UV garantisce l'igiene dell'acqua.

Our Undercounter models are available in the Remote (Wireless), Electromechanical and Electronic versions. Compact and elegant, the Undercounter dispenser supplies cold, room temperature and sparkling microfiltered water. Very easy to install and noiseless, this dispenser, which can be adapted to meet any and all requirements, is perfect for any environment where space is a problem.
Undercounter is controlled by a microprocessor which, through special sensors, signals any malfunction and turns off the dispenser when dangerous conditions arise, such as leaks. It is equipped with a monitoring system that, through the use of chip card technology, controls the filter's service life and advises the user when it should be replaced. Thanks to its low power consumption the Undercounter water dispenser fully complies with the strictest regulations while UV debacterialization guarantees maximum hygiene.

Undercounter *wireless*

Undercounter *electronic*

Undercounter *electro-mechanical*

Rubinetto non incluso
Tap not included

Nella versione con bombola esterna ricaricabile, Undercounter è ideale anche per l'impiego nel settore bar-ristorazione.

In the version with an external refillable cylinder, Undercounter is also ideal for use in bars and other food service businesses.

COMPANY
ECOLOGY
TECHNOLOGY
HOME-FAMILY
OFFICE-SCHOOL
RESTAURANT-BAR
ACCESSORIES

Home-Family

	SMILE	SORGENTE	UNDERCOUNTER
TENSIONE DI ALIMENTAZIONE POWER SUPPLY VOLTAGE	220-230V - 50Hz - monofase 220-230V - 50Hz - monophase	220-230V - 50Hz - monofase 220-230V - 50Hz - monophase	220-230V - 50Hz - monofase 220-230V - 50Hz - monophase
MASSIMA POTENZA ASSORBITA MAX POWER CONSUMPTION	[1] 230W - 0.84A	[1] 230W - 0.84A	230W - 0.84A
TEMPERATURA AMBIENTALE DI ESERCIZIO ROOM WORK TEMPERATURE	10-32 °C	10-32 °C	10-32 °C
COMPRESSORE POTENZA ASSORBITA COMPRESSOR POWER	Ermetico 65W Hermetic 65W	Ermetico 65W Hermetic 65W	Ermetico 65W Hermetic 65W
GAS REFRIGERANTE QUANTITÀ REFRIGERANT GAS QUANTITY	R134a 40g	R134a 40g	R134a 40g
SISTEMA DI GASATURA CARBONATION SYSTEM	Saturatore 4 l Saturator 4 l	Saturatore 4 l Saturator 4 l	Saturatore 4 l Saturator 4 l
TEMPERATURA ACQUA EROGATA DISPENSED WATER TEMPERATURE	Regolabile da 4 °C a 8 °C Adjustable from 4 °C to 8 °C	Regolabile da 4 °C a 8 °C Adjustable from 4 °C to 8 °C	Regolabile da 4 °C a 8 °C Adjustable from 4 °C to 8 °C
PRODUZIONE ACQUA FREDDA E GASSATA COLD AND SPARKLING WATER OUTPUT	16 l/h	16 l/h	16 l/h
PRESSIONE DI ESERCIZIO H_2O MIN - MAX H_2O WORKING PRESSURE MIN - MAX	150-400 kPa (1.5 - 4 bar)	150-400 kPa (1.5 - 4 bar)	150-400 kPa (1.5 - 4 bar)
GASATORE CAPACITÀ CARBONATOR CAPACITY	INOX AISI 316L - 4 l	INOX AISI 316L - 4 l	INOX AISI 316L - 4 l
DISPOSITIVO ANTIALLAGAMENTO ANTI-LEAKAGE SYSTEM	Elettrovalvola di sicurezza Safety solenoid valve	Elettrovalvola di sicurezza Safety solenoid valve	Elettrovalvola di sicurezza Safety solenoid valve
PRESSIONE DI ESERCIZIO CO_2 MIN - MAX CO_2 WORKING PRESSURE MIN - MAX	350-600 kPa (3.5 - 6 bar)	350-600 kPa (3.5 - 6 bar)	350-600 kPa (3.5 - 6 bar)
STRUTTURA ESTERNA CHASSIS	Plastica Riciclabile Recyclable plastic	Plastica Riciclabile Recyclable plastic	Plastica Riciclabile Recyclable plastic
CONTROLLO DELLE FUNZIONI MONITORING SYSTEM	Chip Card Filter Life Control	Chip Card Filter Life Control	Chip Card Filter Life Control
PESO CON IMBALLO WEIGHT WITH PACKAGE	18 kg	18 kg	18 kg
DIMENSIONI EROGATORE LxPxH WATER DISPENSER DIMENSIONS LxPxH	240x420x370 mm	240x420x370 mm	240x420x370 mm
NOTE	[1] 1500W per modello con acqua calda [1] 1500W for the Hot Water model	[1] 1500W per modello con acqua calda [1] 1500W for the Hot Water model	